A-A-1582
February 20, 1981

COMMERCIAL ITEM DESCRIPTION

LAMP, FLUORESCENT, F96T12/LW, ENERGY SAVING

The General Services Administration has authorized the use of this commercial item description.

This commercial item description covers 425 ma, instant-start, 60 watt, energy saving fluorescent lamp.

Salient characteristics:

T-12 bulb.
Nominal length - 96 inches.
Base - single pin contact.
Average rated life - 3 hours per start - 12,000 hours
12 hours per start - 18,000 hours.
Initial lumens after 100 hours burning - 5,650 lumens.
Lumens at 40 percent of life - 5,200 lumens.
Color - lite white or equal.
Designed for use on one or two lamps, 75 watt, instant/start high power factor, lead ballasts that meet ANSI C-82 and UL 935 requirements.
Dimensional characteristics shall be in accordance ith ANSI C78-810.

The issues of ANSI C78-810, C-82, and UL 935 in effect on the date of solicitation shall be used to determine compliance with stated requirements.

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices, and is the same product sold in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Regulatory requirements. The manufacturer shall utilize recovered materials to the maximum extent practicable.

Packaging, packing, and marking. The items shall be packaged in accordance with normal commercial practice and packed to assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling, and storage. The shipping container shall be in compliance with National Motor Freight Classification and Uniform Freight Classification. Shipping containers shall be marked as specified in the contract or order.

Copies of ANSI C78-810 and C-82 are available from the American National Standards Institute, 1430 Broadway, New York, NY 10018.

Copies of UL 935 are available from Underwriters' Laboratories (UL), Inc., 1285 Walt Whitman Rd., Melville, Long Island, NY 11747.

Preparing activity:

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:15
Check the source to verify that this is the current version before use.