[METRIC]
A-A-1688A
NOVEMBER 30, 1995
SUPERSEDING
A-A-1688
JULY 23, 1981

COMMERCIAL ITEM DESCRIPTION

TAPE, PRESSURE-SENSITIVE ADHESIVE (PAPER PHOTOGRAPHIC)

1. SCOPE

This Commercial Item Description covers photographic, pressure-sensitive adhesive tape.

2. SALIENT CHARACTERISTICS

2.1 The tape shall be flat black (matte, no gloss) crepe paper for use in edging and blocking out purposes in the development and printing of photographic negatives. It may also be used for sealing cans of film.

2.2 The tape shall comply with the test requirements stated in section 4.3 when tested with the appropriate test methods.

Workmanship. The tape shall be uniformly constructed and free from defects which may impair usefulness of the material for the intended use. The adhesive shall be coated in a smooth uniform layer over the entire surface of one side of the tape backing. The tape shall be evenly and tightly wound with no voids. The edges shall be clean cut. When unwound, the tape shall not tear nor shall the adhesive separate from the backing.

3. REGULATORY REQUIREMENTS

The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulations (FAR).

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: General Services Administration, Federal Supply Service, 26 Federal Plaza, New York, NY 10278 ATTN.: Engineering Branch (2FYEE).

FSC 7510

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:15Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE

4.1 Contractor Certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

4.2 Sampling for examination and testing shall be in accordance with Section 6 of ASTM D 3715M with an AQL of 4 percent defective. The sample unit shall be one roll of tape.

4.3 Physical Characteristics.

	Requirement	Test Method
Adhesion, minimum	11 N/100 mm (10 oz/in width)	ASTM D 3330M Method A
Elongation, Percent Minimum	6	ASTM D 3759M
Tensile, minimum	290 N/100 mm (16 oz/in width)	ASTM D 3759M

Pin Hole Test. The tape shall be pinhole free when tested by placing a 102 mm by 102 mm (4" by 4") piece of tape, made by overlapping by 3 mm (1/8") several strips of the tape, and placing this piece over one end of a 76 mm (3") round or square 607 mm (2') long tube. Look into the open end of the tube at a 100 watt bulb placed approximately 303 mm (12") from the closed end of the tube. After allowing one minute for the eye to adjust to the darkness observe any pin holes in the tape placed over the closed end of the tube.

5. PREPARATION FOR DELIVERY

Packaging, packing and marking of the tapes shall be as specified in the contract or purchase order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:15Z
Check the source to verify that this is the current version before use.

6. APPLICATION FOR COPIES OF DOCUMENTS REFERENCED HEREIN:

The issue date in effect on the date of invitation for bids or request for proposals shall apply.

ASTM standard test methods can be obtained from the American Society for Testing and Materials; 1916 Race Street; Philadelphia, PA 19103.

Federal Acquisition Regulations (FAR) is available from the Superintendent of Documents, Government Printing Office, Washington, D.C. 20402.

7. NOTES.

7.1 Ordering Data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

A) The width and length of tape.
B) Packaging, packing and marking.

7.2 NATIONAL STOCK NUMBERS (NSNs).

The following is a list of NSNs assigned which correspond to this CID. The list may not be indicative of all possible NSNs associated with the CID.

7510-00-285-2931
7510-00-285-2930
7510-00-062-3931

Military Interest:

User Activity:
Army-GL

Preparing activity:

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:15Z
Check the source to verify that this is the current version before use.