A-A-1984
January 11, 1982

COMMERCIAL ITEM DESCRIPTION

# LAMP, FLUORESCENT
# (F30T12/CW/RS, ENERGY SAVING)

The General Services Administration has authorized the use of this commercial item description.

This description covers 25 watt, rapid-start type, energy saving fluorescent lamps.

Salient characteristics:

Bulb - T-12
Nominal overall length - 36 inches
Base - medium bipin
Average rated life - three hours per start - 18,000 hours
Initial lumens (after 100 hours burning) - 2,000 lumens
Lumens at 40 percent of life - 1,700 lumens
Color - cool white when tested in accordance with ANSI C78.376
Designed to operate only on two-lamp lead circuit, high power factor, 30 watt rapid-start indoor ballasts that meet ANSI C82.1 and UL 935 requirements, and in ambient temperature of not less than 18° C (65° F)
Dimensional characteristics shall be in accordance with ANSI C78.1

The issues of ANSI C78.1, ANSI C78.376, ANSI C82.1 and UL Standard 935 in effect on the date of the solicitation shall be used to determine compliance with these requirements.

Workmanship. There shall be no defects that affect serviceability or appearance.

Regulatory requirements. The manufacturer shall utilize recovered materials to the maximum extent practicable.

Packaging, packing, and marking. Packaging, packing, and marking shall be as specified in the contract or order.

Copies of ANSI standards are available from the American National Standards Institute, Inc., 1430 Broadway, New York, NY 10018.

UL standards are available from Underwriters Laboratories, Inc., 333 Pfingsten Road, Northbrook, IL 60062.

MILITARY INTERESTS:

Custodians

Navy - SH
Army - ME
Air Force - 99

CIVIL AGENCY COORDINATING ACTIVITIES:

COMMERCE - NBS
GSA - FSS

PREPARING ACTIVITY:

GSA - FSS

FSC 6240

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:18Z
Check the source to verify that this is the current version before use.