A-A-1996
February 8, 1983

COMMERCIAL ITEM DESCRIPTION

SPECTACLES, INDUSTRIAL (METAL FRAMES)

The General Services Administration has authorized the use of this commercial item description in preference to Federal Specification GGG-S-620, type I, styles A, B C, and D.

This description covers spectacles for the protection of personnel engaged in occupations where small flying particles of relatively light impact are encountered; such as in light grinding and polishing metal and wood burning, and drilling. In addition, spectacles with absorptive lenses provide protection from the harmful effects of intense light in the vicinity of gas or electric welding and other sources of intense glare. Spectacle frames and lenses shall be one of the following types, styles and classes:

Frames:

Metal

Style A - without side shields
Style B - with wire mesh side shields
Style C - with perforated clear plastic side shields
Style D - with green plastic side shields

Lenses:

Type I - Glass, plano, impact-resistant.

Class A - clear
Class B - absorptive. Shall be available in shade numbers 1.7, 2.0, 2.5, and 3.0, as specified.

Type II - Polycarbonate, plano, impact-resistant, mar-resistant coated.

Class A - clear
Class B - absorptive. Shall be available in shade numbers 1.7, 2.0, 2.5, and 3.0, as specified.

Salient characteristics:

Lens Shape - S-7

Lens Sizes - 44, 46, 48, and 50 mm, as specified. A tolerance of ± 0.1 mm applies

Frame Sizes - 44, 46, 48 and 50 mm, as specified. Shall accommodate S-7 lenses

Glare Protection - Side shields used in Class B lens spectacles when used to enhance glare protection, shall have transmission to incident radiation (visible, ultra-violet and infrared) less than or equal to the lens in the front. Side shields shall be solid with no perforations or openings.

Bridge Sizes - From 18 to 26 mm, as specified. A tolerance of ± 1.0 mm is permitted.

Temples - Shall be cable or spatula type, as specified.

Nose Pads - Shall be equipped with adjustable rocking-pad type, or an integral, rigid pad. A universal fitting bridge may be furnished,

Conformance. Spectacles and lenses furnished under this specification shall comply with the applicable requirements of ANSI Z 87.1, except as otherwise specified herein.

Workmanship. The spectacles shall be constructed in a thoroughly workmanlike manner, and shall be free of defects which may impair their appearance, durability, or serviceability.

Note. Purchaser to specify type, class, style, lens size, frame size, bridge size, and whether temples are to be cable or spatula type.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:18Z
Check the source to verify that this is the current version before use.

Preservation, packaging, packing, labeling, and marking. The preservation, packaging, packing, labeling, and marking, shall be as specified in the contract or order.

ANSI Standard Z 87.1 is available from the American National Standards Institute, 1430 Broadway, New York, NY 10018.

MILITARY INTERESTS:

Review Activities

Army - AR
Navy - SH, MS
Air Force - 99

Custodians

Army - AR
Navy - SH
Air Force - 99

PREPARING ACTIVITY:

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:18Z
Check the source to verify that this is the current version before use.