A-A-96
October 8, 1979

COMMERCIAL ITEM DESCRIPTION

CLEANING COMPOUND, OVEN (AEROSOL)

The General Services Administration has authorized the use of this commercial item description in lieu of Federal Specification P-C-1947.

This commercial item description covers an aerosol oven cleaner suitable for removing heavy baked-on grease and carbonized soil deposit on grills, oven, fryer, other kitchen equipment and vertical and horizontal surfaces where such deposits might occur.

Salient characteristics:

pH. The oven cleaner (propellant-free) shall have a pH at 25° C not less than 13.0 using ASTM E 70.

Delivery rate. The aerosol oven cleaner shall have a delivery rate at 21° C of 1.0 to 3.5 grams per second using ASTM D 3069.

Cleaning performance. The aerosol oven cleaner shall be capable of completely removing a soil of the following composition, when baked at 425° - 450° F for 20 minutes:

*Soil composition	Wt. percent
Corn oil (Mazola)	84
Sugar (granulated)	8
Flour (Standard bleached)	8

*See note at the end of this document for the procedure for the determination of cleaning performance.

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices and is the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Packaging, packing, and marking. The aerosol oven cleaner will be packaged and packed in accordance with normal commercial practice to insure delivery at destination to provide for redistribution by the initial receiving activity, and shall be acceptable by common carrier under National Motor Freight Classification and Uniform Freight Classification.

ASTM methods are available from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

Acceptable brand name products but not limited to:

Boyle - Midway's Easy-Off.
Dow's Oven cleaner.
Drackett's Mr. Muscle.

Note:

Cleaning performance:

Preparation of soil. While stirring, heat corn oil to 190° - 200° F. While continuing to stir, add sugar and flour and mix thoroughly. Allow mixture to cool to room temperature before use.

Equipment. One paint brush, 1 1/2 by 3 inches wide, and two procelain enamel test plates, 3 by 3 inches may be obtained from the Ferro Corporation, 4150 E. 56th Street, Cleveland, OH.

Test procedure. Soil mixture is stirred constantly during application to panels. Apply soil in a thin film using a paint brush to the enamel panel. To aid in spreading, brush an even coat in one direction only. Bake panels in a horizontal position at 425° - 450° F for 20 minutes. After panel has cooled to room temperature place them in a horizontal position. Using the aerosol, apply the oven cleaner to the soil panel until the cleaner completely covers the surface of the soiled panel. Allow panel to set for 30 minutes in a horizontal position at room temperature. Damp sponge lightly and flush with water to remove the soil. Dry panel and apply aerosol oven cleaner again and repeat the procedure. After damp sponging and flushing with water, the oven cleaner shall by visual observation, completely remove all the soil on the panel.

FSC 7930

Source: https://assist.dla.mil -- Downloaded: 20260-26T08:04Z
Check the source to verify that this is the current version before use.