MIL-R-2726/22A(SH)
3 July 1986
SUPERSEDING
MIL-O-2726/22(SHIPS)
30 June 1967

MILITARY SPECIFICATION SHEET

(A) RECEPTACLE, OUTLET, ELECTRICAL, WELDING, 200-AMPERE, DIRECT CURRENT, CONSTANT POTENTIAL (SYMBOL NO. 770.2)

(A) This specification is approved for use within the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

(A) The requirements for acquiring the receptacle described herein shall consist of this specification and the latest issue of MIL-R-2726.

(A) denotes changes.

AMSC N/A FSC 5935
DISTRIBUTION STATEMENT A Approved for public release; distribution unlimited

Source: https://assist.dla.mil - Downloaded: 2026-10-16T15:25Z
Check the source to verify that this is the current version before use.






FIGURE 1. Dimensions and configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T15:25Z
Check the source to verify that this is the current version before use.





SH 9099-1

NOTES:

1. Dimensions are in inches. Unless otherwise specified, tolerances are ± 1/64 inch for fractions and ± 0.005 inch for decimals.
2. Supersedes: Drawing 9000-S6202-74204, symbol 770.1.

FIGURE 1. Dimensions and configuration. - Continued

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T15:25Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

1. Dimensions and configurations: See figure 1.
2. Effectiveness of enclosure: Submersible (15 foot) in accordance with MIL-STD-108.
3. Connectors: Burndy Quicklug, type Q2B (250 MCM - 300 MCM), or equal.
4. Mating plug: Drawing 9-S-5259-L, type M (not furnished).
5. Enclosure assembly: In accordance with MIL-E-24142/6, part number M24142/6-003.
6. Electrical rating: 200-ampere, direct current.
7. Part number: M2726/22-001 (assembly)
   M2726/22-002 (rapid coupling)
8. Identification and warning plate shall be furnished.
9. Caps shall be furnished.

QUALITY ASSURANCE:

Quality assurance shall be as specified in MIL-R-2726 and table I herein. The first article and quality conformance inspections shall consist of the inspections as specified in table I, in the order shown.

TABLE I. First article and quality conformance inspection.

Inspection	Requirement	Test method	First article	Quality conformance
Examination	3.1, 3.3, 3.4, 3.5, 3.6 and 3.7	4.6.1	X	X
Insulation resistance	3.5.1	4.7.1	X	X
Dielectric withstanding voltage	3.5.2	4.7.2	X	X
Current load	3.5.12	4.7.12	X	
Vibration	3.5.9	4.7.9	X	
Shock	3.5.10	4.7.10	X	
Effectiveness of enclosure	3.5.4	4.7.4	X	X
Dielectric withstanding voltage	3.5.2	4.7.2	X	

Preparing activity:
Navy - SH
(Project 5935-N255-23)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T15:25Z
Check the source to verify that this is the current version before use.