INCH-POUND
MIL-PRF-32383/3A
16 December 2021

SUPERSEDING
MIL-PRF-32383/3
16 JUNE 2011

PERFORMANCE SPECIFICATION SHEET

BATTERY, RECHARGEABLE, SEALED, BB-2590A/U

The requirements for acquiring the product herein shall consist of this specification sheet and MIL-PRF-32383.




FIGURE 1. BB-2590A/U

NOTES
Approximate size: 5in x 2.5in x 4.4in. See FIGURE 2 for exact dimensions.

For clarity, MIL-PRF-32383 tables are labeled with capital Roman numerals (e.g. IX) and MIL-PRF-32383/3A tables are labeled with lower case Roman numerals (e.g. ix).

REQUIREMENTS
BB-2590A/U Type – III (see 1.2 for classification) PIN – M32383/3-3 (see 1.3 for PIN)

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:06Z
Check the source to verify that this is the current version before use.

Specification requirements and test methods: The following requirements and test methods of MIL-PRF-32383, identified therein as “when specified”, are applicable as indicated below:

TABLE i. *"When specified" requirements*

Requirement	Requirement Paragraph	Test Method Paragraph	Applicability
Additional material requirements	*3.3.7*	*4.7.1.9*	*No*
Connector pull force	*3.4.4.1.1.1*	*Certification*	*No*
Connector insertions	3.4.4.1.1.2	4.7.1.3	Yes
Multilayer finish	3.4.4.1.3	Certification	Yes
Gold plating	*3.4.4.1.4*	*Certification*	*No*
USB power port connector(s)	*3.4.4.1.5*	*4.7.2.17*	*No*
USB type A connector(s)	*3.4.4.1.5.1*	*4.7.2.17*	*No*
USB type C connector(s)	*3.4.4.1.5.2*	*4.7.2.17*	*No*
Surface friction	3.4.5.6	4.7.1.8	Yes
Item unique identification (IUID)	*3.4.6.1.1*	*4.7.1.1*	*No*
Additional physical characteristics requirements	*3.4.8*	*4.7.1.10*	*No*
Inrush current	3.5.5	4.7.2.12	Yes
Charge enable	3.5.6.2	4.7.2.6	Yes
Display, non-smart, always on	3.5.8.1.1	4.7.2.14.1	Yes
Display, non-smart, user activated	*3.5.8.1.2*	*4.7.2.14.1*	*No*
Display, smart	*3.5.8.2*	*4.7.2.14.2*	*No*
SMBus	3.5.9.1	4.7.2.15.1	Yes
USB power delivery	*3.5.9.2*	*4.7.2.15.2*	*No*
Dual-role power device	*3.5.9.2.1*	*4.7.2.14.2*	*No*
Concurrent charge/discharge	*3.5.11*	*4.7.2.16*	*No*
Additional electrical requirements	*3.5.12*	*4.7.2.18*	*No*
Temperature shock high altitude high opening (HAHO) simulation	*3.6.3*	*4.7.3.5.1*	*No*
Temperature shock high altitude low opening (HALO) simulation	*3.6.3*	*4.7.3.5.2*	*No*
Vibration, loose cargo transportation	*3.6.5*	*4.7.3.7.1*	*No*
Immersion, shallow	3.6.6	4.7.3.8.1	Yes
Immersion, deep	*3.6.6*	*4.7.3.8.2*	*No*
Transit drop, normal	*3.6.7*	*4.7.3.9.1*	*No*
Transit drop, severe	3.6.7	4.7.3.9.2	Yes
Drop while mated	*3.6.7*	*4.7.3.9.2*	*No*
Impact	*3.6.9*	*4.7.3.11*	*No*
Solar radiation	*3.6.10*	*4.7.3.12*	*No*

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:06Z
Check the source to verify that this is the current version before use.

TABLE i. *"When specified" requirements* - Continued

Requirement	Requirement Paragraph	Test Method Paragraph	Applicability
Salt fog	*3.6.11*	*4.7.3.13*	*No*
Electrostatic discharge (ESD)	*3.6.12*	*4.7.3.14*	*No*
Chemical resistance	*3.6.13*	*4.7.3.15*	*No*
Rapid decompression	*3.6.14*	*4.7.3.16*	*No*
Explosive atmosphere	*3.6.15*	*4.7.3.17*	*No*
Combined temperature, altitude, and humidity	*3.6.16*	*4.7.3.18*	*No*
Additional environmental requirements	*3.6.17*	*4.7.3.19*	*No*
Nail penetration, cell	3.7.1.2	4.7.4.4	Yes
Crush, cell	3.7.1.3	4.7.4.5	Yes
Inter-cell protective devices	*3.7.2.6*	*Certification*	*No*
Redundant safety protection	*3.7.2.7*	*Certification*	*No*
Projectile	3.7.2.8	4.7.4.11	Yes
Nail penetration, battery	*3.7.2.9*	*4.7.4.12*	*No*
Lithium battery safety program (US Navy)	3.7.2.10	4.7.5	Yes
Weapons characterization	*3.7.2.11*	*4.7.4.13*	*No*
Additional safety requirements	*3.7.3*	*4.7.4.14*	*No*
Electromagnetic interference	*3.8*	*4.7.7*	*No*
Additional transportation requirements	*3.9.1*	*4.7.8*	*No*
Reliability	*3.11*	*4.7.2.4.1*	*No*

Details: The following are details specific to M32383/3-3 including those referenced in MIL-PRF-32383 as “specified”.

1. Dimensions and weight (3.4.3).
Dimensions: See FIGURE 2
Maximum weight: 3.2lb

2. Connector (3.4.4.1.1).
Connector: Drawing SC-C-179495 (or equivalent).
The face of connector shall be flush to 0.031 inch below top of battery
Mating connector: N/A
Multilayer finish: Flat contacts shall be brass with multilayer finish
Gold plating: N/A
Battery charger adapter: J-6358B/P

3. Battery case vent (3.4.5.3).
See FIGURE 2 for quantity and location.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:06Z
Check the source to verify that this is the current version before use.

4. Marking (3.4.6).
See FIGURE 2 for the location of required markings as indicated. The locations for other required markings from MIL-PRF-32383 are optional.

5. Instructions / notes (3.4.6.5).
See FIGURE 2.

6. Simplified battery label (3.4.6.6).
The simplified battery label location is optional. It shall be sized to remain legible.

7. Battery condition for shipping (3.4.7).
The instruction card shall at a minimum contain operation, storage, handling, maintenance, and warranty (if applicable) information.

8. Battery voltage (3.5.2).
Battery open circuit voltage:

Minimum		Maximum	
Single / Parallel	Series	Single / Parallel	Series
10 V	20 V	16.5 V	33 V

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:06Z
Check the source to verify that this is the current version before use.

9. Capacity (3.5.3).

Cutoff voltage: 20 V (series mode)

Each battery, discharged at the specified rate to cutoff voltage, shall have the following minimum capacity:

Test	Requirement Paragraph	Test Method Paragraph	Discharge Rate (A)	Minimum Capacity (Ah)
Capacity discharge	3.5.3	4.7.2.3	2	7.5
Cycle life (224th cycle)	3.5.4	4.7.2.4	2	6.5
High rate discharge	3.5.3	4.7.2.5	10	6.5
Low temperature discharge	3.5.3	4.7.2.7	2	6.5
High temperature discharge	3.5.3	4.7.2.8	2	6.5
Inrush current	3.5.5	4.7.2.12	See 3.5.5	6.5
Charge acceptance	3.5.10.1	4.7.2.9	2	6.5
Retention of charge	3.5.10.2	4.7.2.10	2	6.5
Pulse discharge[1]	3.5.3	4.7.2.11	See 4.7.2.11	10.5
Extreme low temperature discharge	3.6.1	4.7.3.2	2	5.5
Extreme high temperature discharge	3.6.1	4.7.3.3	2	5.5
Temperature shock (post-test)	3.6.3	4.7.3.5	2	7.5
Mechanical shock (post-test)	3.6.4	4.7.3.6	2	7.5
Vibration (during test)	3.6.5	4.7.3.7	0.8	7.5
Battery storage life	3.6.8	4.7.3.10	2	6.5
Overcharge/electric leakage (post-test)	3.7.2.2	4.7.4.7	2	7.5
Short circuit protection (post-test)	3.7.2.3	4.7.4.8	2	7.5
High temperature temporary cut off	3.7.2.4	4.7.4.9	2	6.5

NOTES

[1] Parallel mode; cutoff is 10 V

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:06Z
Check the source to verify that this is the current version before use.

10. Inrush current (3.5.5).

The discharge profile shall be no less than as follows.

Step	Start time (minute:second:millisecond)	End time (minute:second:millisecond)	Current (A)
1	00:00:000	**05**:00:000	5
1a	**05**:00:000	05:00:**000.2**	60
2	05:00:**000.2**	05:00:**010**	22.5
3	05:00:**010**	05:00:**020**	20
4	05:00:**020**	05:00:**030**	19
5	05:00:**030**	05:00:**040**	18
6	05:00:**040**	05:00:**060**	17
7	05:00:**060**	05:00:**100**	16
8	05:00:**100**	05:00:**175**	15
9	05:00:**175**	05:00:**325**	14
10	05:00:**325**	05:00:**575**	13
11	05:00:**575**	05:00:**850**	12
12	05:00:**850**	05:**01**:000	11
13	05:**01**:000	**10**:00:000	10
14	Repeat steps 1 through 13		
15	**20**:00:010	Until cutoff voltage	5

11. Charging interface (3.5.6.1).

See FIGURE 2.

12. Charge enable (3.5.6.2).

The charge enable terminal shall comply with the following:

Maximum charge without enable: 400 mA

Equivalent resistor: 235 Ω

Equivalent diode V_F: 1.3 V

Approximate activation current: 7 mA

13. High temperature temporary cut off devices (3.7.2.4).

Not less than four devices.

14. High temperature permanent cut off devices (3.7.2.5).

Not less than two devices.

15. First article inspection (4.4).

Groups 1, 3, 4, and 5 apply

h. Group 5 (GR5) – Nail penetration tests (battery level and Weapons Characterization tests – samples size of six (6).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:06Z
Check the source to verify that this is the current version before use.

16. Constant potential, current limited (4.6.1).
A constant potential of 16.5 V shall be applied to each battery section independently with current limited to 3 A, to a charge cut off of 100 mA.

17. Alternate charging (4.6.3).
b. Charge each section independently with a constant potential of 16.5 V and current limit of 3 A max.

18. Capacity discharge (4.7.2.3).
c. 2 A in series mode.

19. Cycle life test (4.7.2.4).
a. and b. 2 A

20. Pulse discharge (4.7.2.11).
d. Battery sections connected in parallel with 36 A for 5 seconds followed by 25 seconds off

21. Nail penetration, cell (4.7.4.4).
SOC not less than 50%

22. Overcharge / electrical leakage (4.7.4.7).
c. Charge in parallel mode at 4 A with a charge voltage limit of 40 V.
f. 2 A

ADDITIONAL FIGURES

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:06Z
Check the source to verify that this is the current version before use.




FIGURE 2. BB-2590A/U details

NOTES

Dimensions are in inches. Tolerance is ± 0.031 inches.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:06Z
Check the source to verify that this is the current version before use.

NOTES: (This section contains information of a general nature which may be helpful, but is not mandatory)

Nominal ratings: The following are the nominal ratings for the battery described by this specification sheet. They are provided for information purposes.

Battery PIN: M32383/3	**-3**
Type Classification:	BB-2590A/U
Chemistry:	Li-Ion
Color:	"Tan 686A" Chip number 33446
Weight (max):	3.2 lbs (1.5 kg)
Voltage Range:	20-33 V
Nominal Voltage:	28.8 V
Nominal Capacity:	7.4 Ah
Nominal Energy (new battery):	213 Wh
Rated power output:	≤ 200 W
Battery Life:	≥ 224 cycles, ≥ 3 years
Continuous load rating:	≤ 10 A
Pulse load rating:	≤ 36 A (5 SEC)
Charge temperature range:	-4 to 122 ºF (-20 to 50 ºC)
Operating temperature range:	-22 to 140 ºF (-30 to 55 ºC)
Storage temperature range:	-4 to 122 ºF (-20 to 50 ºC)
MAX abusive temperature: (non-operating):	199 ºF (93 ºC)
Connector:	SC-C-179495
Overall Dimensions:	~ 5 in. x 2.5 in. x 4.4 in.
Non-rechargeable equivalent / Specification:	BA-5590()/U, BA-5390()/U and BA-5790()/U / MIL-PRF-32271/1

Other data:

Navy safety tests of NAVSEA S9310-AQ-SAF-010 are required for the BB-2590A/U battery during first article testing. The test data provided from the testing will be used to evaluate applications for specific using devices and Navy platforms. Devices using this battery will require US Navy Safety Approval prior to use by Department of Navy users unless such approval has already been granted. Please consult with NAVSEA Instruction 9310.1 for further information.

Changes from previous issue: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:06Z
Check the source to verify that this is the current version before use.

Custodians:
Army – CR
Navy – MC
Air Force – 71
DLA - CC

Review activities:
Navy – AS, SH

Preparing activity:
Army – CR
(Project Number 6140-2021-012)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:06Z
Check the source to verify that this is the current version before use.