INCH-POUND

MIL-V-18318B
AMENDMENT 3
10 January 1996
SUPERSEDING
AMENDMENT 2
5 January 1978

MILITARY SPECIFICATION

VALVE, PRESSURE REGULATING, OXYGEN SYSTEM

This amendment forms a part of MIL-V-18318B, dated 29 September 1966, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1 SPECIFICATIONS - Federal

Delete the following:

"O-T-236 Trichloroethylene (perchloroethylene) Technical Grade
O-T-634 Trichloroethylene, Technical"

SPECIFICATIONS - Military

Delete the following:

"MIL-F-22191 Films, Transparent, Flexible, Heat Sealable for Packaging Applications

"MIL-C-81302 Cleaning Compound, Solvent, Trichlorotrifluoroethane"

Add the following:

"MIL-B-22191 Barrier, Materials, Transparent, Flexible, Heat Sealable"

Add the following to the bottom of the page:

"Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Systems Engineering Department, Code 4.1.4B120-3, Naval Air Warfare Center Aircraft Division, Highway 547, Lakehurst, NJ 08733-5100, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter."

DISTRIBUTION STATEMENT A. Approved for public release: distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:16Z
Check the source to verify that this is the current version before use.

PAGE 3

2.1 STANDARDS - Military

Delete the following:

"MS 33586 Metals, Definition of Dissimilar"

Add the following:

"MIL-STD-889 Dissimilar Metals

* MIL-STD-1359 Cleaning Methods and Procedures for Breathing Oxygen Equipment"

3.1 - Delete

PAGE 4

3.4.1.1 - Delete “MS 33586” and substitute "MIL-STD-889."

PAGE 7

3.7.4.1, line 3 - Delete "exceeds 120" and substitute “rises to 120 ± 10".

3.7.4.2, line 3 - Delete "exceeds 600": and substitute “rises to 625 ± 25".

* 3.7.8 - Delete "3.7.8" and substitute "3.7.8.1."

* Add new paragraph "3.7.8 Oxygen test."

* Add new paragraph "3.7.8.2 Oxygen purge. When tested as specified in 4.7.9.2, the valve shall not ignite and there shall be no evidence of charring or deterioration."

PAGE 8

* 3.13 - Delete and substitute the following:

"3.13 Degreasing. All parts of the valve shall be degreased in accordance with MIL-STD-1359. Ultrasonics may be used in conjunction with vapor decreasing for the cleaning of components. After assembly. the absence of cleaning compounds shall be verified in accordance with MIL-STD-1359 All parts shall then be protected to prevent recontamination."

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:16Z
Check the source to verify that this is the current version before use.

PAGE 9

4.2(a) - Delete

4.3 - Delete

4.3.1 - Delete

4.4 - Delete and substitute the following:

"4.4 First article inspection - First article inspection shall consist of all the examinations and tests of this specification."

4.4.1 - Delete and substitute the following:

"4.4.1 First article samples - Unless otherwise specified, as soon as practicable, after the award of the contract or order, the manufacturer shall submit two valves. The samples shall be representative of the construction, workmanship, components, and materials to be used during production. When a manufacturer- is in continuous production of these units from contract to contract, submission of further first article samples on the new contract may be waived at the discretion of the procuring activity (see 6.2). Approval of the first article samples or the waiving of first article inspection does not preclude the requirements of submitting to the quality conformance inspection. The first article inspection samples shall be furnished to the Government as directed by the contracting officer (see 6.2)."

4.4.1.1 - Delete

PAGE 10

4.4.1.2 - Delete

* 4.5 - Add to bottom of list “Oxygen purge, if required."

PAGE 11

* 4.6.2 - After last sentence, add "If oxygen is not used as the test gas, oxygen in accordance with MIL-O-27210, type 1 shall be used to purge in accordance with 3.7.8.2 and 4.7.9.2."

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:16Z
Check the source to verify that this is the current version before use.

PAGE 12

Add to bottom of table II:

Oxygen purge	Critical	4.7.9.2	Every valve	Reject all defective units

PAGE 13

4.7.3, Note 1/ at bottom of page - Delete

PAGE 14

4.7.4, Note/ at bottom of paragraph - Delete

PAGE 15

* 4.7.9 - Delete "4.7.9" and substitute "4.7.9.1."

* Add new paragraph "4.7.9 Oxygen test."

* 4.7.9.1 - Delete "4.7.9.1" and substitute “4.7.9.1 .1."

PAGE 16

* 4.7.9.2 - Delete "4.7.9.2" and substitute "4.7.9.1.2."

* Add new paragraph "4.7.9.2 Oxygen purge. The valve shall be connected to a regulated source of oxygen (see 4.6.2). An inlet pressure of 70 psig shall be applied to the type I valve and the valve shall free flow for 3 to 5 minutes. An inlet pressure of 400 psig shall be applied to the type II valve and the valve shall free flow for 3 to 5 minutes. The valve shall meet the applicable requirements of 3.7.8.2."

5.1.1, line 4 - Delete "MIL-F-22191" and substitute "MIL-B-22191."

PAGE 19

6.2(c), line 2 - Delete "4.4.1.1 and 4.4.1.2" and substitute "4.4.1."

6.4 - Delete

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:16Z
Check the source to verify that this is the current version before use.

Note: The margins of this amendment are marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - AV
Navy - AS
Air Force - 99

Review activity:
Air Force - 11

Preparing activity:
Navy - AS

(Project 4820-0668)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:16Z
Check the source to verify that this is the current version before use.