MILITARY SPECIFICATION

BELT, SAFETY, SHOULDER, HARNESS, TROOP, TYPE D-2

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type of aircraft safety belt, designated Type D-2, used in securing flying personnel in their seats.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

TT-I-542	Ink, Marking, Laundry, Black
PPP-B-566	Boxes, Folding, Paperboard
PPP-B-636	Boxes, Fiberboard

MILITARY

MIL-P-116	Preservation, Method of
MIL-L-15040	Labels, Garment (Woven, Rayon)

STANDARDS

MILITARY

MIL-STD-129	Marking for Shipment and Storage
MIL-STD-130	Identification Marking of U.S. Military Property
MIL-STD-849	Inspection Requirements, Definitions and Classification of Defects for Parachutes

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: HQ AFLC CASO/LODS, Federal Center, Battle Creek, MI 49016 by using the self addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:46Z
Check the source to verify that this is the current version before use.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS

Air Force 49D7079	Belt Assembly - Safety Shoulder Harness, Troop, Type D-2

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS.

3.1 General. The requirements specified in Drawing 49D7079 shall be applicable as requirements of this specification. Additional requirements shall be as specified herein.

3.1.1 Where the requirements of Drawing 49D7079 and the requirements of this specification conflict, the requirements of this specification shall govern.

3.2 Materials. When materials are used which are not specifically designated, they shall be entirely suitable for the purpose intended.

3.3 Construction. The safety belt shall be of such strength as to withstand a static load of 1,500 pounds, without weakening of the webbing and stitching, and without slippage of the adjusting hardware, or deformation of the metal fitting.

3.4 Performance. The belt shall be capable of satisfactorily meeting the requirements as specified in Section 4.

3.5 Marking. Each shoulder harness shall be marked by means of a sewed label located on the harness as shown on the applicable detail drawing. This label shall be in accordance with Specification MIL-L-15040, type I, side 1, except that the lettering shall consist of white letters on a black background, lettering to read in the direction of the warp of the label. The data appearing on the label shall be in accordance with Standard MIL-STD-130, and shall consist of the following information:

Belt, Safety, Shoulder Harness
Troop, Type D-2
Specification MIL-B-5428B(USAF)
Stock No.....
Part No. 49D7079
Contract or Order Number
Date of Manufacture
Manufacturer's "Name or Trademark"

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:46Z
Check the source to verify that this is the current version before use.

3.5.1 Stock Number. The stock number entered in the space provided shall be as specified by the procuring agency. The stock number shall include the name or standard abbreviations of the Service having jurisdiction of the equipment.

3.6 Workmanship. The belt, including all parts and accessories, shall conform to the quality established by this specification and documents referenced herein. Particular attention shall be given to marking of parts and assemblies and freedom of hardware from burrs and sharp edges. The occurrence of defects shall not exceed the acceptance criteria established herein. Repair of items not allowed.

3.7 Reclaimed materials. The use of reclaimed materials shall be encouraged to the maximum extent possible.

4. QUALITY ASSURANCE PROVISIONS.

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Method of examination and tests. All the tests required for the testing of safety belts are classified as Inspection tests, for which necessary sampling techniques and methods of testing are specified in this section. The contractor shall furnish all samples and shall be responsible for accomplishing the required tests. When inspection is conducted at the contractor's plant, all inspection and testing shall be under the supervision of the Government Inspector. Contractors not having laboratory testing facilities satisfactory to the Government shall engage the services of a commercial testing laboratory acceptable to the procuring agency. The contractor shall furnish test reports, showing the results for all tests required by this specification, and signed by an authorized representative of the contractor or laboratory, as applicable. Acceptance or approval of material during course of manufacture shall in no case be construed as a guaranty of the acceptance of the finished product.

4.2 Individual Tests. Each belt shall be subjected to the following tests.

4.2.1 Examination of Product. Each safety belt shall be inspected to determine compliance with the requirements specified herein.

4.2.2 Visual and dimensional examination. Each belt assembly and component thereof shall be examined for conformance to MIL-STD-849. Belt assembly shall meet the requirements of personnel parachute harness in MIL-STD-849; however, repair of item in classification of defects table not authorized.

4.2.3 Proof Load. Each belt shall be assembled in a testing machine and subjected to a 1,000-pound static load. The belts shall be assembled in the testing machine by attaching both the snap fasteners and the link fasteners to the movable head while the webbing of the belt is passed around a 2-inch

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:46Z
Check the source to verify that this is the current version before use.

diameter bar, fixed perpendicular to the direction of pull, and attached to the stationary head. Installation shall be such that there will be no twisting of the webbing. The belt shall be adjusted to assure an equal transmittal of the load through each strap. The load shall be applied evenly until the specified load is attained. There shall be no signs of weakening of webbing and stitching, slippage of the webbing through the adjusting hardware, or deformation fo the metal fittings.

4.3 Sampling Tests.

4.3.1 Not less than one finished belt out of each 100 shipped on any order shall be assembled in the testing maching (see paragraph 4.2.2) and tested in tension under a static load of 1,500 pounds. After testing, there shall no signs of weakening of the webbing and stitching, slippage of the webbing through the adjusting hardware, or deformation of the metal fittings.

4.3.2 Belts subjected to the 1,500 pounds static test, shall be disposed of upon completion of the test, and shall not be counted as part of the order.

4.4 Rejection and Retests. Rejected safety belts shall not be resubmitted for inspection without furnishing full particulars concerning previous rejection and measures taken to overcome defects.

4.5 All parts, specimens, or assemblies destroyed in making tests required by this specification and drawings, to determine compliance with the specification and drawings, shall be in addition to the quantity specified in the contract or purchase order and shall be furnished without increasing the cost of the contract or order.

5. PACKAGING.

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.2).

~~5.1.1 Level A. The Harness shall be preserved and packaged Method III of~~ MIL-P-116 and placed in snug fitting box conforming to specification PPP-B-566.

5.1.2 Level C. The Harness shall be preserved and packaged in a manner that will afford adequate protection against deterioration and physical damage during shipment from the supply source to the first receiving activity for immediate use. This may conform to the supplier's commercial practice provided the latter meets the requirement of this level.

5.2 Packing. Packing shall be level A, B or C as specified (see 6.2).

5.2.1 Level A. The Harness preserved and packaged as specified in 5.1.1. shall be packed in a container conforming to class Weather Resistant of PPP-B-636. The closure of shipping container shall be in accordance with the appendix of the shipping container specification.

5.2.2 Level B. Same as Level A except the container shall be class Domestic of PPP-B-636.

5.2.3 Level C. The Harness preserved and packaged as specified in 5.1.1 shall be packed in a manner to insure carrier acceptance and safe delivery at destination.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:46Z
Check the source to verify that this is the current version before use.

Containers shall be in accordance with either the Uniform Freight Classification Rules or regulations of other carriers as applicable to the mode of Transportation.

6. NOTES.

6.1 Intended Use. The harness covered by this specification is intended for use by military personnel in aircraft using side facing seats (as a restraining safety harness.)

6.2 Ordering Data. Purchase requests and invitations for bids should specify whether the harness should be prepared for domestic or overseas shipment.

(a) Selection of applicable levels of preservation, packaging and packing (see 5.1 and 5.2).

6.3 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Air Force - 99

Preparing Activity:
Air Force 99

Project No. 1680-0498

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:46Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE
MIL-B-5428B

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 OCT 76 1426 PREVIOUS EDITION WILL BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:46Z
Check the source to verify that this is the current version before use.