INCH-POUND
MIL-DTL-5423/13E
9 August 2019
SUPERSEDING
MIL-DTL-5423/13D
17 February 2009

DETAIL SPECIFICATION SHEET

BOOT, DUST AND WATER SEAL, TYPE D (FOR LEVER OPERATED CIRCUIT BREAKERS), STYLE 1 (PANEL MOUNTED WITHOUT MOUNTING FRAME)

This specification sheet is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-5423.






FIGURE 1. Dimensions and configuration boots type D, style 1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:43Z
Check the source to verify that this is the current version before use.



(For number of screws and location see table II.)



Inches	mm
0.016	.41
0.5	12.7
0.906	23.01
1.000	25.40
1.812	46.02
2.500	63.50

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerances are ±.02 (.51mm) for two place decimals and ±.031 (.79 mm) for three place decimals.
4. The number of mounting screws shall be supplied as indicated.
5. Edges shall be smooth and free from burrs.

FIGURE 1. Dimensions and configuration boots type D, style 1 - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:43Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

Dimensions and configuration: See figure 1.

Silicon rubber: Grade 50, class III, transparent.

Splashproof: In accordance with MIL-STD-108, table I.

Endurance: 10,000 operations. Minute cracks after life test, which do not permit leakage, shall not be cause for rejection.

Part or Identifying Number (PIN): See tables I and II.

Table I. Dimensions.

PIN M5423/13-	Dimensions ±.031 (.79)			
	L1	W1	W2	L2
01	1.250 (31.75)	.750 (19.05)	.531 (13.49)	.60 (15.24)
02	1.312 (33.32)	1.500 (38.10)	1.250 (31.75)	.60 (15.24)
03	1.281 (32.54)	2.250 (57.15)	2.000 (50.80)	.60 (15.24)

Table II. Mounting holes, markings, and panel cutout.

PIN M5423/13-	Mounting holes			Markings	Panel cutout	
	Number of screws	Location				
		B	B1		X	Y
01	2	Yes	None	None	1.250 (31.75)	.531 (13.49)
02	4	None	.375 (9.53)	On-off	1.312 (33.32)	1.250 (31.75)
03	6	Yes	.750 (19.05)	None	1.281 (32.54)	2.000 (50.80)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:43Z
Check the source to verify that this is the current version before use.

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Referenced documents:
MIL-DTL-5423
MIL-STD-108
ASTM-A493

Custodians:
Army - CR
Navy - AS
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5930-2019-026)

Review activities:
Army - AT, AV, CR4, MI
Navy - CG, EC, MC

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/ .

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:43Z
Check the source to verify that this is the current version before use.