MILITARY SPECIFICATION

HYDRAULIC SYSTEMS, AIRCRAFT, TYPES I AND II, DESIGN AND INSTALLATION REQUIREMENTS FOR

This amendment forms a part of Military Specification MIL-H-5440G, dated 28 November 1975, and is approved for use by all Departments and Agencies of the Department of Defense

PAGE 3

2.1, under SPECIFICATIONS, Military, delete:

"MIL-C-8956	Clamps, Loop, Tube Support".

Add after MIL-F-83300:

"MIL-C-85052	Clamp, Loop, Cushion, General Specification for
MIL-C-85052/1	Clamp, Loop, Tube, 17-7PH CRES, 275°F, Fuel Resistant, General Purpose
MIL-C-85052/3	Clamp, Loop, Tube, 17-7PH CRES, 500°F, General Purpose".

PAGE 4

2.1 under STANDARDS, Military, delete:

"MS21105	Clamp, Loop Cushioned, Wedge, Fluid Resistant, 500°F, CRES, Type III, Class B".

PAGE 31

3.11.28.8 line 2, delete:
"MS21105 (MIL-C-8956, Type III, Class B)" and substitute:
"MIL-C-85052 (MIL-C-85052/1 or MIL-C-85052/3 to be compatible with temperature environment)".

PAGE 32

3.11.28.9, add:
"Marriage clamps shall not be used to support hydraulic tubing by adjacent runs of hydraulic tubing. Where required, marriage clamps may be used to maintain clearances between tubing runs."

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:47Z
Check the source to verify that this is the current version before use.

6.2.1.e, add:

"(4) Hydraulic system tubing life. Hydraulic system tubing (including quality items such as ovality) shall be analyzed to show durability for the expected life of the airframe. Additionally, the contractor shall describe the tube bending controls and tubing installation controls to ensure tubing durability."

Custodians:
Army - AV
Navy - AS
Air Force - 11

Review activity:
Air Force - 99

User activity:
Army - MI

Preparing activity:
Air Force - 11

Project 1650-0345

* U.S. GOVERNMENT PRINTING OFFICE: 1979—603-022/4017

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:47Z
Check the source to verify that this is the current version before use.