MILITARY SPECIFICATION

Transmitters, Pressure, Synchro, Aircraft,
165-Degree Movement

This amendment forms a part of Military Specification MIL-T-5483D(WP) dated 1 December 1964, and has been approved by the Naval Air Systems Command, Department of the Navy.

By this amendment basic Specification MIL-T-5483D(WP) is changed to MIL-T-5483D(AS), and throughout the specification Bureau of Naval Weapons shall be changed to Naval Air Systems Command.

Page 2

Paragraph 2.1 - Under "SPECIFICATIONS Military", delete reference to:

"MIL-R-23094	Reliability Assurance For Production Acceptance of Avionic Equipment, General Specification For
MIL-D-70327	Drawings, Engineering and Associated Lists"

Under "STANDARDS Military", add the following:

"MIL-STD-100	Engineering Drawing Practices
MIL-STD-781	Reliability Tests Exponential Distribution
MIL-STD-785	Reliability Program For Systems and Equipment Development and Production."

FSC 6620

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:51Z
Check the source to verify that this is the current version before use.

Page 3

Following the list of "STANDARDS Military", add the following heading:

"PUBLICATIONS Naval Air Systems Command, Requirement" and list the following:

"AR-34 Failure Classification For Reliability Testing, General Requirements For"

Page 7

Paragraph 3.6.1 - Delete this para. and substitute the following para:

"3.6.1 Reliability - The contractor shall conduct a reliability program using MIL-STD-785 as a guide. On a reorder from a supplier who has previously produced the equipment, the program previously used may be continued unless otherwise indicated in the contract or order."

Page 10

Paragraph 3.8 - Delete reference to "MIL-D-70327" and substitute "MIL-STD-100"

Pages 13, 14 & 15

Paragraphs 4.4.3 through 4.4.3.2 - Delete these paras. and substitute:

"4.4.3 Reliability Assurance Tests - Reliability Assurance Tests shall be conducted using MIL-STD-781. Qualification Phase and Sampling Phase Tests shall be conducted. Equipments selected for reliability assurance tests shall first have passed the individual tests. Test Levels of MIL-STD-781 shall be used for the reliability tests. Classification of failure shall be in accordance with MIL-STD-781 and AR-34. The test details such as the length of the Test cycle, the length of the heat portion of the cycle, the performance characteristics to be measured, special failure criteria, preventive maintenance to be allowed during the test, etc., shall be part of the test procedures to be submitted to and approved by the procuring activity prior to the beginning of the Reliability Qualification Test Phase of the Reliability Assurance Tests. As a minimum the test details shall include 4.4.3.3 Duty Cycle, 4.4.3.4 Performance Characteristics to be measured, 4.4.3.5 Failure Criteria, and 4.4.3.6 Preventive Maintenance.

4.4.3.1 Reliability Qualification Phase Tests - Prior to approval for listing on the Qualified Products Lists, a minimum of three (3) equipments shall be tested as outlined in MIL-STD-781, under the section

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:51Z
Check the source to verify that this is the current version before use.

entitled "Qualification Phase of Production Reliability Tests." The maximum number of equipments to be used shall be those listed in Table 5 of MIL-STD-781. For the Qualification Phase Test Level E and the Accept-Reject Criteria for Test Plan I shall be used.

4.4.3.2 Reliability Sampling Phase Tests - Samples of the equipment shall be tested,throughout production, as outlined in MIL-STD-781 under the section entitled "Sampling Phase of Production Reliability Tests." Test level E shall be used. The Accept-Reject Criteria for Test Plan II shall be used to determine the length of the tests (until an accept or reject decision is reached).

4.4.3.2.1 Lot Size for Sampling Phase - Each consecutive 15 transmitters produced shall be considered a lot. At least one sample shall be chosen at random from each lot."

Page 17

Table I - Delete this table and replace with the Table I on page 4 of this amendment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:51Z
Check the source to verify that this is the current version before use.

TABLE I

Test Points and Tolerances for Test Conditions
Tolerances are Plus or Minus PSI

Range, PSI	0-20	50	100	200	300	500	1000	2000	5000
Test Points, PSI	0 4 8 12 16 20	0 10 20 30 40 50	0 20 40 60 80 100	0 40 80 120 160 200	0 60 120 180 240 300	0 100 200 300 400 500	0 200 400 600 800 1000	0 400 800 1200 1600 2000	0 1000 2000 3000 4000 5000
Overpressure, PSI	40	100	200	400	600	1000	1500	3000	6000
Tolerances, PSI									
Scale error at room temperature	0.4	1.0	2.0	4	6	10	20	40	100
Friction error	0.2	0.5	1.0	2	3	5	10	20	50
Position error	0.2	0.5	1.0	2	3	5	10	20	50
Sensors matching (for differential transmitters only)									
1/5 Range	0.5	1.2	2.5	5	7	12	-	-	-
2/5 Range	0.6	1.5	3.0	6	8	15	-	-	-
3/5 Range	0.7	1.8	3.5	7	9	18	-	-	-
4/5 Range	0.8	2.0	4.0	8	10	20	-	-	-
Full Range	0.9	2.3	4.5	9	11	23	-	-	-
Vacuum	0.5	1.2	2.5	5	7	12	-	-	-
Seasoning	0.4	1.0	2.0	4	6	10	20	40	100
High temperature	0.6	1.5	3.0	6	9	15	30	60	150
Low temperature	0.8	2.0	4.0	8	12	20	40	80	200
Vibration error	0.2	0.5	1.0	2	3	5	10	20	50
Vibration failure	0.4	1.0	2.0	4	6	10	20	40	100
Endurance	0.7	2.0	3.5	7	12	20	40	80	200
Scale error overpressure	0.4	1.0	2.0	4	6	10	20	40	100

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:51Z
Check the source to verify that this is the current version before use.