MIL-T-52864/2B
22 April 1987
SUPERSEDING
MIL-T-52864/2A
1 June 1983

MILITARY SPECIFICATION SHEET

TRUCK, LIFT, FORK: DIESEL-ENGINE-DRIVEN, PNEUMATIC-TIRED,

15,000 POUND CAPACITY AT 24-INCH

LOAD CENTER, 100-INCH LIFT

The complete requirements for acquiring the truck described herein shall consist of this specification and the latest issue of MIL-T-52864.

REQUIREMENTS

1. Capacity: 15,000 pounds at 24-inch load center.
2. Collapsed mast height: 95 inches maximum.
3. Maximum fork height: 100 inches minimum.
4. Free lift height: As applicable.
5. Fork size: 2-9/16 inches maximum thickness X 8-1/16 inches maximum width X 48 inches long, +0 inch -1/2 inch.
6. Fork spacing: 18 inches to minimum 60 inches.
7. Overhead guard height: 116 inches maximum.
8. Right-angle turn dimension "A": 240 inches maximum.
9. Underclearance beneath mast assembly: 6 inches minimum.
10. Transmission: Not less than two speeds forward and two speeds reverse.

Custodian:
Army – ME
Navy - SA
Air Force – 99

Preparing activity:
Army - ME

Project 3930-0625

Review activity:
Army – SM
Navy - OS

User activities:
Army - MT
Navy - MC

AMSC N/A FSC 3930

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:36Z
Check the source to verify that this is the current version before use.