MIL-T-52864/5A
1 June 1983
SUPERSEDING
MIL-T-52864/5
16 June 1975

MILITARY SPECIFICATION SHEET

# TRUCK, LIFT, FORK: DIESEL-ENGINE-DRIVEN, PNEUMATIC-TIRED, 20,000-POUND CAPACITY AT 24-INCH LOAD CENTER, 210-INCH LIFT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the truck described herein shall consist of this document and the latest issue of MIL-T-52864.

## REQUIREMENTS

1. Capacity: 20,000 pounds at 24-inch load center.
2. Collapsed mast height: 165 inches maximum.
3. Maximum fork height: 210 inches minimum.
4. Free lift height: As applicable.
5. Fork size: 3-1/16 inches maximum thickness X 10-1/16 inches maximum width X 72 inches long, plus 0 inch minus 1/2 inch.
6. Fork spacing: 22 inches to minimum 64 inches.
7. Overhead guard height: 116 inches maximum.
8. Right-angle turn dimension "A": 272 inches maximum.
9. Underclearance beneath mast assembly: 8 inches minimum.
10. Transmission: Not less than three speeds forward and three speeds reverse.

Custodians:
Army - ME
Navy - SA
Air Force - 99

Review activity:
Army - SM

User activities:
Army - MT
Navy - MC, SH

Preparing activity
Army - ME

Project 3930-0504

FSC 3930

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:37Z
Check the source to verify that this is the current version before use.