MIL-T-52864/6A
1 June 1983
SUPERSEDING
MIL-T-52864/6
16 June 1975

MILITARY SPECIFICATION SHEET

TRUCK, LIFT, FORK, DIESEL-ENGINE-DRIVEN, PNEUMATIC-TIRED,

10,000-POUND CAPACITY AT 48-INCH

LOAD CENTER, 150-INCH LIFT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirement for procuring the truck described herein shall consist of this document and the latest issue of MIL-T-52864.

REQUIREMENTS

1. Capacity: 10,000 pounds at 48-inch load center.
2. Collapsed mast height: 95 inches maximum.
3. Maximum fork height: 150 inches minimum.
4. Free lift height: 25 inches minimum.
5. Fork size: 2-9/16 inches maximum thickness X 8-1/16 inches maximum width X 72 inches long, plus 0 inch minus 1/2 inch.
6. Fork spacing: 18 inches to minimum 60 inches.
7. Overhead guard height: 95 inches maximum.
8. Right-angle turn dimension "A": 290 inches maximum.
9. Underclearance beneath mast assembly: 6 inches minimum.
10. Transmission: Not less than two speeds forward and two speeds reverse.

Custodians:
Army – ME
Navy - SA
Air Force – 99

Preparing activity
Army - ME

Project 3930-0505

Review activity:
Army - SM

User activities
Army - MT
Navy - MC, SH

FSC 3930

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:37Z
Check the source to verify that this is the current version before use.