MILITARY SPECIFICATION

PILLOW, BED, Polyester Fiber

This Limited Coordination Military Specification has been prepared by the Defense Personnel Support Center based upon currently available technical information. It is subject to modification. However, pending its promulgation as a Coordinated Military Specification, it may be used in procurement.

1. SCOPE

1.1 Scope. This specification covers the requirements for a polyester fiber filled bed pillow.

1.2 Classification.

1.2.1 The pillow shall be of one type and size.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Federal

V-T-276	Thread, Cotton
UU-P-268	Paper, Kraft, Untreated Wrapping
CCC-C-436	Cloth, Ticking, Twill, Cotton
DDD-L-20	Label; for Clothing, Equipage, and Tentage, (General Use).
PPP-B-636	Box, Shipping, Fiberboard.

FSC 7210

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:50Z
Check the source to verify that this is the current version before use.

STANDARDS

Federal

FED-TEST METHOD STD NO. 191	Textile Test Methods
FED STD NO. 751	Stitches, Seams, and Stitchings

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	Marking for Shipment and Storage.
MIL-STD-147	Palletized and Containerized Unit Loads for 40" x 48" Pallets.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposals shall apply.

National Motor Freight Traffic Association, Inc., Agent
National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, D. C. 20036.)

Uniform Classification Committee, Agent

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, Illinois 60606.)

Rules and Regulations Under the Textile Fiber Products Identification Act.

(Copies may be obtained without charge from the Federal Trade Commission, Washington, D. C. 20580).

3. REQUIREMENTS

3.1 Materials.

3.1.1 Ticking. The cotton ticking shall conform to Type II, class 1 of CCC-C-436.

Source: https://assist.dla.mil -- Downloaded: 202610-21T09:50Z
Check the source to verify that this is the current version before use.

3.1.2 Filler. The filler shall be 100% prime grade virgin polyester fiber (as defined in 3.1.2.1) formed into an even batt of an approved fiberfill material (see 6.3). The batt shall be garnet-opened and cross-lapped, and then rolled for consistent density and firmness in the final form. The batt shall have a density of one ounce per square foot, using polyester of nominal 4-3/4 denier, 2 inch filament length. The finished pillow shall contain a minimum of 24 ounces of filler. The use of airblown or garnetted clippings is prohibited.

3.1.2.1 Virgin (as defined in the Textile Fiber Product Identification Act) polyester fiber (see 3.1.2.2).- The use of any form of polyester waste is prohibited, e.g., undrawn fiber, mixture of deniers, lusters or cross sections, and waste from any stage of fiber production; whether drawn, undrawn or mixed or garnetted fiber.

3.1.2.2 Certificate of compliance.- A certificate of compliance is mandatory for this requirement and it shall include: A certified statement that the fiber used is that specified in 3.1.2 above, along with the fiber supplier's type and identification data supported by a certified copy of the fiber producer's certification to the manufacturer of pillows (see 3.1.2.1).

3.1.3 Thread.- The thread utilized in the fabrication of the pillows shall be ticket No. 30, 3 ply, type IA1 (unbleached) or Type IA2 (white), conforming to V-T-276 except that the looper thread shall be ticket No. 50, 3 ply when the 401 stitch is used.

3.2 Size.- The finished pillow shall be rectangular in shape and shall be 21 $\pm$ 1/2 inches in width and 28 $\pm$ 1/2 inches in length. Length and width measurements of the filled and closed pillow shall be determined from end of seam to end of seam.

3.3 Construction.- Pillows shall be made of one piece of ticking with the stripes in the widthwise direction (shorter dimension) of the pillow. The case shall be seamed inside-out leaving one end open. The end opening shall be seamed after turning the case right side out and filling the pillow (see 3.3.2). Stitching shall be not less than 1/4 inch from the edges of the material except that stitching on final closure shall be not less than 1/8 inch from the edge. One end of the identification label and instruction label shall be securely stitched into the closing seam or the seam opposite the closing seam of the pillow. When separate state label is legally required by the state in which the pillow is manufactured, the state label shall be securely stitched adjacent to and in the same seam as the identification label.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:50Z
Check the source to verify that this is the current version before use.

3.3.1 Stitches, seams, and stitchings. Stitches, seams, and stitchings shall conform to the requirements of FED. STD. 751. All stitches except closing seam shall be stitch type 301 or type 401. The closing seam shall be stitch type 301. Stitches shall be 10 ± 2 stitches per inch. All seams, except closing seam, shall be seam type SSa-1. The closing seam shall be seam SSc-1. Ends of all stitching produced with type 301 stitch, when not caught in other seams and stitching, shall be backtacked not less than 1/4 inch. Both ends of all seams and stitching produced with 401 stitch type when not caught in other seams or stitching shall have a 1/2 inch minimum chain extending beyond each end. Thread breaks (all stitch types) shall be secured by stitching back of the break not less than 1 inch. Skipped stitches or thread breaks (401 stitch type) may be repaired by using type 301 stitch. Seam allowances shall be maintained with seams properly sewn so that no raw edges, runoffs, twists, pleats, puckers, or open seams will result.

3.3.2 Filling the pillow case. A funnel shaped compression chute or suitable mechanical means shall be used to place the fiberfill batt into the casing. The use of a blower attachment for placing the fiberfill into the casing is prohibited. Underweight batts shall not be "pieced in".

3.4 Labels

3.4.1 State labeling requirements.- When required, each pillow shall have a label attached to conform with the legal requirements of the state in which it is manufactured. When allowed under state law, the information required under state regulations may be combined in the identification label.

3.4.2 Identification and size label (see 3.4.4).- Each pillow shall have a combination identification and size label conforming to type I, class 4 of DDD-L-20. The end item is intended to be laundered.

3.4.3 Instruction label (see 3.4.4).- Each pillow shall have an instruction label conforming to type I, class 3 of DDD-L-20. The end item is intended to be laundered. The content shall be as follows:

CARE INSTRUCTIONS
Launder and dry by Formula G of TM 10-354 (Army).
Tumble dry at 150 to 180°F.

3.4.4 The identification, size and instruction labels may be combined into one combination label.

3.5 Workmanship.- The pillows shall conform to the quality and grade of product established by this specification. The occurrence of defects shall not exceed the applicable acceptable quality levels.

Source: https://assist.dla.mil -- Downloaded: 202610-21T09:50Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.1 Certificate of compliance.- Where certificates of compliance are submitted, the Government reserves the right to check test such items to determine the validity of the certification.

4.2 Quality conformance inspection.- Sampling for inspection shall be performed in accordance with MIL-STD-105 except where otherwise indicated hereinafter.

4.2.1 In process inspection.- Inspection shall be made during the filling of the pillows to determine whether the operation is accomplished as specified in 3.3.2. The Government reserves the right to exclude from consideration for acceptance any material or service for which in-process inspection has indicated nonconformance.

4.2.2 Intermediate inspection.-

4.2.2.1 Visual examination of cases. Examinations of unfilled ticking cases shall be made. Defects of construction and workmanship in the inner seams shall be classified in accordance with table I. The sample unit for this examination shall be one ticking case, inside out. The inspection level shall be S-3 and the acceptable quality level (AQL) shall be 2.5 defects per hundred units.

TABLE I. Intermediate examination defects

Examine	Defect
Construction and workmanship	Not specified stitch type Not specified seam type. Less than 8 stitches per inch. More than 12 stitches per inch. Any open seam.
NOTE:	A seam shall be classified as open when one or more stitches joining a seam are broken, or when two or more consecutive skipped or runoff stitches occur.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:50Z
Check the source to verify that this is the current version before use.

TABLE I. Intermediate examination defects (cont'd)

Examine	Defect
	Stripes not in widthwise direction Stitching less than 1/4 inch from edge of material, except on final closure. Loose tension resulting in a loose seam. Tight tension (stitches break when normal pull tension is applied). Stitching irregular or uneven, resulting in twisted, pleated or bulging edges. Ends of seams produced with 301 stitch type (When not caught in other seams or stitching) back-tacked less than 1/4 inch. Ends of seams produced with 401 stitch type (When not caught in other seams or stitching) not having chain extending beyond each end, or having chain extending less than 1/2 inch beyond each end. Any thread break not backstitched a minimum of 1 inch.

4.2.3 Determination of weight of ticking cases. A determination for average weight of ticking cases shall be made for each lot. This determination is for use in calculating the weight of fiberfill in the finished pillows, see 4.2.4.2. The average ticking case weight shall be the average weight obtained from weighing not less than 100 ticking cases in the lot.

4.2.4 Inspection of the end item.

4.2.4.1 Examination for visual characteristics. Examination shall be made for defects in material, workmanship, cleanness, construction, and marking. All defects shall be classified in accordance with table II. The qualification "clearly visible", shall be based on normal inspection distance of a nominal 3 feet. The sample unit for this examination shall be one completely fabricated pillow. The inspection level shall be S-3 and the AQL shall be 1.5 major defects per 100 units and 4.0 total defects per 100 units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:50Z
Check the source to verify that this is the current version before use.

TABLE II. End item defect classification

Examine	Defect	Classification Major	Minor
Quality of material	Hole, cut, tear or any mend	X	
	Any smash	X	
	Abrasion mark, tender or weak place	X	
	Broken or missing yarns, two or more contiguous	X	
	Crack, clearly visible	X	
	Slub, more than three times the thickness of normal yarns		X
	Any spot, stain or streak, clearly visible		X
Cleanness	Untrimmed thread ends on exterior of pillow, fiberfill not removed throughout outside of pillow		X
	Offensive or objectionable odor	X	
Construction and workmanship (of closing seam only)	Formation of lumps.	X	
	Loose tension resulting in loose seam	X	
	Tight tension (stitches break when normal pull tension is applied)	X	
	Ends of seams produced with 301 stitch type (when not caught in other seams or stitching) backtacked less than 1/4 inch		X
	Stitching irregular or uneven, resulting in badly twisted, pleated or bulging edges	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:50Z
Check the source to verify that this is the current version before use.

TABLE II. End item defect classification (cont'd)

Examine		Defect	Classification Major	Classification Minor
Construction and workmanship (of closing seam only) (cont'd)		Any thread break not backstitched a minimum of one inch		X
		Any open seam	X	
	NOTE:	A seam shall be classified as open when one or more stitches are broken, or when two or more consecutive skipped or runoff stitches occur.		
		Wrong seam or stitch type: -Seriously affecting serviceability	X	
		-Affecting serviceability but not seriously		X
		Raw edge over 1/2 inch in length	X	
		Raw edge over 1/4 inch up to and including 1/2 inch in length		X
	NOTE:	Raw edge not securely caught in stitching shall be classified as open seam		
		Two or more stitches per inch less or more than required	X	
		One stitch per inch less or more than required		X
		Covering spliced or not fabricated of one piece of material	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:50Z
Check the source to verify that this is the current version before use.

TABLE II. End item defect classification (cont'd)

Examine	Defect	Classification Major	Minor
Construction and workmanship (of closing seam only) (cont'd)	Row of stitching less than 1/8 inch from edge		X
Label or labels	Missing, incorrect, illegible or not securely attached		X

4.2.4.2 Weight of fiberfill (3.1.2). Determination shall be made of the weight of fiberfill contained in the finished pillow, calculated as the total weight of the pillow minus the average weight of the ticking case as determined in 4.2.3. Any weight of fiberfill which is less than the specified minimum shall be classified as a defect with respect to weight of fiberfill. The sample unit for this examination shall be one completely finished pillow. The inspection level shall be level S-3 and the AQL shall be 2.5 defects per 100 units.

4.2.4.3 Examination for dimensions. Examination shall be made to determine compliance with the applicable dimensional requirements. Dimensions shall be along seams, from end of seam to end of seam. Any dimension that is not within the specified tolerances for dimensions in 3.2 shall be classified as a defect with respect to dimensions. The sample unit for this examination shall be one completely finished pillow. The inspection level shall be level S-3 and the AQL shall be 2.5 defects per 100 units.

4.3 Examination of preparation for delivery requirements. An examination shall be made to determine that packaging, packing and marking comply with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully prepared for delivery except that it need not be closed. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 2.5 defects per hundred units.

Examine	Defect
Marking (exterior and interior)	Omitted, incorrect, illegible, of improper size, location, sequence or method of application
Materials	Any component missing, damaged or not as specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:50Z
Check the source to verify that this is the current version before use.

Examine	Defect
Workmanship	Inadequate application of components, such as: incomplete closure of container flaps, loose strapping, improper taping or inadequate stapling. Open and non-continuous heat sealed seams and closure of polyethylene bag. Incorrectly fabricated bag. Provisions for escape of air not as specified. Bulged or distorted containers.
Content	Number of packages per shipping container is more or less than required.

4.3.1 Examination for palletization. An examination shall be made to determine that the palletization complies with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one palletized unit load fully prepared for delivery. The lot size shall be the number of palletized unit loads in the end item inspection lot. The inspection level shall be S-1 and the AQL shall be 6.5 defects per hundred units.

Finished dimension	Length, width, or height exceeds specified maximum requirements.
Palletization	Not as specified. Pallet pattern not as specified. Load not bonded with required straps as specified.
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence or method of application.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:50Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or C as specified (see 6.2).

5.1.1 Unit of issue. One pillow, as specified, constitutes one unit of issue.

5.1.2 Level A. Each pillow shall be inserted in a close-fitting clear polyethylene film bag having a thickness of 0.00125-inch (± 25 percent tolerance). The bag shall be formed with heat sealed seams that are straight, continuous and parallel to each other and the formed edges of the bag. The final closure of the bag shall be heat sealed with the heat seal made as close as possible to the open end. The bag may be fabricated from polyethylene film tubing or sheeting. Open vents of approximately one inch at each side of the closure or a 1/2 inch hole in each of the opposite corners of the bag shall be provided for the escape of excess air. Alternatively, the final closure of the bag shall be accomplished by folding over and securing the open end of the bag body with pressure-sensitive tape.

5.1.3 Level C. Pillows shall be packaged to afford adequate protection against physical damage during shipment from the supply source to the first receiving activity. The supplier may use his standard practice when it meets this requirement.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. Ten pillows, packaged as specified shall be packed in a fiberboard shipping container conforming to style RSC-L, grade V3c of PPP-B-636. The inside of each shipping container shall be fitted with a taped box liner conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-B-636. Level A packages shall be packed flat, five in depth within the shipping container. Inside dimensions of each shipping container shall approximate 44 inches in length, 17-3/4 inches in width, and 19-1/2 inches in depth. Approximate dimensions are furnished as a guide only. Each container shall have the contents completely covered on the top and bottom with a sheet of 30 pound minimum basis weight kraft paper conforming to grade B of UU-P-268. Prior to closure of the shipping container sufficient compression shall be applied to the pillows to insure proper closure of the container. Each shipping container shall be closed in accordance with method V, and strapped as specified in the appendix of PPP-B-636.

5.2.2 Level B. Ten pillows, packaged as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC-L, type CF (variety SW) or SF, class domestic, grade 200 of PPP-B-636. The inside of each shipping container shall be fitted with a taped box liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. Level A packages shall be packed flat, five in depth within the shipping container. Inside dimensions of each shipping container shall approximate 44 inches in length, 17-3/4 inches in width, and 19-1/2 inches in depth. Approximate dimensions are furnished as a guide only. Each container shall have the contents completely covered on the top and bottom with a sheet of 30 pound minimum basis weight kraft paper conforming to

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:50Z
Check the source to verify that this is the current version before use.

grade B of UU-P-268. Prior to closure of the shipping container sufficient compression shall be applied to the pillows to insure proper closure of the container. Each shipping container shall be closed in accordance with method II and reinforced as specified in the appendix of PPP-B-636.

5.2.3 Level C. Pillows packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification Rules or National Motor Freight Classification Rules as applicable.

5.3 Marking. Each unit package (plastic bag) and each exterior container shall be marked in accordance with MIL-STD-129.

NOTE: Marking may be printed directly on the plastic bag or on paper label inserted within the bag, in such a manner, so as to permit ready identification.

6. NOTES

6.1 Intended use. The pillows are primarily intended for use as bed pillows.

6.2 Ordering data. Procuring documents specify the following:

(a) Title, number, and date of this specification.

(b) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).

(c) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).

(d) When palletization is not required (see 5.3).

6.3 The following products are approved (see 3.1.2):

a. Celanese - Fortrel 7 Polyester Fiberfill
b. DuPont - Dacron Fiberfill II
c. Eastman - Kodel Fiberfill 232

6.4 The pillow covered by this specification is listed in the Federal Supply Catalog under the following stock number:

National Stock Number	Item Identification
7210-00-119-5358	PILLOW, BED, Polyester Fiber

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:50Z
Check the source to verify that this is the current version before use.

6.5 This specification does not include all types, classes, grades, or sizes of the commodity indicated by the title of this specification, or which are commercially available, but is intended to cover the types which are normally procured to meet military requirements.

Custodians:
Army - MD
Navy - MS
Air Force - 03

Review activities:
Army - MD
Navy - MS
Air Force - 03

Preparing activity:
Defense Supply Agency - DM

Project No. 7210-0192

Review information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on the information in the current DODISS.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:50Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:50Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

MIL-P-37042 (DSA-DM)

NAME OF ORGANIZATION AND ADDRESS	CONTRACT NUMBER
	MATERIAL PROCURED UNDER A ☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:50Z
Check the source to verify that this is the current version before use.

FOLD

DEFENSE PERSONNEL SUPPORT CENTER
2800 South 20th Street
Philadelphia, Pa. 19101

POSTAGE AND FEES PAID
DEFENSE SUPPLY AGENCY
DoD - 304



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

HEADQUARTERS, DEFENSE PERSONNEL SUPPORT CENTER
ATTN: DIRECTORATE OF MEDICAL MATERIEL, CODE ATT
2800 SOUTH 20TH STREET
PHILADELPHIA, PA. 19101

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:50Z
Check the source to verify that this is the current version before use.