MILITARY SPECIFICATION

SEMICONDUCTOR DEVICE, TRANSISTOR, PNP, SILICON, POWER
TYPES 2N5967, 2N5969, TX2N5967, AND TX2N5969

Inactive for new design after the date of this amendment.

This amendment forms a part of Military Specification MIL-S-19500/459A(EL), dated 5 October 1973, and is approved for use by US Army Electronics Research and Development Command, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

TITLE, delete and substitute:

"SEMICONDUCTOR DEVICE, TRANSISTOR, PNP, SILICON, POWER
TYPES 2N5967 and 2N5969
NON-TX, TX, AND TXV"

1.1: At end of paragraph, add "The prefix 'TXV' is used on devices submitted to and passing the internal visual inspection specified in 4.7."

PAGE 4

Add the following new paragraphs:

"3.3.2 Internal visual (PRECAP) inspection and process-conditioning, testing, and screening of 'TXV' types. The 'TXV' device type shall, in addition to all performance requirements, be internally visually inspected and process-conditioned, tested, and screened in accordance with 4.7."

"3.4.2 'TXV' identification marking. Devices in accordance with the 'TXV' requirements shall include the additional marking 'TXV' preceding the type designation."

* 4.2, delete "Qualification and Quality Conformance Inspection" and substitute "Qualification is not required. Quality Conformance Inspection." Line 4, delete "Tables I, II, and III" and substitute "Table I (100 percent), Tables II and III (LTPD)."

* 4.2.2 and 4.2.2.1, delete in their entirety.

PAGE 8

Add the following new paragraph:

"4.7 Internal visual (PRECAP) inspection and process-conditioning, testing, and screening of 'TXV' types. The internal visual inspection shall be performed in accordance with test method 2072 of MIL-STD-750 prior to encapsulation on a 100 percent basis and shall also include process-conditioning, testing, and screening as specified in 4.4.1 through 4.4.7.4. The manufacturer shall permit the authorized government representative to witness concurrent with time of manufacturer's performance of these tests, the process-conditioning, testing, and screening of the devices. Those conditioning and screening tests normally performed by a manufacturer as standard production tests, need not be repeated when these are predesignated and acceptable to the Government as being equal to or more severe than the test specified herein."

PAGES 9 and 10

* TABLE I, LTPD column, delete in their entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:11Z
Check the source to verify that this is the current version before use.

PAGE 11

TABLE II, Group B inspection, LTPD column, TX subcolumn, add "TXV".

PAGE 12

TABLE II, Group B inspection, LTPD column, TX subcolumn, add "TXV".

PAGE 13

TABLE II, Group B inspection, LTPD column, TX subcolumn, add "TXV".

PAGE 14

TABLE II, Group B inspection, LTPD column, TX subcolumn, add "TXV".

PAGE 15

TABLE III, Group C inspection, LTPD column, TX subcolumn, add "TXV".

PAGE 22

6.6, delete in its entirety.

The margins of this amendment are marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army - ER

Agent:
DLA - ES

Preparing activity:
Army - ER

(Project 5961-A850-4)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:11Z
Check the source to verify that this is the current version before use.