FED. SUP CLASS
6640



PART NUMBER	DIAMETER MM	DIAMETER VARIATION MM	LENGTH ± 6 MM
MS35998-1	2	.4	1219†
MS35998-6	3	.4	1219
MS35998-2	4	.4	1219
MS35998-7	5	.4	1219
MS35998-3	6	.4	1219
MS35998-8	7	.4	1219
MS35998-4	8	.4	1219
MS35998-9	9	.4	1219
MS35998-5	10	.4	1219
MS35998-10	11	.4	1219

† 1219 mm equals approximately 48 inches.

MATERIAL: Rods shall be of borosilicate glass in accordance with ASTM E 438, Type I, Class A.

DESIGN: Rods shall be cylindrically shaped with square ends.

NOTES:
1. Items differing from this Military Standard by minor variations in design or dimensions are considered standard under this document, provided such variations do not affect performance and are not in conflict with the material requirements specified herein.
2. Referenced documents shall be of the issue in effect on date of invitations for bid.
3. FSCM: 14674, 18575, 21519, 64484, 84116.

APPROVED 16 Nov 1959 REVISED (A) 20 June 1969 (B) 4 Dec 1985

(B) ENTIRE STANDARD REVISED

P.A. EA	INTERNATIONAL INTEREST	TITLE ROD, GLASS	MILITARY STANDARD
Other Cust MS 99			MS35998
Procurement Specifications NONE	SUPERSEDES:		SHEET 1 OF 1

DD FORM 1 MAY 73 672 (COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE PROJECT NUMBER 6640-1308

USER ACTIVITIES: ARMY - ME, EA; NAVY - MS; AIR FORCE - 03

REVIEWER ACTIVITIES: ARMY - MD; NAVY - AS, YD

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:32Z
Check the source to verify that this is the current version before use.