REVIEW ACTIVITIES: ARMY - MD
NAVY - AS, OS, TD
USER ACTIVITIES: ARMY - MR, PS
NAVY - MC

FED. SUP CLASS
6640



BEADED OR TOOLED RIM RING NECK GROUND JOINT

PART NUMBER	CAPACITY (ml)	NECK STYLE	MOUTH DATA		
			STYLE	STOPPER SIZE ACCOMMODATED	GROUND JOINT SIZE
MS36054-1	125	short	ground joint		24/40
MS36054-2	250	long	beaded or tooled rim	4 or 5	
MS36054-3	250	short	ground joint		24/40
MS36054-4	500	long	beaded or tooled rim	5 or 6	
MS36054-5	500	long	ring neck	6	
MS36054-6	1000	long	beaded or tooled rim	7 or 8	
MS36054-7	1000	long	ring neck	7 or 8	
MS36054-8	3000	long	beaded or tooled rim	9	

MATERIAL: Borosilicate glass in accordance with Federal Specification DD-G-541, Type I, Class A.

DESIGN: Each flask shall have a marking area located in accordance with commercial practice.

Each flask shall be permanently and legibly marked with manufacturer's name or trademark and capacity.

Mouths shall be designed to accommodate standard rubber stoppers as specified in Federal Specification ZZ-S-751.

Mouths designed to accommodate ground joints shall be in accordance with Federal Specification DD-G-675, Type I, Composition 1, Grade A.

NOTES:
1. Flasks are not supplied with stoppers.
2. Items differing from this Military Standard by minor variations in design or dimensions are considered standard under this document, provided such variations do not affect performance and are not in conflict with the material requirements as specified herein.
3. For design feature purposes this standard takes precedence over procurement documents referenced herein.
4. Referenced documents shall be of the issue in effect on date of invitations for bid.

APPROVED 29 Jun 1960 REVISED (A) 15 Aug 1969

(A) ENTIRE STANDARD REVISED

P.A. MU Other Cust MS 82	TITLE FLASK, BOILING flat bottom	MILITARY STANDARD MS36054	
PROCUREMENT SPECIFICATION NNN-F-240	SUPERSEDES:	SHEET 1 OF 1	

DD FORM 1 SEP 67 672-1 (Coordinated)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

☆ U. S. GOVERNMENT PRINTING OFFICE: 1969-353-643/5-1343

This military standard is approved by the Department of Defense and is mandatory on all activities. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:33Z
Check the source to verify that this is the current version before use.