MILITARY SPECIFICATION

BOOSTER, FUZE, MARK 60 MOD 2

This amendment forms a part of Military Specification MIL-B-85599(AS) Dated 17 October 1983, and is approved for use within the Naval Air Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 6

4.2.2, line 10, Delete: "Table B-1, k value" and substitute "Table B-1, Sample size code letter G, k value."

PAGE 13

4.6.3.3b, Delete in its entirety and substitute:

"4.6.3.3b, Subject the booster to the test of MIL-STD-810, Method 514.2, Equipment Category d.1, Procedure IIA, Table 514.2-IV, Figure 514.2-4, parametric values f1=1000 Hz., f2=2000 Hz., w1=.01 g2/Hz., w2=.12 g2/Hz. The vibration shall be applied for a period of one hour along each of three mutually perpendicular axes, for a total test time of three hours. First article boosters shall be temperature-conditioned to and vibrated at the following temperatures (see Figure 4):

(1) Ten boosters at +160 $\pm 5^{0}$F.
(2) Ten boosters at -65 $\pm 5^{0}$F.

NOTE: To prevent damage to test equipment, limiting of instantaneous acceleration peaks to three times the overall root-mean-square acceleration level is permitted."

PAGE 14

4.6.4.3, Before warning note add the following note:

"NOTE

A New FSU-10/A simulator (SA1137AS2160-102) will be required for each cook-off test."

FSC 1336

AMSC N/A

Preparing activity
Navy - AS
(Project 1336-N534)

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:12Z
Check the source to verify that this is the current version before use.