MILITARY SPECIFICATION

LOW LEVEL SIGNALING DEVICE TT-523( )/GGC

1. SCOPE

1.1 This specification covers one type of teletype signal processor designated as Low Level Signaling Device TT-523( )/GGC.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-T-76	Tape, Pressure-Sensitive Adhesive Paper (for carton sealing)
PPP-T-97	Tape, Pressure-Sensitive Adhesive Filament Reinforced
PPP-F-320	Corrugated Padding
PPP-B-566	Boxes, Folding, Paperboard
PPP-B-636	Boxes, Fiberboard
PPP-B-640	Box, Fiberboard, Corrugated Triple Wall
PPP-S-760	Strapping Nonmetallic and Connectors
PPP-C-843	Cushioning Material, Cellulosic

MILITARY

MIL-P-116	Preservation, Method of
MIL-L-6085	Lubricating Oil; Aircraft Instrument, Low Volatility
MIL-R-11177	Reperforator, Teletypewriter Set (AN/GGC-3( ))
MIL-P-11268	Parts, Materials and Processes Used in Electronic Communication Equipment
MIL-M-13231	Marking of Electronic Items
MIL-F-14072	Finishes for Ground Signal Equipment
MIL-G-23827	Grease, Aircraft and Instrument, Gear and Actuator Screw

FSC 5815

Source: https://assist.dla.mil -- Downloaded: 202610-22T23:49Z
Check the source to verify that this is the current version before use.

MIL-B-43291	Boxes, Fiberboard, Corrugated, Double Wall, Weather Resistant
MIL-I-46058	Insulating Compound Electrical (for coating printed circuit assemblies)

STANDARDS

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by attributes
MIL-STD-129	Marking for Shipment and Storage
MIL-STD-147	Palletized and Containerized Unit Loads 40 Inch x 48 Inch Pallets, Skids, Runners, or Pallet Type Base
MIL-STD-252	Wired Equipment, Classification of Visual and Mechanical Defects
MIL-STD-454	Standard General Requirements for Electronic Equipment
MIL-STD-461	Electromagnetic Interference Characteristics Requirements for Equipment
MIL-STD-462	Electromagnetic Interference Characteristics Measurement of
MIL-STD-810	Environmental Test Methods

DRAWINGS

ELECTRONICS COMMAND

SC-DL-603719	Low Level Signaling Device TT-523()/GGC
SM-A-603723	Manufacturing Test Process for Low Level Signaling Device TT-523A/GGC

(Copies of specifications, standards, drawings, required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer. Both the title and number or symbol should be stipulated when requesting copies).

3. REQUIREMENTS

3.1 Description.- Low Level Signaling Device TT-523( )/GGC is intended for operation with Teletypewriter Sets TT-76A, B, or C/GGC to reduce the current and voltage at the teletypewriter contacts to a low level and then to amplify it for operation of the selector magnet.

3.2 First Article (preproduction) samples.- The contractor shall furnish two preproduction samples for approval, if required by the invitation for bid and contract.

Source: https://assist.dla.mil -- Downloaded: 202610-22T23:49Z
Check the source to verify that this is the current version before use.

3.3 Construction.- The equipment shall be constructed in accordance with the requirements of this specification and of Drawing and Data List SC-DL-603719.

3.4 Parts, materials and processes; general.- In addition to the requirements of this specification, the requirements of MIL-P-11268, including the selection requirements therein, shall apply.

3.5 Finish.- The equipment shall be finished in accordance with MIL-F-14072 and the equipment drawings. (See 4.4)

3.6 Marking.- (See 4.4)

3.6.1 General.- Marking shall conform to MIL-M-13231. Front panel marking shall be Group I as described in that specification.

3.6.2 Visibility.- Whenever practicable, parts shall be so mounted that their identification markings will be readily visible with minimum disassembly of the equipment.

3.6.3 Serial numbers.- The equipment shall be serial numbered.

3.7 Fungus.- The equipment shall show no evidence of viable fungus or corrosion when subjected to the test specified in 4.9. Corrosion is any visible degradation that can be attributed to flaky, pitted, blistered, or otherwise loosened finish or metal surface. (See 4.9)

3.8 Interchangeability.- Like units, assemblies, subassemblies and replaceable parts shall conform to Requirement 7 of MIL-STD-454. (See 4.10)

3.9 Service conditions.- The equipment shall meet the following service conditions: (See 4.8)

3.9.1 Temperature.-

3.9.1.1 Low.- During and after testing as specified in 4.8.1.1, the equipment shall meet full specification performance of 3.12.

3.9.1.2 High.- During and after testing as specified in 4.8.1.2, the equipment shall meet full specification performance of 3.12.

3.9.2 Humidity (moisture-resistance).- During and after testing as specified in 4.8.2, the equipment shall meet full specification performance of 3.12.

3.9.3 Altitude.- The equipment shall meet full specification performance of 3.12 both during and after testing as specified in 4.8.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:49Z
Check the source to verify that this is the current version before use.

3.9.4 Vibration.- The equipment shall have no mechanical resonance between 10 to 55 Hertz when tested as specified in 4.8.4.

3.9.5 Shock.- After testing as specified in 4.8.5, the equipment shall meet full specification performance of 3.12.

3.10 Electromagnetic interference characteristics.- The equipment shall meet the electromagnetic interference requirements specified in MIL-STD-461 for Class IC. Tests and test methods shall be as specified in MIL-STD-462. If the contractor considers it feasible to modify the equipment proper in order to facilitate conformance to the specified test limits, he shall obtain approval from the contracting officer before proceeding with the modification.

3.11 Preconditioning.- The equipment shall be capable of meeting the requirements herein, without subsequent processing, after subjection to the bounce preconditioning of 4.6.

3.12 Electrical.-

3.12.1 Teletypewriter TT-76( )/GGC.- The equipment shall be tested with teletypewriters adjusted for operation at 100 words per minute in accordance with MIL-R-11177 and paragraph 4.11. There shall be no degradation in performance characteristics of the teletypewriter when the signaling device is added.

3.12.2 TD Send, TR Send, Receive.- With the equipment installed in the teletypewriter, perfect copy shall be obtained when sending from both keyboard and TD. Perfect copy is defined as ten consecutive error free typed copies of: The quick brown fox jumped over the lazy dogs back 1234567890 -$!&"()"/:;?,.

3.12.3 TD Send, Local Punch, Local Repunch.- The following electrical characteristics shall be obtained:

(a) The open circuit voltage across the contacts shall be 0.70 volts ± 30%.

(b) The Mark-Hold contact current shall be 68 microamperes ±10%.

(c) The voltage at the selector magnet (measured from the high potential side to common) shall be 26 volts ±10% in Mark-Hold (pin 8). The voltage in Space condition shall be within one volt of the voltage in Mark condition.

(d) The Mark-Hold current through the selector magnet shall be 27 milliamperes ±10%.

Source: https://assist.dla.mil -- Downloaded: 202640-22T23:49Z
Check the source to verify that this is the current version before use.

3.13 Workmanship.- The equipment shall be manufactured and assembled in accordance with Requirement 9 of MIL-STD-454 (See also 4.7) and the applicable portion of the following:

(a) In MIL-P-11268

General requirements for plastic material and plastic parts.
Wiring and cabling, including:
- Slack.
- Protection.
- Clearance.
- Splicing.
- Connections, general.
- Grounding, general.
- Shielding on wire and cable.

Soldering and brazing.
Cleaning of units.
General requirements for securing of parts.
Process for welding.
Cleaning after welding.
Controls.
Self-tapping screws.
Cleaning prior to welding.

(b) In this specification:

Construction

3.14 Printed wiring assemblies.- Printed wiring assemblies shall be processed in such a manner as to meet the requirements specified, to be uniform in quality, and to be free from defects that will affect life and serviceability (See 4.4).

3.14.1 Printed wiring boards used in the construction of printed wiring assemblies shall be manufactured and assembled in accordance with Requirement 17 of MIL-STD-454.

3.14.2 Protective coating.- Printed wiring assemblies shall be protected on both component and circuitry sides with an epoxy-type conformal coating. The coating shall be Class A, Type ER in accordance with Specification MIL-I-46058. Prior to coating, the printed wiring assemblies shall be clean and free from flux, dirt, oil, corrosion, corrosion products, salt, smut, grease, fingerprints, and all other foreign matter. The thickness of the coating shall be 0.002 $\pm$0.001 inch.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may use his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:49Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspection.- Inspection shall be classified as follows:

(a) First Article (preproduction) inspection (does not include preparation for delivery). (See 4.3)

(b) Inspection covered by subsidiary documents. (See 4.4)

(c) Quality conformance inspection.

(1) Quality conformance inspection of equipment before preparation for delivery. (See 4.5)

(2) Quality conformance inspection of preparation for delivery. (See 4.12)

4.3 First Article (preproduction) inspection.- This inspection shall consist of the inspection specified in the subsidiary documents covering the items listed in 4.4, and the inspection specified for Group A and Group C (see tables II and III). The first article (preproduction) inspection shall be performed in the order shown in Table I according to the number of samples specified in the contract or order.

Table I - Order of Preproduction and Group C Inspection

Inspection (Note 1)	Unit 1	Unit 2
Non-damaging (Note 2)		
Temperature, Low	1	
Temperature, High	2	
Altitude (elevation)	3	
Vibration		1
Potentially damaging		
Humidity (moisture-resistance)	4	
Fungus		2
Shock		3

NOTE 1: Other preproduction inspection may precede, follow, or be interspersed between the non-damaging tests.

NOTE 2: The order on non-damaging tests and the choice of which units are subjected to the non-damaging tests may be varied if convenient, except that the vibration test should be performed on the same unit used for the bounce and shock tests.

Source: https://assist.dla.mil -- Downloaded: 202640-22T23:49Z
Check the source to verify that this is the currentversion before use.

4.4 Inspection covered by subsidiary documents.- The following shall be inspected under the applicable subsidiary documents as part of the inspection of equipment before preparation for delivery:

Item	Where required
Construction	3.3
Finish	3.5
Marking	3.6
*Electromagnetic Interference Characteristics	3.10
Printed Wiring Assemblies	3.14

*First Article Test only.

4.5 Quality conformance inspection of equipment before preparation for delivery.- Each unit of each lot of equipment shall be subjected to the preconditioning (See 3.11) prior to inspection. The contractor shall perform the inspection specified in 4.4 and 4.5.1 through 4.5.4. This does not relieve the contractor of his responsibility for performing any additional inspection which is necessary to control the quality of the product and to assure compliance with all specification requirements. Failure to meet any requirement as a result of preconditioning shall be classified as a defect and recorded as such. The Government will review and evaluate the contractor's inspection procedures and examine the contractor's inspection records. In addition the Government—at its discretion—may perform all or any part of the specified inspection, to verify the contractor's compliance with specified requirements. (See 6.5) Test equipment for Government verification inspection shall be made available by the contractor.

4.5.1 Group A inspection.- Each unit of each lot of equipment shall be inspected for conformance to all the inspection and test requirements of Table II. Each lot will be subjected to verification utilizing the procedures of MIL-STD-105 Inspection Level III and the AQL's indicated in Table II.

Table II - Group A Inspection

Inspection	Req. para.	Insp. para.	AQL Major	AQL Minor
Visual and Mechanical	3.13	4.7	1.0%	4.0%
Electrical			1%	-
Teletypewriter	3.12.1	4.11		
TD Send, TR Send, Rec	3.12.2	4.11		
TD Send, Loc Punch, Loc Repunch	3.12.3	4.11		

Source: https://assist.dla.mil -- Downloaded: 202610-22T23:49Z
Check the source to verify that this is the current version before use.

4.5.2 Group B inspection.- Not required except as specified in subsidiary documents.

4.5.3 Group C inspection.- This inspection shall consist of the tests specified in Table III and shall be performed on sample units that have been subjected to and met Group A inspection.

4.5.3.1 Sampling for inspection.- Two each TT-523( )/GGC shall be selected at random for all inspections in Table III from every 500 units and fraction thereof produced. The first samples selected shall be at the start of the contract from the first quality conformance inspection production lot.

4.5.3.2 Noncompliance.- The contractor shall immediately report in writing each Group C failure occurrence, including details of the failure and characteristics affected. The contractor shall immediately investigate the cause of failure and further report the results of investigation and details of the proposed corrective action on (i) the process and materials, as applicable, and, (ii) all units of product which were manufactured under the same conditions and which the Government considers subject to the same failure. Reports shall be forwarded to the responsible technical activity designated in the contract through the Quality Assurance Representative. After corrective action has been taken, additional sample units shall be subjected to Group C inspection (all inspections, or the inspections which the sample failed, at the option of the Government) and Group A inspection may be reinstituted, however, final acceptance and shipment will be withheld until the Group C reinspection results have shown that the corrective action was effective.

4.5.4 Disposition of Group C sample units.- Sample units which have been subjected to Group C inspection shall not be delivered on the contract or order.

Table III - Group C Inspection of Equipment

Inspection	Req. para.	Insp. para.
Fungus	3.7	4.9
Interchangeability	3.8	4.10
Temperature	3.9.1	4.8.1
Humidity	3.9.2	4.8.2
Altitude	3.9.3	4.8.3
Vibration	3.9.4	4.8.4
Shock	3.9.5	4.8.5

Source: https://assist.dla.mil -- Downloaded: 202610-22T23:49Z
Check the source to verify that this is the current version before use.

4.5.5 Disposition of nonconforming product.- Disposition of rejected lots and defective sample units shall be in accordance with Standard MIL-STD-105. When resubmitted for acceptance, such product shall be suitably tagged or identified by equivalent means to indicate the cause of failure and means employed to correct the fault. The required information shall be presented to the Government when the product is resubmitted and shall become the property of the Government.

4.6 Preconditioning.- (See 3.11)

4.6.1 Bounce.- The unit shall be placed in its normal operation position on the table of the Package Tester, Type 1000-SC, as made by the L.A.B. Corporation, Skaneatales, New York, or equal. The package tester, shafts in phase, shall have a speed such that it is just possible to insert a 1/32-inch thick strip of material under one corner or edge of the unit to a distance of 3 inches as the unit bounces. The unit shall be subjected to this preconditioning for 1 minute. After bounce preconditioning, the unit shall not be repaired, alined, cleaned, or otherwise changed prior to subjection to inspection.

4.6.2 Electrical.- After final adjustments, the unit shall be energized with its operating voltage. The unit shall be maintained in this state for 50 hours continuously at nominal room ambient. (See 4.5)

4.7 Visual and mechanical inspection of equipment.- Equipment shall be examined for the defects listed in Standard MIL-STD-252, for the requirements of MIL-P-11268 and for conformance to the construction drawings. (See 3.13)

4.8 Service Conditions Test.- The equipment shall be tested for the following service conditions: (See 3.9)

4.8.1 Temperature test.- (See 3.9.1)

4.8.1.1 Low temperature.- The equipment shall be tested in accordance with Method 502, Procedure 1, of MIL-STD-810. The storage temperature shall be -65°C for a period of 24 hours, and the operating temperature shall be 0°C.

4.8.1.2 High temperature.- The equipment shall be tested in accordance with Method 501, Procedure II, of MIL-STD-810. The operating temperature shall be +55°C.

Source: https://assist.dla.mil -- Downloaded: 202610-22T23:49Z
Check the source to verify that this is the current version before use.

4.8.2 Humidity (moisture-resistance) test.- The equipment shall be tested in accordance with Method 507, Procedure II of MIL-STD-810. Prior to testing, the equipment shall meet full specification performance for the measurements specified in 3.12. Measurements shall be made during the periods shown on the figure for the cycle. Do not move equipment from the humidity chamber for measurements and do not leave power on after measurements have been completed. If any equipment fails to meet the specified performance during cycling, it does not pass the test. In addition, if the equipment fails to meet specified requirements after final conditioning, it does not pass the test. (See 3.9.2)

4.8.3 Altitude (elevation) test.- The equipment shall be tested in accordance with Method 500, Procedure I, of MIL-STD-810. (See 3.9.3)

4.8.4 Vibration.- The equipment shall be tested in accordance with Method 514, Procedure IX, Part I of MIL-STD-810. (See 3.9.4)

4.8.5 Shock.- The equipment shall be tested in accordance with Method 516, Procedure I, except with 15g peak for 11 ms per MIL-STD-810. (See 3.9.5)

4.9 Fungus.- The equipment shall be tested in accordance with Method 508, Procedure I of MIL-STD-810. Spraying shall include parts and materials on and under the chassis and the interior of the equipment case. The equipment shall remain in an open condition during the test. Operation is not required. (See 3.7)

4.10 Inspection for dimensional interchangeability.- The dimensions listed below shall be gaged or measured to determine conformance to the physical interchangeability requirement of 3.8. When a listed dimension is not within specified or design limits, it shall be considered a major defect.

(a) External and internal dimensions of cases, covers, and insertable assemblies, when such dimensions affect mating of parts.

(b) Dimensions of cavities, when such dimensions affect insertion of items.

(c) Location of hinges and fasteners on separable parts or assemblies which must mate, such as cases, covers, and mountings.

(d) Location of connectors, locking pins, fasteners, slides, and mountings which receive mating parts of plug-in assemblies and major units; and location of the mating parts on the plug-in assembly or major unit.

(e) Size and form of special threads.

Source: https://assist.dla.mil -- Downloaded: 202610-22T23:49Z
Check the source to verify that this is the current version before use.

4.11 Electrical.- (See 3.12) The equipment shall be tested in accordance with Drawing SM-A-603723 and the applicable portions of MIL-R-11177.

4.12 Quality conformance inspection of preparation for delivery.- Preparation for delivery shall be inspected in accordance with Specification MIL-P-116 to determine conformance to requirements of Section 5.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.- Preservation and packaging shall be level A or C as specified. (See 6.2)

5.1.1 Level A.-

5.1.1.1 Cleaning.- TT-523( )/GGC shall be cleaned in accordance with Process C-1 of MIL-P-116.

5.1.1.2 Drying.- TT-523( )/GGC shall be dried in accordance with the applicable procedures of MIL-P-116.

5.1.1.3 Preservation application.- None required.

5.1.1.4 Unit packaging.- Unit packaging shall be in accordance with methods in MIL-P-116 as specified herein.

5.1.1.4.1 TT-523( )/GGC shall be packaged Method III, as follows; Cushion each signaling device by wrapping in cushioning material conforming to PPP-C-843, Type II, Class A. Secure the cushioning material with pressure-sensitive tape conforming to PPP-T-76. Place the cushioned signaling device within a paperboard folding box conforming to PPP-B-566. Box closure shall be in accordance with the appendix of the box specification.

5.1.1.4.2 Intermediate package.- Place six each signaling devices packaged as specified in 5.1.1.4.1, within a close fitting fiberboard box conforming to PPP-B-636, weather resistant, W6c. Box closure shall be in accordance with the appendix of the box specification.

5.1.2 Level C.- TT-523( )/GGC shall be packaged in a manner that will afford adequate protection against corrosion, deterioration and damage during shipment from the supply source to the first receiving activity.

5.2 Packing.- Packing shall be Level A, B or C, as specified.

5.2.1 Level A.-

Source: https://assist.dla.mil -- Downloaded: 202610-22T23:49Z
Check the source to verify that this is the current version before use.

5.2.1.1 Palletized load.- TT-523( )/GGC packaged as specified in 5.1, shall be placed on a pallet, load type 1, conforming to MIL-STD-147. A fiberboard cap shall be employed over the load having two sides extending down the stacked load at least, 12 inches to accommodate marking requirements. The cap shall be fabricated of fiberboard conforming to PPP-F-320, class weather resistant, W5s. The load shall be bonded to the pallet by strapping.

5.2.1.2 Less than a pallet load.- When quantities per destination are less than a pallet load, a quantity of items packaged as specified in 5.1, shall be packed within a closefitting fiberboard box conforming to PPP-B-640, Class 2, Grade A, Style E or MIL-B-43291. Closure shall be in accordance with the appendix of the applicable box specification. Reinforcing shall be by nonmetallic strapping or pressure-sensitive filament tape banding conforming to PPP-S-760, Type II or PPP-T-97, Type IV respectively. Selection of the material and application shall be in accordance with the appendix of the applicable box specification.

5.2.2 Level B.- TT-523( )/GGC packaged as specified in 5.1, shall be packed as specified in 5.2.1.

5.2.3 Level C.- TT-523( )/GGC packaged as specified in 5.1, shall be packed as specified in 5.2.1 except that pallets, fiberboard boxes and fiberboard caps shall be of the type, size and kind commonly used for the purpose and shall comply with the rules and regulations of the common carrier as applicable to the mode of transportation. Packing shall be accomplished in a manner that will afford adequate protection to the package and its contents during shipment from the supply source to the first receiving activity.

5.3 Marking.- In addition to any special marking required by the contract or order, interior and exterior shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use.- The equipment covered by this specification is a signal processor for use with Teletypewriter TT-76( )/GGC. Its operating power is obtained from the TTY.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:49Z
Check the source to verify that this is the current version before use.

6.2 Ordering data.- Procurement documents should specify the following:

(a) Title, number and date of this specification and any amendment thereto.

(b) Level of packaging and level of packing required for shipment. (Level A, Level B, or Level C).

(c) Samples required. (See 3.2)

(d) Marking and shipping of samples.

6.3 Nomenclature.- The parentheses in the nomenclature will be deleted or replaced by a letter identifying the particular design, for example, TT-4W/TG. As soon as possible after the award of contract, the contractor should apply to the contracting officer for nomenclature in accordance with the applicable clause of the contract. (See 1.1)

6.4 Group C inspection.- Approval to ship may be withheld, at the discretion of the Government, pending the decision of the contracting officer on the adequacy of corrective action. (See 4.5.3.2)

6.5 Verification inspection.- Verification by the Government will be limited to the amount deemed necessary to determine compliance with the contract and will be limited in severity to the definitive quality assurance provisions established in this specification and the contract. The amount of verification inspection by the Government will be adjusted to make maximum utilization of the contractor's quality control system and the quality history of the product.

6.6 Lubricants.- Unless otherwise stated, lubricating oil shall conform to MIL-L-6085 and grease to MIL-G-23827.

Custodian:
Army-EL

Preparing Activity
Army-EL

Project No. 5815-A052

Source: https://assist.dla.mil -- Downloaded: 202610-22T23:49Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

II-L-55658(1) LC. [illegible]

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

ESC-FM 1068-68

To detach this form, cut along this line

Source: https://assist.dla.mil -- Downloaded: 202610-22T23:49Z
Check the source to verify that this is the current version before use.