MIL-C-42061
DATED 29 July 1988

MILITARY SPECIFICATION

CAP, SCREW, BOTTLE AND JAR

This specification is approved for use by all departments and agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type of threaded closure cap for use with aircraft lubricants and hydraulic fluids.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

PPP-B-601 - Boxes, wood, cleated plywood
PPP-B-621 - Box, wood, nailed and lock-corner
PPP-B-636 - Box, shipping, fiberboard

MILITARY

MIL-L-10547 - Liner, case, and sheet, overwrap, water Vaporproof or Waterproof, flexible
MIL-P-116 - Preservation, Methods of

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Headquarters, Defense Personnel Support Center ATTN: Directorate of Medical Materiel DPSC-RST, 2800 South 20th Street, Philadelphia, PA 19101, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC/NA FSC 6640

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:18Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-129 - Marking for Shipment and Storage.

MIL-STD-147 - Palletized Unit Loads.

MIL-STD-794 - Parts and Equipment, Procedures for Packaging of.

3. REQUIREMENTS

3.1 Material. Shall be fabricated from white urea material (see 6.1).

3.2 Size. Shall be a size 24-400 closure cap.

3.3 Construction. Shall be a closure cap with an internal thread for closure on a glass bottle with a 24 millimeter GPI 400 finish (see 6.3). The outside of the closure cap shall have ribbed surfaces to facilitate gripping. The ribbed surfaces shall cover at least fifty (50) percent of the gripping surface. Shall be supplied without a liner.

3.4 Durability. Shall be capable of withstanding a 14 day immersion in typical aircraft lubricants and hydraulic fluids without any evidence of deterioration that would cause softening, cracking or failure as a closure cap on a glass bottle holding aircraft lubricant or hydraulic fluid samples (see 6.4).

3.5 Intended use. Shall be suitable for use as a closure cap on a bottle used for transporting samples, and then as a specimen cup for evaluating a sample in a fluid analysis flame spectrophotometer. As a specimen cup for use with a flame spectrophotometer, shall be capable of withstanding heating of oil without evidence of melting or other types of deterioration (see 6.4).

3.6 Workmanship. The screw cap shall be free from defects which detracts from its appearance or impairs its serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified

Source: https://assist.dla.mil -- Downloaded: 202610-21T20:18Z
Check the source to verify that this is the current version before use.

herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Records. Records of examinations and tests performed by or for the contractor shall be maintained by the contractor and made available to the Government upon the Government's request, at any time, or from time to time, during the performance of the contract and for a period of three years after delivery of the supplies to which such records relate.

4.1.2 Inspection. Inspection, as used herein, is defined as both examination (such as visual or auditory investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties) of the item.

4.1.3 Certificates of quality. Certificates of quality, supplied by the manufacturer of any component or material, may be furnished in lieu of actual performance of such testing by the contractor, provided lot identity has been maintained and can be demonstrated to the Government. The certificate shall include the name of the contractor, the contract number, the name of the manufacturer or supplier, the National Stock Number(NSN), the item identification, the name of the component/material, the lot number, the lot size, the sample size, the date of testing, the test method, individual test results, and the specification requirements.

4.2 Sampling.

4.2.1 Sampling for examination. Sampling for examination shall be in accordance with commercial practice.

4.2.2 Sampling for tests. Sampling for tests shall be in accordance with commercial practice.

4.3 Examination. Examination shall be conducted in accordance with commercial practice.

Source: https://assist.dla.mil -- Downloaded: 202610-21T20:18Z
Check the source to verify that this is the current version before use.

4.4 Inspection of packaging. The sampling and inspection of the preservation and interior package marking shall be in accordance with groups A and B quality conformance inspection requirements of MIL-P-116. The sampling and inspection of the packing and marking for shipment and storage shall be in accordance with the quality assurance provisions of the applicable container specification and the marking requirements of MIL-STD-129.

4.5 Tests. Test shall be conducted in accordance with commercial practice.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or C, as specified (see 6.2).

5.1.1 Level A.

5.1.1.3 Unit package. Thirty-six hundred caps, shall be packaged in accordance with MIL-P-116, method IC-1.

Closure shall be as specified in the applicable box specification.

5.1.2 Level C.

5.1.2.1 Unit package. Preservation for caps shall conform to the requirements of MIL-STD-794 for level C.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 Level A. Twelve unit packages containing caps, shall be packed in an exterior container designed for a type 2 load and conforming to PPP-B-601, overseas type, PPP-B-621, class 2, or PPP-B-636, class weather-resistant. Closure and strapping shall be as specified in the applicable box specification.

5.2.1.1 Case liner. Each level A wood box shall be lined with a waterproof case liner conforming to MIL-L-10547. Closure and sealing shall be as specified in the liner specification. Case liner shall not be required for fiberboard boxes. Each fiberboard box shall be waterproofed as specified in PPP-B-636.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:18Z
Check the source to verify that this is the current version before use.

5.2.2 Level B. Twelve unit packages containing caps, shall be packed in an exterior container designed for a type 2 load, and conforming to PPP-B-601, domestic type, PPP-B-621, class 1, or PPP-B-636, class domestic. Closure shall be as specified in the applicable box specification.

5.2.3 Level C. Twelve unit packages containing caps, shall be packed in accordance with the requirements of MIL-STD-794 for level C.

5.2.4 Packing variation permitted. If the required number of units to be shipped is less than the number of units specified to be overpacked in an exterior container, such units shall be packed in an exterior container of suitable size and design, acceptable to a common carrier, which will insure safe delivery to destination.

5.2.5 Unitized loads. Unitized loads, commensurate with the level of packing specified in the contract or order, shall be used whenever total quantities for shipment to one destination exceed 250 pounds or 20 cubic feet. Loads shall be unitized on pallets conforming to MIL-STD-147. Quantities less than 20 cubic feet need not be unitized. Pallet loads including the pallet shall not exceed 54 inches in height, 43 inches in length and, 52 inches in width. Pallet shall conform to Type IV or Type V.

5.2.5.1 Levels A and B. Caps packed as specified in 5.2.1 and 5.2.2 shall be unitized on pallets as specified in 5.2.5.

5.2.5.2 Level C. Caps packed as specified in 5.2.3 shall be unitized as specified in MIL-STD-794.

5.3 Marking.

5.3.1 Levels A, B and C. Each unit pack, intermediate package, exterior container and unitized load shall be marked as specified in MIL-STD-129.

5.4 General.

5.4.1 Exterior container. Exterior container (see 5.2.1, 5.2.2, and 5.2.3) shall be of minimum tare and cube consistent with the protection required and shall contain equal quantities of identical stock numbered items to the greatest extent practicable.

5.4.2 Packaging inspection. The inspection of these packaging requirements shall be in accordance with 4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:18Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The closure cap is intended for use in an oil analysis program for checking the condition of aircraft lubricants and hydraulic fluids. The 24-400 cap size is intended to fit a stock listed glass bottle (see 6.3) that is used for transporting fluid samples.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) National Stock Number (NSN).
(c) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).

6.3 Stock listing. This specification covers the following item listed in the Federal Supply Catalog:

NSN	Item Identification
6640-01-042-6583	CAP, SCREW, BOTTLE AND JAR

The following item listed in the Federal Supply Catalog is the bottle that is intended for use with the screw cap:

NSN	Item Identification
8125-00-933-4414	BOTTLE, SCREW CAP

6.4 The white urea material, specified in 3.1, is intended to withstand the heating of a fluid sample when used as a specimen cup in a flame spectrophotometer. The whitish color is required in order to provide a contrasting color to facilitate a visual inspection of a fluid sample when the cap is used as a specimen cup.

6.5 First article samples or pre-award samples, when required, may be forwarded for evaluation to the Technical Support Center for Joinst Analysis Program at the Naval Air Station (Pensacola, Florida). The evaluation will include a determination as to a cap's capability for use as a specimen cup with a flame spectrophotometer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:18Z
Check the source to verify that this is the current version before use.

6.6 Qualification. This specification does not cover all types, classes, grades or sizes of the commodity indicated by the title of this specification, or those which are commercially available, but is intended to cover the types which are normally procured to meet military requirements.

6.7 For information only. The following products, as of the date of this document, are purported by the following companies to meet the salient characteristics of the item described herein:

Kerr Glass Manufacturing Corporation - Item 46124/DS 24-400 White Urea Cap

Owens-Illinois/Closure Operation/ Glass Container Div. - Mold No. 2429(white urea) Size 24-400 closure cap

MILITARY INTERESTS:

Custodians:

Army - MD
Navy - MS
Air Force - 99

Preparing activity:

DoD - MB

Agent:

DLA-DM

Project No. 6640-1484

Location: MILSP/Disk #14
CAP/SCREW/BOTTLE/JAR/S31

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:18Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:18Z
Check the source to verify that this is the current version before use.