MIL-C-43011A(ME)
10 January 1978
SUPERSEDING
MIL-C-43011(CE)
23 March 1961

MILITARY SPECIFICATION

CARRYING CASE, TEST SET, SOIL TRAFFICABILITY

This specification is approved for use by the Mobility Equipment Research and Development Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a carrying case for the soil trafficability test set.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

QQ-S-781	- Strapping, Steel, and Seals.
PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-636	- Boxes, Shipping, Fiberboard.

MILITARY

MIL-P-116	- Preservation-Packaging, Methods of.

FSC 6635

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Mobility Equipment Research and Development Command, ATTN: DRDME-DS, Fort Belvoir, VA 22060 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:22Z
Check the source to verify that this is the current version before use.

STANDARDS

FEDERAL

FED. STD. No. 751	- Stitches, Seams, and Stitching.

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-130	- Identification Marking of US Military Property.

DRAWINGS

ME

TA13200E9860	- Carrying Case, Test Set, Soil Trafficability.

(Copies of specifications, standards, and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, ATTN: Tariff Publishing Officer, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., ATTN: Traffic Department, 1616 P Street, NW, Washington, DC 20036.)

Source: https://assist.dla.mil -- Downloaded: 202640-21T20:22Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Description. The carrying case shall be in accordance with Top Assembly TA13200E9860 and as specified herein.

3.1.1 Drawings. The drawings forming a part of this specification are end product drawings. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Where tolerances could cumulatively result in incorrect fits, the contractor shall provide tolerances within those prescribed on the drawings to insure correct fit, assembly, and operation of the carrying case. Any data (i.e., shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the contractor or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or his designated representative.

3.2 First article (first-produced carrying case). The contractor shall furnish one or more carrying cases as specified (see 6.2), for examination and testing within the time frame specified (see 6.2), to prove that his in Section 4 and shall be subject to surveillance and approval by the Government (see 6.3).

3.3 Material. Material shall be as specified herein and on the applicable drawings. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification (see 6.4).

3.4 Stitching. Stitching for cotton duck and cotton webbing shall be in accordance with FED. STD. No. 751, Type 301, 6 to 8 stitches per inch. Each end or break shall be backstitched not less than 1 inch. All exposed ends of cotton duck and cotton webbing shall be turned under to prevent raveling. Adjustment of the thread tension shall be maintained to prevent loose stitches and to assure imbedding of the stitches with thread lock in the center of the material thickness.

3.5 Identification marking. Each carrying case shall be identified in accordance with MIL-STD-130 and as specified herein.

3.6 Workmanship. The carrying case shall be clean and free from abrasion marks, permanently embedded creases and wrinkles, loopy and loose edges, dye stains, and streaks.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:22Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Material inspection. The contractor is responsible for insuring that materials used are manufactured, examined, and tested in accordance with referenced specifications and standards, as applicable.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) First-produced carrying case inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).
(c) Inspection of packaging (see 4.6).

4.3 First-produced carrying case inspection.

4.3.1 Examination. The carrying case shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.4.2 Examination. Samples selected in accordance with 4.4.1 shall be examined for the major and minor defects specified in 4.5.1. AQL shall be 2.5 percent defective for major defects and 4.0 percent defective for minor defects.

4.5 Inspection procedure.

4.5.1 Examination.

Major

101. Dimensions not as specified.
102. Materials not as specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:22Z
Check the source to verify that this is the current version before use.

103. Stitching not as specified.
104. Missing components or improper assembly.
105. Workmanship not as specified.

Minor

201. Color not as specified.
202. Identification marking missing or illegible.

4.6 Inspection of packaging.

4.6.1 Quality conformance inspection of pack.

4.6.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.6.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.6.1.3 Examination. Samples selected in accordance with 4.5.1.2 shall be examined for the following defects. AQL shall be 2.5 percent defective.

106. Materials, methods, and containers not as specified for Level A or B. Each incorrect material, method, or container shall be considered one defect.
107. Consolidation not as specified for Level A or B
108. Packing not as specified for Level A or B.
109. Strapping not as specified for Level A.
110. Marking missing, illegible, incorrect, or incomplete for Level A, B, or Commercial.

5. PACKAGING

5.1 Preservation. Preservation shall be Level A, Level B, or Commercial as specified (see 6.2).

5.1.1 Level A. Each carrying case shall be preserved in accordance with MIL-P-116, Method IC-1 or IC-3.

5.1.1.1 Consolidation. Carrying cases, preserved as specified in 5.1.1 shall be consolidated together in a close-fitting box conforming to PPP-B-636, W5c, style optional, in quantities not to exceed the weight or size limitation of the box.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:22Z
Check the source to verify that this is the current version before use.

5.1.2 Level B. Preservation shall be as specified for Level A.

5.1.3 Commercial. Each carrying case shall be preserved in a manner to assure protection against deterioration and damage from the supply source to the initial destination.

5.2 Packing. Packing shall be Level A, Level B, or Commercial as specified (see 6.2).

5.2.1 Level A. Carrying cases, preserved as specified in 5.1, shall be packed in close-fitting boxes conforming to PPP-B-601, Overseas Type, Grade B, style optional, in quantities not to exceed the weight limitation of the box. Box closure and strapping shall be in accordance with the appendix to the box specification. Strapping shall conform to QQ-S-781, Class 1, Type I or IV, size as applicable. Unless otherwise specified (see 6.2), strapping shall be Finish B. When specified (see 6.2), strapping shall be Finish A.

5.2.2 Level B. Carrying cases, preserved as specified in 5.1, shall be packed in close-fitting boxes conforming to PPP-B-636, V3c, style optional, in quantities not to exceed the weight or size limitation of the box. Box closure and strapping shall be in accordance with the appendix to the box specification.

5.2.3 Commercial. Carrying cases, preserved as specified in 5.1, shall be packed to assure carrier acceptance and safe delivery to destination at lowest ratings in containers complying with Uniform Freight Classification rules or National Motor Freight Classification rules.

5.3 Marking.

5.3.1 Military. Marking for military levels of protection shall be in accordance with MIL-STD-129.

5.3.2 Commercial. Marking for commercial packaging shall reflect as a minimum, the item name, National Stock Number, quantity, contract number, and appropriate address markings on the shipping container. The marking shall be applied with a waterproof material, be legible, and shall provide a definite contrast.

6. NOTES

6.1 Intended use. The carrying case is used to house, protect, and permit easy portability for the complete soil trafficability test set.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:22Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Time frame required for submission of first-produced model, and number of carrying cases required (see 3.2)
(c) Degree of preservation and packing required (see 5.1 and 5.2).
(d) When other than Finish E strapping is required (see 5.2.1).

6.3 First-produced carrying case. Any changes or deviations of production carrying cases from the approved first-produced carrying case during production will be subject to the approval of the contracting officer. Approval of the first-produced carrying case will not relieve the contractor of the obligation to furnish carrying cases conforming to this specification

6.4 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the specification (see 3.3).

Custodian:
Army - ME

Preparing activity:
Army - ME

Review activity:
DLA - GS

Project 6635-A053

User activity:
Army - GL

Source: https://assist.dla.mil -- Downloaded: 202610-21T20:22Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS This form is provided to solicit beneficial comments which may improve this document and enhance its use DoD contractors government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government Fold on lines on reverse side staple in corner and send to preparing activity Attach any pertinent data which may be of use in improving this document If there are additional papers attach to form and place both in an envelope addressed to preparing activity A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed

NOTE This form shall not be used to submit requests for waivers deviations or clarification of specification requirements on current contracts Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements

DOCUMENT IDENTIFIER (Number) AND TITLE

MIL-C-43011A(ME) Carrying Case, Test Set, Soil Trafficability

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1 ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID RESTRICTIVE LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW

A GIVE PARAGRAPH NUMBER AND WORDING

B RECOMMENDED WORDING CHANGE

C REASON FOR RECOMMENDED CHANGE(S)

2 REMARKS

SUBMITTED BY (Printed or typed name and address — Optional)

TELEPHONE NO

DATE

DD FORM 1 OCT 76 1426

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:22Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Mobility Equipment Research
and Development Command
ATTN: DRDME-DS
Ft. Belvoir, VA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-21T20:22Z
Check the source to verify that this is the current version before use.