INCH-POUND
MIL-H-42064
20 March 1989
SUPERSEDING
A-A-0053002 (DM)
27 July 1987

MILITARY SPECIFICATION

HOOD, DENTAL LABORATORY GRINDING AND POLISHING MACHINE, Collapsible, Field

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a collapsible hood consisting of a pan with folding back, top and sides, complete with cover.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

Federal Specifications

QQ-A-250/8F - Aluminum Alloy 5052, Plate and Sheet.
PPP-B-601 - Boxes, Wood, Cleated-Plywood.
PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636 - Boxes, Shipping, Fiberboard.

AMSC N/A FSC 6520

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Defense Personnel Support Center, Directorate of Medical Materiel, DPSC-RSTE,2800 South 20th Street, Philadelphia, PA 19101-8419, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:19Z
Check the source to verify that this is the current version before use.

Federal Standards

FED-STD-151 - Metals, Test Methods.

Military Specifications

MIL-P-116 - Preservation, Methods of.
MIL-L-10547 - Liners, Case, and Sheet, Overwrap; Water-Vaporproof, or Waterproof, Flexible.

Military Standards

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-147 - Palletized Unit Loads.
MIL-STD-794 - Parts and Equipment, Procedures for Packaging of.
MS20257 - Hinge, Continuous.

Drawing

Defense Personnel Support Center (DPSC).

#5053 - Hood, Dental Laboratory Grinding and Polishing Machine, Collapsible, Field.

(Copies of specifications, and standards required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity).

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification takes precedence. Nothing in this specification, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 General. The components of the collapsible hood shall be in accordance with the applicable requirements as specified herein.

3.2 Materials. The hood, cover and hinges shall be fabricated of aluminum alloy 5052, having a temper of H34 in accordance with Federal Specification QQ-A-250/8F, for composition only.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:19Z
Check the source to verify that this is the current version before use.

3.3 Style, design, and dimensions. The style, design, and dimensions shall be in accordance with Defense Personnel Support Center (DPSC) Drawing number 5053. All corners shall be welded or brazed. All edges and corners shall be ground smooth to eliminate burrs and sharp or jagged edges. The cover shall fit snugly. The hinges shall be designed in accordance with Military Standard MS20257. The hinges shall be spotwelded and free moving.

3.4 Finish. All surfaces of the hood shall be given a protective coating, followed by one coat of lustreless olive drab enamel. The enamel shall be sprayed on and baked in high-temperature ovens. The finish shall be hard, smooth and highly resistant to abrasion, chipping and cracking.

3.5 Identification marking. The hood shall be legibly and permanently marked with the name or registered trademark of the manufacturer.

3.6 Workmanship. The hood and cover shall be free from burrs, sharp edges, binding hinges or any other defects which may impair its serviceability, proper function or intended use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.1 Records. Records of examinations and tests performed by or for the contractor shall be maintained by the contractor and made available to the Government, upon the Government's request, at any time, or from time to time, during the performance of the contract and for a period of three years after delivery of the supplies to which such records relate.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:19Z
Check the source to verify that this is the current version before use.

4.1.2 Inspection. Inspection, as used in this specification, is defined as both examination (such as visual or auditory investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties) of the item.

4.1.3 Certificates of quality. Certificates of quality, supplied by the manufacturer of the materials used in the hood, may be furnished in lieu of actual performance of such testing by the contractor, provided that lot identity has been maintained and can be demonstrated to the Government.

4.2 Sampling for examination. Sampling for examination shall be conducted in accordance with MIL-STD-105, and as indicated in table I. The unit of product for examination purposes shall be one hood and cover.

TABLE I. Sampling for examination.

Type defect	Inspection level	AQL (Percent defective)
Major	S-2	1.0
Minor	S-2	2.5

4.3 Sampling for tests. Sampling for tests shall be conducted in accordance with MIL-STD-105, and as indicated in table II. The unit of product for test purposes shall be one hood and cover.

TABLE II. Sampling for tests.

Characteristic	Requirement	Test procedure	Inspection level	AQL (Percent defective)
Chemical analysis	3.2	4.4.1	/2	/1

/1 Acceptance number shall be zero for all sample sizes.

/2 A sufficient quantity of each lot of aluminum alloy raw material used in the fabrication of the hood, hinges and cover shall be selected for chemical analysis.

4.4 Examination. The hood and cover shall be examined for the defects listed in table III, but not limited to those listed in the table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:19Z
Check the source to verify that this is the current version before use.

TABLE III. Classification of defects.

Categories	Defects
Major	
101	Style and design of the hood not as specified.
102	Exposed surface of the hood and cover not finished as specified.
103	Hood and cover not free of burrs, sharp or jagged edges.
Minor	
201	Surface of the hood and cover not free of coarse grind marks, pits and dents.
202	Identification marking not permanently and legibly marked.
203	Exposed spot welds not smooth.
204	Dimensions of collapsible hood not within tolerances specified.

4.5 Tests. Tests shall be conducted to determine compliance with specification requirements.

4.5.1 Chemical analysis. In the absence of certificates of quality for the aluminum alloy, chemical analysis shall be conducted in accordance with method 111 or method 112 of FED-STD-151. In case of dispute, method 111 shall govern.

4.6 Inspection of packaging. The sampling and inspection of the preservation and interior package marking shall be in accordance with groups A and B quality conformance inspection requirements of MIL-P-116. The sampling and inspection of the packing and marking for shipment and storage shall be in accordance with the quality assurance provisions of the applicable container specification and the marking requirements of MIL-STD-129.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or C, as specified (see 6.1).

5.1.1 Level A.

5.1.1.1 Cleaning and drying. The hood shall be cleaned and dried in accordance with MIL-P-116.

Source: https://assist.dla.mil -- Downloaded: 202640-21T20:19Z
Check the source to verify that this is the current version before use.

containers of the type, size, and kind commonly used for the purpose

5.1.1.2 Preservative applications. Preservatives shall not be used.

5.1.1.3 Unit package. Each hood shall be packaged in accordance with MIL-P-116, method IC-1. Closure shall be as specified in the applicable box specification.

5.1.2 Level C.

5.1.2.1 .Unit package. Preservation for the hood shall conform to the requirements of MIL-STD-794 for level C.

5.2 Packing. Packing shall be level A, B or C, as specified (see 6.1).

5.2.1 Level A. Twenty-four unit packages containing the hood shall be packed in an exterior container designed for a type 2 load and conforming to PPP-B-601, overseas type, PPP-B-621, class 2, or PPP-B-636, class weather-resistant. Closure and strapping shall be as specified in the applicable box specification.

5.2.1.1 Case liner. Each level A wood box shall be lined with a waterproof case liner conforming to MIL-L-10547. Closure and sealing shall be as specified in the liner specification. Case liner shall not be required for fiberboard boxes. Each fiberboard box shall be waterproofed as specified in PPP-B-636.

5.2.2 Level B. Twenty-four unit packages containing the hood shall be packed in an exterior container designed for a type 2 load and conforming to PPP-B-601, domestic type, PPP-B-621, class 1, or PPP-B-636, class domestic. Closure shall be as specified in the applicable box specification.

5.2.3 Level C. The level C packaging for the hood shall be packed in accordance with the requirements of MIL-STD-794 for level C.

5.2.4 Packing variation permitted. If the required number of units to be shipped is less than the number of units specified to be overpacked in an exterior container, such units shall be packed in an exterior container of suitable size and design, acceptable to a common carrier, which will insure safe delivery to destination.

5.2.5 Unitized loads. Unitized loads, commensurate with the level of packing specified in the contract or order, shall be used whenever total quantities for shipment to one destination exceed 250 pounds or 20 cubic feet. Loads shall be unitized on pallets conforming to MIL-STD-147.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:19Z
Check the source to verify that this is the current version before use.

Quantities less than 20 cubic feet need not be unitized. Pallet loads including the pallet shall not exceed 43 inches in length, 52 inches in width, and 54 inches in height. Pallets shall conform to Type IV or Type V.

5.2.5.1 Levels A and B. The hood packed as specified in 5.2.1 and 5.2.2 shall be unitized on pallets as specified in 5.2.5.

5.2.5.2 Level C. The hood packed as specified in 5.2.3 shall be unitized as specified in MIL-STD-794.

5.3 Marking.

5.3.1 Levels A, B and C. Each unit pack, intermediate package, exterior container and unitized load shall be marked as specified in MIL-STD-129.

5.4 General.

5.4.1 Exterior container. Exterior container (see 5.2.1, 5.2.2, and 5.2.3) shall be of minimum tare and cube consistent with the protection required and shall contain equal quantities of identical stock numbered items to the greatest extent practicable.

5.4.2 Packaging inspection. The inspection of these packaging requirements shall be in accordance with 4.5.

6. NOTES

6.1 Ordering data.

6.1.1 Acquisition requirements. Acquisition documents should specify the following:

(a) Title, number, and date of the specification.

(b) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).

6.2 National Stock Number (NSN) coverage. This specification covers the following items appearing in the Federal Supply Catalog:

National Stock Number	Item Identification
6520-00-539-1060	HOOD, DENTAL LABORATORY GRINDING AND POLISHING MACHINE, Collapsible, Field

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:19Z
Check the source to verify that this is the current version before use.

6.3 Subject term (key word) listing.

Hood
Collapsible
Dental

MILITARY INTERESTS:

Custodians:

Army - MD
Navy - MS
Air Force - 03

Review Activities:

Army - MD
Navy - MS
Air Force - 03

CIVIL AGENCY COORDINATING ACTIVITIES:
VA-OSS
PHS
FDA-MPQAS

Preparing Activity:

DoD-MB

Agent:

DLA-DM

Project No. 6520-2114

48054

Location: NCR Disk #10

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:19Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-H-42064	HOOD, DENTAL LABORATORY GRINDING AND POLISHING MACHINE, Collapsible, Field

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:19Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEFENSE LOGISTICS AGENCY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 4966 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEFENSE LOGISTICS AGENCY

Commander
Defense Personnel Support Center
Attn: DPSC-BSTE
2800 South 20th Street
Philadelphia, PA 19101

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:19Z
Check the source to verify that this is the current version before use.