MILITARY SPECIFICATION

REMOLDING SET, SOIL-COMPACTION

This specification is approved for use within the USA Belvoir Research, Development, and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a soil-compaction remolding set.

1.2 Specification part number. Items procured under this specification shall be identified by the following specification-based part number: M43010-1.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards and drawings. The following specifications, standards and drawings form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specification and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

QQ-S-781	- Strapping, Steel, and Seals.
PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-636	- Boxes, Shipping, Fiberboard.
PPP-B-640	- Boxes, Fiberboard, Corrugated Triple-Wall.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: USA Belvoir Research, Development, and Engineering Center, ATTN: STRBE-TSE, Fort Belvoir, VA 22060-5606 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document, or by letter.

AMSC N/A FSC 6635

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:22Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-P-116 - Preservation, Methods of.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

MIL-STD-129 - Marking for Shipment and Storage.

MIL-STD-130 - Identification Marking of US Military Property.

MIL-STD-889 - Dissimilar Metals.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings and publications form a part of this specification to the extent specified herein. Unless otherwise specified the issues shall be those in effect on the date of the solicitation.

DRAWINGS

ME

TA13200E9830 - Remolding Set, Soil Compaction.

(Copies of specifications, standards and drawings required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the non-Government documents which is current on the date of the solicitation.

AMERICAN NATIONAL STANDARD INSTITUTE (ANSI)

ANSI/ASME B46.1 - Surface Texture.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:22Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the American National Standards Institute, 1430 Broadway, New York, NY 10018.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION (NMFTA)

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, ATTN: Traffic Department, 1616 P Street, NW, Washington, DC 20036.)

UNIFORM CLASSIFICATION COMMITTEE (UCC)

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, ATTN: Tariff Publishing Officer, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Non-Government standards and other publications are normally available from the organizations which prepare or distribute the documents. These documents also may be available in, or through, libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of the specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Description. The remolding set shall be in accordance with Top Assembly Drawing TA13200E9830 and as specified herein.

3.1.1 Drawings. The drawings forming a part of this specification are end product drawings. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Where tolerances could cumulatively result in incorrect fits, the contractor shall provide tolerances within those prescribed on the drawings to insure correct fit, assembly and operation of the remolding set. Any data (e.g., shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the contractor or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or his designated representative.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:22Z
Check the source to verify that this is the current version before use.

3.2 First article. Unless otherwise specified (see 6.2), a sample shall be subjected to first article inspection (see 4.3 and 6.3). Any changes or deviations of the remolding set from the approved first article during production will be subject to the approval of the contracting officer. Approval of the first article will not relieve the contractor of his obligation to furnish remolding sets conforming to this specification.

3.3 Material. Material shall be as specified herein and on the applicable drawings. Material not specified shall be selected by the contractor and shall be subject to all provisions of this specification (see 4.1.2).

3.3.1 Material deterioration prevention and control. The remolding set shall be fabricated from compatible materials, inherently corrosion resistant or treated to provide protection against the various forms of corrosion and deterioration that may be encountered in any of the applicable operating and storage environments to which the remolding set may be exposed.

3.3.1.1 Dissimilar metals. Dissimilar metals shall not be used in intimate contact with each other unless protected against galvanic corrosion. Dissimilar metals and methods of protection are defined and detailed in MIL-STD-889.

3.3.1.2 Identification of materials and finishes. The contractor shall identify the specific material, material finish or treatment for use with component and subcomponent, and shall make information available upon request to the contracting officer or designated representative.

3.3.2 Recovered materials. For the purpose of this requirement, recovered materials are those materials which have been collected from solid waste and reprocessed to become a source of raw materials, as distinguished from virgin raw materials. The components, pieces and parts incorporated in the remolding set may be newly fabricated from recovered materials to the maximum extent practicable, provided the remolding set produced meets all other requirements of this specification. Used, rebuilt or remanufactured components, pieces and parts shall not be incorporated in the remolding set.

3.4 Dimensions. Tolerance and gages for metal fits shall conform to the limits specified herein and on the applicable drawings.

3.5 Finish. Surface finishes shown on the drawings shall conform to ANSI/ASME B46.1.

3.6 Identification marking. The remolding set shall be identified in accordance with MIL-STD-130 and shall include the specification part number (see 1.2).

3.7 Workmanship.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:22Z
Check the source to verify that this is the current version before use.

3.7.1 Metal fabrication. Metal used in fabrication shall be free from kinks and sharp bends. The straightening of material shall be done by methods that will not cause injury to the material. Corners shall be square and true. Flame-cutting, using tips suitable for the thickness of the steel, may be made with controlled means to insure uniformity of size and shape. Precautions shall be taken to avoid overheating. Heated steel shall be allowed to cool slowly. External surfaces shall be free from burrs, sharp edges, and corners, except when sharp edges or corners are required or where they are not detrimental to safety.

3.7.2 Machine work. Tolerance and gage for metal fits shall conform to the limits specified herein and on the applicable drawings.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall be come a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirement of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Component and material inspection. The contractor is responsible for insuring that components and materials are manufactured, examined and tested in accordance with referenced specifications and standards as applicable.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:22Z
Check the source to verify that this is the current version before use.

c. Inspection of packaging (see 4.6).

4.3 First article inspection.

4.3.1 First article examination. The first article shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.4.2 Examination. Samples selected in accordance with 4.4.1 shall be examined as specified in 4.5.1. Acceptable quality level (AQL) shall be 1.0 percent defective for major defects and 4.0 percent defective for minor defects.

4.5 Inspection procedure.

4.5.1 Examination. The remolding set shall be examined as specified herein for the following defects.

Major

101. Materials not as specified (see 3.3).

102. Material not resistant to corrosion and deterioration, or treated to be resistant to corrosion and deterioration for the applicable storage and operating environments (see 3.3.1).

103. Dissimilar metals, as defined in MIL-STD-889, are not effectively insulated from each other (see 3.3.1.1).

104. Contractor does not have documentation available for identification of material, material finishes or treatment (see 3.3.1.2).

105. Used, rebuilt or remanufactured components, pieces or parts incorporated in the remolding set (see 3.3.2).

106. Dimensions not as specified (see 3.4).

107. Components missing or not as specified.

108. Metal fabrication not as specified (see 3.7.1).

109. Machine work not as specified (see 3.7.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:22Z
Check the source to verify that this is the current version before use.

Minor

201. Finish not as specified (see 3.5).

202. Identification marking missing, incomplete or illegible (see 3.6).

4.6 Inspection of packaging.

4.6.1 Quality conformance inspection of pack.

4.6.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.6.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.6.1.3 Examination. Samples selected in accordance with 4.6.1.2 shall be examined for the following defects. AQL shall be 1.0 percent defective.

110. Materials, methods and containers not as specified for level A or B. Each incorrect material, method or container shall be considered one defect.

111. Contents of box not cushioned and secured for level A.

112. Box not closed and sealed as specified for level A.

113. Quantities packed together exceed the size or weight limitation of the box for level A or B.

114. Strapping not as specified for level A.

115. Marking missing, illegible, incorrect or incomplete for level A, B or commercial.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A. Each remolding set shall be preserved in accordance with MIL-P-116, method I, applying type P-7 preservative to those components requiring the application of a preservative in accordance with MIL-P-116. Each molding set shall then be placed in a close-fitting box conforming to PPP-B-636, W5c or W6c, style optional. The contents shall be cushioned and secured to prevent free movement or damage. The box shall be closed and sealed as specified for method V in the appendix to the box specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:22Z
Check the source to verify that this is the current version before use.

5.1.2 Commercial. Each remolding set shall be preserved in a manner to afford protection against mechanical or physical damage from the supply source to the initial destination.

5.2 Packing. Packing shall be level A, B or Commercial as specified (see 6.2).

5.2.1 Level A. Remolding sets, preserved as specified in 5.1, shall be packed in close-fitting boxes conforming to PPP-B-601, overseas type, style optional, in quantities not to exceed the weight limitation of the box. Box closure and strapping shall be in accordance with the appendix to the box specification. Strapping shall conform to QQ-S-781, class 1, type I or IV, size as applicable. Unless otherwise specified (see 6.2), strapping shall be finish B. When specified (see 6.2), strapping shall be finish A.

5.2.2 Level B. Remolding sets, preserved as specified in 5.1, shall be packed as specified in 5.2.1, except boxes shall be domestic type. As an alternate, boxes conforming to PPP-B-636, V3c, V11c, V13c or V15c; or boxes conforming to PPP-B-640, class 2, style optional may be used when the quantity to be packed does not exceed the gross weight or size limitation of the box. Box closure and strapping shall be in accordance with the appendix to the applicable box specification.

5.2.3 Commercial. Remolding sets, preserved as specified in 5.1, shall be packed to assure carrier acceptance and safe delivery to destination at lowest ratings in containers complying with Uniform Freight Classification rules or National Motor Freight Classification rules.

5.3 Marking.

5.3.1 Military. Marking for military levels of protection shall be in accordance with MIL-STD-129.

5.3.2 Commercial. Marking for commercial packaging shall reflect, as a minimum, the item name, National Stock Number, quantity, contract number and appropriate address markings on the shipping container. The marking shall be applied with a waterproof material, be legible and shall provide a definite contrast.

6. NOTES

6.1 Intended use. The remolding set is used to hold samples of soil for strength measurement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:22Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number and date of this specification.

b. Specification part number (M43010-1) (see 1.2).

c. Timeframe required for submission of first article and number of units required (see 3.2).

d. When a first article is not required (see 3.2).

e. Level of preservation and packing required (see 5.1 and 5.2).

f. When other than finish B strapping is required (see 5.2.1).

6.3 First article. When a first article inspection is required, the item should be a preproduction model. The first article should consist of one or more units. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, tests and approval of the first article test results and disposition of the first article.

6.4 Subject term (key word) listing.

Remolding Set
Set, Remolding
Soil-Compaction Set

6.5 Changes from previous issue. Asterisks or (vertical lines) are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army - ME

Preparing activity:
Army - ME

Review activity:
DLA - GS

Project 6635-A133

☆U.S GOVERNMENT PRINTING OFFICE 1988 - 505-033/91882

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:22Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12062 WASHINGTON D C
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Belvoir RD&E Center
ATTN: STRBE-TSE
Fort Belvoir, VA 22060-5606

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:22Z
Check the source to verify that this is the current version before use.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-R-43010B(ME)	Remolding Set, Soil-Compaction

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)* _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording

b. Recommended Wording

c. Reason/Rationale for Recommendation

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:22Z
Check the source to verify that this is the current version before use.