MIL-S-43026D
8 June 1981
SUPERSEDING
MIL-S-43026C
24 April 1970

MILITARY SPECIFICATION

SEWING MACHINES, INDUSTRIAL, COMPLETE WITH CARRYING, SHIPPING, AND STORAGE CASES

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers industrial sewing machines complete with cases for carrying, shipping, and storage.

1.2 Classification. The portable industrial sewing machines and cases shall be of the following types as specified (see 6.2):

Type I	-	Medium-heavy duty sewing machine (see 3.4.1) with type I carrying case.
Type II	-	Extra-heavy duty sewing machine (see 3.4.2) with type II operational, shipping, and storage case.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Natick Research and Development Laboratories, Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 3530

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:23Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

OO-S-256/1	-	Sewing Machines, Industrial, Flatbed, Single, Needle.
TT-C-490	-	Cleaning Methods and Pretreatment of Ferrous Surfaces for Organic Coatings.
TT-E-529	-	Enamel, Alkyd, Semi-Gloss.
TT-P-636	-	Primer Coating, Alkyd, Wood and Ferrous Metal.
MMM-A-181	-	Adhesives, Phenol, Resorcinolor Melamine Base.
PPP-B-601	-	Boxes, Wood, Cleated-Plywood.
PPP-B-621	-	Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636	-	Boxes, Shipping, Fiberboard.
PPP-T-60	-	Tape; Pressure-Sensitive Adhesive, Waterproof for Packaging.

MILITARY

MIL-P-116	-	Preservation, Methods of.

STANDARDS

FEDERAL

FED-STD-595	-	Colors.

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	-	Marking for Shipment and Storage.
MIL-STD-130	-	Identification Marking of US Military Property.
MIL-STD-147	-	Palletized Unit Loads.
MIL-STD-1188	-	Commercial Packaging of Supplies and Equipment.

DRAWINGS

US ARMY NATICK RESEARCH AND DEVELOPMENT LABORATORIES

6-1-6403	-	Sewing Machine, Industrial, Type I with Carrying Case; Assembly Complete.
6-1-6451	-	Drawing List for Sewing Machine, Industrial, Type I with Carrying Case.
5-13-1979	-	Sewing Machine Industrial, Type II with Operational, Shipping and Storage Carrying Case; Assembly Complete.
5-13-1980	-	Top, Side and End Panel Assemblies.
5-13-1981	-	Base Assembly and Details.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:23Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply:

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 2016 - Moisture Content of Wood

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Alternate components. Wherever a specific manufacturer's part number is identified on the reference drawings for a component, the contractor may use an equivalent component from another manufacturer. Such components shall be functionally equal to the manufacturer's part number identified and of equal or better quality. The incorporation and inclusion of such a component in the design of the specified end product shall not require modification or change to any other specified component, and shall not reduce ease of maintenance to it or any other specified component, unless such modification or change is specifically approved by the contracting officer. Prior to manufacture of the first article or if none is required, prior to commencing production, the contractor shall submit for the contracting officer's approval, a list identifying each proposed alternate component, together with proof that each listed component complies with requirements specified herein. The contracting officer, at his option, may require a physical sample of the proposed substitution. Approval of the submitted listing, together with necessary supporting data, authorizes the commencement of the first article or production manufacture, as applicable, and does not relieve the contractor of responsibility that these components perform in accordance with specified requirements when incorporated into the end product.

3.2 First article. When specified (see 6.2), the contractor shall furnish a sample for first article inspection and approval (see 4.3 and 6.3).

3.3 Materials and components. The materials and components shall be as specified herein and as shown on the applicable drawings. Materials and components not definitely specified shall be of the quality normally used by the manufacturer provided the completed item complies with all the provisions of this specification (see 6.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:23Z
Check the source to verify that this is the current version before use.

3.3.1 Lumber. Lumber used in the fabrication of the case shall be uniformly dried without brashness, case-hardening, or honey-combing. Moisture content at time of fabrication shall be between 8 to 12 percent when tested as specified in 4.4.1.1. Lumber shall be free from decay, holes, loose knots, sound-tight knots not over 1/2 inch diameter, larvae channels, shake, split, or warp. The following defects are permissable: Mineral streaks, medium stain, scattered sound burls, pitch pocket and fine surface checks not over 3 inches in length which occur on the surface only. All wood members shall be nominal size in cross section. Spruce, pine or fir species of wood may be used in the frame members.

3.4 Design and construction.

3.4.1 Type I. The design and construction of the type I sewing machine and case shall be as specified herein, and as shown on Drawing 6-1-6403 and the drawings listed on Drawing 6-1-6451. The referenced dimensions specified in the drawings for the case were developed based on using the sewing machine components identified on the drawings. If the components of a different manufacturer are used it may be necessary to adjust the referenced dimensions in order for the sewing machine to fit and function properly within the case. Any increases to the referenced dimensions shall be a minimum. The weight of the complete sewing machine and case shall not exceed 225 pounds. The case joints, supports, reinforcing strips and blocks shall be fastened and glued in position using adhesive conforming to MMM-A-181. Screw holes shall be predrilled and countersunk to a diameter to accommodate the applicable screws. The adhesive for binding felt to wood surfaces shall be a polychloroprene base solvent. The sewing machine complete with a set of applicable accessories shall be as specified herein and with the following exceptions:

a. When automatic lubrication is provided, the oil reservoir shall be of the sealed type.

b. The knee lifter and round leather belt with metal fastener shall be provided as required for the sewing machine.

The clothing sewing machine shall be suitable for general sewing operations and conform to stitch type 301 class 3 of OO-S-256/1. The machine shall have a motor, pulley, thread winder with base, bobbin winder, knee lever assembly suitable for operating all equipment. Fifty each round point, chromium finished spare needles shall be furnished with each machine nominal sizes of 0.042 inch and 0.044 inch diameter. The size of the needle shall be the diameter of the blade at the needle eye. Five bobbins, three bobbin cases, a rotary hook or one shuttle, as applicable shall be furnished with each machine.

3.4.2 Type II. The design and construction of the type II sewing machine and case shall be as specified herein and shown on Drawings 5-13-1979, 1980 and 1981. The sewing machine complete with tools and a set of applicable accessories shall be

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:23Z
Check the source to verify that this is the current version before use.

as specified herein and with the exception that the overall dimensions of the sewing machine and related components shall be such as to fit within spaces provided within the carrying case as shown on the applicable drawings. This heavy duty machine shall be suitable for sewing heavy bulk items. The machine shall conform to stitch type 301 class 6 of OO-S-256/1. The machine shall have a feed H, reversible feed mechanism and a work space of 30 inches. Fifty each round point, chromium finished needles shall be furnished with each nominal size 0.065 inch. A 6 foot length of No. 14 gage wire power cable, type SO shall be installed between the power source and the switch.

3.5 Contract data requirements. The contract data requirements shall be as specified (see 6.2 and 6.2.1).

3.6 Finish.

3.6.1 Cleaning. All hardware shall be cleaned and treated for painting in accordance with type I or II of TT-C-490. Wood surfaces shall be cleaned first, free of grease, oil, dirt and other foreign matter before priming.

3.6.2 Priming.

3.6.2.1 Hardware. After cleaning and prior to attachment to the cases, hardware shall be given a coat of metal primer conforming to TT-P-636.

3.6.2.2 Wood. All interior and exterior wood surfaces shall be primed in accordance with the manufacturer's standard practice and allowed to dry thoroughly before attaching hardware items.

3.6.3 Enamel. The finish coat enamel color shall be Forest Green No. 34079 of FED-STD-595. The finish coat enamel shall conform to class A of TT-E-529 and shall be applied, after attachment of hardware, to the interior and exterior surfaces of the case.

3.7 Marking. Each outside surface end of the case shall be marked in Gothic style lettering "US" in accordance with MIL-STD-130 or may be burned in lettering filled with paint. The letters shall be white in color and painted or stenciled with indelible, waterproof ink.

3.8 Workmanship. The finish shall be free of blisters, peel, chipped areas or areas of no film. The finish shall be free of poor touch-up, scale, scratches, stain, overspray, sag, imprint or embedded foreign matter. All bolts, nuts and screws shall be drawn tight.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:23Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

First article inspection (see 4.3).
Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 3.2), it shall be examined for defects in table III and 4.4.3.2. The presence of any defect shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.1.1 Component testing. In addition to the quality assurance provisions of referenced specifications, tests shall be performed on each lot of lumber specified in 3.3.1 offered for inspection at time of fabrication for moisture content in accordance with D 2016. Three determinations shall be taken on each sample unit and results shall be the average of three determinations. The inspection level shall be S-2 with an acceptable quality level (AQL) of 2.5, expressed in terms of defects per hundred units. The sample unit shall be one piece of lumber. Any nonconformance with moisture requirements of 3.3.1 shall be cause for rejection of the lot.

4.4.2 In-process inspection.

4.4.2.1 In-process examination. Examination shall be made of the operations listed in table I to establish conformance with specified requirements. Whenever nonconformance is noted, correction shall be made to the process and all items processed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:23Z
Check the source to verify that this is the current version before use.

TABLE I. In-process examination

Requirement	Paragraph
Gluing of wood components	3.4.1
Predrilling and counter-sinking of screw holes	3.4.1
Cleaning of hardware before priming	3.6.1
Priming of interior and exterior surfaces of wood and hardware	3.6.2.1 and 3.6.2.2

4.4.2.2 In-process visual examination. The case prior to application of finish shall be examined for the defects listed in table II. The inspection level shall b level II with an AQL of 2.5 major and 6.5 total (major and minor combined) expresse in terms of defects per hundred units. The inspection lot shall consist of all cases offered for inspection at one time. The sample unit for this examination shall be one case prior to application of finish.

TABLE II. Case (prior to application of finish) defects

Examine	Defect	Classification Major	Minor
Cases	Sound tight knot over 1/2 inch average diameter	X	
	Loose knots or holes		X
	Split	X	
	Surface check over 3 inches in length occurring on suface	X	
	Not species of wood specified	X	
	Excess glue or foreign matter		X

4.4.3 End item inspection. A lot shall consist of all cases submitted for acceptance at one time. The sample unit shall be one completely assembled case.

4.4.3.1 Visual examination. Examination shall be made of the end item for defects in table III. The inspection level shall be level II with an AQL of 2.5 major and 10.0 total (major and minor combined) expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:23Z
Check the source to verify that this is the current version before use.

TABLE III. End item defects

Examine	Defect	Classification Major	Minor
Finish	Color not as specified		X
	Blistered, peeled, chipped or area of no film		X
	Poor touch-up, scale, scratched, stained, overspray, sag, imprint, or foreign matter embedded		X
Design, construction and workmanship, general (applicable to all components and assemblies)	Any component or part missing or not specified type or size	X	
	Component not assembled to cases as specified	X	
Felt	Missing, not located or bonded as specified	X	
	Cover assembly does not align with base assembly	X	
Bolts, nuts, screws, studs and other types of threaded fasteners	Broken, stripped, fractured or not tight		X
Marking	Missing, incomplete, not legible		X

4.4.3 Dimensional and weight examination. Examination shall be made of the end item for compliance with dimensions and weight specified. Any nonconformance shall be classified as a defect. The inspection level shall be S-2 with an AQL of 4.0 defects, expressed in terms of defects per hundred units.

4.4.4 Packaging inspection. An examination shall be made to determine that preservation, packing, and marking comply with section 5. Defects shall be scored in accordance with table IV. The sample unit shall be one shipping container fully packaged. The lot shall be the number of containers offered for inspection at one time. The inspection level shall be S-2 and the AQL shall be 4.0 expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:23Z
Check the source to verify that this is the current version before use.

TABLE IV. Packing defects

Examine	Defect
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Any nonconforming component, component missing, damaged or otherwise defective.
Workmanship	Inadequate application of components such as: incomplete closure of container flaps, loose strapping, bulged or distorted container.

4.4.5 Examination of palletization. An examination shall be made to determine that palletization is in compliance with section 5. Defects shall be scored as specified in table IV. The sample unit for this examination shall be one palletized unit load ready for shipment. The lot shall be the number of palletized unit loads submitted for inspection at one time. The inspection level shall be S-1 with an AQL of 6.5 expressed in terms of defects per hundred units.

TABLE IV. Examination of palletization

Examine	Defect
Finished dimension	Length, width, or height exceeds specified maximum requirement.
Palletization	Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded with required straps specified.
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Preservative methods.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:23Z
Check the source to verify that this is the current version before use.

5.1.1.1.1 Machine head and motor. Each machine head and mechanical components shall be preserved in accordance with Method I of MIL-P-116. Openings in the motor shall be sealed with waterproof tape conforming to PPP-T-60. Parts of the head and motor that are free to move or rotate shall be secured in a fixed position to prevent movement or vibration while in transit.

5.1.1.1.2 Tools, needles, and repair parts. Tools, needles, and repair parts shall be preserved by Method 1C-1 of MIL-P-116. The pulley belt may remain on the pulley in a relaxed position.

5.1.1.1.3 Manual and handbook of instructions. Manual and handbook shall be preserved by Method 1C-1 of MIL-P-116.

5.1.1.2 Unit pack.

5.1.1.2.1 Type I. Tools, needles, repair parts, manual and handbook of instructions shall be placed in the tool compartment of the carrying case. The sewing machine head and motor, shall be mounted and secured to the base in the normal operating position. The case cover shall be secured in place. Each hasp and locking assembly shall be immobilized by taping to the carrying case.

5.1.1.2.2 Type II. Tools, needles, repair parts, manual and handbook of instructions preserved as specified in 5.1.1.1.2 and 5.1.1.1.3 shall be packaged in a snug fitting fiberboard box, conforming to style RSC, grade V3s, V3c or V4s of PPP-B-636. Closures and waterproofing shall be in according with the appendix of PPP-B-636. The box containing the tools, etc., shall be secured in an unused portion of the shipping container under the table top.

5.1.2 Commercial. Sewing machines shall be preserved in accordance with MIL-STD-1188.

5.2 Packing. Packing shall be level A, B or Commercial as specified (see 6.2).

5.2.1 Level A packing.

5.2.1.1 Type I. Each sewing machine, complete with carrying case, preserved as specified in 5.1, shall be packed in a snug-fitting shipping container conforming to overseas type, style A, B, I, or J of PPP-B-601 or class 2, style 2, 4, or 4-1/2 of PPP-B-621. Built up pads, scored fiberboard sheets, or wood spacers shall be fitted into each corner of the shipping container to provide a minimum of 1/2-inch clearance between ends and sides of the shipping container and protruding parts of the carrying case. Closure and strapping shall be in accordance with the applicable container specification.

5.2.1.2 Type II. The sewing machine head, preserved as specified in 5.1.1.1.1, shall be placed in the recessed section of the case base and secured with the clamps provided. The spool holder shall be secured to the case base cross member with screws provided. The table shall be mounted to the case base using hardware specified on Drawing 5-13-1981. The table top shall be lowered to allow the transmitter to rest securely in the support and the leg bolts tightened to maintain this position on the base member using the screws specified on above drawing. The case top, sides, and end panels shall be assembled to base as shown on Drawing 5-13-1979.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:23Z
Check the source to verify that this is the current version before use.

5.2.2 Level B packing.

5.2.2.1 Type I. Each sewing machine, complete with carrying case, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC, grade V3c, V3s, or V4s of PPP-B-636, except that the weight limitations shall be waived. Built-up pads or scored fiberboard sheets of the same material as the container or wood spacers shall be fitted into each corner of the shipping container to provide a minimum of 1/2-inch clearance between ends and sides of the shipping container and protruding parts of the carrying case. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V, and reinforced in accordance with the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.4.

5.2.2.2 Type II. Each sewing machine, complete with case, shall be packed as specified in 5.2.1.2.

5.2.3 Commercial packing. Sewing machines complete, preserved as specified in 5.1, shall be packed in accordance with MIL-STD-1188.

5.3 Palletization. When specified (see 6.2), complete sewing machines, packed as specified shall be palletized in accordance with load type I of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern intended to be used shall be submitted to and approved by the contracting officer prior to its use.

5.4 Marking. In addition to any special marking required by the contract, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129 or MIL-STD-1188, as applicable.

5.4.1 Additional marking. Cases for type II sewing machines shall be marked with the words "To open remove leg screws" on two sides of the container in letters not less than 1-inch high.

6. NOTES

6.1 Intended use. The type I industrial sewing machine is intended to be used in the field for repairing uniforms and work clothing. The type II industrial sewing machine is intended to be used in the field for repairing tentage and tarpaulins.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:23Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Type required (see 1.2).
(c) When a first article is required (see 3.2, 4.2 and 6.3).
(d) Contract data requirements (see 3.5).
(e) Selection of the applicable levels of preservation and packing, (see 5.1 and 5.2).
(f) When palletization is required (see 5.3).

6.2.1 Contract data requirements. Any data item to be delivered under any contract for items covered by this specification should be specifically called for in accordance with the applicable regulation of the procuring activity (see 3.5 and 6.2).

6.3 First article. The items require first article examination and approval under the appropriate provisions of paragraph 7-104.55 of the Defense Acquisition Regulations. The first article should be a preproduction sample, or other specific item described under the definition of a first article in the DAR. The contracting officer should specify the appropriate type of first article and the number of units to be furnished.

6.4 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification (see 3.3).

6.5 Sewing machine sources. The clothing sewing machines (3.4.1) are available under Singer 331U104, Chandler C765 and Pfaff 463-34/01. Sewing machines (heavy duty) (3.4.2) are available under Singer 144A and Adler 220 76-73.

6.6 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodians:

Army - GL
Air Force - 99

Review activity:

Army - MD

User activity:

Navy - MC

Preparing activity:

Army - GL

Project No. 3530-0068

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:23Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and Development
Command
ATTN: DRDNA-ES
Natick, MA 01760

FOLD

☆ U.S. GOVERNMENT PRINTING OFFICE: 1981—703-023/4287 2-1

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:23Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE
MIL-S-43026D Sewing Machines, Industrial, Complete With Carrying, Shipping, And Storage Cases

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:23Z
Check the source to verify that this is the current version before use.