[INCH-POUND]
A-A-1718A
December 16, 1996
SUPERSEDING
A-A-1718
April 27, 1981

COMMERCIAL ITEM DESCRIPTION

MAGNETIC STRIP

The General Services Administration has authorized the use of this commercial item description (CID) by all federal agencies.

1. SCOPE.

1.1. Scope. This commercial item description covers flexible magnetic strip rolls with adhesive backing.

2. CLASSIFICATION.

2.1 Classification. The magnetic strips covered by this CID shall be furnished in one-hundred (100) foot (30.5m) rolls and conform with the following sizes.

	Width/ in (mm)	Thickness/ in (mm)
	+ or - 1/16 (1.58)	+ or - .01 (.254)
Size 1	- 0.500 (12.7)	0.06 (1.524)
Size 2	- 1.00 (25.4)	0.06 (1.524)
Size 3	- 1.00 (25.4)	0.09 (2.057)
Size 4	- 2.00 (50.8)	0.06 (1.524)

3. SALIENT CHARACTERISTICS.

3.1 Construction. The magnetic strip shall consist of a fine magnetic powder thoroughly dispersed in a flexible thermoplastic, curable plastic or rubber binder. The polymers shall be resistant to ozone, oxygen, acids or other corrosive chemicals.

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any other data which may improve this document should be sent to: General Services Administration, Engineering Group (7FXEE), 819 Taylor Street, Fort Worth, TX 76102.

FSC 5340

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:16Z
Check the source to verify that this is the current version before use.

3.1.1 Adhesion: The magnetic strip shall have a pressure sensitive adhesive on one side of the strip/tape. The adhesive side shall have a removable protective cover.

3.1.2 Performance Criteria: The following pre-conditioning criteria should be established prior to any performance testing of the magnetic strip:

> The contact surface area shall be clean and smooth. The strip shall be applied and adhere to a vertical plane surface.

3.1.2.1 Glass/Plexiglas surfaces. The adhesive back surface of the strip shall be capable of maintaining a load of 8-oz (236.58ml) per square inch, for a minimum of two (2) minutes, without any measurable downward vertical movement of the strip when tested on glass or Plexiglas surfaces.

3.1.2.2 Metallic surfaces. The magnetic surface of the strip shall be capable of maintaining a load of 5-oz (147.86ml) per square inch, for a minimum of two (2) minutes, without any measurable downward vertical movement of the strip when tested on metallic surfaces.

3.2 Finish. The magnetic strip shall not contain any materials or ingredients that will attack paint.

3.3 Workmanship. The magnetic strips shall be clean, rigid, and free from cracks, sharp fins or edges. Finish shall be free from lumps, blisters, grit, uncoated areas, flaking and foreign material. There shall be no defects that affect appearance, function or serviceability.

4. REGULATORY REQUIREMENTS

4.1 Regulatory Requirements. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:16Z
Check the source to verify that this is the current version before use.

4.2 Metric Products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within the tolerances specified and all other requirements of this document are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable.

5. QUALITY ASSURANCE PROVISIONS

5.1 Product Conformance. The products provided shall meet the salient characteristics of this description, conform to the producer's own drawings, specifications standards and quality assurance practices and be the same product offered for sale in the commercial market. The Government reserves the right to require proof of such conformance.

6. PACKAGING

6.1 Packaging. The preservation packing, and marking shall be as specified in the contract or order.

7. NOTES

7.1 Part Identification Number (PIN). Magnetic strip rolls conforming to this commercial item description shall be identified by a part number configuration consisting of identification from a portion of the CID number and size. An example of the part number configuration is shown below. This part numbering system is intended for identification and cross-indexing of the item within numbering procedure is for government purposes and does not constitute a requirement for the contractor.

A17181
| |----Size depicted in inches
|----- Basic CID number

PART NUMBER	SIZE	NSN
A17181	1	5340-00-761-7471
A17182	2	5340-00-914-5107
A17183	3	5340-00-914-5109
A17184	4	5340-00-914-5110

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:16Z
Check the source to verify that this is the current version before use.

7.2 Ordering data. Purchaser's should select the preferred options permitted herein and include the following information in procurement documents (if applicable).

a. Title, number, and date of this commercial item description.
b. Size.
c. The preservation, packing and marking desired.

Military Coordinating Activity

Air Force 99 (CASC)

Reviewing Activity:

Air Force 82 (SA-ALC)

Preparing Activity
GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:16Z
Check the source to verify that this is the current version before use.