MIL-B-43542B
31 December 1985
SUPERSEDING
MIL-B-43542A(GL)
20 November 1978

MILITARY SPECIFICATION

BOOT, DOG

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers the requirements for one type of dog boot.

1.2 Classification. The dog boot shall be of the following sizes as specified (see 6.2): Regular and Large.

2. APPLICABLE DOCUMENTS

2.1 Government documents. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this document to the extent specified herein.

SPECIFICATIONS

FEDERAL

V-T-285	- Thread, Polyester
KK-L-2004	- Leather, Cattlehide, Deerskin and Horsehide, Chrome Tanned

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to U.S. Army Natick Research and Development Center, Natick, MA 01760-5014, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 3770

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:39Z
Check the source to verify that this is the current version before use.

DDD-L-20 - Label: For Clothing, Equipage, and Tentage, (General Use)
PPP-B-601 - Boxes, Wood, Cleated-Plywood
PPP-B-636 - Boxes, Shipping, Fiberboard

MILITARY

MIL-C-7219 - Cloth, Duck, Nylon
MIL-F-21840 - Fastener Tapes, Hook and Pile, Synthetic

STANDARDS

FEDERAL

FED-STD-751 - Stitches, Seams, and Stitchings

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads

DRAWING

U.S. ARMY NATICK RESEARCH AND DEVELOPMENT CENTER

2-1-78 - Boot, Dog; Sizes Regular and Large; Assembly and Details

(Copies of documents required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

* 2.2 Other publications. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this document to the extent specified herein.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:39Z
Check the source to verify that this is the current version before use.

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of conflict between the text of this document and the references cited herein, the text of this document shall take precedence.

3. REQUIREMENTS

3.1 First article. When specified, a sample shall be subjected to first article inspection (see 4.3, 6.2, and 6.3).

* 3.2 Materials and components. The materials and components shall conform to the referenced documents and requirements specified herein. Recycled material may be used (see 6.4).

* 3.2.1 Cloth, duck, nylon. The cloth for body A and body B shall be a plain weave nylon duck conforming to type III, class 3 of MIL-C-7219. The color shall be olive green 106.

3.2.2 Thread, polyester. The thread shall conform to type I, class 1, sub-class B, shade S-1 (Cable No. 66022) of V-T-285. The dyed thread shall show fastness to weathering equal to or better than the standard shade sample. When no standard shade sample is available, the thread shall show good fastness to weathering. Thread sizes shall be as follows:

For stitching fabric to fabric - Size FF
For stitching leather to fabric - Size E

3.2.3 Leather, deerskin. The leather used in the dog boot sole shall be full grain, soft, flexible deerskin conforming to type II, class 2 of KK-L-2004.

3.2.3.1 Thickness. The thickness of the leather for the dog boot shall be not less than 2 1/2 ounces nor more than 4 ounces. (NOTE: One ounce equals 1/64 inch).

3.2.3.2 Color. The color of the leather shall be brown. Variation in shade on the flesh side caused by shaving will be permissible.

3.2.4 Fastener tape. The fastener tape shall be 1 inch wide and shall conform to type II, class 1 of MIL-F-21840. The color of the tape shall be OG-106.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:39Z
Check the source to verify that this is the current version before use.

3.3 Construction. The construction of the dog boot shall conform to Drawing 2-1-78 and as specified herein. As an alternative to overstitching the raw edges of the cloth (see section N-N), the "burn edge" process may be used.

3.3.1 Stitching, machine.

3.3.1.1 Types of stitching. All stitch types shall conform to FED-STD-751 as follows:

For stitching fabric to fabric	- Type 301, 5 to 7 stitches per inch
For stitching leather to fabric	- Type 301, 5 to 7 stitches per inch

Thread tension shall be maintained so there will be no loose stitching resulting in a loose bobbin or top thread or no excessively tight stitching resulting in puckering of the materials sewn.

* 3.3.1.2 Stitching ends. Stitching ends shall be overstitched not less than 1 inch on stitch type 301, except where ends are turned under in a hem, where ends are held down by other stitching, or where stitching is performed automatically. As an alternate to overstitching the raw edges of the nylon, the "burn edge" process may be used.

3.3.1.3 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

a. When thread breaks or bobbin run-outs occur during sewing, the stitching shall be repaired by restarting the stitching a minimum of 1 inch back of the end of the stitching.

b. Thread breaks, two or more consecutive skipped stitches or runoffs noted during inspection of the item (in-process or end item) shall be repaired by overstitching. The stitching shall start a minimum of 1 inch in back of the defective area, continue over the defective area, and continue a minimum of 1 inch beyond the defective area onto the existing stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching, without damaging the materials, and restitching in the required manner.

c. When making the repairs in (a) and (b), the ends of the stitching are not required to be backstitched.

3.3.1.4 Lubrication of thread. The addition of any lubricant to the polyester thread prior to or during sewing operation is prohibited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:39Z
Check the source to verify that this is the current version before use.

3.4 Marking. All marking shall conform to DDD-L-20.

3.4.1 Special marking. The application of the letters "US" shall conform to type IV, class 9 in the size characters and in the locations shown on Drawing 2-1-78. Class 9 markings shall be clearly legible after subjection to accelerated weathering.

3.4.2 Identification marking. The identification marking shall conform to type IV, class 5 in the location shown on Drawing 2-1-78.

3.5 Replacement of defective components. During the spreading, cutting, and manufacturing process, components having material defects or damages that are classified as defects in 4.4.3.1 shall be removed from production and replaced with non-defective and properly matched components.

3.6 Workmanship. The finished boots shall be manufactured in such a manner as to be uniform in quality and shall be free from holes, cuts, tears, stains, open seams, and other defects that will adversely affect life, serviceability, or appearance.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 6.3), it shall be inspected in accordance with the quality assurance provisions of this document and evaluated for overall appearance. Any failure to conform to the quality assurance provisions of this document or any appearance failure shall be cause for rejection of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:39Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.4.2 In-process inspection. Inspection shall be made at any point or during any phase of manufacturing to determine whether operations or assemblies are accomplished as specified. The Government reserves the right to exclude from consideration for acceptance any material or services for which in-process inspection has indicated nonconformance.

4.4.3 End item inspection. The lot shall consist of all completely fabricated boots offered for inspection at one time. The sample unit for this inspection shall be one completely fabricated boot.

4.4.3.1 Visual examination. Visual examination shall be made of the completely fabricated boot for the defects listed in table I. The inspection level shall be II, and the acceptable quality level (AQL) shall be 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

TABLE I. Classification of visual defects

Examine	Defect	Classification	
		Major	Minor
Fabric	Any smash, weak place, broken or missing yarns, multiple floats or open place clearly visible at normal inspection distance (approximately 3 feet)		X
	Shade bar or fine or coarse filling bar		X
	Hole (except drill hole), cut or tear	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:39Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of visual defects - Continued

Examine	Defect	Classification	
		Major	Minor
Leather			
Quality	Any hole	X	
	Any cut or rupture	X	
	Brand, scar tissue, brittle or bony area		X
	Abraded, scratched or other grain damage		X
	Flanky, spongy, or stretchy leather	X	
	Wrinkles		X
Cleanness	Stains		X
Component and assembly	Any component or required operation omitted (unless otherwise classified herein)	X	
Seams and stitching	Any row of stitching omitted	X	
	Less than 5 stitches per inch	X	
	More than than 7 stitches per inch		X
	Any open seams	X	
	Repair of open seam not as specified		X
	NOTE: A seam shall be classified as open when one or more stitches joining a seam are broken or when two or more consecutive skipped or runoff stitches occur.		

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:39Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of visual defects - Continued

Examine	Defect	Classification	
		Major	Minor
Stitching ends	Thread ends not trimmed where required		X
Seam and stitch type	Wrong seam or stitch type		X
Stitch tension	Loose, resulting in a loosely secured seam or locks exposed on surface of leather		X
	Tight, causing stitches to rupture leather	X	
Marking	Omitted, incomplete, incorrect, not legible, not specified size, not in proper location, or not accomplished as specified		X

4.4.3.2 Dimensional examination. Examination shall be made of dog boots for compliance with specified dimensions. Any dimension that is not within specified tolerances shall be classified as a defect. The inspection level shall be S-3, and the AQL shall be 4.0, expressed in terms of defects per hundred units.

4.4.4 Packaging inspection. An examination shall be made to determine that the preservation, packing, and marking comply with the section 5 requirements. Defects shall be scored in accordance with table II. The lot shall be all the containers offered for inspection at one time. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2, and the AQL shall be 2.5, expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:39Z
Check the source to verify that this is the current version before use.