12-29-82

MIL-S-43505D(GL)
10 September 1982
SUPERSEDING
MIL-S-43505C(GL)
27 January 1975

MILITARY SPECIFICATION

SHIRT, WOMAN'S, POLYESTER/COTTON

This specification is approved for use by the Natick Research and Development Laboratories, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

* 1.1 Scope. This document covers a woman's polyester/cotton shirt with collar tab.

1.2 Classification. The shirt shall be one type in the following sizes as specified (see 6.2):

Schedule of sizes

6	14
8	16
10	18
12	20

2. APPLICABLE DOCUMENTS

* 2.1 Government documents. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addresssed to: US Army Natick Research and Development Laboratories, Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 8410

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:34Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

V-B-871	-	Button, Sewing Hole, and Button, Staple, (Plastic)
DDD-L-20	-	Label: For Clothing, Equipage and Tentage (General Use)
PPP-B-636	-	Boxes, Shipping, Fiberboard
PPP-B-665	-	Boxes: Paperboard, Metal Edged and Components
PPP-B-676	-	Boxes, Setup

MILITARY

MIL-C-43479	-	Cloth, Broadcloth, Polyester and Cotton
MIL-T-43548	-	Thread, Polyester, Cotton-Covered
MIL-C-43843	-	Cloth, Plain Weave, Polyester/Cotton, Precured, Durable Press
MIL-C-43836	-	Cloth, Interlining, Non-Woven

STANDARDS

FEDERAL

FED-STD-751	-	Stitches, Seams, and Stitchings

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-1188	-	Commercial Packaging of Supplies and Equipment

(Copies of documents required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

Technical Manual of the American Association of Textile Chemists and Colorists

(Application for copies of the AATCC Manual should be addressed to the American Association of Textile Chemists and Colorists, Research Triangle Park, P.O. Box 12215, Durham, NC 27709.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

Source: https://assist.dla.mil -- Downloaded: 202640-21T21:34Z
Check the source to verify that this is the current version before use.

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence.

3. REQUIREMENTS

3.1 Guide samples. Guide samples, when furnished, are solely for guidance and information to the contractor (see 6.3). Variations from this document may appear in the sample, in which case this document shall govern.

* 3.2 Materials (see 6.6).

3.2.1 Basic material. The basic material shall be polyester/cotton broadcloth, bleached white, conforming to type I, class 1 of MIL-C-43479.

3.2.2 Collar tabs. The material for the collar tabs shall be plain weave, poplin, precured, durable press polyester/cotton cloth, Black 305, conforming to MIL-C-43843. As an alternate, the material may be Klopman Mills, Black 305, "Utopia Plus" style No. 5409 or equal.

3.2.3 Collar interlining. The material for collar interlining shall be non-woven interlining cloth conforming to type I, class 1 of MIL-C-43836.

3.2.4 Labels. Each shirt shall have an identification, a size and instruction label conforming to DDD-L-20. The fastness to laundering requirements of DDD-L-20 shall apply.

3.2.4.1 Identification. The identification label shall conform to type IV or VI, class 1.

* 3.2.4.2 Size label. The size label shall conform to type IV or VI, class 2.

3.2.4.3 Instruction label. The instruction label shall conform to type IV or VI, class 3 (except that the item identification need not be repeated) and shall contain the following information:

LAUNDERING INSTRUCTIONS

Launder in warm water using
mild soap or detergent. Scrub
soiled areas. DO NOT BLEACH.
Rinse thoroughly in clear, warm
water. Do not squeeze or wring out.
Press when dry or nearly dry on wrong
side with steam iron set at low heat.

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:34Z
Check the source to verify that this is the current version before use.

3.2.4.4 Combination label. A combination identification label (class 1) and instruction label (class 3) may be used. The combination label shall conform to the requirements of type IV or VI, class 3 label.

* 3.2.5 Thread. Thread for seaming and stitching shall be cotton-covered polyester conforming to ticket numbers 70-2 ply and 80-2 ply of MIL-T-43548.

3.2.5.1 Color and colorfastness. The thread shall be Black AA, C.A. 66043 for making the collar tabs, and White AH, C.A. 66050 for all other stitchings and tacking the collar tabs. The dyed thread shall show fastness to laundering (after 3 cycles) and light equal to or better than the standard sample. When no standard sample is available, the dyed thread shall show "good" fastness to laundering (after 3 cycles) and light.

3.2.6 Buttons. The buttons for front closure shall be type II, style 25, class K, 14-line for neck closure and 21-line for front, Polyester White, Shade BA, Cable No. 62031, conforming to V-B-871.

3.2.7 Snap fasteners. The snap fasteners for the collar tab closure shall be round or square sew-on type, size 00, brass with black japan finish.

* 3.3 Design. The shirt is hip length, semi-fitted, short sleeved, with a one piece back-to-front yoke and a collar with rounded ends and collar tabs designed with 2 snap fasteners (see figure 1).

3.4 Figure. Figure 1 is furnished for information only. To the extent of any inconsistencies between the document and the figure, the document shall control.

3.5 Patterns. Standard patterns for use in cutting working patterns will be furnished by the Government. The working patterns shall be identical to the Government patterns which shall not be altered in any way. The patterns provide a seam allowance of 1/4 inch for collar tabs, collar, collar stand and collar setting, and 1/2 inch for overedged seams and for bottom of facings. In the safety stitch construction, the 1/2 inch seam allowance shall be maintained even though the finished seam allowance shall measure from 3/8 to 7/16 inch wide (1/16 to 1/8 inch trimmed off).

3.5.1 Pattern parts. The component parts shall be cut from materials as specified and according to the number of parts listed in table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:34Z
Check the source to verify that this is the current version before use.

TABLE I. List of pattern parts

Material	Pattern nomenclature	Cut parts
Polyester/cotton cloth	Front	2
	Back	1
	Yoke	1
	Sleeve	2
	Top collar 1/	1
	Under collar	1
	Collar stand	2
Plain weave, precured, durable press, polyester/ cotton cloth (black)	Collar tab	2
Non-woven polyester interlining cloth	Top collar interlining 1/	1
	Buttonhole Marker	

1/ Use same pattern part.

3.6 Construction.

3.6.1 Stitches, seams and stitching. Stitch, seam and stitching types, specified in table II, shall conform to FED-STD-751. Where two or more seam or stitch types are given for the same operation, any one of them may be used. Seam allowances shall be maintained with the seams sewn so that no raw edges, runoffs, twists, pleats, puckers or open seams will result (see 6.4). All seams shall start and finish evenly. Thread tension shall be maintained so that there is no tight or loose stitching. Seams required to be worked out that have a depth between the fold of 1/16 inch or more shall be considered a defect.

3.6.2 Stitches per inch. The minimum and maximum number of stitches per inch shall be as specified in table II.

3.6.3 Thread breaks and ends of seams. Ends of all seams and stitching (except darts), when not caught in other seams, shall be backtacked not less than 1/4 inch. The ends of a continuous line of stitching, except on labels, shall be overlapped not less than 1/2 inch. The ends of label stitching shall be overlapped not less than three stitches. Thread breaks shall be secured by stitching back of the break not less than 1/2 inch. Skipped stitches or thread breaks on 401 stitch type may be repaired by using 301 stitch type. The thread ends of darts shall be trimmed to a length of 1/2 to 3/4 inch.

3.6.4 Buttonholes. The buttonholes shall be straight cut, and tacked at both ends.

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:34Z
Check the source to verify that this is the current version before use.

3.6.5 Seam appearance rating. A seam appearance rating of the shirt better than Standard 3 is considered acceptable. One or more seams on the shirt not meeting the rating shall be considered one defect. The seams as listed in 4.2.2 shall be evaluated.

3.7 Manufacturing operations requirements. The shirt shall be manufactured in accordance with operation requirements specified in table II. The contractor is not required to follow the exact sequence of operations listed.

3.7.1 Shade and size marking. The component parts of the shirt shall be marked to insure a uniform shade and size throughout the shirt. Any method of marking may be used except:

(a) Corrosive metal fastening devices.
(b) Sew-on type tickets.
(c) Adhesive type tickets which leave traces of paper or adhesive on the material upon removal of the tickets.

3.7.2 Pressing. Pressing, as required in table II, shall be performed with a heated pressing iron or machine, set at a suitable temperature for synthetics.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:34Z
Check the source to verify that this is the current version before use.

NO.	TABLE II. MANUFACTURING OPERATIONS REQUIREMENTS	STITCH TYPE	SEAM AND STITCHING TYPE	STITCHES PER INCH	THREAD		
					NEEDLE	BOBBIN/ LOOPER	COVER
1.	Cutting. a. Cut the shirt in strict accordance with the patterns furnished, which show directional lines, size, and notches for proper assembly of parts. Directional lines shall be placed in the warp direction of the material. b. Cut basic material parts of each shirt out of the same piece of material except top and under-collar stands which may be cut from ends. Parts cut from ends shall approximate the shade of the shirt.						
2.	Replacement of damaged parts. Care shall be exercised during the spreading, cutting and manufacturing operations to assure that material defects and damages as classified in 4.2.2 are excluded and replaced with non-defective and properly matched material.						
3.	Marking (see 3.7.1). a. Mark, ticket or bundle all component parts of the shirt, except those cut from ends, to insure correct size and a uniform shade throughout the shirt. b. Apply size marking (type IV label) on the top collar stand at center back. On the finished shirt the marking shall not be horizontally off center by more than 1/4 inch nor vertically off center by more than 1/8 inch. (See operation 14.d if type VI label is used.)						

NATICK Form 903
1 Dec 76 EDITION OF 1 OCT 76 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:34Z
Check the source to verify that this is the current version before use.

NO.	TABLE II. (cont'd) MANUFACTURING OPERATIONS REQUIREMENTS	STITCH TYPE	SEAM AND STITCHING TYPE	STITCHES PER INCH	THREAD		
					NEEDLE	BOBBIN/ LOOPER	COVER
3.	Marking (see 3.7.1). (cont'd)						
	c. Apply the instruction label on the left facing (as worn), positioned at the bottom of the facing so that on the finished shirt the bottom line of printing will not be less than 1/4 inch from the back edge of facing and the right side of the label will be 1/2 to 3/4 inch from the finished bottom.						
	d. Apply the identification label on the left front facing with the bottom of the label not less than 1/2 inch from the top of the instruction label and the left side of the label not less than 1/4 inch from the back hemmed edge of facing.						
	e. Combination label, if used, shall be positioned as in "c" above.						
	NOTE: On stamped (type IV) labels, ink shall not be through shirt front.						
4.	Make collar tabs.						
	a. Fold tab in half and stitch from folded edge around curve and tab extension, terminating the stitching one stitch below end of diagonally slashed seam allowance. Pivot at this point and stitch back on line of stitching for 3/8 to 1/2 inch.	301	SSa-1	10-14	70-2 (black)	70-2 (black)	
	b. Trim (if necessary), turn, work out edges and tab extension and baste or press edges.	Hand or machine					

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:34Z
Check the source to verify that this is the current version before use.

NO.	TABLE II. (cont'd) MANUFACTURING OPERATIONS REQUIREMENTS	STITCH TYPE	SEAM AND STITCHING TYPE	STITCHES PER INCH	THREAD		
					NEEDLE	BOBBIN/ LOOPER	COVER
5.	Make collar.						
	a. Stitch top collar to interlining around the outer edge. The stitching shall not be exposed on the finished collar.	301	SSa-1	6-8	70-2	70-2	
*	b. Stitch top collar (interlining attached) to undercollar, matching notches and distributing fullness of top collar. Trim curves, turn collar and raise stitch with the seam turned toward the under collar, and the stitching 1/32 to 1/16 inch from joining seam. The raise stitching shall start and finish 2 to 3 inches from each end of collar, or the raise stitching may start at end of collar and be sewn continuously to opposite end.	301 or 401 301	LSq-2(a) LSq-2(a) and LSq-2(b)	10-14 10-14 10-14	70-2 70-2 70-2	70-2 80-2 70-2	
	c. Press entire collar flat.						
	d. Place collar (three plies) between the collar stands with notches matched and edges even and stitch all plies together.	301	SSq-2(a)	10-14	70-2	70-2	
	e. Turn down collar stands and raise stitch top collar stand through under collar stand 1/32 to 1/16 inch from edge.	301	SSq-2(b)	10-14	70-2	70-2	
	f. Position collar tabs under collar with the tabs extending 1/2 ± 1/16 inch beyond collar at neck and with point of slash on tab extension aligned with the front edge of collar 1/4 inch down. Baste tab to collar along neck edge 3/16 inch from edge. Collar and tabs shall be uniformly shaped and tabs shall extend equally at each collar end. The tab extensions shall measure 3/4 ± 1/8 inch beyond collar-to-neck joining seam on the finished shirt.	Hand or machine			70-2 70-2		

Source: https://assist.dla.mil - Downloaded: 2026-02-21T21:04Z
Check the source to verify that this is the current version before use.

TABLE II. (cont'd)

NO.	MANUFACTURING OPERATIONS REQUIREMENTS	STITCH TYPE	SEAM AND STITCHING TYPE	STITCHES PER INCH	THREAD		
					NEEDLE	BOBBIN/ LOOPER	COVER
5.	Make collar. (cont'd) The ends of the collar shall be in line with the inner edge of tab extension.						
6.	Tack collar tabs. Tack the collar tabs to the under collar at the lower end of the straight edge. Do not catch the top collar in the stitching. On the finished shirt the collar, under collar and tabs shall lie flat and the under collar shall not be pleated near the tack at the lower end of the straight edge of the tab. The lower back edge of the tabs at the edge of the collar shall end the same distance from the front ends of the collar and shall not extend beyond the edge of the collar.	Hand or 306 or 314 or 101		3-6 per tack 3-6 per tack 3-6 per tack	70-2 70-2 70-2	70-2 70-2 70-2	
7.	Make sleeve (alternate pre-hemmed method). Hem sleeve as indicated by marks on pattern, with the hem folded to the inside of the sleeve, with the raw edge turned in and the stitching 1/16 to 1/8 inch from edge. The hem shall finish 2 inches wide.	301	EFb-1	12-16	70-2	70-2	
8.	Make darts on fronts and backs. Fold darts as indicated by marks on pattern and stitch across top, pivot and taper to nothing 3/4 inch beyond drill holes.	301	OSf-1	10-14	70-2	70-2	

Source: https://assist.dla.mil -- Downloaded: 2020-10-21T21:04Z
Check the source to verify that this is the current version before use.

NO.	TABLE II. (cont'd) MANUFACTURING OPERATIONS REQUIREMENTS	STITCH TYPE	SEAM AND STITCHING TYPE	STITCHES PER INCH	THREAD		
					NEEDLE	BOBBIN/ LOOPER	COVER
9.	Attach yoke.						
	a. Stitch yoke to fronts and backs with a safety stitch folding pleats on front and back as indicated by marks on pattern. The folded edge of the pleats shall face the sides on the outside of shirt.	515 or 516 or 519	LSbm-3(a)	10-14	80-2 (chain 80-2 (overedge)	80-2 stitch) 80-2	
	b. Raise stitch seams with seams turned toward yoke and with the stitching 1/16 to 1/8 inch from joining seam.	301	LSbm-2(b)	10-14	70-2	70-2	
10.	Set sleeves.						
	a. Place a tension (shirr) stitch at cap of sleeve, between notches, to distribute fullness evenly. (If sleeve setting machine has an automatic device for distributing cap fullness, this operation may be omitted.)	301		8-14	70-2	70-2	
	b. Set sleeve with a safety stitch distributing fullness equally over the cap between the notches.	515 or 516 or 519	SSa-2	10-14	80-2 (chain 80-2 (overedge)	80-2 stitch) 80-2	
11.	Join sides.						
	a. If alternate method of pre-hemming cuff (operation 7) is used, form sleeve cuff to finish 1-1/4 ± 1/8 inches wide and join side seams and underarm seams in one operation with a safety stitch. Sleeve setting seam, at underarm, staggered more than 1/4 inch will not be acceptable. (If machine does not have an automatic trimmer, the turned cuff seam allowance at the underarm shall be trimmed to match the underarm seam allowance of sleeve, prior to joining the side and underarm seams).	515 or 516 or 519	SSa-2	10-14	80-2 (chain 80-2 (overedge)	80-2 stitch) 80-2	

NATICK Form 903
1 Dec 76 EDITION OF 1 OCT 76 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-02-21 21:34Z
Check the source to verify that this is the current version before use.

NO.	TABLE II. (cont'd) MANUFACTURING OPERATIONS REQUIREMENTS	STITCH TYPE	SEAM AND STITCHING TYPE	STITCHES PER INCH	THREAD		
					NEEDLE	BOBBIN/ LOOPER	COVER
11.	Join sides. (cont'd)						
	b. Turn underarm seam allowance toward back of sleeve and horizontally bartack bottom of cuff fold 1/8 to 3/16 inch from bottom, with a 1/2 to 5/8 inch bartack, catching the turned back seam allowance and the end of chain thread (if chain thread seam is used in operation "a" above.	Bartack		28 per 1/2 inch	70-2	70-2	
	-or (if cuff is not pre-hemmed)-						
	c. Join side seams and sleeve seams in one operation with a safety stitch with the ends of seams even at start and finish, and with the sleeve setting seam turned toward sleeve. Sleeve setting seam, at underarm, staggered more than 1/4 inch will not be acceptable. (Edges of the seam that will be enclosed in the hemmed cuff need not be overedged.)	515 or 516 or 519	SSa-2	10-14	80-2 (chain stitch) 80-2 (overedge)	80-2 80-2	
12.	Hem sleeves (if not pre-hemmed).						
	a. Hem sleeves, as indicated by marks on pattern, with hem folded to the inside of the sleeve with the raw edge turned in and the stitching 1/16 to 1/8 inch from edge. The underarm seams shall be turned toward the back.	301	EFb-1	10-14	70-2	70-2	
	b. Make cuff by folding up bottom of sleeve 1-1/4 ± 1/8 inches. Stitch the cuff to sleeve through all plies. The stitching shall be the full width of the cuff and shall superimpose or be immediately adjacent to the stitching of the underarm seam.	301		10-14	70-2	70-2	

Source: https://assist.dla.mil -- Downloaded: 2026-01-21T21:34Z
Check the source to verify that this is the current version before use.

NO.	TABLE II. (cont'd) MANUFACTURING OPERATIONS REQUIREMENTS	STITCH TYPE	SEAM AND STITCHING TYPE	STITCHES PER INCH	THREAD		
					NEEDLE	BOBBIN/ LOOPER	COVER
13.*	Hem facing.						
	a. Overedge the top and back raw edge of facings.	502 or 503	EFd-1	6-10	80-2	80-2	
	- or -						
	b. Facing need not be hemmed if cut on the selvage.						
14.	Set collar.						
	Finished appearance. The collar shall fit smoothly with the ends uniform. The ends of the collar shall meet at center front (in line with buttonholes on the finished shirt). The right tab extension shall overlap the left tab. The steps shall finish 3/4 inch wide.						
	a. Prior to folding facing, stitch collar to outside of shirt 1/4 inch from edges. Continue stitching to a point 1/4 to 3/8 inch beyond end of collar tab. Slash seam allowance and stitch under collar stand to shirt. Terminate stitching 1/4 to 3/8 inch before the edge of the collar tab on the opposite end of the collar. Repeat procedure at other end of collar with stitching superimposing and overlapping 1/2 inch the previous row of stitching joining under collar to shirt.	301	SSa-1	10-14	70-2	70-2	
*	b. Fold facing over front of shirt and collar and with raw edges even, stitch across step, maintaining the 1/4 inch seam allowance and continue	301	LScf-2(a)	10-14	70-2	70-2	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:34Z
Check the source to verify that this is the current version before use.

NO.	TABLE II. (cont'd) MANUFACTURING OPERATIONS REQUIREMENTS	STITCH TYPE	SEAM AND STITCHING TYPE	STITCHES PER INCH	THREAD		
					NEEDLE	BOBBIN/ LOOPER	COVER
14.	Set collar. (cont'd)						
	stitching through all plies to within 3/8 to 1/2 inch from top end of facing; slash seam allowance at end of stitch line. Repeat procedure at other end of collar. Slash gorge seam if necessary.						
	- or -						
	Position collar to front notch and fold facing over collar, forming step. Stitch step and collar with 1/4 inch seam allowance and continue stitching to a point 1/4 to 3/8 inch beyond end of collar tab. Slash seam allowance through all plies. Continue to stitch under collar, matching center notch to center yoke, to within 1/4 to 3/8 inch of opposite collar tab. Fold facing over collar according to notch, slash seam allowance through all plies, and continue to stitch to end of step.						
	c. Turn facings to finished position; work out corner and edges.						
	d. Turn seam toward collar from slash to slash, turn in seam allowance of top collar stand, place unstitched seam allowance at end of facing under turned in top collar stand and stitch 1/16 to 3/32 inch from end, through under collar stand, catching the top edge of the size label (type VI label) in stitching (if applicable). Label shall not be off center by more than 1/4 inch.	301	LScf-2(b)	10-14	70-2	70-2	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:34Z
Check the source to verify that this is the current version before use.

NO.	TABLE II. (cont'd) MANUFACTURING OPERATIONS REQUIREMENTS	STITCH TYPE	SEAM AND STITCHING TYPE	STITCHES PER INCH	THREAD		
					NEEDLE	BOBBIN/ LOOPER	COVER
14.	Set collar. (cont'd)						
	e. With the facings and fronts smooth and flat, securely tack the top of facing to the edge of the yoke seam-allowance. An automatic straight tack may be used. (Operations d and e may be performed simultaneously.)	Hand or	SSa-1	4-6 per tack	70-2		
		301 or	SSa-1	10-14 per tack	70-2	70-2	
		301 (line tack)	SSa-1	28 per tack	70-2	70-2	
15.	Finish bottom of facings and hem shirt.						
	a. Fold back bottom of facings at notches and with the edges even stitch to bottom edge of shirt. Bottom edge of each facings is slightly longer than shirt in order to prevent tension.	301 or	SSa-1	10-14	70-2	70-2	
		401	SSa-1	10-14	70-2	80-2	
	b. Turn facings to their finished positions; force out corners and edges.						
	c. Turn in raw edge and stitch hem 1/16 to 1/8 inch from turned in edge, with the side seams turned toward back of shirt. The hem shall finish 1/4 + 1/16 inch and the stitching shall extend across the facing to the front edges of the shirt.	301	EFb-1	10-14	70-2	70-2	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:34Z
Check the source to verify that this is the current version before use.

NO.	TABLE II. (cont'd) MANUFACTURING OPERATIONS REQUIREMENTS	STITCH TYPE	SEAM AND STITCHING TYPE	STITCHES PER INCH	THREAD		
					NEEDLE	BOBBIN/ LOOPER	COVER
15.	Finish bottom of facings and hem shirt. (cont'd)						
	- or -						
	d. Fold back bottom of facing at notches. Turn in raw edge and stitch hem 1/16 to 1/8 inch from turned in edge, with side seams turned toward back of shirt. The hem shall finish 1/4 ± 1/16 inch and the stitching shall extend across the facing to the front edges of the shirt.	301	EFb-1	10-14	70-2	70-2	
16.	Make buttonholes.						
	a. Make a horizontal 3/8 inch (finished cut-length) buttonhole at the top of the right front through the shirt and facing with the front end of the opening 5/16 inch from the front edge of shirt, as indicated by the buttonhole marker.	304		36-40 per buttonhole including tack	70-2 (whip) or 70-2 (purl)	70-2 (whip) or 80-2 (purl)	
	b. Make five vertical 5/8 inch (finished cut-length) buttonholes on right front through shirt and facing as indicated by the buttonhole marker. The opening shall be 3/4 inch from the front edge.	304		52-56 per buttonhole including tack	70-2 (whip) or 70-2 (purl)	70-2 (whip) or 80-2 (purl)	
17.	Attach buttons and snap fasteners.						
	a. Sew a 14-line button at the top of the left front to correspond with the front end of horizontal buttonhole at top of right front, with the stitching through the front and facing. Collar ends shall be centered equidistant from center of shirt front and shall not overlap. When shirt is buttoned the ends of the collar shall meet.	301 101 or Hand		14-16 per button 14-16 per button 8-10 per button	70-2 70-2 70-2	70-2	

Source: https://assistdla.mil -- Downloaded: 2020-04-21T21:34Z
Check the source to verify that this is the current version before use.

NO.	TABLE II. (cont'd) MANUFACTURING OPERATIONS REQUIREMENTS	STITCH TYPE	SEAM AND STITCHING TYPE	STITCHES PER INCH	THREAD		
					NEEDLE	BOBBIN/ LOOPER	COVER
17.	Attach buttons and snap fasteners. (cont'd)						
	b. Sew five 21-line buttons on the left front to correspond with center of the five vertical buttonholes on the right front, with the stitching through the front and facings.	301 or		14-16 per button	70-2	70-2	
		101 or		14-16 per button	70-2		
		Hand		8-10 per button	70-2		
	NOTE: Hand sewn button shall be sewn with double thread and shall be tacked off with not less than two stitches.						
*	c. Sew a male part of a snap fastener on the underside of the right collar tab extension and another male part on the top side of the left collar tab extension with the center of the fasteners 1/4 to 3/8 inch from end of tab extension. Sew a female part on the top side of the left collar tab and a female part on the underside of the right collar tab. The stitching of both parts of the snap fasteners may be through both plies. When the snap fasteners are engaged, the tabs, tab extensions, collar and front of shirt shall be smooth and flat without twists, pleats or bulges.	301 or		11 per fastener	70-2	70-2	
		101 or		20-22 per fastener	70-2		
		Hand		14-16 per fastener	70-2		
18.	Clean shirt.						
	a. Trim thread ends and remove loose threads.						
	b. Remove all spots, stains and marking tickets.						

NATICK Form 903
1 Dec 76 EDITION OF 1 OCT 76 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-02-21T21:34Z
Check the source to verify that this is the current version before use.

NO.	TABLE II. (cont'd) MANUFACTURING OPERATIONS REQUIREMENTS	STITCH TYPE	SEAM AND STITCHING TYPE	STITCHES PER INCH	THREAD		
					NEEDLE	BOBBIN/ LOOPER	COVER
19.	Press shirt. a. Press shirt smooth and flat. The inside folded edge of back darts shall be pressed toward center back and front darts toward center front. The cuffs shall be uniform without twists. The top collar shall not show impressions of collar tab. The sleeves shall not be center creased and the sleeves setting seam allowance shall be pressed toward the sleeve. b. Button shirt.						

Source: https://assist.dla.mil -- Downloaded: 2026-02-21 21:34Z
Check the source to verify that this is the current version before use.

3.8 Measurements. The finished measurements of the shirt shall conform to all the measurements shown in table III. The tolerance for all measurements shall be ± 3/8 inch.

TABLE III. Measurements (in inches)

	Size							
	6	8	10	12	14	16	18	20
Half bust 1/	18-1/8	18-7/8	19-5/8	20-1/4	21	21-3/4	22-3/4	23-3/4
Cross back 2/	14-5/8	15	15-1/4	15-3/8	15-5/8	16	16-1/2	17
Back length 3/	24-1/4	24-1/2	24-3/4	25	25-1/4	25-1/2	25-3/4	26
Sleeve width 4/	5-1/2	5-3/4	6	6-1/4	6-1/2	6-3/4	7-1/4	7-1/2
Collar 5/	12-3/4	13	13-1/4	13-1/2	13-3/4	14-1/8	14-1/2	14-5/8

1/ With shirt buttoned and laid flat measure across front, at base of armholes, from folded edge to folded edge.

2/ Measure across back yoke seam.

3/ Measure down center back from neck seam to bottom of shirt.

4/ With the sleeves laid flat, measure across bottom of cuff from folded edge to folded edge.

5/ With collar open and flat, measure in a straight line at neck from end of collar to end of collar. Do not include tabs.

3.9 Workmanship. The finished shirt shall conform to the quality of the product established by this document. As a final step in the contractor's production control plan, before formation of the lot, each shirt shall be buttoned and examined on an inspection table. A shirt containing a selected major defect shall not be included in the end item lot. The selected major defects are those major defects listed in 4.2.2 indicated by an asterisk (*). The occurrence of defects other than selected major defects shall not exceed the limits established by the applicable acceptable quality levels.

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:34Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Certificate of compliance. Where certificates of compliance are submitted, the Government reserves the right to check test such items to determine the validity of the certification.

4.2 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.2.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified or qualified in this document or applicable purchase documents.

4.2.1.1 Certification. A certificate of compliance will be acceptable as evidence that the snap fasteners comply with the requirements specified in 3.2.7.

4.2.2 End item visual examination. The end item shall be examined for the defects listed below. The lot size shall be expressed in units of one shirt. The sample unit shall be one shirt. The inspection level shall be III and the acceptable quality level (AQL) shall be 1.5 major, 6.5 major and minor A combined, and 15.0 total (major, minor A and minor B combined) defects per hundred units. The finding of one or more asterisk defects, identified by an asterisk (*) in the classification column, shall be cause for rejection of the lot.

Defect	Classification Major	Minor A	Minor B
Pressing			
a. Omitted.		X	
b. Burned or scorched.	X		
c. Gloss, wrinkles or creases.			X
d. Edge bulky (not pressed solidly).			X

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:34Z
Check the source to verify that this is the current version before use.

Defect	Classification Major	Minor A	Minor B
Pressing (cont'd)			
e. Sleeve center creased.			X
f. One or more darts or seams not pressed in the direction specified.			X
g. Cuff not pressed evenly.			X
*Material defects and damages			
a. Any hole, cut, tear, smash, burn, visible mend, darn, patch, or multiple float:			
1. On outside (longest dimension in any direction).			
- up to 1/4 inch inclusive	X		
- more than 1/4 inch. 1/	(*)		
2. On inside (longest dimension in any direction).			
- up to 1/4 inch inclusive			X
- more than 1/4 inch.		X	
b. Knot or slub on outside 2/:			
1. Knot larger than B, or a slub larger than C above bottom button.	X		
2. Knot larger than C, or a slub larger than D below bottom button.			X
c. Misweave, missing yarn, broken yarn, woven in waste, thin place, shade bar; on outside. 3/	X		
d. Permanent crease in cloth (when caught in stitching).	X		
e. Loose yarn, snagged thread, coarse yarn or woven in waste. 3/			X

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:34Z
Check the source to verify that this is the current version before use.

Defect	Classification Major	Minor A	Minor B
*Material defects and damages (cont'd)			
f. Needle chew on outside (largest dimension in any direction):			
1. Up to 1/2 inch, inclusive.		X	
2. More than 1/2 inch.	X		
1/ If any of these defects appear on the outside, below the bottom button, they shall each be scored as a major defect.			
2/ For these defects use a Sears Fabric Defect Scale (see 6.5).			
3/ These defects shall not be scored when they appear below the bottom button.			
Shaded parts			
a. Outside part except collar stand shaded.	(*)		
b. Top collar stand, or under collar stand, badly shaded.			X
Cleanness			
a. Spot or stain, clearly noticeable:			
- on outside.	X		
- on inside.			X
b. One or more marking tickets not removed.			X
c. Any marking clearly visible on outside.	X		
d. Thread ends not trimmed, or loose threads not removed.			X
e. Visible basting thread not removed.			X
Component and assembly			
a. Any component part or required operation omitted or added (unless otherwise classified herein).	X		
b. Any operation not performed as specified (unless otherwise classified herein).			X

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:34Z
Check the source to verify that this is the current version before use.

Defect	Classification Major	Minor A	Minor B
Cutting			
Any component part not cut in conformance with directional lines indicated on patterns or not cut in accordance with specification requirements.	X		
Seams and stitching			
a. Accuracy of seaming and stitching:			
1. Seams or part twisted, puckered or pleated.	X		
NOTE: Photographic standards for evaluating single needle stitching prepared by the American Association of Textile Chemists and Colorists (see 2.2) are available for use as a guide for scoring this defect. Seam appearance better than Standard 3 is considered acceptable. One or more seams on the shirt not meeting the rating shall be considered one defect. The following seams shall be evaluated: Armhole, Sides and sleeves, Shoulders, Collar setting, Back yoke, Collar tab			
2. Part of material caught in unrelated operation or stitching:			
- caught in or up to, and including, 1/4 inch of stitching		X	
- caught in more than 1/4 inch of stitching.	X		
3. End of stitching when not caught in other seams or stitching backtacked less than 1/4 inch.			X
4. Stitching overlapping end of thread break less than 1/2 inch.			X
5. Ends of a continuous line of stitching overlapped less than three stitches on labels or less than 1/2 inch on all other continuous stitching.			X
6. Raw edge more than 1/4 inch long.			X

Source: https://assist.dla.mil -- Downloaded: 20261O-21T21:34Z
Check the source to verify that this is the current version before use.

Defect	Classification Major	Minor A	Minor B
Seams and stitching (cont'd)			
b. Gage of stitching and seam allowances:			
1. Irregular, i.e., unevenly gaged or corresponding stitching not uniformly gaged (to be scored only when condition exists along major portion of seam).		X	
2. Width not as specified or not within range of gage specified or varies more than 1/16 inch when no range is specified.			X
c. Stitches, broken or missing (except buttonholes):			
1. All stitching except overedging:			
- up to 1/4 inch inclusive.			X
- more than 1/4 inch to 1/2 inch inclusive.		X	
- more than 1/2 inch.	X		
2. On overedging:			
- 1 inch or more.			X
d. Skipped stitches or runoff stitches:			
- 1/4 inch up to 1/2 inch long			X
- more than 1/2 inch long.		X	
e. Seam and stitch type:			
- seam type or stitch type not as specified.		X	
f. Stitches per inch (to be scored only when condition exists on major portion of seam):			
- less than minimum or more than maximum specified.			X
g. Stitch tension (except buttonholes):			
1. Loose tension resulting in a loose seam.	X		
2. Loose tension (exposed loops of top or bottom threads) more than 1/2 inch in length.			X
3. Tight tension (stitches break when strain is applied in the direction of the seam or stitching).		X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:34Z
Check the source to verify that this is the current version before use.

Defect	Classification Major	Minor A	Minor B
Buttonholes			
a. One or more omitted or added.	X		
b. Front end of opening of horizontal top buttonhole less than 9/32 inch or more than 11/32 inch from front edge of shirt.		X	
c. Opening in any one of the lower buttonholes less than 23/32 inch or more than 25/32 inch from front edge of shirt.		X	
d. One or more slanted.		X	
e. Top buttonhole positioned vertically.	X		
f. One or more of the lower five buttonholes positioned horizontally.	X		
g. The lower five buttonholes unequally spaced by more than 1/4 inch.			X
h. Stitches not securely caught in fabric (stitches pull away from fabric).	X		
i. One or more broken or more than two continuous skipped stitches in one or more buttonholes.		X	
j. Loose stitch tension.			X
k. Ragged edge in one or more.			X
l. Not specified type or uncut.			X
m. Tacking omitted on end.		X	
Buttons			
a. One or more buttons missing, broken or malformed.	X		
b. Hand sewn button tacked off with less than two stitches.			X
c. Buttons not sewn through facing or insecurely sewn.		X	
d. Stitching not locked at end of cycle (tug at loose end of thread to determine if it will ravel).		X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:34Z
Check the source to verify that this is the current version before use.

Defect	Classification Major	Minor A	Minor B
Snap fasteners			
a. Any part omitted, defective or mismated, affecting function.	X		
b. Any part not securely sewn.			X
Labels			
* a. Size label:			
- omitted, incorrect, illegible, or type IV label (when used) not completely on top collar stand.	X		
- horizontally off center by more than 1/4 inch or vertically off center by more than 1/8 inch (type IV label) or by more than 1/4 inch (type VI label).			X
b. Identification label (marking):			
- omitted, incorrect or illegible.		X	
- not positioned on lower end of left facing.		X	
- bottom of label positioned more than 1/2 inch from top of instruction label.		X	
- left side of label less than 1/4 inch from the back edge of facing.			X
c. Instruction label (or combination label, if applicable):			
- omitted, incorrect or illegible.		X	
- not positioned on lower left facing.		X	
- bottom of label positioned less than 1/4 inch from back edge of facing.			X
- right side of label less than 1/2 inch or more than 3/4 inch from finished shirt bottom.			X
Darts			
a. Front or back darts not uniform in length by more than 1/2 inch.		X	
b. Any dart tapered less than 3/4 or more than 1 inch beyond drill hole.			X
c. Thread ends less than 1/2 inch or more than 3/4 inch long.			X
Collar and front closure			
a. Neck edge of collar tab not completely caught in the collar setting seam (inside finished edge of tab extension not in line with front edge of collar).		X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:34Z
Check the source to verify that this is the current version before use.

Defect	Classification Major	Minor A	Minor B
Collar and front closure (cont'd)			
b. Collar tab extends beyond collar less than 7/16 or more than 9/16 inch at ends.			X
c. Collar tab extends beyond front edge of collar more on one side than the other by more than 3/32 inch.		X	
d. Collar twisted, or collar ends or tabs not uniform in size or shape by more than 3/16 inch at any area of the curve.	(*)		
e. Back end of collar tab extends beyond edge of collar at point of tacking.		X	
f. Left collar tab extension overlaps right tab.			X
g. Collar tab extension less than 5/8 or more than 7/8 inches long.			X
h. Slash at end of tab extension exposed on top or under ply of tab.	X		
i. Collar tab not tacked to under collar at lower end of straight edge, insecurely tacked or straight edge of tab not flat against under collar when tacked.			X
j. Collar tab tacking exposed on top collar.	X		
k. Pleat on under collar at the lower end of the straight edge of tab.			X
l. Top collar edges curled.		X	
m. Edges not worked out (having folds 1/16 inch or more deep) or under collar exposed beyond edge of top collar for a distance of more than 1/2 inch.			X
n. Stitching joining top collar interlining visible on outside of collar.	X		
o. Ends of collar overlapping, or more than 3/16 inch apart when shirt is buttoned and snap fasteners are engaged.		X	

Source: https://assist.dla.mil -- Downloaded: 20261-21T21:34Z
Check the source to verify that this is the current version before use.

Defect	Classification Major	Minor A	Minor B
Collar and front closure (cont'd)			
p. Snap fastener on collar tab or collar tab extension positioned so that collar, collar tab, tab extension or shirt front are twisted, pleated or puckered when snap fasteners are engaged.		X	
q. Center of snap fastener less than 1/4 or more than 3/8 inch from end of tab extension.			X
r. Top button on shirt positioned so that front edge of shirt does not fall in a straight line when shirt is buttoned.		X	
s. Button not aligned with buttonhole causing twists or puckers when shirt is buttoned.		X	
t. Top end of either facing not securely caught to yoke seam allowance.		X	
u. Either facing does not lie flat on front in the area between second button and edge of yoke seam allowance.			X
v. Width of step less than 11/16 or more than 13/16 inch wide.			X
w. Front uneven in length at bottom when buttoned by: - more than 1/4 inch - up to 1/4 inch (inclusive).	X	X	
x. Front facing tight or twisted causing bulge or twist on outside of shirt.		X	
Yoke			
a. Folded edge of pleat on outside of shirt faced toward center of shirt.	X		
b. Seam allowances of fronts and backs not turned toward yoke.		X	

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:34Z
Check the source to verify that this is the current version before use.

Defect	Classification Major	Minor A	Minor B
Sleeves			
a. Sleevehead fullness misplaced or omitted.	X		
b. Sleeve setting seam at underarm staggered more than 1/4 inch (measured from center of seam to center of seam).			X
c. Sleeve-setting stitching irregular.		X	
d. Width of cuff less than 1-1/8 inches or more than 1-3/8 inches wide.			X
e. Cuff twisted.		X	
f. Cuff not uniform in width.		X	
g. Stitching through cuff at underarm not superimposing or not immediately adjacent to the stitching of underarm seam (off by more than 1/8 inch) (post-hemmed cuff).		X	
h. Length of the stitching through cuff at underarm finishing less than 1/8 inch from the width of the cuff (post-hemmed cuff).			X
i. Stitching through cuff at underarm not through all plies (post-hemmed cuff).		X	
j. Underarm seam allowance not turned toward back or not caught in bartack (pre-hemmed cuff).			X
k. End of chain stitch at underarm not caught in bartack (pre-hemmed cuff).		X	
l. Bottom edge of cuff at underarm seam, uneven by 1/16 inch or more.		X	
Seams			
a. Side seams not turned toward back of shirt at hem or bottom of sleeve or sleeve setting seam not turned toward sleeve.			X

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:34Z
Check the source to verify that this is the current version before use.

* 4.2.3 End item dimensional examination. The end item shall be examined for the defects listed below. The lot size shall be expressed in units of one shirt. The sample unit shall be one shirt. The inspection level shall be S-3 and the AQL shall be 4.0 defects per hundred units.

Half bust Cross bust Back length Sleeve width Collar	Any measurement deviating from the nominal dimensions and tolerance specified in table III shall be scored as a defect.
Equal length of sleeves	Sleeves unequal in length by more than 1/4 inch shall be scored as a measurement defect.

4.2.4 Packaging inspection. An examination shall be made to determine that the preservation, packing and marking comply with the section 5 requirements. Defects shall be scored in accordance with list below. The sample unit shall be one shipping container fully packaged with the exception that it need not be closed. Defects of closure listed below shall be examined on shipping containers fully packaged. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 2.5 defects per hundred units.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Any component missing, damaged, or not as specified.
Workmanship	Inadequate application of components, such as incomplete closure of container flaps, loose strapping, inadequate stapling, improper taping, open and noncontinuous heat sealed seams and closure of polyethylene bag. Incorrectly fabricated bag. Alternative closure of the polyethylene bag not provided with tuck or reverse flap. Omission of vent hole in polyethylene bag. Bulged or distorted container.
Content	Number of intermediate packages per shipping container is more or less than required. Number of shirts per intermediate package is more or less than required. 1/ Size shown on one or more shirts not as specified on container. 1/

1/ For this defect, two intermediate packs from each container in the sample shall be examined.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:34Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Unit packing. Each fully-buttoned shirt shall be neatly folded to approximate dimensions of 8-1/2 by 13 inches, secured with stainless steel (AISI type 304 or 316) pins, aluminum clips, or plastic fasteners, and placed in a snug-fitting flat style clear polyethylene film bag of 0.00125 inch thickness ± 25 percent tolerance). The polyethylene bag shall be formed with heat sealed seams that are straight, continuous, and parallel to each other and the formed edge of the bag. The final closure of the bag shall be heat sealed with the heat seal made as close as possible to the open end. The bag may be fabricated from polyethylene film tubing or sheeting. A 1/4 inch diameter hole shall be made at one corner of each polyethylene bag to allow excess air to escape. Alternatively, the final closure of the polyethylene bag may be accomplished by means of a tuck or reverse flap.

5.1.1.2 Intermediate packing. Six shirts of one size only, unit packed as specified in 5.1.1.1, shall be placed in a intermediate setup paperboard box conforming to type II, variety 1, class A, style 4 of PPP-B-676. Inside dimensions of setup box shall be 13-1/4 inches in length, 8-3/4 inches in width, and 3-1/2 inches in depth. The depth of the cover shall be not less than 1 inch.

5.1.2 Commercial. Shirts shall be preserved in accordance with MIL-STD-1188.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

5.2.1 Level A packing. Ninety-six shirts of one size only, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC, grade V2s of PPP-B-636. Level A intermediate packs shall be packed flat two in length, two in width, and four in depth within a shipping container. Inside dimensions of each shipping container shall approximate 27-1/2 inches in length, 18-1/2 inches in width, and 15 inches in depth. Approximate dimensions are furnished as a guide only. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V and reinforced as specified in the appendix of PPP-B-636 except that the inspection shall be in accordance with 4.2.4. Toward the end of the contract, or when there are less than the required amount per shipping container of the same size, mixed sizes may be packed within the same container.

5.2.2 Level B packing. Ninety-six shirts of one size only, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC, type CF (variety SW) or SF, class domestic, grade 200 of PPP-B-636. Level A intermediate packs shall be packed flat two in length, two in width, and four in depth within a shipping container. Inside dimensions of each shipping container shall approximate 27-1/2 inches in length, 18-1/2 inches in width, and 15 inches in depth. Approximate dimensions are furnished as a guide only. Each

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:34Z
Check the source to verify that this is the current version before use.

shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636 except that the inspection shall be in accordance with 4.2.4. Toward the end of the contract, or when there are less than the required amount per shipping container of the same size, mixed sizes may be packed within the same container.

5.2.2.1 Weather-resistant fiberboard containers. When specified (see 6.2), the shipping container shall be a grade V3c, V3s or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of the container specification, except that the inspection shall be in accordance with 4.2.4.

* 5.2.3 Commercial packing. Shirts, preserved as specified in 5.1 shall be packed in accordance with MIL-STD-1188.

5.3 Marking. In addition to any special marking required by the contract or purchase order, intermediate packs and shipping containers shall be marked in accordance with MIL-STD-129 or MIL-STD-1188, as applicable.

5.3.1 Polyethylene bagged unit packs. Polyethylene bagged unit packs shall have the required identification information legibly printed or stamped in black directly on the bag across the center face or on a white paper label inserted within the bag so as to permit ready identification.

5.3.2 Labels, mixed sizes. Each shipping container, packed with mixed sizes, shall have securely attached to the end and side, directly under the printing or stenciling, a white paper label 5 by 4 inches with the words "MIXED SIZES" plainly printed or stamped thereon, and under these words shall be legibly printed or stamped the correct quantity and sizes contained therein.

6. NOTES

6.1 Intended use. The shirts are intended for use by female military personnel of the Department of the Army as a component of the service uniform.

6.2 Ordering data. Acquisition documents should specify the following:

(a) Title, number and date of this document.
(b) Size required (see 1.2).
(c) Selection of applicable levels of preservation and packing (see 5.1 and 5.2).
(d) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).

6.3 Sample and shade samples. For access to sample and shade samples of the material, address the contracting activity issuing the invitation for bids.

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:34Z
Check the source to verify that this is the current version before use.

6.4 Suggested sewing techniques. Experience has shown that if precautions are observed in using proper components and setting up the sewing machines, seam puckering will be held to an acceptable minimum level. The needles used should be as fine as possible consistent with the size or diameter of the thread. The finest feed (approximately 18 teeth per inch) possible should be used with a presser foot to exactly match the shape and size of the feed. The face of the presser foot should be highly polished to eliminate roughness and reduce drag. The bobbin tension should be highly polished to eliminate roughness and reduce drag. The bobbin tension should be adjusted so that when a full bobbin is placed in the bobbin case and threaded through the tension spring, the bobbin and case shall ride slowly down the thread, when the free end of the thread is held in the vertical position. Needle tension should be adjusted after the bobbin tension to provide slightly more needle thread than bobbin thread in the stitch.

6.5 Sears Fabric Defect Scales are available from: Sears, Roebuck and Company, Department 733C, "Sears Defect Replica Kit", Sears Tower, Chicago, IL 60684.

6.6 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the document (see 3.2).

6.7 Changes from previous issue. The margins of this document are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL

Review actvities:

Army - MD
DLA - CT

Preparing activity:

Army - GL

Project No. 8410-A529

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:34Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:34Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO 12062 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and Development Command
ATTN: DRDNA-ES
Natick, MA 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 202640-21T21:34Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-S-43505D(GL) Shirt, Woman's, Polyester/Cotton

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 202640-21T21:34Z
Check the source to verify that this is the current version before use.