8 August 1974
SUPERSEDING
MIL-W-43531
11 August 1967

MILITARY SPECIFICATION

WASTE RECEPTACLES, PLASTIC

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE AND CLASSIFICATION

* 1.1 Scope. This specification covers the requirements for three types of plastic waste receptacles.

1.2 Classification. The plastic waste receptacles shall be of the following types as specified (see 6.2);

Type I - Step on - 3-gallon.

Type II - Step on - 5-gallon.

Type III - Swinging door - 50-quart.

2. APPLICABLE DOCUMENTS

* 2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

L-P-390	-	Plastic, Molding Material, Polyethylene, Low and Medium Density.
L-P-398	-	Plastic Molding Material, Styrene-Butadiene.
PPP-B-636	-	Boxes, Shipping, Fiberboard.

FSC 7240

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:38Z
Check the source to verify that this is the current version before use.

PPP-T-45 - Tape, Gummed, Paper, Reinforced and Plain; for Sealing and Securing.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer).

* 2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

National Motor Freight Traffic Association, Inc., Agent

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

3. REQUIREMENTS

3.1 Standard product. The plastic waste receptacles shall be the manufacturers' standard commercial design, except as specified herein.

3.2 Materials. The materials used in the manufacture of the items shall conform to the requirements specified herein. Where materials are not definitely specified, they shall be of the quality and type normally used for the purpose in commercial practice.

Source: https://assist.dla.mil -- Downloaded: 20260-21T21:38Z
Check the source to verify that this is the current version before use.

3.2.1 Plastic.

3.2.1.1 Styrene butadiene (high impact). The plastic material shall conform to type IV, class 2 of L-P-398. Clean, unburned plastic material in the form of imperfect parts, sprues, runners or other scrap of the same composition as the virgin material and produced in the molding or finishing operation may be reground and mixed with the material specified. Items made by rotational molding shall be made from virgin material only.

3.2.1.2 Polyethylene. The plastic material shall conform to type I, class L or M, grades 1, 2 or 3 of L-P-390. Clean, unburned plastic material in the form of imperfect parts, sprues, runners or other scrap of the same composition as the virgin material and produced in the molding or finishing operation may be reground and mixed with the material specified. Items made by rotational molding shall be made from virgin material only.

3.3 Design and construction. The types I and II waste receptacles shall provide a sanitary enclosure for waste material within an inner container (insert) supported within an outer container. The outer container shall be fitted with an automatically closing cover hinged at the rear; activated by a cover-lifting mechanism operated by a foot pedal at the bottom. Foot pressure on the pedal shall not affect the stationary position of the receptacle. The insert shall be provided with a handle for lifting the insert from the outer container. The type III waste receptacle shall be square in shape and provided with a removable swinging door type cover so that the receptacle may be emptied easily by tipping.

3.3.1 Waste receptacle (type I). The type I waste receptacle, outer container, with suitable cover, shall be made of the material specified in 3.2.1.1 or in 3.2.1.2. It shall be of seamless, rigid, one-piece construction and equipped with a suitable non-corrosive step-on mechanism to activate the hinged cover. It shall conform to the requirements specified in table I and shall be equipped with one or two suitable plastic molded-in or metal handles for ease in handling.

3.3.2 Waste receptacles (type II). The type II waste receptacle, outer container, with suitable cover, shall be made of the material specified in 3.2.1.1 or 3.2.1.2. It shall be of the seamless, rigid, one-piece construction and equipped with a suitable non-corrosive step-on mechanism to activate the hinged cover. It shall conform to the requirements specified in table I and shall be equipped with one or two plastic molded-in or metal handles for ease in handling.

3.3.3 Waste receptacles (type III). The type III waste receptacle, with suitable removable or hinged swinging door type cover, shall be made of the material specified in 3.2.1.2. It shall be of seamless rigid, water tight, one-piece construction and equipped with a suitable non-corrosive swing door mechanism to activate the door. It shall conform to the requirements specified in table I and may be equipped with one or two suitable plastic molded-in or metal handles for ease in handling.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:38Z
Check the source to verify that this is the current version before use.

* 3.3.4 Inner containers (inserts). The inner containers or inserts used only with the types I and II waste receptacles shall be made of the material specified in 3.2.1.2. They shall be of seamless, rigid, water tight, one-piece construction and equipped with a non-corrosive handle to facilitate easy removal. They shall conform to the requirements specified in table I. If applicable, non-corrosive metal or other non-plastic parts shall be used to assemble the inserts to the applicable type of waste receptacle.

* TABLE I. Requirements

Type	Capacity (nominal)	Capacity of insert	Dimensions (inches-nominal) 1/			
			Diameter	Length	Width	Height
I	3 gals	10-3/4 qts - 3 gals	10-1/2	N/A	N/A	13-1/2 - 15
II	5 gals	15-1/2 qts - 5 gals	NA	12-1/2	11	20-1/2
III	50 qts (min)	--	NA	18	18	34-1/2

1/ With additional space at top, back and bottom front for lift mechanism and activator pedal, respectively, for types I and II.

3.3.5 Leakage. The type III waste receptacle and the inner containers (inserts) for types I and II shall show no evidence of leakage when tested as specified in 4.2.2.3.

* 3.4 Color and finish. Unless otherwise specified (see 6.2), the waste receptacle and inserts, when applicable, shall have a natural color and smooth finish.

* 3.5 Precautionary label. The type I, II and III waste receptacles shall be labeled on the outside surface in two places on opposite sides, in positions that will be noticeable to the user. The labels shall conform to the following:

> The labels shall be a minimum of 2 inches high and a minimum of 3-1/2 inches long. The label shall read "CAUTION" in yellow letters, 13/32 to 21/32 inches high on a black or dark blue background 13/16 to 15/16 inches wide. The remainder of the label shall have a yellow background with black or dark blue letters reading "COMBUSTIBLE CONTAINER" in letters 3/8 to 9/16 inches high.

The labels shall be water resistant and applied with water resistant adhesive.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:38Z
Check the source to verify that this is the current version before use.

* 3.6 Workmanship. The plastic waste receptacles, and inserts, when applicable, shall be free from blisters, mold marks, weld marks, cracks, bumps and other defects affecting the appearance or utility of the item.

4. QUALITY ASSURANCE PROVISIONS

4.1. Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated hereinafter.

4.2.1 Component and material inspection. In accordance with 4.1 above, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase documents.

4.2.1.1 Certificates of compliance. Components and materials, listed below may be accepted on the basis of a supplier's certificate of compliance for requirements specified in applicable paragraphs of this specification.

Component	Characteristic	Requirement paragraph
Plastic material	Composition	3.2.1.1
Plastic material	Composition	3.2.1.2

Where certificates of compliance are submitted, the Government reserves the right to check test such items to determine the validity of the certification.

* 4.2.2 Inspection of the end item. The end item shall be inspected in accordance with the applicable sub-paragraphs below and at the inspection levels and acceptable quality levels (AQLs) set forth in 4.2.2.5. Random samples shall be drawn from each lot of end items for examinations and tests. The lot for purposes of determining the sample size in accordance with MIL-STD-105 shall be all end item waste receptacles of one type and size offered for inspection at one time. The sample unit shall be one waste receptacle.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:38Z
Check the source to verify that this is the current version before use.

* 4.2.2.1 Visual examination. The waste receptacles shall be examined for defects listed below.

Examine	Defect
Color	Not as specified. Chalked, burned, blurred or scaly.
Construction and workmanship (types I and II)	Outer container and insert not free of fins and flash, rough or sharp edges, weld or mold marks. Outer container and insert not smooth and uniform in texture. Outer container and insert warped, twisted, malformed, crazed, pitted, bubbled, heat marked, blistered or uneven surface. Outer container not equipped with hinged cover, cover malformed and will not function, step on pedal missing, step on pedal and mechanism will not function, cover material not as specified. Handle or handles on outer container missing. Outer container not seamless, not rigid, not one-piece construction; step on pedal and mechanism not non-corrosive material. Inserts not seamless, rigid or of one-piece construction. Insert handle missing or malformed or will not function. Inserts too big for container; hard to remove from container.
Construction and workmanship (type III)	Not of seamless, rigid one-piece construction. Not free of fins or flash, rough or sharp edges, weld or mold marks. Not smooth and uniform in texture; twisted, malformed, crazed, pitted, bubbled, heat marked, blistered or uneven surface. Cover twisted, malformed pitted, bubbled, warped, heat marked or uneven surface. Cover missing. Swinging door mechanism will not function. Mechanism not non-corrosive. Handle or handles missing or malformed. Handle or handles not non-corrosive material.
Precautionary label	Not as specified, missing, not located as specified. Labels or adhesive not water resistant.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:38Z
Check the source to verify that this is the current version before use.

* 4.2.2.2 Dimensional examination. The waste receptacles shall be examined for defects in dimensions. Any dimension that does not conform to the requirements specified in table I shall be classified as a defect.

* 4.2.2.3 Testing of the end item. The end items, with inserts, when applicable, shall be tested for leakage as specified in 4.3.1. The requirement is applicable to the individual unit, the number of determinations per unit shall be one and the result reported as "pass or fail".

* 4.2.2.4 Examination of preparation for delivery requirements. An examination shall be made to determine that the packaging, packing and marking complies with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully prepared for delivery with the exception that it need not be closed. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery. The lot shall be the number of shipping containers in the end item inspection lot.

Examine	Defect
Markings (exterior and interior)	Incorrect; incomplete; illegible; omitted, of improper size, location, sequence or method of application.
Materials	Any component missing, damaged, or not as specified.
Workmanship	Inadequate application of components; such as incomplete closure of container flaps, improper taping, loose or inadequate sealing, strapping, or inadequate stapling. Bulged or distorted container.
Contents	Number of waste receptacles per shipping container is more or less than required.

* 4.2.2.5 Inspection levels and acceptable quality levels (AQLs). The inspection levels for determining the sample size and the acceptable quality levels (AQLs) expressed as defects per 100 units, shall be as follows:

Examination paragraph	Inspection levels	AQLs
4.2.2.1	II	2.5
4.2.2.2	S-2	4.0
4.2.2.3	S-2	2.5
4.2.2.4	S-2	2.5

Source: https://assist.dla.mil -- Downloaded: 202640-21T21:38Z
Check the source to verify that this is the currentversion before use.

4.3 Test procedures.

* 4.3.1 Leakage test. The type III waste receptacles and inserts for types I and II waste receptacles, shall be filled with water (within one to two inches from the top) and allowed to stand in its normal position for 24 hours, at room temperature. At the end of this period, the test units shall be examined for leakage (see 3.3.5).

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or C, as specified (see 6.2).

* 5.1.1 Level A. Each waste receptacle shall be packaged upright in a snug-fitting fiberboard box conforming to style RSC (end opening), type CF, (variety SW), class domestic, grade 200 of PPP-B-636. Each box shall be closed with a 2 inch minimum width gummed paper tape conforming to type III, grade B of PPP-T-45.

* 5.1.2 Level C. Each waste receptacle shall be packaged to afford adequate protection against physical damage during shipment from the supplier to the first receiving activity. The package and the quantity per package shall be the same as that normally used by the supplier for retail distribution.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

* 5.2.1 Level A. Four waste receptacles of one type only, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, grade V2s of PPP-B-636. Level A packages shall be packed upright, two in length and two in width within a shipping container. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V, and reinforced as specified in the appendix of the container specification.

5.2.2 Level B Four waste receptacles of one type only, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, type CF (variety SW), or SF, class domestic, grade 275 of PPP-B-636. Level A packages shall be packed upright, two in length and two in width within a shipping container. Each shipping container shall be closed in accordance with method II as specified in the appendix of the container specification.

* 5.2.2.1 When weather resistant grade fiberboard shipping containers are required (see 6.2), the containers shall be a grade V3c, V3s or V4s, fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of the box specification.

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:38Z
Check the source to verify that this is the current version before use.

* 5.2.3 Level C (Commercial packing). Waste receptacles, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. The quantity per shipping container shall be the same as that normally used by the supplier for retail distribution. Containers shall comply with the Uniform Freight Classification Rules or National Motor Freight Classification Rules, as applicable.

5.3 Marking. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

* 6.1 Intended use. The types I, II and III plastic waste receptacles covered by this specification are intended for temporary disposal of waste materials in Military establishments.

* 6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Type waste receptacle required (see 1.2).
(c) Color, if different from color specified (see 3.4).
(d) Selection of the applicable levels of packaging and packing (see 5.1 and 5.2).
(e) When weather resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).

* 6.3 The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and suppliers are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Air Force - 84

Review activity:

Army - MD

User activities:

Navy - YD, MC, CG

Preparing activity:

Army - GL

Project No. 7240-0195

Source: https://assist.dla.mil -- Downloaded: 202640-21T21:38Z
Check the source to verify that this is the currentversion before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:38Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE
WASTE RECEPTACLES, PLASTIC MIL-W-43531A

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?
   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1426 REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USE

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:38Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
US ARMY NATICK LABORATORIES
NATICK, MA 01760

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD - 314

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

STSNL-TD

Commander
US Army Natick Laboratories
ATTN: STSNL-TD
Natick, Massachusetts 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:38Z
Check the source to verify that this is the current version before use.