MIL-B-63369(AR)
16 MARCH 1981

MILITARY SPECIFICATION

BOOSTER ASSEMBLY, INERT FOR DEMOLITION KIT
CRATERING, TRAINING, XM270
PARTS FOR, LOADING, ASSEMBLING AND PACKING

This specification is approved for use by US Army Armament Research and Development Command and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification contains the parts, loading assembly, and packing for one type of Inert Booster Assembly for one type of rocket motor assembly designated as Rocket Motor for Demolition Kit, Cratering, Training, XM270.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids, or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1188 - Commercial Packaging of Supplies and Equipment

FSC 1375

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:43Z
Check the source to verify that this is the current version before use.

DRAWINGS (See 6.4)

U.S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND (ARRADCOM)

9331665 - Booster Assembly (Inert)

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer).

3. REQUIREMENTS

3.1 Material. Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Components and assembly. The components and assembly shall comply with all requirements specified on Dwg. 9331665, and associated drawings, and with all requirements specified in applicable specifications and standards.

3.3 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.4 Workmanship. All parts and assemblies shall be fabricated and loaded in a thorough workmanlike manner. They shall be free of burrs, sharp edges, cracks, dirt, grease, rust, and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined. All packing components shall be dry.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections

a. First Article Inspection

b. Quality Conformance Inspection

4.3 First article inspection

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:43Z
Check the source to verify that this is the current version before use.

4.3.1 Submission. The contractor shall submit a first article sample designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part Description	Drawing	Quantity
Base, Booster	9244448	10
Cup, Booster	9244450	10
Cup and Base Assembly	9244451	10
Booster Assembly	9331665	10
Washer, Retainer	9244453	10
Disc, Booster	9244454	10
Cup, Lead	9312808	10

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:43Z
Check the source to verify that this is the current version before use.

TABLE I. First Article Inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63369(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
	Booster Assembly				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Base, Booster (Dwg. 9244448) Examination for defects	10		3.2	4.4.2.1
	Cup, Booster (Dwg. 9244450) Examination for defects	10		3.2	4.4.2.2
	Cup and Base Assembly (Dwg. 9244451) Examination for defects	10		3.2	4.4.2.3
	Booster Assembly (Dwg. 9331665) Examination for defects	10		3.2	4.4.2.4
	Washer, Retainer (Dwg. 9244453) Examination for defects	10		3.2	4.4.2.5
	Disc, Booster (Dwg. 9244454) Examination for defects	10		3.2	4.4.2.6
	Cup, Lead (Dwg. 9312808) Examination for defects	10		3.2	4.4.2.7

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:43Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of Booster Assemblies shall contain:

a. Metal parts from not more than one interfix lot number from one manufacturer.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and test tables, sampling plans with major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:43Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63369(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.1	Base, Booster		9244448
			NEXT HIGHER ASSEMBLY 9244451

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length		0.40%	3.2	Gage
102	True position of bottom hole with datum A		0.40%	3.2	Gage
103	Outside diameter		0.40%	3.2	Gage
Minor					
201	Location of small hole		0.65%	3.2	Gage
202	Diameter of small hole		0.65%	3.2	Gage
203	Thickness		0.65%	3.2	Gage
204	Diameter of bottom hole		0.65%	3.2	Gage
205	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:43Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63369(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.2	Cup, Booster		9244450
			NEXT HIGHER ASSEMBLY 9244451

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length		0.40%	3.2	Gage
102	True position of small hole with datum A		0.40%	3.2	Gage
103	Inside diameter		0.40%	3.2	Gage
Minor					
201	Diameter of small hole		0.65%	3.2	Gage
202	Thickness of bottom		0.65%	3.2	Gage
203	Outside diameter		0.65%	3.2	Gage
204	Radius at bottom, max.		0.65%	3.2	Gage
205	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:43Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63369(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.3	Cup and Base Assembly		9244451
			NEXT HIGHER ASSEMBLY 9331665

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Distance between inner surface and base and cup, max.		0.40%	3.2	Gage
102	True position of large hole with datum A		0.40%	3.2	Gage
103	Adhesive bond inadequate		0.40%	3.2	Manual
104	Adhesive showing at surface indicated by note 5		0.40%	3.2	Visual
105	360° runout between inner surfaces of base cup		0.40%	3.2	Gage
Minor					
201	Protective finish inadequate, scratched or damaged		0.65%	3.2	Visual
202	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:43Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63369(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Booster Assembly (Inert)				9331665
					NEXT HIGHER ASSEMBLY
					9331653
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Total length, maximum (max.)		0.40%	3.2	Gage
102	Swage missing, improper, or less than 360°		0.40%	3.2	Visual
103	Any part missing or not assembled properly		0.40%	3.2	Visual
104	Adhesive missing		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:43Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63369(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.5	Washer, Retainer		9244453
			NEXT HIGHER ASSEMBLY
			9331665

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter		0.40%	3.2	Gage
102	Diameter of hole		0.40%	3.2	Gage
Minor					
201	Thickness		0.65%	3.2	Gage
202	Protective finish inadequate, scratched or damaged		0.65%	3.2	Visual
203	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:43Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63369(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.6	Disc, Booster		9244454
			NEXT HIGHER ASSEMBLY 9331665

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter		0.40%	3.2	Gage
102	Thickness		0.40%	3.2	Gage
103	Flatness		0.40%	3.2	Gage
Minor					
201	Protective finish inadequate, scratched or damaged		0.65%	3.2	Visual
202	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil - Downloaded: 2026-10-23T02:43Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63369(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.7	Cup, Lead				9312808
					NEXT HIGHER ASSEMBLY
					9331665
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Flange diameter, max.		0.40%	3.2	Gage
102	Length from bottom of cup to flange, max.		0.40%	3.2	Gage
103	Outside diameter		0.40%	3.2	Gage
Minor					
201	Thickness of bottom, min.		0.65%	3.2	Gage
202	Radius at bottom		0.65%	3.2	Gage
203	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:43Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection Tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the inspections and tests prescribed in this specification is identified in the 'Paragraph Reference/Inspection Method' column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval, inspection equipment designs in accordance with the terms of the contract. See section 6 of MIL-A-48078 and 6.3 herein.

4.5 Test method and procedures

4.5.1 Materials, components and processes. Compliance with all requirements of Section 3 of this specification shall be ascertained by current and continuing examination of inspection and test data to determine that all components (parts, subassemblies, and materials) have been inspected and tested and found to comply with their respective drawing and specification requirements, and that all specified manufacturing processes have been followed.

4.5.1.1 Visual and mechanical inspections. The visual, manual and mechanical inspections and tests shall verify compliance with requirements of Sections 3 and 5 of this specification in accordance with 4.4.2 herein and Table I.

5. PACKING

5.1 Preservation and packaging. Packaging shall be in accordance with MIL-STD-1188.

5.2 Packing. Packing shall be in accordance with MIL-STD-1188.

5.3 Marking. Marking shall be in accordance with MIL-STD-1188.

6. NOTES

6.1 Intended use. The booster assembly covered by this specification is used in the Rocket Motor Assembly and is a component of the Demolition Kit Cratering, Training, XM270.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment designs for approval. See MIL-A-48078. Submit equipment designs as required to Commander, U.S. Army Research and Development Command, ATTN: DRDAR-QAA-I, Dover, New Jersey 07801.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:43Z
Check the source to verify that this is the current version before use.

6.4 Drawings. Drawings listed in Section 2 of this specification under the heading U.S. Army Research and Development Command (ARRADCOM) may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARRADCOM.

6.5 Distribution of ammunition data cards. Distribution of data cards shall include the following: Commander, ARRADCOM, ATTN: DRDAR-QAA-M, Dover, New Jersey 07801.

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project No.: 1375-A185

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:43Z
Check the source to verify that this is the current version before use.