MILITARY SPECIFICATION

CHARGE, PROPELLING, M204
LOADING, ASSEMBLING, AND PACKING

This Amendment forms a part of Military Specification MIL-C-48867B(AR), dated 31 March 1984, and is approved for use within the U. S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

* 3.4, Delete in its entirety and substitute the following:

"3.4 Velocity. The propelling charges shall impart a corrected mean muzzle velocity of not more than 810 feet per second (fps) and not less than 780 fps when tested as specified in 4.4.3.1 and 4.5.4 (see 6.9). The standard deviation of the lot shall not exceed 7.5 fps."

PAGE 7

4.4.2.1 Critical 3, Delete in its entirety and substitute the following:

Critical		AQL	Reg Para	Para Ref
"3	Container assembly or seal between top, bottom and closure damaged or unbonded to the extent that propellant can escape	100%	3.2	Visual (4.5.5)"

AMSC N/A FSC 1310

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:42Z
Check the source to verify that this is the current version before use.

4.4.2.1 Major 105, Delete in its entirety and substitute the following:

Major		AQL	Reg Para	Para Ref
"105	Container assembly or seal between top, bottom and closure damaged or unbonded but not to the extent that propellant can or is likely to escape	100%	3.2	Visual (4.5.5)"

PAGE 10

* 4.4.3.1, Delete in its entirety and substitute the following:

"4.4.3.1 Velocity.

4.4.3.1.1 First article. The sampling plan for cartridges required and procedures/acceptance criteria shall be in accordance with MIL-STD-414, Section B, Table B-3 using Code Letter M and an AQL of 1%. The lower (L) and upper (U) specification limits for this plan shall be 770 and 820 fps respectively. If the calculated percent lot defective exceeds the applicable requirement in Table B-3, the first article shall be rejected. In addition, if the mean velocity or standard deviation does not comply with the applicable requirements, the first article shall be rejected. The test shall be performed as specified in 4.5.4.

4.4.3.1.2 Production.

4.4.3.1.2.1 Initial production. Beginning with the first production lot and continuing until three consecutive lots have complied with the applicable requirements, the sampling plan and procedures/acceptance criteria for this test shall be in accordance with MIL-STD-414, Section B, Table B-3 using Code Letter M and an AQL of 1%. The lower (L) and upper (U) specification limits for this plan shall be 770 and 820 fps respectively. If the calculated percent lot defective exceeds the applicable requirement in Table B-3, the propelling charge lot shall be rejected. In addition, if the mean velocity or standard deviation does not comply with the applicable requirements, the lot of propelling charges shall be rejected. The test shall be performed as specified in 4.5.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:42Z
Check the source to verify that this is the current version before use.

4.4.3.1.2.2 Subsequent production. After three consecutive production lots have met the criteria of 4.4.3.1.2.1, the sampling plan for cartridges and procedures/acceptance criteria for this test shall be in accordance with MIL-STD-414, Section B, Table B-3 using Code Letter I and an AQL of 1%. The lower (L) and upper (U) specification limits for this test shall be 770 and 820 fps respectively. If the calculated percent lot defective exceeds the applicable requirement in Table B-3, the propelling charge lot shall be rejected. In addition, if the mean velocity or standard deviation does not comply with the applicable requirements, the lot of propelling charges shall be rejected. The test shall be performed as specified in 4.5.4. In the event of lot rejection, the sampling plan of 4.4.3.1.2.1 shall be required beginning with the next lot and continuing until three consecutive lots of propelling charges have complied with the applicable requirements."

PAGE 11

4.5.1.2 Delete in its entirety and substitute the following:

"4.5.1.2 Automated method.

4.5.1.2.1 Method 1. The contractor may elect to perform this operation with automated equipment and mandatory process controls. The automated equipment shall weigh the container and place this weight in memory and then weigh and check weigh the propellant before loading. After loading, the total weight of the container/propellant combination shall be weighed to verify complete loading by subtracting the increment weight (from memory) from the total weight to obtain the loaded propellant weight. In such cases, process control plans in accordance with Data Item DI-P-1604 must be submitted to the Technical Agency (see 6.6) for review of the automated operation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:42Z
Check the source to verify that this is the current version before use.

4.5.1.2.2 Method 2. The empty increments shall be sorted into discreet weight groups with a minimum group range of 0.6 grains to minimize container weight variance. After the empty increments are sorted, they will be loaded by groups. The automated equipment shall weigh and check weigh the propellant before loading. After loading, the total weight of the container and propellant combination shall be used to verify complete loading by subtracting the increment group weight from the total weight to obtain the loaded propellant weight."

NOTE: The margins of this amendment are marked with an asterisk or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1310-A444)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:42Z
Check the source to verify that this is the current version before use.