MILITARY SPECIFICATION

CONTAINER, AMMUNITION, METAL, FOR PROPELLING CHARGES AND CARTRIDGES

This specification is approved for use by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type of metal container used for packing propelling charges for separate loaded artillery ammunition and for packing cartridges.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposals form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

TT-C-490	-Cleaning and Preparation of Ferrous and Zinc Coated Surfaces for Organic Protective Coatings

MILITARY

MIL-W-12332	-Welding Resistance, Spot, Seam and Production, for Fabricating Assemblies of Low-Carbon Steel
MIL-A-48078	-Ammunition, Standard Quality Assurance Provisions, General Specification For

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC: 8140

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:56Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105	-Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-171	-Finishing of Metal and Wood Surfaces
MIL-STD-1188	-Commercial Packaging of Supplies and Equipment
MIL-STD-1261	-Welding Procedures for Constructional Steel

DRAWINGS (see 6.2)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND (ARRADCOM)

9331196	-Container, Ammo., Metal: PA91
9331197	-Container, Ammo., Metal: PA92
9331198	-Container, Ammo., Metal: PA93
9331199	-Container, Ammo., Metal: PA94
9331200	-Container, Ammo., Metal: PA95
9331201	-Container, Ammo., Metal: PA96
9331202	-Container, Ammo., Metal: PA97
9331203	-Container, Ammo., Metal: PA98
9331204	-Container, Ammo., Metal: PA99
9331205	-Container, Ammo., Metal: PA100

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

AMERICAN SOCIETY FOR TESTING MATERIALS

ASTM-D412	-Tension Testing of Vulcanized Rubber, Standard Method of
ASTM-D2240	-Indentation Hardness of Rubber and Plastics by Means of a Durometer, Standard Method of Test for
ASTM-E8	-Tension Testing of Metallic Materials, Standard Method of

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:56Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING MATERIALS (Cont'd)

ASTM-E18 -Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials, Test for

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103)

3. REQUIREMENTS

3.1 Materials. Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Containers. The containers (container assemblies) shall comply with all requirements specified on drawings (dwgs.) 9331196 through 9331205 as applicable, and associated drawings and with all requirements specified in applicable specifications and standards.

3.3 Welding. The welding shall comply with the requirements of MIL-W-12332 or MIL-STD-1261.

3.3.1 Tensile strength (if applicable). The tensile strength of the longitudinal body weld shall not be less than 65 percent of the tensile strength of body material when tested as specified in 4.5.1.

3.4 Painted surface. The painted exterior surface of the container shall comply with the requirements of TT-C-490 except that the film thickness, and salt spray requirements of TT-C-490 shall not apply to the interior surfaces and welded spots and sharp corners of the exterior surface of the containers.

3.5 Cover assembly. Upon assembly of the cover assembly to the body assembly (body weldment), the cover assembly shall freely engage and rotate within the body assembly. As the cover assembly is rotated with the "Y" handle in the open position, the "Y" handle shaft ends shall freely engage into the respective bayonet slots of the rim. When the "Y" handle is in the closed position (rotated 180°), the spring clip shall engage and lock the handle in place. When the spring clip is disengaged and the handle rotated to the open position, the cover assembly shall disengage from the body assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:56Z
Check the source to verify that this is the current version before use.

3.6 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.7 Workmanship.

3.7.1 Containers. The containers shall be regular, smooth, and free from wrinkles, pin holes, cracks, rough spots, burrs, sharp edges and any other defect that might affect the serviceability, durability, safety and appearance of the container.

3.7.2 Paint coating. The paint coating shall be in accordance with applicable drawings and comply with instructions in MIL-STD-171.

3.7.3 Parts. All parts shall be free of chips, dirt, grease, rust and foreign material. The cleaning method used shall not be injurious to any of the parts nor shall any of the parts be contaminated by the cleaning agents used.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First Article Inspection
b. Quality Conformance Inspection

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of five (5) painted container assemblies, five (5) painted cover assemblies, five (5) unpainted cover assemblies, and ten (10) each of every subassembly and component (unpainted).

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:56Z
Check the source to verify that this is the current version before use.

TABLE I

FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63461 (AR)

PARAGRAPH CATEGORY	TITLE: Assemblies and components		SHEET 1 OF 2		DRAWING NUMBER: See Below NEXT HIGHER ASSEMBLY
	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Container assemblies, painted				
	a) Examination for defects	5		3.2	4.4.2.20
	b) Air pressure	5		3.2	4.5.8.2
	Body assembly (weldment), unpainted				
	a) Examination for defects	5		3.2	4.4.2.19
	b) Air pressure	5		3.2	4.5.8.1
	c) Weld of rim to body (see Note)	5		3.2	4.5.2/ Dwg. 9331684
	Cover assembly, unpainted				
	a) Examination for defects	5		3.2	4.4.2.12
	b) Air pressure	5		3.2	4.5.8.1
	Cover assembly, painted				
	Examination for defects	5		3.2	4.4.2.13
	Body, unpainted				
	a) Examination for defects	10		3.2	4.4.2.17
	b) Tensile strength (see Note)	5		3.2	4.5.1/ Dwg. 9331679
	Spring, unpainted				
	a) Examination for defects	10		3.2	4.4.2.2
	b) Embrittlement (see Note)	3		3.2	4.5.3/ Dwg. 9331694

NOTES: The weld security inspections, spring tests and gasket tensile stress test shall be performed after the other inspections have been performed on the applicable samples.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:56Z
Check the source to verify that this is the current version before use.

FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
	Assemblies and components				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	c) Hardness (see Note)	3		3.2	4.5.4/ Dwg. 9331694
	d) Deflection load (see Note)	3		3.2	4.5.5/ Dwg. 9331694
	Gasket				
	a) Examination for defects	10		3.2	4.4.2.10
	b) Hardness	3		3.2	4.5.7/ Dwg. 9331685
	c) Tensile stress (see Note)	3		3.2	4.5.6/ Dwg. 9331685
	Remaining subassemblies and components				
	Examination for defects	10		3.2	Applicable subparagraph of 4.4.2.

NOTES: The weld security inspections, spring tests and gasket tensile stress test shall be performed after the other inspections have been performed on the applicable samples.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:56Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of containers shall contain material from lots with the same interfix number from one manufacturer.

4.4.2 Examination - See MIL-A-48078. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63461 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Clamp	1 OF 1	9331696
			NEXT HIGHER ASSEMBLY 9331697

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined.				
Major					
101.	Diameter of hole (two places)		0.40%	3.2	Gage
102.	Vertical location of holes		0.40%	3.2	Gage
103.	Horizontal location of holes		0.40%	3.2	Gage
104.	True position of holes		0.40%	3.2	Gage
Minor					
201.	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63461 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9331694
4.4.2.2	Spring				NEXT HIGHER ASSEMBLY 9331697
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined.				
Major					
101.	Diameter of hole (two places)		0.40%	3.2	Gage
102.	True position of holes		0.40%	3.2	Gage
103.	Vertical location of holes		0.40%	3.2	Gage
104.	Horizontal location of holes		0.40%	3.2	Gage
105.	Radius of bend		0.40%	3.2	Gage
106.	Thickness		0.40%	3.2	Gage
107.	Length from center of holes to lower edge of bend		0.40%	3.2	Gage
Minor					
201.	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63461 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Support, Shaft	1 OF 1	9331687
			NEXT HIGHER ASSEMBLY: 9331697

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined.				
Major					
101.	Diameter of large hole and slot		0.40%	3.2	Gage
102.	Diameter of small hole		0.40%	3.2	Gage
103.	True position of large hole and slot		0.40%	3.2	Gage
104.	Vertical location of large hole and slot		0.40%	3.2	Gage
105.	Horizontal location of large hole and slot		0.40%	3.2	Gage
106.	True position of small hole		0.40%	3.2	Gage
107.	Vertical location of small hole		0.40%	3.2	Gage
108.	Horizontal location of small hole		0.40%	3.2	Gage
109.	Distance between large hole and slot		0.40%	3.2	Gage
110.	Diameter of holes located on side to be assembled with spring and clamp		0.40%	3.2	Gage
111.	True position of holes located on side (used for assembly of spring and clamp)		0.40%	3.2	Gage
112.	Vertical location of holes on side		0.40%	3.2	Gage
113.	Horizontal location of holes on side		0.40%	3.2	Gage
114.	Wall thickness		0.40%	3.2	Gage
115.	Distance between center line of large hole and slot, and the tab used to assemble the spring and clamp		0.40%	3.2	Gage
Minor					
201.	Radius not present on edges of tab		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63461 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Shaft Support Assembly	1 OF 1	9331697
			NEXT HIGHER ASSEMBLY 9331692

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	Component missing		0.40%	3.2	Visual
102.	Rivet missing or improperly applied		0.40%	3.2	Visual
Minor					
201.	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63461 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.5	Handle		9331688
			NEXT HIGHER ASSEMBLY
			9331683

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined.				
Major					
101.	Diameter of small hole		0.40%	3.2	Gage
102.	True position of small hole		0.40%	3.2	Gage
103.	Vertical location of small hole		0.40%	3.2	Gage
104.	Horizontal location of small hole		0.40%	3.2	Gage
105.	Width of shaft hexhole (three (3) readings, 60° apart), 2 places		0.40%	3.2	Gage
106.	Vertical location of shaft hexhole, 2 places		0.40%	3.2	Gage
107.	Horizontal location of shaft hexhole, 2 places		0.40%	3.2	Gage
108.	Largest width of handle		0.40%	3.2	Gage
109.	Wall thickness		0.40%	3.2	Gage
110.	Distance from center of shaft hexholes to nearer edge of spring slot		0.40%	3.2	Gage
111.	Width of spring slot		0.40%	3.2	Gage
MINOR					
201.	Distance from center of shaft hex hole to outer edge of tabs		0.65%	3.2	Gage
202.	Overall length of tabs		0.65%	3.2	Gage
203.	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63461 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.6	Shaft		9331689
			NEXT HIGHER ASSEMBLY
			9331683

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined.				
Major					
101.	Width across flats of hexagon segment (three readings, 60° apart)		0.40%	3.2	Gage
102.	Length of hexagon segment of shaft		0.40%	3.2	Gage
103.	Length of small diameter segment (two places)		0.40%	3.2	Gage
104.	Large diameter (two places)		0.40%	3.2	Gage
105.	Small diameter (two places)		0.40%	3.2	Gage
106.	Total length of large diameters and hexagon segments		0.40%	3.2	Gage
107.	Small diameter segment not tangent to large diameter segment and side of hexagon segment		0.40%	3.2	Visual
Minor					
201.	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63461 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.7	Washer	1 OF 1	9331690
			NEXT HIGHER ASSEMBLY: 9331683

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101.	Inside diameter		0.40%	3.2	Gage
102.	Outside diameter		0.40%	3.2	Gage
103.	Height		0.40%	3.2	Gage
Minor					
201.	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil - Downloaded: 2026-10-23T02:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63461 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.8	Retainer, Washer				9331693
					NEXT HIGHER ASSEMBLY
					9331683
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined.				
Major					
101.	Diameter of hole		0.40%	3.2	Gage
102.	Inside diameter		0.40%	3.2	Gage
103.	Wall thickness		0.40%	3.2	Gage
104.	Inside depth		0.40%	3.2	Gage
Minor					
201.	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63461 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.9	Cover	1 OF 1	9331686
			NEXT HIGHER ASSEMBLY: 9331692

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined.				
Major					
101.	Outside diameter		0.40%	3.2	Gage
102.	Wall thickness		0.40%	3.2	Gage
103.	Depth of groove		0.40%	3.2	Gage
104.	Width of groove		0.40%	3.2	Gage
105.	Height of cover		0.40%	3.2	Gage
106.	Height of threads (min.)		0.40%	3.2	Gage
107.	Location of air test hole with rib		0.40%	3.2	Gage
108.	Location of ribs to each other		0.40%	3.2	Gage
109.	Flatness of bottom surface inside annular ring and surrounding air test hole		0.40%	3.2	Gage
110.	Inside depth of annular ring		0.40%	3.2	Gage
Minor					
201.	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2022-10-23T02:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63461 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.10	Gasket	1 OF 1	9331685
			NEXT HIGHER ASSEMBLY 9331683

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined.				
Major					
101.	Inside diameter, max.		0.40%	3.2	Gage
102.	Large width		0.40%	3.2	Gage
103.	Middle width		0.40%	3.2	Gage
104.	Small width		0.40%	3.2	Gage
105.	Height		0.40%	3.2	Gage
106.	Height from top edge of lip		0.40%	3.2	Gage
107.	Misalignment of joint		0.40%	3.2	Gage
Minor					
201.	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63461 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.11	Cover Weldment	1 OF 1	9331692
			NEXT HIGHER ASSEMBLY 9331683

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined.				
Major					
101.	Component missing		0.40%	3.2	Visual
102.	Weld missing, incomplete or visually inadequate		0.40%	3.2	Visual/Manual
103.	Location of shaft support slot with respect to cover air hole		0.40%	3.2	Gage
Minor					
201.	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-23T02:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.12	Cover Assembly, prior to painting	1 OF 1	9331683
			NEXT HIGHER ASSEMBLY: Applicable Container Assy. (see 2.1)

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined.				
Major					
101.	Component missing or inadequately assembled		0.40%	3.2	Visual
102.	Gap max. remaining after crimping over shaft		0.40%	3.2	Gage
103.	Rotating of shaft inadequate after crimping		0.40%	3.2	Manual
Minor					
201.	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-23T02:56Z
Check the source to verify that this is the current revision before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63461 (AR)

PARAGRAPH	TITLE		SHEET		DRAWING NUMBER
4.4.2.13	Cover Assembly, after painting		1 OF 1		9331683
					NEXT HIGHER ASSEMBLY: Applicable Container Assy. (see 2.1)
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101.	Gasket not secured or secured improperly to cover		0.40%	3.2	Visual
Minor					
201.	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63461 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.14	Rim				9331680
					NEXT HIGHER ASSEMBLY
					9331684
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined.				
Major					
101.	Wall thickness		0.40%	3.2	Gage
102.	Diameter of larger hole on side of rim		0.40%	3.2	Gage
103.	Diameter of smaller hole on side of rim		0.40%	3.2	Gage
104.	Location of larger hole		0.40%	3.2	Gage
105.	Location of smaller hole		0.40%	3.2	Gage
106.	Location of bayonet slot, 4 places		0.40%	3.2	Gage
107.	Inside dimension across flats, 2 places		0.40%	3.2	Gage
108.	Inside dimension across corners, 2 places		0.40%	3.2	Gage
Minor					
201.	Drainage hole missing		0.65%	3.2	Visual
202.	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63461 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.15	Ring		9331681
			NEXT HIGHER ASSEMBLY 9331684

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined.				
Major					
101.	Wall thickness		0.40%	3.2	Gage
102.	Diameter of larger hole on side on ring		0.40%	3.2	Gage
103.	Diameter of smaller hole on side on ring		0.40%	3.2	Gage
104.	Location of larger hole with respect to edge of ring		0.40%	3.2	Gage
105.	Location of smaller hole with respect to edge of ring		0.40%	3.2	Gage
106.	Inside dimensions across flats, 2 places		0.40%	3.2	Gage
Minor					
201.	Drainage hole missing		0.65%	3.2	Visual
202.	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63461 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.16	Bottom		9331682
			NEXT HIGHER ASSEMBLY 9331684

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined.				
Major					
101.	Wall thickness		0.40%	3.2	Gage
102.	Length, minimum (min.)		0.40%	3.2	Gage
Minor					
201.	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63461 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9331679
4.4.2.17	Body				NEXT HIGHER ASSEMBLY 9331684
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined.				
Major					
101.	Wall thickness		0.40%	3.2	Gage
102.	Inside diameter, min.		0.40%	3.2	Gage
103.	Length, min.		0.40%	3.2	Gage
104.	Weld incomplete or missing (if applicable)		0.40%	3.2	Visual
Minor					
201.	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63461 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.18	Plug, Stacking	1 OF 1	9331698
			NEXT HIGHER ASSEMBLY: 9331684

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined.				
Major					
101.	Plug (smaller) diameter		0.40%	3.2	Gage
102.	Knob (larger) diameter		0.40%	3.2	Gage
103.	Length of plug		0.40%	3.2	Gage
104.	Length of knob		0.40%	3.2	Gage
Minor					
201.	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil. Downloaded: 2026-10-23T02:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63461 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9331684
4.4.2.19	Body Weldment (Body Assembly), prior to painting				NEXT HIGHER ASSEMBLY Applicable Container Assy. (see 2.1)
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined.				
Major					
101.	True position of holes of ring(s), rim and stacking plug		0.40%	3.2	Gage
102.	Location of hole in rim relative to holes in inside rings, as applicable and stacking plugs		0.40%	3.2	Gage
103.	Location of hole in rim relative to hole in outside ring and stacking plug		0.40%	3.2	Gage
104.	Perpendicularity of ring and rims with Datum-A		0.40%	3.2	Gage
105.	Any weld of ring, rim or bottom to body missing, incomplete or visually inadequate		0.40%	3.2	Visual
Minor					
201.	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.20	Container Assembly				Applicable Container Ass'y. (2.1)
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined.				
Major					
101.	Cover assembly assembled to body assembly		0.40%	3.5	Visual/Manual
102.	Compression of gasket (Four readings, 90° apart)		0.40%	3.2	Gage
Minor					
201.	Protective finish damaged, bare spots exposing metal, etc.		0.65%	3.2	Visual
202.	Marking missing, incomplete or illegible (see dwg. 9331684)		0.65%	3.2	Visual
203.	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:56Z
Check the source to verify that this is the current version before use.

4.4.3 Testing.

4.4.3.1 Tensile strength (see 3.3.1), Major Defect.- Five (5) bodies shall be randomly selected for this test. Four specimens, approximately equally spaced along the axis, shall be taken from each body at right angles to the weld. If one or more specimens of a sample fail to comply with the requirement, that sample shall be classed defective. If two or more samples are classed defective, the lot shall be rejected.

4.4.3.2 Weld of rim to body (see 9331684), Major Defect.- Five (5) body assemblies shall be selected for this test. If any sample fails to comply with the requirement, the lot shall be rejected.

4.4.3.3 Spring embrittlement (see dwg. 9331694), Major Defect.- Five (5) springs shall be randomly selected from each heat treatment lot for this test. If any spring fails to meet the requirement, the heat treatment lot shall be rejected.

4.4.3.4 Hardness of spring (see dwg. 9331694), Major Defect.- Five (5) springs shall be randomly selected from each heat treatment lot for this test. If any spring fails to meet the requirement, the heat treatment lot shall be rejected.

4.4.3.5 Deflection load of spring (see dwg. 9331694), Major Defect.- Ten (10) springs shall be randomly selected from each heat treatment lot for this test. If any spring fails to meet the requirement, the heat treatment lot shall be rejected.

4.4.3.6 Tensile stress of gasket (see dwg. 9331685), Major Defect.- Five (5) gaskets shall be randomly selected from each lot for this test. If any gasket fails to meet the requirement, the lot shall be rejected.

4.4.3.7 Hardness of gasket (see dwg. 9331685), Major Defect.- Five (5) gaskets shall be randomly selected from each lot for this test. If any gasket fails to meet the requirement, the lot shall be rejected.

4.4.3.8 Air pressure.

4.4.3.8.1 Air pressure of unpainted cover assembly (see applicable container assembly dwg. (see 2.1)), Major defect.- The cover assemblies shall be checked 100 percent. If any cover assembly fails to comply with the requirement, the cover assembly shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:56Z
Check the source to verify that this is the current version before use.

4.4.3.8.2 Air pressure of unpainted body assembly (body weldment) (see applicable container assembly dwg. (see 2.1)), Major defect.- The body assemblies shall be checked 100 percent. If the body assembly fails to comply with the requirement, the body assembly shall be rejected.

4.4.3.8.3 Air pressure of painted container assembly. (see applicable container assembly drawing (see 2.1)), Major defect.- The container assemblies shall be sampled in accordance with MIL-STD-105, with an AQL of 0.40 percent.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the 'Paragraph Reference/Inspection Method' column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Methods of inspection. (see 6.4)

4.5.1 Tensile strength. The tensile strength shall be determined in accordance with ASTM-E8.

4.5.2 Weld of rim to body. The test shall be performed in accordance with ASTM-E8.

4.5.3 Spring embrittlement. The spring shall be repeatedly stretched with increasing loads until it does not return to its original free height. That point shall indicate minimum distortion. Any unit which fractures prior to extension to minimum distortion shall be classed defective.

4.5.4 Hardness of spring. The hardness of the spring shall be determined in accordance with ASTM-E18.

4.5.5 Deflection load of spring. Clamp the spring and apply a load in accordance with dwg. 9331695. A measurement shall be made for the required deflection.

4.5.6 Tensile stress of gasket. The tensile stress shall be determined in accordance with ASTM-D412.

4.5.7 Hardness of gasket.- The hardness shall be determined in accordance with ASTM-D2240.

4.5.8 Air pressure test

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:56Z
Check the source to verify that this is the current version before use.

4.5.8.1 Air pressure of unpainted cover assembly and unpainted body assembly. Subject the cover assembly and container body to the internal air pressure, specified in the applicable container assembly drawing, for one of the test times specified. For the cover assembly, apply the pressure when the cover assembly is assembled to a master body assembly (or its equivalent) equipped with a gasket. For the body assembly, apply the pressure when the body assembly is assembled to a master cover (or equivalent) and gasket. The master cover and the master body assembly shall be provided with satisfactory means for applying and maintaining the pressure during the test and for showing evidence of leakage. Observation shall be made for a pressure drop exceeding the requirement for the corresponding test time (as specified in the applicable drawing). A cover assembly or body assembly which exceeds the requirement, shall be classed defective.

4.5.8.2 Air pressure of painted container assembly. Subject the container assembly to the internal air pressure, specified in the applicable container assembly drawing, for one of the test times specified. Observation shall be made for a pressure drop exceeding the requirement for the corresponding test time (as specified in the applicable drawing). A container assembly, which exceeds the requirement, shall be classed defective.

5. PACKAGING

5.1 Packaging requirements. None required.

5.2 Packing. Packing shall be commercial. Propelling charge containers shall be prepared in accordance with paragraph 2.3.1 of MIL-STD-1188.

5.3 Marking. Shipping marking shall comply with MIL-STD-1188 and the following additional instructions. No shipping marking shall be placed directly on the containers. Commercial shipping tags attached with wire shall be used unless otherwise specified. The following information shall be shown: Item name and model number, part number and revision, contract number, lot number and date, name and address of manufacturer. If containers are bundled, boxed or palletized, the gross weight and quantity shall be included. The above information may be placed on pallets or boxes by labeling or stenciling.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:56Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ordering data. See MIL-A-48078.

6.2 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Command (ARRADCOM) may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARRADCOM.

6.3 Submission of inspection equipment for design approvals - See MIL-A-48078. Submit designs as required to: Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAR-I, Dover, New Jersey 07801.

6.4 Prior approval of the Contracting Officer is required for use of equivalent test methods. A description of the proposed method should be submitted through the Contracting Officer to: Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAR-Q, Dover, New Jersey 07801. This description should include but not be limited to the accuracy and precision of the method, test data demonstrating the accuracy and precision and drawings of any special equipment required.

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project Number: 8140-A-532

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:56Z
Check the source to verify that this is the current version before use.