MILITARY SPECIFICATION

FLUID CONTAINER ASSEMBLY, TRAINING

This specification is approved for use within U.S. Army Chemical Research, Development and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the fluid container assembly, training for the M13 Decontaminating Apparatus, Portable.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-C-22750 - Coating, Epoxy-Polyamide.
MIL-I-45607 - Inspection Equipment, Acquisition, Maintenance and Disposition of.

: Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed: to: Commander, U.S. Army Chemical Research, Development and Engineering Center, ATTN: SMCCR-SPT-S, Aberdeen Proving Ground, MD 21010-5423 by using: the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter. :

AMSC N/A FSC 6910

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:03Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-1168 - Ammunition Lot Numbering.
MIL-STD-45662 - Calibration Systems Requirements.

2.1.2 Drawings. The following drawings form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

U.S. ARMY ARMAMENT, MUNITIONS AND CHEMICAL COMMAND

CHEMICAL RESEARCH, DEVELOPMENT AND ENGINEERING CENTER

DRAWINGS

5-51-528 - Fluid Container Assembly, Training.

SPECIAL PACKAGING INSTRUCTIONS (SPI)

P5-51-528 - Fluid Container Assembly, Training.

(Copies of specifications, standards, and drawings required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

ASTM STANDARDS

B 117 - Salt Spray (Fog) Testing.
D 1654 - Evaluation of Painted or Coated Specimens Subjected to Corrosive Environments.

(Application for copies should be addressed to ASTM, 1916 Race Street, Philadelphia, PA 19103.)

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:03Z
Check the source to verify that this is the current version before use.

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on Drawing 5-51-528 shall conform to the specifications listed thereon and to the specific characteristics set forth on the drawings.

3.1.2 Components. All components of the training fluid container assembly shall conform to the specifications and drawings listed on Drawing 5-51-528.

3.2 Manufacture and assembly. The training fluid container assembly shall be manufactured and assembled in accordance with Drawing 5-51-528.

3.3 Performance.

3.3.1 Fluid container assembly, training (Drawing 5-51-528).

3.3.1.1 Lifting handle. The lifting handle shall support a load of at least 150 pounds for a minimum of 5 seconds without weld tears, or distortion of handle parts when tested in accordance with 4.4.5.1(a).

3.3.1.2 Leakage. The training container shall not leak when subjected to a minimum internal pressure of 15 psig, for a minimum of 15 seconds when tested in accordance with 4.4.5.1(b).

3.3.1.3 Drop strength. The training container shall not leak when dropped from a height of 4 feet onto solid concrete so as to strike on the weakest structural seam. The container shall be filled to 98 percent capacity with water, when tested in accordance with 4.4.5.1(c).

3.3.1.4 Adhesion. The coating shall exhibit no removal from the container and the film shall show no blistering or defects when tested as specified in 4.4.5.1(d).

3.3.1.5 Salt spray corrosion resistance. The container shall have a mean creepage from scribe of no more than 1.0 millimeter and shall show no evidence of rust or blisters on other concerned areas when tested as specified in 4.4.5.1(e).

3.4 Preproduction. Unless otherwise specified in the contract, a preproduction sample of training containers shall be produced in accordance with this specification for examination and test (see 4.3 and 6.2) prior to the start of regular production.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:03Z
Check the source to verify that this is the current version before use.

3.5 Workmanship. The training container shall be free from cracks, dents, sharp edges, unpainted surfaces, rust, and foreign matter such as dirt, grease, and oily or viscous materials.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Objective evidence. The contractor shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) Preproduction inspection (see 4.3)
(b) Quality conformance inspection (see 4.4)

4.3 Preproduction inspection.

4.3.1 Lot. Unless otherwise specified (see 6.2) a preproduction lot of 100 training containers (Drawing 5-51-528) shall be manufactured using the same methods, processes, materials, and equipment that will be used during regular production.

4.3.2 Submission. Unless otherwise specified in the contract, the contractor shall submit a preproduction sample (4.3.1 and 4.3.3) for evaluation in accordance with the provisions of 4.3 and 6.2. The preproduction sample shall consist of the quantities and items specified in 4.3.1 and 6.2. A preproduction sample, or portion thereof, as directed by the contracting officer, shall

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:03Z
Check the source to verify that this is the current version before use.

also be submitted whenever there is a lapse in production for a period in excess of 90 days or whenever a change occurs in manufacturing process, material, drawings, specifications, or source of supply as to significantly affect product uniformity as determined by the Government.

4.3.3 Sampling.

4.3.3.1 For examination. A random sample of 20 training containers shall be taken from the preproduction lot for examination.

4.3.3.2 For nondestructive test. A random sample of 20 training containers shall be taken from the preproduction lot for nondestructive testing.

4.3.3.3 For destructive test. A random sample of eight training containers shall be taken from the preproduction lot for destructive test.

4.3.4 Inspection procedures.

4.3.4.1 For examination. The sample of training containers shall be examined in accordance with the classification of defects. The Acceptable Quality Levels (AQLs) specified in the classification of defects do not apply. The acceptance number is zero.

4.3.4.2 For nondestructive tests. The sample of training containers shall be tested for defects listed in the classification of defects. The AQLs do not apply; the acceptance number is zero.

4.3.4.3 For destructive test. Five sample training containers shall be tested in accordance with 4.4.5.1(c); the acceptance number is zero. Three sample training containers (cleaned, pretreated and primed (without topcoat)) shall be tested in accordance with 4.4.5.1.(e); the acceptance number is zero.

4.3.5 Tests. Inspection equipment which is to be acquired by the contractor and used in the performance of the following tests shall be in accordance with 4.4.4. Unless otherwise specified, tests shall be performed at room temperature, 20°-30°C (68°-86°F).

4.3.6 Rejection. If any assembly, component, or test specimen fails to comply with any of the applicable requirements, the preproduction sample shall be rejected. The Government reserves the right to terminate inspection upon any failure of any assembly, component or test specimen to comply with any of the requirements. The contractor shall obtain written approval from the contracting officer prior to proceeding with regular production.

4.4 Quality conformance inspection.

4.4.1 Lotting. A lot of training containers (see 6.2) shall consist of those like items produced at the same place utilizing the same batches of materials, lot of components, process runs, fabrication techniques, assembly

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:03Z
Check the source to verify that this is the current version before use.

methods, tools, equipment and facilities but shall not exceed one month's production. Each lot shall be controlled and identified in accordance with MIL-STD-1168.

4.4.2 Sampling.

4.4.2.1 For examination. The training containers shall be sampled in accordance with MIL-STD-105 at the specified AQL (see 4.4.3.4).

4.4.2.2 For nondestructive test. The training containers shall be sampled in accordance with MIL-STD-105, level S-4 at the specified AQL (see 4.4.3.4).

4.4.2.3 For destructive test. The training containers shall be sampled in accordance with MIL-STD-105, level S-1 at the specified AQL (see 4.4.3.3).

4.4.3 Inspection procedures.

4.4.3.1 For examination. The sample training containers and the packaging shall be examined in accordance with the classification of defects (4.4.3.4) and MIL-STD-105.

4.4.3.2 For nondestructive tests. The sample training containers shall be tested in accordance with the classification of defects (4.4.3.4) and MIL-STD-105.

4.4.3.3 For destructive test. The sample training containers shall be tested for drop strength in accordance with 4.4.5.1(c) at an AQL of 4.0 percent defective. The sample training containers (cleaned, pretreated and primed (without topcoat)) shall be tested for salt spray corrosion resistance in accordance with 4.4.5.1(e) at an AQL of 4.0 percent defective.

4.4.3.4 Classification of defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:03Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.3.4(a)	Fluid Container Assembly, Training				5-51-528
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Leakage		0.15%	3.3.1.2	4.4.5.1(b)
102	Lifting handle strength (Note 1)	Note 2	0.65%	3.3.1.1	4.4.5.1(a)
103	Height dimension incorrect		1.0%	3.1.2	CIE*
104	Length, width and radius dimensions incorrect		1.0%	3.1.2	CIE
105	Weldments incorrect		1.0%	3.1.2	Visual/CIE
106	Protective finish incorrect or missing		1.0%	3.1.2	CIE
107	Adhesion	Note 2	1.0%	3.3.1.4	4.4.5.1(d)
Minor					
201	Components missing or incorrectly assembled		2.5%	3.1.2	Visual
202	Labels missing, incorrect or incorrectly located		2.5%	3.1.2	Visual
203	Workmanship		2.5%	3.5	Visual

NOTES: 1. Alternate test; test shall be imposed either as above or in accordance with 4.4.3.4(e), category Major 104.
2. Sample level S-4
CIE* - Commercial Inspection Equipment

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:03Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.3.4(b)	Adapter Assembly				5-51-566
					NEXT HIGHER ASSEMBLY 5-51-523
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Components missing, incorrect or incorrectly assembled		1.0%	3.1.2	Visual
102	Brazing incorrect		1.0%	3.1.2	Visual
Minor					
201	Workmanship		2.5%	3.5	Visual
202	Crimped end opening incorrect		2.5%	3.1.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:03Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.3.4(c)	Adapter Assembly				5-51-565
					NEXT HIGHER ASSEMBLY
					5-51-523
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Components missing, incorrect, or incorrectly assembled		1.0%	3.1.2	Visual
102	Length incorrect		1.0%	3.1.2	CIE*
103	Brazing incorrect		1.0%	3.1.2	CIE
Minor					
201	Workmanship		2.5%	3.5	Visual

NOTES:

CIE* - Commercial Inspection Equipment

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:03Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.3.4(d)	Packaging - Packing - Palletization				SPI P5-51-528
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Filler pads missing or incorrect		1.0%	5.1	Visual
102	Marking incorrect or missing		1.0%	5.1	Visual
103	Banding straps broken, missing or loose or incorrectly located		1.0%	5.1	Visual
104	Container size incorrect		1.0%	5.1	Visual
Minor					
201	Pallet incorrect, split or damaged		2.5%	5.1	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:03Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.3.4(e)	Top-Reservoir Assembly				5-51-523
					NEXT HIGHER ASSEMBLY
					5-51-528
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Lock clip location incorrect		1.0%	3.1.2	CIE*
102	Lifting handle location incorrect		1.0%	3.1.2	CIE
103	Weld or braze incorrect		1.0%	3.1.2	Visual
104	Lifting handle strength (Note 1)	Note 2	0.65%	3.3.1.1	4.4.5.1(a)
Minor					
201	Workmanship		2.5%	3.5	Visual

NOTES: CIE* - Commercial Inspection Equipment
1. Alternate test; test shall be imposed either as above or in accordance with 4.4.3.4(a), category Major 102.
2. Sample level S-4.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:03Z
Check the source to verify that this is the current version before use.

4.4.4 Inspection equipment. Unless otherwise specified in the contract, the contractor shall furnish and maintain inspection equipment in accordance with MIL-I-45607 and MIL-STD-45662 (see 4.4.5 and 6.2).

4.4.5 Tests. Inspection equipment which is to be acquired by the contractor and used in the performance of the following tests shall be in accordance with 4.4.4. Unless otherwise specified, tests shall be performed at room temperature, 20°-30°C (68°-86°F).

4.4.5.1 Fluid container assembly, training. The training container shall be tested as follows:

(a) Lifting handle. Secure the top reservoir or the container assembly and apply the specified static load uniformly over the handle for the specified time. Examine lifting handle and top-reservoir or lifting handle and container assembly, as applicable.

(b) Leakage. With the container openings sealed and with the specified air pressure introduced into the container through a fitting, submerge the container in water containing a wetting agent to a depth of no more than 3 inches below the surface for the specified time and observe for leakage. A steady stream of bubbles shall be an indication of leakage.

(c) Drop strength. Fill the container as specified and seal the openings. Drop the container as specified on bottom seam diagonally opposite from the vent/coupling area.

(d) Adhesion. The container shall be tested for coating adhesion in accordance with Adhesion (tape test) of MIL-C-22750 except that items to be tested shall be training containers.

(e) Salt spray corrosion resistance. A straight scribe mark shall be made on the container as described in ASTM D 1654. The scribe mark shall not contact the edge of the specimen and must penetrate all coatings on the metal, leaving a uniformly bright line free of burrs. For the purpose of this test the significant surface of the container shall be 3 inches on either side of the scribe mark. This significant area shall be from top to bottom of the container. Procedures for evaluation shall be in accordance with ASTM D 1654. The cleaned, pretreated and primed (without topcoat) container shall be exposed to a 5 percent salt spray for 336 hours in accordance with ASTM B 117. Upon removal, the container shall be washed in warm running water maintained at a temperature of not greater than 100°F until free from any visible salt deposits and examined immediately in accordance with method 1 or 2 of ASTM D 1654. The mean creepage from scribe shall be as specified herein.

5. PACKAGING

5.1 Packaging. Packaging shall be as specified in SPI P5-51-528.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:03Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The training fluid container assembly is intended to be used as a training container for the M13 Portable, 14 Liter, Decontaminating Apparatus. The training container is to be filled with water or other approved simulant for DS2.

6.2 Ordering data. Acquisition documents should specify the following:

(a) Title, number, and date of this specification.
(b) Level of preservation, packaging, packing, palletization required and shelf life code (see section 5).
(c) Preproduction/First Article:

(1) First Article Inspection and Report requirements.
(2) Delivery schedule for First Article Report.
(3) Destination and delivery schedule of First Article Samples when testing is performed by the Government.
(4) First Article Test report approval time.

(d) Production

(1) Destination and delivery schedule requirements.
(2) Production and inspection report requirements.

6.3 Submission of requests for inspection equipment approval. Contractor shall submit request for inspection equipment approval to AMSMC-QAV-T (A), Aberdeen Proving Ground, MD 21010-5423.

6.4 Submission of test results required by contract. Contractor shall submit data in accordance with DD Form 1423.

6.5 Caution. Due to the hazards inherent in pressure testing, contractors are advised to take all necessary precautions to protect personnel while testing.

6.6 Significant places. For the purpose of determining conformance with this specification, an observed or calculated value should be rounded off "to the nearest unit" in the last right-hand place of figures used in expressing the limiting value, in accordance with the rounding-off method of ASTM E 29.

6.7 Supersession data. This specification supersedes and includes the requirements of Chemical Research and Development Center Purchase Description EA-F-1450, dated 16 November 1984.

6.8 Subject term (key word) listing.

Chemical agents
Decontamination
Decontamination equipment
Training container

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:03Z
Check the source to verify that this is the current version before use.

Custodian:

Army - EA

Preparing activity:

Army - EA

Project No. 6910-A078

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:03Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-F-51532(EA)	FLUID CONTAINER ASSEMBLY, TRAINING

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:03Z
Check the source to verify that this is the current version before use.