MILITARY SPECIFICATION

PROJECTILE, 8 INCH: DUMMY, M845

This specification is approved for use by US Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the manufacturing, loading and assembling of metal parts for projectile, 8 Inch: Dummy, M845.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078	-Ammunition, Standard Quality Assurance Provisions, General Specification for

STANDARDS

MILITARY

MIL-STD-105	-Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

9333956	-Projectile, 8 Inch: Dummy, M845
93407096	-Packing and Marking for Box, for Projectile, 8 Inch, Dummy, M845

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

☆ U.S. GOVERNMENT PRINTING OFFICE: 1981—703-023/6007

FSC: 1320

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.

2.2 Other Publications. The following documents form a part of the specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply:

ANSI B46.1 - Surface Texture

(Application for copies should be addressed to the: American National Standards Institute (ANSI), 1430 Broadway, New York, New York 10018).

3. REQUIREMENTS

3.1 Material. Materials, parts and assemblies shall comply with the requirements specified on the applicable drawings and specifications.

3.2 Projectile Metal Parts Assembly. The projectile assembly and components shall comply with all requirements specified on Drawing (dwg.) 9333956 and with all requirements specified in applicable specifications.

3.3 Rotating Band. The rotating band blank shall be in the form of a solid ring. It shall comply with the requirements specified on Drawing 9333955 and with all requirements specified in applicable specifications.

3.4 Surface Finish. The requirements for surface finish are as detailed on the applicable drawing.

3.5 Metal Defects. The body, including the cavity, shall be free from cracks.

3.6 Workmanship. The requirements for workmanship are as shown on the applicable drawings and specifications and the following:

3.6.1 Surface preparation. Preparation of metal surfaces shall be as specified on the applicable drawings and specifications. Cleaning and preparation are required by component details, the finish specified shall apply to indicated surfaces regardless of contour configuration.

3.6.2 Painting. Painting shall comply with the requirements of the applicable drawings and specifications. All paint shall be dry to the touch before packing for shipment. Drying time prior to testing shall be in accordance with the applicable specification.

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:48Z
Check the source to verify that this is the current version before use.

3.6.3 Surface finish. The requirements for surface finish are as detailed on the applicable drawing. The roughness comparison specimens prescribed by ANSI-B46.1 shall be used as a basis for surface roughness determination.

3.6.4 Threads. Threads shall be full and undamaged for the entire minimum length or depth as specified on the applicable drawing.

3.6.5 Burr. No part shall have a burr which might interfere with the assembly or function of the projectile or which might be injurious to personnel handling the item.

3.6.6 Foreign matter. No part or assembly shall contain dirt, grease, rust, corrosion or other foreign matter.

3.6.7 Protection of rotating band. The machined rotating band shall be protected from being nicked, burred or otherwise damaged in subsequent handling prior to shipment.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. A quality conformance inspection shall be conducted on this item.

4.2.1 Rejection. See MIL-A-48078.

4.3 Quality conformance inspection.

4.3.1 Inspection lot formation. Inspection lots shall comply with lot formation provisions of MIL-A-48078.

4.3.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:48Z
Check the source to verify that this is the currentversion before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63409

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.3.2.1	Band Rotating		9333955
			NEXT HIGHER ASSEMBLY 9333956

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major	None Defined				
Minor					
201	Inside Diameter		0.65%	3.2	Gage
202	Outside Diameter		0.65%	3.2	Gage
203	Width		0.65%	3.2	Gage
204	Location of Groove (8 Places)		0.65%	3.2	Visual
205	Depth of Groove		0.65%	3.2	Gage
206	Extent of Taper (.57 + .03)		0.65%	3.2	Gage
207	Band OD Face (7.98 - .02), 2 Places		0.65%	3.2	Gage
208	Chamfer and Tapers Missing or Incorrect		0.65%	3.2	Visual
209	Radius Missing or Incorrect		0.65%	3.2	Gage

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63409

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.3.2.2	Bar, Base		9335573
			NEXT HIGHER ASSEMBLY 9335661

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major	None Defined				
Minor					
201	Length		0.65%	3.2	Gage
202	Width		0.65%	3.2	Gage
203	Thickness		0.65%	3.2	Gage

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63409

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9335574
4.3.2.3	Disc, Body				NEXT HIGHER ASSEMBLY 9335666
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major	None Defined				
Minor					
201	Thickness		0.65%	3.2	Gage
202	Diameter		0.65%	3.2	Gage

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63409

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.3.2.4	Body Assembly				9335660
					NEXT HIGHER ASSEMBLY 9333956
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Diameter of Bourrelet, Maximum		0.40%	3.2	Gage
102	Weld Improper or Missing		0.40%	3.2	Visual
Minor					
201	Lubricant Missing on Threads		0.65%	3.2	Visual
202	Protective Coating on Exterior Surface Inadequate or Damaged		0.65%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63409

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.3.2.5	Body (Modified)		9335570
			NEXT HIGHER ASSEMBLY 9335660

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Pitch Diameter, Threads Maximum		0.40%	3.2	Gage
102	Minor Diameter, Threads Maximum		0.40%	3.2	Gage
103	Minor Diameter, Threads Minimum		0.40%	3.2	Gage
104	Position of Holes (Four Holes)		0.40%	3.2	Gage
105	Diameter Hole (Four Holes) (3/8-24UNF-3B)		0.40%	3.2	Gage
106	Runout of Pitch Diameter with Rear Face and Bourrelet Undercut		0.40%	3.2	Gage
107	Diameter Bourrelet, Maximum		0.40%	3.2	Gage
108	Length of Thread Including Thread Undercut		0.40%	3.2	Gage
109	Diameter Thread Undercut		0.40%	3.2	Gage
110	Diameter Body Disc Undercut		0.40%	3.2	Gage
111	Length of effective thread, min.		0.40%	3.2	Gage
Minor					
201	Length Body Disc Undercut		0.65%	3.2	Gage
202	Length, Total			3.2	Gage
203	Diameter Bourrelet Undercut		0.65%	3.2	Gage
204	Distance from Rear Face to Hole		0.65%	3.2	Gage

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63409

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.3.2.6	Plug				9335572
					NEXT HIGHER ASSEMBLY
					9333956
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major	None Defined				
Minor					
201	Diameter		0.65%	3.2	Gage
202	Length		0.65%	3.2	Gage
203	Hardness		0.65%	3.2	Gage

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63409

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.3.2.7	Grommet Modified				9341608
					NEXT HIGHER ASSEMBLY 9333956
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major	None Defined				
Minor					
201	Diameter (2 Places)		0.65%	3.2	Gage

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63409

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.3.2.8	Base Plug				9341609
					NEXT HIGHER ASSEMBLY 9333956
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Pitch Diameter of Thread, Maximum		0.40%	3.2	Gage
102	Minor Diameter of Thread, Maximum		0.40%	3.2	Gage
103	Minor Diameter of Thread, Minimum		0.40%	3.2	Gage
104	Perpendicularity of Shoulder to Threads		0.40%	3.2	GAge
Minor					
201	Width of Shoulder		0.65%	3.2	Gage
202	Diameter of Hole (Two Holes)		0.65%	3.2	Gage
203	Depth of Hole (Two Holes)		0.65%	3.2	Gage
204	Location of Holes		0.65%	3.2	Gage
205	Width of Undercut		0.65%	3.2	Gage
206	Radii of Chamfers Missing or Incorrect		0.65%	3.2	Visual
207	Protective Coating Inadequate		0.65%	3.2	Visual
208	Lubricant Missing on Threads		0.65%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63409

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9341607
4.3.2.9	Supplementary Charge Assembly (Inert)				NEXT HIGHER ASSEMBLY 9333956
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major	None Defined				
Minor					
201	Length		0.65%	3.2	Gage
202	Marking Missing or Incorrect		100%	3.2	Visual
203	Pad Missing or Loose		100%	3.2	Visual
204	Tab Missing or Loose		100%	3.2	Visual
205	Crimp Missing or Improper		100%	3.2	Visual
206	Disc, Closing or Missing		100%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63409

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.3.2.10	Base				9335571
					NEXT HIGHER ASSEMBLY 9335661
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Pitch Diameter Threads Min. Forward Face		0.40%	3.2	Gage
102	Minor Diameter Threads Max. Forward Face		0.40%	3.2	Gage
103	Major Diameter Threads Min. Forward Face		0.40%	3.2	Gage
104	Pitch Diameter Threads Max. in Base		0.40%	3.2	Gage
105	Minor Diameter Threads Max. in Base		0.40%	3.2	Gage
106	Runout of Band Seat to Bourrelet		0.40%	3.2	Gage
107	Runout of Rear Threads to Bourrelet and Rear Face		0.40%	3.2	Gage
108	Length of Base		0.40%	3.2	Gage
Minor					
201	Width of Band Seat		0.65%	3.2	Gage
202	Width of Forward Threads Including Undercut		0.65%	3.2	Gage
203	Diameter of Thread Undercut		0.65%	3.2	Gage
204	Diameter of Bourrelet		0.65%	3.2	Gage
205	Diameter of Band Seat		0.65%	3.2	Gage
206	Radii and Chamfers Missing or Incorrect		0.65%	3.2	Visual
207	Protective Coating Missing or Inadequate		0.65%	3.2	Visual
208	Lubricant Missing from Threads		0.65%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63409

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9335661
4.3.2.11	Base and Bar Weldment				NEXT HIGHER ASSEMBLY 9333956
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Overall Length (Minimum)		0.40%	3.2	Gage
Minor					
201	Distance of Base Bar to Rear Face		0.65%	3.2	Gage
202	Weld Improper or Missing		0.65%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63409

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.3.2.12	Projectile, 8 Inch Dummy, M845, Filling Procedures				9341606
					NEXT HIGHER ASSEMBLY 9333956
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major	None Defined				
Minor					
201	Lubricant Missing on Threads		0.65%	3.2	Visual
202	Torque Test Failure of Base Plug		0.65%	3.2	Test
203	Weight Improper		100%	3.2	Scale
204	Fuze Cavity Diameter		0.65%	3.2	Gage
205	Fuze Cavity Depth		0.65%	3.2	Gage

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63409

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.3.2.13	Projectile, 8 Inch Dummy M845				9333956
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Rotating Band Missing		100%	3.2	Visual
102	Lifting Plug Missing or Improperly Assembled		100%	3.2	Visual
Minor					
201	Grommet Missing, Damaged or Improperly Assembled		0.65%	3.2	Visual
202	Protective Coating Damaged		0.65%	3.2	Visual
203	Liner Missing		0.65%	3.2	Visual
204	Supplementary Charge Missing or Improperly Assembled		0.65%	3.2	Visual
205	Spacer Missing		0.65%	3.2	Visual
206	Marking, Misleading or Unidentifiable		0.65%	3.2	Visual
207	Evidence of Poor Workmanship		100%	3.2	Visual
208	Gasket missing		0.65%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.

4.3.3 Testing.

4.4.3.1 Cleaning and application of protective coating. The sample size and acceptance criteria for the inspection of cleaning the item and the application of protective coating shall be as specified in the applicable specification. Failure to comply with the applicable requirements shall be cause for taking the actions recommended therein.

4.4.4 Inspection equipment. The contractor shall submit for approval of inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078.

4.4.5 Tool control dimensions.

a. Dimensions marked tool control shall be gaged at the beginning or end of each working day (24 hours) during First Article Inspection and for the first component after each tooling change, adjustment or repair. Where destruction of the component is necessary to gage such dimensions, measurements of the tool may be substituted provided the contractor has established correlation between the tool dimensions and the component dimensions prior to the start of production.

b. When the contractor has satisfied (a) above, visual inspection of tool control dimensions will be permitted. Visual inspection shall be performed every two (2) hours for each machine in operation. If any tool control dimension(s) is in doubt during visual inspection, the dimension(s) shall be immediately gaged (see "a" above) to determine acceptability. Corrective action will immediately be instituted by the contractor whenever a defective tool control dimension is found.

5. PACKING

5.1 Packing and marking. The projectile shall be packed in accordance with Drawing 9340709.

5.1.1 Level A and B. Level A and B apply.

6. NOTES

6.1 Intended use. The components covered by this specification are intended for use on the 8 Inch M845 projectile.

6.2 Ordering data. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.

6.3 Submission of inspection procedures and/or equipment designs for approval. See MIL-A-48078. Submit equipment designs as required to: Commander, ARRADCOM, ATTN: DRDAR-QAR-I, Dover, New Jersey 07801.

6.4 Visual examination qualification. When compliance with the applicable requirement is in doubt as a result of visual examination, the characteristics may be measured or gaged to determine acceptability.

6.5 Alternative testing procedures. Alternative testing procedures may be used by the contractor when such testing and procedures provide as a minimum the quality assurance provisions specified herein. Prior to applying alternative procedures, the contractor shall describe them in a written proposal and shall demonstrate for the approval of the responsible Government technical agency that their effectiveness is equal to, or better than the quality assurance provisions specified herein.

6.6 This projectile shall be fabricated from 8 Inch M106 parts where possible.

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project No.: 1320-A573

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:48Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-P-63409 Projectile, 8 INCH: DUMMY, M845

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.