MILITARY SPECIFICATION

# WARHEAD, INERT, FOR DEMOLITION KIT, TRAINING, XM270 LOADING ASSEMBLY

This specification is approved for use by US Army Armament Research and Development Command and is available for use by all Departments and Agencies of the Department of Defense.

## 1. SCOPE

1.1 This specification covers the loading assembly for one type of warhead designated as Warhead, Inert, for Demolition Kit, Training, XM270.

## 2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)

FSC: 1375

**Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.**

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:44Z
Check the source to verify that this is the current version before use.

DRAWINGS (See 6.4)

U.S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

9329744 - Warhead Loading Assembly (Inert)
9244445 - Coupling, Flush Hatch, Warhead

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer).

3. REQUIREMENTS

3.1 Material. Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Assembly. The assembly shall comply with all requirements specified on drawing (Dwg.) 9329744 and with all requirements specified in applicable specifications.

3.3 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.4 Workmanship. All parts and assemblies shall be fabricated and loaded in a thorough workmanlike manner, and all manufacturing, processing, and assembly operations shall be correctly performed. They shall be free of burrs, sharp edges, unblended radii, surface defects, chips, dirt, grease and oil (except where specifically required), corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part or assembly nor shall they be contaminated by the cleaning agent. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings and stampings shall be neat and sharply defined. (Required packing shall be dry).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification. Each lot of warheads shall contain: Parts from not more than one lot interfix number for one manufacturer.



Source: https://assist.dla.mil -- Downloaded: 202610-23T02:44Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. The following types of inspections shall be conducted on this item.

a. First Article Inspection

b. Quality Conformance Inspection

4.3 First article inspection

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2 and 4.3.3. The first article sample shall consist of the following items in sample quantities as indicated (see Table I).

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:44Z
Check the source to verify that this is the current version before use.

TABLE I. First Article Inspection

## CLASSIFICATION OF DEFECTS & TESTS

MIL-W-63374(AR)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| | Warhead, For Demolition Kit, M180 Loading Assembly | | | | See Below |
| | | | | | NEXT HIGHER ASSEMBLY |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| | Loading Assembly, Warhead (Dwg. 9329744) | | | | |
| | Examination for defects | 10 | 100% | 3.2 | 4.4.2.1 |
| | Weight of filler | 10 | 100% | 3.3 | 4.4.3.1 |

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:44Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. See MIL-A-48078. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.4.4.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:44Z
Check the source to verify that this is the current version before use.

# CLASSIFICATION OF DEFECTS & TESTS

MIL-W-63374(AR)

| PARAGRAPH | TITLE | SHEET 1 OF 1 | DRAWING NUMBER |
|---|---|---|---|
| 4.4.2.1 | Loading Assembly, Warhead | | 9329744 |
| | | | NEXT HIGHER ASSEMBLY 9331717 |

| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
|---|---|---|---|---|---|
| Critical | None defined | | | | |
| Major | | | | | |
| 101 | Diameter of fuze cavity | | 0.40% | 3.2 | Gage |
| 102 | Depth of fuze cavity | | 0.40% | 3.2 | Gage |
| 103 | True position of diameter of fuze cavity with outside diameter of flange | | 0.40% | 3.2 | Gage |
| 104 | Protrusion of inert filler above surface of flange | | 0.40% | 3.2 | Gage |
| 105 | Component missing or improperly assembled | | 0.40% | 3.2 | Visual/Manual |
| 106 | Marking missing or incorrect | | 0.40% | 3.2 | Visual |
| 107 | Flush latch coupling insecure or missing | | 100% | 3.2 | Visual/Manual |
| Minor | | | | | |
| 201 | Evidence of poor workmanship | | 1.00% | 3.5 | Visual |

NOTES:





Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:44Z
Check the source to verify that this is the current version before use.

4.4.3 Testing

4.4.3.1 Weight of inert filler. Major defect. This test shall be performed one hundred percent as specified in 4.5.1 using test equipment in accordance with 4.4.4. Any warhead which does not meet the specified requirement shall be classified defective and removed from the lot (Non-destructive test).

4.4.4 Inspection equipment. The inspection equipment required to perform the inspections and tests prescribed in this specification is identified in the 'Paragraph Reference/Inspection Method' column in the tables starting with paragraph 4.4.2.1, and the test method paragraphs (see 4.5). The contractor shall submit for approval, inspection equipment designs in accordance with the terms of the contract. See section 6 of MIL-A-48078, and 6.2 herein.

4.5 Test methods and procedures

4.5.1 Weight of inert filler. Before loading, the shell assemblies shall be labeled and weighed to the nearest .01 pound (4.5 grams). This tared weight shall be subtracted from the loaded, machined warhead weight.

5. PACKING

5.1 Preservation and packaging. If the warhead is shipped interplant, separate from the rest of the kit, packaging shall be in accordance with MIL-STD-1188.

5.2 Packing. Packing shall be in accordance with MIL-STD-1188.

5.3 Marking. Marking shall be in accordance with MIL-STD-1188.

6. NOTES

6.1 Ordering data. Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Provisions for submission of first article samples.

c. Provisions of MIL-A-48078.

6.2 Submission of inspection equipment designs for approval. (See MIL-A-48078). Submit equipment designs as required to Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAA-I, Dover, New Jersey 07801.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:44Z
Check the source to verify that this is the current version before use.

6.3 Distribution of ammunition data cards. Distribution of data cards shall include the following: Commander, ARRADCOM, ATTN: DRDAR-QAA-M, Dover, New Jersey 07801.

6.4 Drawings. Drawings listed in Section 2 of this specification under the heading, "US Army Armament Research and Development Command (ARRADCOM)" may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARRADCOM.

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project No.: 1375-A139



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:44Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-W-63374 Warhead, Inert, for Demolition Kit, Training, XM270 Loading Assembly

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1 ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:44Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

**BUSINESS REPLY CARD**

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Armament R&D Command
ATTN: DRDAR-QAA
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:44Z
Check the source to verify that this is the current version before use.