| INCH-POUND |

MIL-M-38510/55F
AMENDMENT 2
30 September 1988
SUPERSEDING
AMENDMENT 1
21 September 1984

MILITARY SPECIFICATION

MICROCIRCUITS, DIGITAL, CMOS, BUFFER/CONVERTER,
TRUE/COMPLEMENT BUFFER, MONOLITHIC SILICON

This amendment forms a part of MIL-M-38510/55F, dated 30 April 1984, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* 1.2.3, add new case outlines as follows:

"N	F-5A (16-lead, .440" x .285" x .115"), flat package
T	F-2A (14-lead, .390" x .260" x .115"), flat package"

---

* The attached insertable replacement pages listed below are replacements for stipulated pages. When the new pages have been entered in the document, insert the amendment as the cover sheet to the specification.

Replacement page	Page replaced
5	5
6	6
25	25
26	26
29	29
30	30
33	33
34	34
35	35
36	36

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
Source: https://assist.dla.mil -- Downloaded: 2026-10-21T13:05Z
Check the source to verify that this is the current version before use.

1.3, delete and substitute:

"1.3 Absolute maximum ratings.

Device types 01 and 02

Supply voltage range (V_{DD} - V_{SS}):	
$V_{CC} \leq V_{DD}$	-0.5 V to +15.5 V
Output load capacitance (each output)	200 pF when $V_{CC} > 10$ V
Input voltage range	$(V_{SS} - 0.5\ V) \leq V_I \leq (V_{DD} + 0.5\ V)$

Device types 51 and 52

Supply voltage range (V_{DD} - V_{SS}):	
$V_{CC} \leq V_{DD}$	-0.5 V to +18.0 V
Output load capacitance (each output)	200 pF when $V_{CC} > 10$ V
Input voltage range	$(V_{SS} - 0.5\ V) \leq V_I \leq (V_{DD} + 0.5\ V)$
DC output source or sink current per pin	I_{OH} = -4 mA I_{OL} = +12 mA
DC supply current, per pin (I_{DD}, I_{CC})	±25.0 mA
DC ground current (I_{GND})	+50 mA

Device types 03 and 04

Supply voltage range (V_{CC} - V_{SS})	-0.5 V to +15.5 V
Input voltage range	$(V_{SS} - 0.5\ V) \leq V_I \leq (V_{CC} + 0.5\ V)$

Device types 53 and 54

Supply voltage range (V_{CC} - V_{SS})	-0.5 V to +18.0 V
Input voltage range	$(V_{SS} - 0.5\ V) \leq V_I \leq (V_{CC} + 0.5\ V)$
DC output source or sink current per pin	I_{OH} or I_{OL} = ±12.0 mA
DC supply or ground current per pin (I_{CC}, I_{GND})	±50 mA

Device type 05

Supply voltage range (V_{DD} - V_{SS})	-0.5 V to +15.0 V
Input voltage range	$(V_{SS} - 0.5\ V) \leq V_I \leq (V_{DD} + 0.5\ V)$

Device type 55

Supply voltage range (V_{DD} - V_{SS})	-0.5 V to +18.0 V
Input voltage range	$(V_{SS} - 0.5\ V) \leq V_I \leq (V_{DD} + 0.5\ V)$
DC output source or sink current per pin:	
True output	I_{OH} or I_{OL} = ±12.0 mA
Complement output	I_{OH} or I_{OL} = ±6.0 mA
DC supply or ground current per pin (I_{DD}, I_{GND})	±50 mA

All device types

Input current (each input)	±10 mA
Storage temperature range	-65°C to +175°C
Maximum power dissipation (P_D)	200 mW
Lead temperature (soldering, 10 seconds)	+300°C
Thermal resistance, junction-to-case	See MIL-M-38510, appendix C
Junction temperature	T_J = +175°C "

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T13:05Z
Check the source to verify that this is the current version before use.

PAGE 4

4.2a: Delete "3.1.9 through 3.1.13" and substitute "initial (pre-burn-in) electrical parameters (3.1.10) through interim (post-burn-in) electrical parameters (3.1.14)".

PAGE 7

* Table I, t_{PHL}, t_{PLH}, t_{THL}, and t_{TLH}, min limits column: Delete all entries and substitute "6".

PAGE 8

* Table II, line 9: Insert "10 and 11" in subgroup column for class B.
Line 12: Delete entire line.
Line 13: Delete "13" and substitute "12".

PAGE 9

* 4.4.1, insert 4.4.1d and 4.4.1e as follows:

"d. Subgroups 9 and 11 shall be measured only for initial qualification and after process or design changes which may affect dynamic performance.

e. When the 01 through 03 device types are qualified by extension (see 4.3.1), these device types will be inspected (QCI) according to the 51 through 53 device type requirements respectively."

PAGES 15 AND 16

* Table III: Delete "Cases E, F, Z" and substitute "Cases E, F, N, and Z".

PAGE 17

* Table III: Delete "Cases E, F, Z" and substitute "Cases E, F, N, and Z".

* Table III, t_{PHL}, min limits columns: Delete "7/2" throughout and substitute "6", "9", "6", respectively. t_{PLH}, min limits columns: Delete "10/8" throughout and substitute "6", "9", "6", respectively. t_{THL}, min limits columns: Delete "20/5" throughout and substitute "6", "9", "6", respectively. t_{TLH}, min limits columns: Delete "20" throughout and substitute "6", "9", "6", respectively.

PAGES 18 AND 19

* Table III: Delete "Cases E, F, Z" and substitute "Cases E, F, N, and Z".

PAGE 20

* Table III: Delete "Cases E, F, Z" and substitute "Cases E, F, N, and Z".

* Table III, t_{PHL}, min limits columns: Delete "7/11" throughout and substitute "6", "9", "6", respectively. t_{PLH}, min limits columns: Delete "10/17" throughout and substitute "6", "9", "6", respectively. t_{THL}, min limits columns: Delete "20/5" throughout and substitute "6", "9", "6", respectively. t_{TLH}, min limits columns: Delete "20" throughout and substitute "6", "9", "6", respectively.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T13:05Z
Check the source to verify that this is the current version before use.

PAGE 23

Table III, test 112, pin column 11: Delete "OUT"; pin column 12: Delete "IN" and substitute "OUT"; pin column 13: Add "IN".

* Table III, t_{PHL}, min limits columns: Delete "8" throughout and substitute "6", "9", "6", respectively. t_{PLH}, min limits columns: Delete "9" throughout and substitute "6", "9", "6", respectively. t_{THL}, min limits columns: Delete "8" throughout and substitute "6", "9", "6", respectively. t_{TLH}, min limits columns: Delete "9" throughout and substitute "6", "9", "6", respectively.

PAGE 27

* Table III: Delete "Cases E, F, Z" and substitute "Cases E, F, N, and Z".

PAGE 28

* Table III: Delete "Cases E, F, Z" and substitute "Cases E, F, N, and Z".

* Table III, t_{PHL}, min limits columns: Delete "5/2", "7/2", "5/2" and substitute "6", "9", "6", respectively. t_{PLH}, min limits columns: Delete "7/8", "10/8", "7/8" and substitute "6", "9", "6", respectively. t_{THL}, min limits columns: Delete "3/3", "10/8", "3/3" and substitute "6", "9", "6", respectively. t_{TLH}, min limits columns: Delete "13", "20", "13" and substitute "6", "9", "6", respectively.

PAGE 31

* Table III: Delete "Cases E, F, Z" and substitute "Cases E, F, N, and Z".

PAGE 32

* Table III: Delete "Cases E, F, Z" and substitute "Cases E, F, N, and Z".

* Table III, t_{PHL}, min limits columns: Delete "5/7", "7/11", "5/7" and substitute "6", "9", "6", respectively. t_{PLH}, min limits columns: Delete "7/11", "10/17", "7/11" and substitute "6", "9", "6", respectively. t_{THL}, min limits columns: Delete "3", "4/5", "3" and substitute "6", "9", "6", respectively. t_{TLH}, min limits columns: Delete "13", "20", "13" and substitute "6", "9", "6", respectively.

PAGE 37

* 4.4.3: Delete 4.4.3c and substitute as follows:

"c. When the 01 through 03 device types are qualified by extension (see 4.3.1), these device types will be inspected (QCI) according to the 51 through 53 device type requirements respectively."

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T13:05Z
Check the source to verify that this is the current version before use.

6.3: Delete "V_{DD}" and substitute "V_{DD} and V_{CC}".

After I_{SS} add:

"I_{DD} and I_{CC} - - - - - - - - - - - - - - - - - DC supply current.
I_{GND} - DC ground current."

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 17
NASA - NA

Review activities:
Army - MI
Air Force - 11, 19, 85, 99
DLA - ES

User activities:
Army - AR, SM
Navy - AS, CG, MC, OS, SH

Preparing activity:
NASA - NA

Agent:
DLA - ES

(Project 5962-1156-6)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T13:05Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical performance characteristics.

Test	Symbol	Conditions V_{SS} = 0 V, -55°C ≤ T_C ≤ 125°C, unless otherwise specified	Device type 1/	Limits		Unit
				Min	Max	
Positive clamping input to V_{DD} or V_{CC}	$V_{IC(pos)}$	T_C = 25°C, V_{DD} and V_{CC} = GND, V_{SS} = Open, Output = Open, I_I = 1 mA	01, 02, 05, 51, 52, 55		+1.5	V dc
Negative clamping input to V_{SS}	$V_{IC(neg)}$	T_C = 25°C, V_{DD} and V_{CC} = Open, V_{SS} = GND, Output = Open, I_I = -1 mA	All		-6	V dc
Quiescent supply current	I_{SS}	V_{DD} and V_{CC} = 15 V dc, any combination of inputs	01-05		-750	nA dc
		V_{DD} and V_{CC} = 18 V dc, any combination of inputs	51-55		-750	nA dc
High level output voltage	V_{OH1}	V_{DD} and V_{CC} = 4.5 V dc, I_{OH} = -0.1 mA (see table III)	01-05	2.50		V dc
	V_{OH2}	V_{DD} and V_{CC} = 5 V dc, I_{OH} = -0.35 mA (see table III)	01-05	4.5		V dc
	V_{OH3}	V_{DD} and V_{CC} = 5 V dc, I_{OH} = 0 (see table III)	01-05	4.95		V dc
	V_{OH4}	V_{DD} and V_{CC} = 12.5 V dc, I_{OH} = 0 (see table III)	01-05	11.25		V dc
	V_{OH5}	V_{DD} and V_{CC} = 15 V dc, I_{OH} = 0 (see table III)	51-55	14.95		V dc
Low level output voltage	V_{OL1}	V_{DD} and V_{CC} = 5.5 V dc, I_{OL} = .23 mA (see table III)	01-05		0.5	V dc
	V_{OL2}	V_{DD} and V_{CC} = 5 V dc, I_{OL} = 2.1 mA (see table III)	01-05		0.5	V dc
	V_{OL3}	V_{DD} and V_{CC} = 5 V dc, I_{OL} = 0 (see table III)	01-05		0.05	V dc
	V_{OL4}	V_{DD} and V_{CC} = 12.5 V dc, I_{OL} = 0 (see table III)	01-05		1.25	V dc
	V_{OL5}	V_{DD} and V_{CC} = 15 V dc, I_{OL} = 0 (see table III)	51-55		0.05	V dc

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T13:05Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical performance characteristics - Continued.

Test	Symbol	Conditions V_{SS} = 0 V, -55°C ≤ T_C ≤ 125°C, unless otherwise specified	Device type 1/	Limits Min	Limits Max	Unit
Input high voltage	V_{IH1}	V_{DD} and V_{CC} = 5 V dc, V_O = (see table III), $\|I_O\| \leq 1$ µA	51, 53	4.0		V dc
			52,54,55	3.5		
	V_{IH2}	V_{DD} and V_{CC} = 10 V dc, V_O = (see table III), $\|I_O\| \leq 1$ µA	51, 53	8.0		V dc
			52,54,55	7.0		
	V_{IH3}	V_{DD} and V_{CC} = 15 V dc, V_O = (see table III), $\|I_O\| \leq 1$ µA	51, 53	12.0		V dc
			52,54,55	11.0		
Input low voltage	V_{IL1}	V_{DD} and V_{CC} = 5 V dc, V_O = (see table III), $\|I_O\| \leq 1$ µA	51, 53		1.0	V dc
			52,54,55		1.5	
	V_{IL2}	V_{DD} and V_{CC} = 10 V dc, V_O = (see table III), $\|I_O\| \leq 1$ µA	51, 53		2.0	V dc
			52,54,55		3.0	
	V_{IL3}	V_{DD} and V_{CC} = 15 V dc, V_O = (see table III), $\|I_O\| \leq 1$ µA	51, 53		2.5	V dc
			52,54,55		4.0	
Output low (sink) current	I_{OL1}	V_{DD} and V_{CC} = 5 V dc, V_{IN} = (see table III), V_{OL} = 0.4 V dc	51-54	2.2		mA dc
		True output	55	1.2		
		Complement output		0.55		
	I_{OL2}	V_{DD} and V_{CC} = 15 V dc, V_{IN} = (see table III), V_{OL} = 1.5 V dc	51-54	17.0		mA dc
		True output	55	8.0		
		Complement output		3.0		
Output high (source) current	I_{OH1}	V_{DD} and V_{CC} = 5 V dc, V_{IN} = (see table III), V_{OH} = 4.6 V dc	51-54	-0.36		mA dc
		True output	55	-1.0		
		Complement output		-0.4		
	I_{OH2}	V_{DD} and V_{CC} = 15 V dc, V_{IN} = (see table III), V_{OH} = 13.5 V dc	51-54	-2.4		mA dc
		True output	55	-6.0		
		Complement output		-2.7		
Input leakage current	I_{IH}	V_{DD} and V_{CC} = 15 V dc	01-05		45	nA
		V_{DD} and V_{CC} = 18 V dc	51-55			
	I_{IL}	V_{DD} and V_{CC} = 15 V dc	01-05		-45	nA
		V_{DD} and V_{CC} = 18 V dc	51-55			
Input test voltage	V_{ZAP}	C_1 = 100 pF, R_Z = 1.5 kΩ (see 4.5.3)	All	400		V

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T13:05Z
Check the source to verify that this is the current version before use.

TABLE III. Group A inspection for device types 51 and 53.

Symbol	MIL-STD-883 method	Cases E,F, N, and Z	For terminal conditions and limits see 1/																Measured terminal	Test limits						Unit
			1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16 2/		Subgroup 1 T_C = 25°C		Subgroup 2 T_C = 125°C		Subgroup 3 T_C = -55°C		
		Test no.	V_{CC}	Y1	A1	Y2	A2	Y3	A3	V_{SS}	A4	Y4	A5	Y5	NC	A6	Y6	V_{DD}		Min	Max	Min	Max	Min	Max	
$V_{IC(pos)}$	3/	1	GND		1 mA													GND	A1		1.5					Vdc
		2	"				1 mA											"	A2		"					
		3	"						1 mA									"	A3		"					
		4	"								1 mA							"	A4		"					
		5	"										1 mA					"	A5		"					
		6	"													1 mA		"	A6		"					
$V_{IC(neg)}$		7			-1 mA					GND									A1		-6					
		8					-1 mA			"									A2		"					
		9							-1 mA	"									A3		"					
		10								"	-1 mA								A4		"					
		11								"			-1 mA						A5		"					
		12								"						-1 mA			A6		"					
I_{SS}	3005 4/	13	18 V		18 V		18 V		18 V	"	18 V		18 V			18 V		18 V	V_{SS}		-75		-750			nAdc
I_{SS}	3005 4/	14	18 V		GND		GND		GND	"	GND		GND			GND		18 V	V_{SS}		-75		-750			nAdc
V_{OH5}	3006	15	15 V		GND													15 V	Y1	14.95		14.95		14.95		Vdc
		16	"				GND											"	Y2	"		"		"		
		17	"						GND									"	Y3	"		"		"		
		18	"								GND							"	Y4	"		"		"		
		19	"										GND					"	Y5	"		"		"		
		20	"													GND		"	Y6	"		"		"		
V_{OL5}	3007	21	15 V		15 V													"	Y1		0.05		0.05		0.05	
		22	"				15 V											"	Y2		"		"		"	
		23	"						15 V									"	Y3		"		"		"	
		24	"								15 V							"	Y4		"		"		"	
		25	"										15 V					"	Y5		"		"		"	
		26	"													15 V		"	Y6		"		"		"	
V_{IH1}		27	5 V		4.0 V		GND		GND	"	GND		GND			GND		5 V	Y1		0.5		0.5		0.5	
		28	"		GND		4.0 V		GND	"	"		"			"		"	Y2		"		"		"	
		29	"		"		GND		4.0 V	"	"		"			"		"	Y3		"		"		"	
		30	"		"		"		GND	"	4.0 V		"			"		"	Y4		"		"		"	
		31	"		"		"		"	"	GND		4.0 V			"		"	Y5		"		"		"	
		32	"		"		"		"	"	"		GND			4.0 V		"	Y6		"		"		"	
V_{IH2}		33	10 V		8.0 V		"		"	"	"		"			GND		10 V	Y1		1.0		1.0		1.0	
		34	"		GND		8.0 V		"	"	"		"			"		"	Y2		"		"		"	
		35	"		"		GND		8.0 V	"	"		"			"		"	Y3		"		"		"	
		36	"		"		"		GND	"	8.0 V		"			"		"	Y4		"		"		"	
		37	"		"		"		"	"	GND		8.0 V			"		"	Y5		"		"		"	
		38	"		"		"		"	"	"		GND			8.0 V		"	Y6		"		"		"	
V_{IH3}		39	15 V		12.5 V		GND		"	"	"		"			GND		15 V	Y1		1.5		1.5		1.5	
		40	"		GND		12.5 V		"	"	"		"			"		"	Y2		"		"		"	
		41	"		"		GND		12.5 V	"	"		"			"		"	Y3		"		"		"	
		42	"		"		"		GND	"	12.5 V		"			"		"	Y4		"		"		"	
		43	"		"		"		"	"	GND		12.5 V			"		"	Y5		"		"		"	
		44	"		"		"		"	"	"		GND			12.5 V		"	Y6		"		"		"	

See footnotes at end of device type 55.

Source: https://assist.dla.mil -- Downloaded: 20260-21T13:05Z
Check the source to verify that this is the current version before use.

TABLE III. Group A inspection for device types 51 and 53 - Continued.

Symbol	MIL-STD-883 method	Cases E,F, N, and Z	For terminal conditions and limits see 1/																Measured terminal	Test limits					Unit
			1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16 2/		Subgroup 1 T_C = 25°C		Subgroup 2 T_C = 125°C		Subgroup 3 T_C = -55°C	
		Test no.	V_{CC}	Y1	A1	Y2	A2	Y3	A3	V_{SS}	A4	Y4	A5	Y5	NC	A6	Y6	V_{DD}		Min	Max	Min	Max	Min	Max	
V_{IL1}		45	5 V		1.0 V		GND		GND	GND	GND		GND			GND		5 V	Y1	4.5		4.5		4.5		Vdc
		46	"		GND		1.0 V		GND	"	"		"			"		"	Y2	"		"		"		
		47	"		"		GND		1.0 V	"	1.0 V		"			"		"	Y3	"		"		"		
		48	"		"		"		GND	"	GND		1.0 V			"		"	Y4	"		"		"		
		49	"		"		"		"	"	"		GND			"		"	Y5	"		"		"		
		50	"		"		"		"	"	"		"			1.0 V		"	Y6	"		"		"		
V_{IL2}		51	10 V		2.0 V		"		"	"	"		"			GND		10 V	Y1	9.0		9.0		9.0		"
		52	"		GND		2.0 V		"	"	"		"			"		"	Y2	"		"		"		
		53	"		"		GND		2.0 V	"	2.0 V		"			"		"	Y3	"		"		"		
		54	"		"		"		GND	"	GND		2.0 V			"		"	Y4	"		"		"		
		55	"		"		"		"	"	"		GND			"		"	Y5	"		"		"		
		56	"		"		"		"	"	"		"			2.0 V		"	Y6	"		"		"		
V_{IL3}		57	15 V		2.5 V		"		"	"	"		"			GND		15 V	Y1	13.5		13.5		13.5		"
		58	"		GND		2.5 V		"	"	"		"			"		"	Y2	"		"		"		
		59	"		"		GND		2.5 V	"	2.5 V		"			"		"	Y3	"		"		"		
		60	"		"		"		GND	"	GND		2.5 V			"		"	Y4	"		"		"		
		61	"		"		"		"	"	"		GND			"		"	Y5	"		"		"		
		62	"		"		"		"	"	"		"			2.5 V		"	Y6	"		"		"		
I_{OL1}		63	5 V	0.4 V	5 V	0.4 V	"	0.4 V	"	"	"	0.4 V	"	0.4 V		GND		5 V	Y1	3.2		2.2		4.0		mA
		64	"		GND		5 V		5 V	"	"		"			"		"	Y2	"		"		"		
		65	"		"		GND		GND	"	5 V		"			"		"	Y3	"		"		"		
		66	"		"		"		"	"	GND		5 V			"		"	Y4	"		"		"		
		67	"		"		"		"	"	"		GND			"		"	Y5	"		"		"		
		68	"		"		"		"	"	"		"			5 V	0.4 V	"	Y6	"		"		"		
I_{OL2}		69	15 V	1.5 V	15 V	1.5 V	"	1.5 V	"	"	"	1.5 V	"	1.5 V		GND		15 V	Y1	24.0		17.0		30.0		"
		70	"		GND		15 V		15 V	"	"		"			"		"	Y2	"		"		"		
		71	"		"		GND		GND	"	15 V		"			"		"	Y3	"		"		"		
		72	"		"		"		"	"	GND		15 V			"		"	Y4	"		"		"		
		73	"		"		"		"	"	"		GND			"		"	Y5	"		"		"		
		74	"		"		"		"	"	"		"			15 V	1.5 V	"	Y6	"		"		"		
I_{OH1}		75	5 V	4.6 V	"	4.6 V	"	4.6 V	"	"	"	4.6 V	"	4.6 V		GND		5 V	Y1	-0.51		-0.36		-0.64		mA
		76	"		"		"		"	"	"		"			"		"	Y2	"		"		"		
		77	"		"		"		"	"	"		"			"		"	Y3	"		"		"		
		78	"		"		"		"	"	"		"			"		"	Y4	"		"		"		
		79	"		"		"		"	"	"		"			"		"	Y5	"		"		"		
		80	"		"		"		"	"	"		"			"	4.6 V	"	Y6	"		"		"		
I_{OH2}		81	15 V	13.5 V	"	13.5 V	"	13.5 V	"	"	"	13.5 V	"	13.5 V		"		15 V	Y1	-3.4		-2.4		-4.2		"
		82	"		"		"		"	"	"		"			"		"	Y2	"		"		"		
		83	"		"		"		"	"	"		"			"		"	Y3	"		"		"		
		84	"		"		"		"	"	"		"			"		"	Y4	"		"		"		
		85	"		"		"		"	"	"		"			"		"	Y5	"		"		"		
		86	"		"		"		"	"	"		"			"	13.5 V	"	Y6	"		"		"		
I_{IN1} 5/	3010	87	18 V		18 V		18 V		18 V	"	18 V		18 V			18 V		18 V	All inputs together		6					nA

See f es at end of device type 55.

Source: https://assist.dla.mil -- Downloaded: 20260-21T13:05Z
Check the source to verify that this is the current version before use.

TABLE III. Group A inspection for device types 52 and 54.

Symbol	MIL-STD-883 method	Cases E,F, N, and Z	For terminal conditions and limits see 1/																Measured terminal	Test limits						Unit
			1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16 2/		Subgroup 1 T_C = 25°C		Subgroup 2 T_C = 125°C		Subgroup 3 T_C = -55°C		
		Test no.	V_{CC}	Y1	A1	Y2	A2	Y3	A3	V_{SS}	A4	Y4	A5	Y5	NC	A6	Y6	V_{DD}		Min	Max	Min	Max	Min	Max	
$V_{IC(pos)}$	3/	1	GND		1 mA		1 mA		1 mA									GND	A1		1.5					Vdc
		2	"								1 mA							"	A2		"					
		3	"										1 mA					"	A3		"					
		4	"													1 mA		"	A4		"					
		5	"															"	A5		"					
		6	"															"	A6		"					
$V_{IC(neg)}$		7			-1 mA		-1 mA		-1 mA	GND									A1		-6					
		8								"	-1 mA								A2		"					
		9								"			-1 mA						A3		"					
		10								"						-1 mA			A4		"					
		11								"									A5		"					
		12								"									A6		"					
I_{SS}	3005 4/	13	18 V		18 V		18 V		18 V	"	18 V		18 V			18 V		18 V	V_{SS}		-75		-750			nAdc
I_{SS}	3005 5/	14	18 V		GND		GND		GND	"	GND		GND			GND		18 V	V_{SS}		-75		-750			nAdc
V_{OH5}	3006	15	15 V		15 V		15 V		15 V	"	15 V		15 V			15 Y		15 V	Y1	14.95		14.95		14.95		Vdc
		16	"							"								"	Y2	"		"		"		
		17	"							"								"	Y3	"		"		"		
		18	"							"								"	Y4	"		"		"		
		19	"							"								"	Y5	"		"		"		
		20	"							"								"	Y6	"		"		"		
V_{OL5}	3007	21	15 V		GND		GND		GND	"	GND		GND			GND		"	Y1		0.05		0.05		0.05	
		22	"							"								"	Y2		"		"		"	
		23	"							"								"	Y3		"		"		"	
		24	"							"								"	Y4		"		"		"	
		25	"							"								"	Y5		"		"		"	
		26	"							"								"	Y6		"		"		"	
V_{IH1}		27	5 V		3.5 V		GND		GND	"	GND		GND			GND		5 V	Y1	4.5		4.5		4.5		
		28	"		GND		3.5 V		GND	"	"		"			"		"	Y2	"		"		"		
		29	"		"		GND		3.5 V	"	3.5 V		"			"		"	Y3	"		"		"		
		30	"		"		"		GND	"	GND		3.5 V			"		"	Y4	"		"		"		
		31	"		"		"		"	"	"		GND			"		"	Y5	"		"		"		
		32	"		"		"		"	"	"		"			3.5 V		"	Y6	"		"		"		
V_{IH2}		33	10 V		7 V		"		"	"	"		"			GND		10 V	Y1	9.0		9.0		9.0		
		34	"		GND		7 V		7 V	"	"		"			"		"	Y2	"		"		"		
		35	"		"		GND		GND	"	7 V		"			"		"	Y3	"		"		"		
		36	"		"		"		"	"	GND		7 V			"		"	Y4	"		"		"		
		37	"		"		"		"	"	"		GND			"		"	Y5	"		"		"		
		38	"		"		"		"	"	"		"			7 V		"	Y6	"		"		"		
V_{IH3}		39	15 V		11 V		GND		"	"	"		"			GND		15 V	Y1	13.5		13.5		13.5		
		40	"		GND		11 V		11 V	"	"		"			"		"	Y2	"		"		"		
		41	"		"		GND		GND	"	11 V		"			"		"	Y3	"		"		"		
		42	"		"		"		"	"	GND		11 V			"		"	Y4	"		"		"		
		43	"		"		"		"	"	GND		GND			"		"	Y5	"		"		"		
		44	"		"		"		"	"	"		"			11 V		"	Y6	"		"		"		

See footnotes at end of device type 55.

Supersedes page 29 of MIL-M-38510/55?
dated 30 April 1984
Source: https://assist.dla.mil -- Downloaded: 2026-10-21T13:05Z
Check the source to verify that this is the current version before use.

TABLE III. Group A inspection for device types 52 and 54 - Continued.

Symbol	MIL-STD-883 method	Cases E,F, N, and Z	For terminal conditions and limits see 1/																Measured terminal	Test limits						Unit
			1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16 2/		Subgroup 1 T_C = 25°C		Subgroup 2 T_C = 125°C		Subgroup 3 T_C = -55°C		
		Test no.	V_{CC}	Y1	A1	Y2	A2	Y3	A3	V_{SS}	A4	Y4	A5	Y5	NC	A6	Y6	V_{DD}		Min	Max	Min	Max	Min	Max	
V_{IL1}		45	5 V		1.5 V		GND		GND	GND	GND		GND			GND		5 V	Y1		0.5		0.5		0.5	Vdc
		46	"		GND		1.5 V		GND	"	"		"			"		"	Y2		"		"		"	
		47	"		"		GND		1.5 V	"	"		"			"		"	Y3		"		"		"	
		48	"		"		"		GND	"	1.5 V		"			"		"	Y4		"		"		"	
		49	"		"		"		"	"	GND		1.5 V			"		"	Y5		"		"		"	
		50	"		"		"		"	"	"		GND			1.5 V		"	Y6		"		"		"	
V_{IL2}		51	10 V		3 V		"		"	"	"		"			GND		10 V	Y1		1.0		1.0		1.0	"
		52	"		GND		3 V		"	"	"		"			"		"	Y2		"		"		"	
		53	"		"		GND		3 V	"	"		"			"		"	Y3		"		"		"	
		54	"		"		"		GND	"	3 V		"			"		"	Y4		"		"		"	
		55	"		"		"		"	"	GND		3 V			"		"	Y5		"		"		"	
		56	"		"		"		"	"	"		GND			3 V		"	Y6		"		"		"	
V_{IL3}		57	15 V		4 V		"		"	"	"		"			GND		15 V	Y1		1.5		1.5		1.5	"
		58	"		GND		4 V		"	"	"		"			"		"	Y2		"		"		"	
		59	"		"		GND		4 V	"	"		"			"		"	Y3		"		"		"	
		60	"		"		"		GND	"	4 V		"			"		"	Y4		"		"		"	
		61	"		"		"		"	"	GND		4 V			"		"	Y5		"		"		"	
		62	"		"		"		"	"	"		GND			4 V		"	Y6		"		"		"	
I_{OL1}		63	5 V	0.4 V	"		"		"	"	"		"			GND		5 V	Y1	3.2		2.2		4.0		mA
		64	"	"	"	0.4 V	"		"	"	"		"			"		"	Y2	"		"		"		
		65	"	"	"	"	"	0.4 V	"	"	"		"			"		"	Y3	"		"		"		
		66	"	"	"	"	"	"	"	"	"	0.4 V	"			"		"	Y4	"		"		"		
		67	"	"	"	"	"	"	"	"	"	"	"	0.4 V		"		"	Y5	"		"		"		
		68	"	"	"	"	"	"	"	"	"	"	"	"		"	0.4 V	"	Y6	"		"		"		
I_{OL2}		69	15 V	1.5 V	"		"		"	"	"		"			"		15 V	Y1	24.0		17.0		30.0		"
		70	"	"	"	1.5 V	"		"	"	"		"			"		"	Y2	"		"		"		
		71	"	"	"	"	"	1.5 V	"	"	"		"			"		"	Y3	"		"		"		
		72	"	"	"	"	"	"	"	"	"	1.5 V	"			"		"	Y4	"		"		"		
		73	"	"	"	"	"	"	"	"	"	"	"	1.5 V		"		"	Y5	"		"		"		
		74	"	"	"	"	"	"	"	"	"	"	"	"		"	1.5 V	"	Y6	"		"		"		
I_{OH1}		75	5 V	4.6 V	5 V		"		"	"	"		"			"		5 V	Y1	-0.51		-0.36		-0.64		"
		76	"	"	GND	4.6 V	5 V		"	"	"		"			"		"	Y2	"		"		"		
		77	"	"	"	"	GND	4.6 V	5 V	"	"		"			"		"	Y3	"		"		"		
		78	"	"	"	"	"	"	GND	"	5 V	4.6 V	"			"		"	Y4	"		"		"		
		79	"	"	"	"	"	"	"	"	GND	"	5 V	4.6 V		"		"	Y5	"		"		"		
		80	"	"	"	"	"	"	"	"	"	"	GND	"		5 V	4.6 V	"	Y6	"		"		"		
I_{OH2}		81	15 V	13.5 V	15 V		"		"	"	"		"			GND		15 V	Y1	-3.4		-2.4		-4.2		"
		82	"	"	GND	13.5 V	15 V		"	"	"		"			"		"	Y2	"		"		"		
		83	"	"	"	"	GND	13.5 V	15 V	"	"		"			"		"	Y3	"		"		"		
		84	"	"	"	"	"	"	GND	"	15 V	13.5 V	"			"		"	Y4	"		"		"		
		85	"	"	"	"	"	"	"	"	GND	"	15 V	13.5 V		"		"	Y5	"		"		"		
		86	"	"	"	"	"	"	"	"	GND	"	GND	"		15 V	13.5 V	"	Y6	"		"		"		
I_{IH1} 5/	3010	87	18 V		18 V		18 V		18 V	"	18 V		18 V			18 V		18 V	All inputs together		6					nA

See foo at end of device type 55.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T13:05Z
Check the source to verify that this is the current version before use.

TABLE III. Group A inspection for device type 55.

Symbol	MIL-STD-883 method	Cases A,C,D,T,X, and Y	For terminal conditions and limits see 1/														Measured terminal	Test Limits						Unit
			1	2	3	4	5	6	7	8	9	10	11	12	13	14		Subgroup 1 T_C = 25°C		Subgroup 2 T_C = 125°C		Subgroup 3 T_C = -55°C		
		Test no.	Y1	$\overline{Y1}$	A1	Y2	$\overline{Y2}$	A2	V_{SS}	Y3	$\overline{Y3}$	A3	Y4	$\overline{Y4}$	A4	V_{DD}		Min	Max	Min	Max	Min	Max	
$V_{IC(pos)}$		1 2 3 4			1 mA			1 mA				1 mA			1 mA	GND " " "	A1 A2 A3 A4		1.5 " " "					Vdc " " "
$V_{IC(neg)}$		5 6 7 8			-1 mA			-1 mA	GND " "			-1 mA			-1 mA		A1 A2 A3 A4		-6 " " "					" " " "
I_{SS} I_{SS}	3005 4/ 3005 5/	9 10			15 V GND			15 V GND	"			15 V GND			15 V GND	15 V "	V_{SS} V_{SS}		-75 -75		-750 -750			nA nA
V_{OH5}	3006	11 12 13 14 15 16 17 18			15 V GND			15 V GND	"			15 V GND			15 V GND	"	Y1 Y2 Y3 Y4 $\overline{Y1}$ $\overline{Y2}$ $\overline{Y3}$ $\overline{Y4}$	14.95		14.95		14.95		Vdc
V_{OL5}	3007	19 20 21 22 23 24 25 26			GND 15 V			GND 15 V	"			GND 15 V			GND 15 V	"	Y1 Y2 Y3 Y4 $\overline{Y1}$ $\overline{Y2}$ $\overline{Y3}$ $\overline{Y4}$		0.05		0.05		0.05	
V_{IH1}		27 28 29 30 31 32 33 34			3.5 V GND " " 3.5 V GND " "			GND 3.5 V GND " " 3.5 V GND GND	"			GND GND 3.5 V GND " " 3.5 V GND			GND " " 3.5 V GND " " 3.5 V	5 V " " " " " " "	Y1 Y2 Y3 Y4 $\overline{Y1}$ $\overline{Y2}$ $\overline{Y3}$ $\overline{Y4}$	4.5 " "	0.5 " "	4.5 " "	0.5 " "	4.5 " "	0.5 " "	
V_{IH2}		35 36 37 38 39 40 41 42			7 V GND " " 7 V GND " "			GND 7 V GND " " 7 V GND GND	"			" " 7 V GND " " 7 V GND			GND " " 7 V GND " " 7 V	10 V " " " " " " "	Y1 Y2 Y3 Y4 $\overline{Y1}$ $\overline{Y2}$ $\overline{Y3}$ $\overline{Y4}$	9.0 " "	1.0 " "	9.0 " "	1.0 " "	9.0 " "	1.0 " "	

See footnotes at end of device type 55.

Source: https://assist.dla.mil -- Downloaded: 20260-21T13:05Z
Check the source to verify that this is the current version before use.

TABLE III. Group A inspection for device type 55 - Continued.

Symbol	MIL-STD-883 method	Cases A,C,D, T,X, and Y	Test no.	For terminal conditions and limits see 1/														Measured terminal	Test limits						Unit
				1	2	3	4	5	6	7	8	9	10	11	12	13	14		Subgroup 1 T_C = 25°C		Subgroup 2 T_C = 125°C		Subgroup 3 T_C = -55°C		
																			Min	Max	Min	Max	Min	Max	
V_{IH3}		43		Y1	Y1	11 V	Y2	Y2	GND	GND	Y3	Y3	GND	Y4	Y4	GND	V_{DD}	Y1	13.5		13.5		13.5		Vdc
		44				GND			11 V				GND			GND		Y2							
		45				-			-				11 V			-		Y3							
		46				-			-				GND			11 V		Y4				1.5			
		47				11 V			-				-			GND		Y1		1.5	1.5				
		48				GND			11 V				-			-		Y2							
		49				-			GND				11 V			11 V		Y3							
		50				-			-				GND			-		Y4							
V_{IL1}		51		Y1	Y1	1.5 V	Y2	Y2	-	GND	Y3	Y3	-	Y4	Y4	GND	V_{DD}	Y1	0.5		0.5		0.5		V
		52				GND			1.5 V				GND			GND		Y2							
		53				-			-				1.5 V			-		Y3							
		54				-			-				GND			1.5 V		Y4				1.5			
		55				1.5 V			-				-			GND		Y1		1.5	1.5				
		56				GND			1.5 V				-			-		Y2							
		57				-			GND				1.5 V			-		Y3							
		58				-			-				GND			1.5 V		Y4							
V_{IL2}		59		Y1	Y1	3 V	Y2	Y2	-	GND	Y3	Y3	-	Y4	Y4	GND	V_{DD}	Y1	1.0		1.0		1.0		V
		60				GND			3 V				GND			GND		Y2							
		61				-			-				3 V			-		Y3							
		62				-			-				GND			3 V		Y4				9.0			
		63				3 V			-				-			GND		Y1		9.0	9.0				
		64				GND			3 V				-			-		Y2							
		65				-			GND				3 V			-		Y3							
		66				-			-				GND			3 V		Y4							
V_{IL3}		67		Y1	Y1	4 V	Y2	Y2	-	GND	Y3	Y3	-	Y4	Y4	GND	V_{DD}	Y1	1.5		1.5		1.5		V
		68				GND			4 V				GND			GND		Y2							
		69				-			-				4 V			-		Y3							
		70				-			-				GND			4 V		Y4				13.5			
		71				4 V			-				-			GND		Y1		13.5	13.5				
		72				GND			4 V				-			-		Y2							
		73				-			GND				4 V			-		Y3							
		74				-			-				GND			4 V		Y4							
I_{OL1}		75		0.4 V	0.4 V	-	0.4 V	0.4 V	-	-	0.4 V	0.4 V	-	0.4 V	0.4 V	-	5 V	Y1	1.6		1.2		2.1		mA
		76				-			-				-			GND		Y2							
		77				-			-				-			-		Y3							
		78				5 V			5 V				-			-		Y4				1.0			
		79			0.4 V	GND		0.4 V	GND			0.4 V	-		0.4 V	-		Y1		0.8	0.55		1.0		
		80				-			-				5 V			GND		Y2							
		81				-			-				GND			5 V		Y3							
		82				-			-				5 V			GND		Y4							
I_{OL2}		83		1.5 V	1.5 V	-	1.5 V	1.5 V	-	-	1.5 V	1.5 V	-	1.5 V	1.5 V	-	15 V	Y1	12.0		8.0		14.0		mA
		84				-			-				-			GND		Y2							
		85				-			-				-			-		Y3							
		86				-			-				-			-		Y4				5.5			
		87			1.5 V	15 V		1.5 V	15 V			1.5 V	15 V		1.5 V	15 V		Y1	4.5		3.0				
		88				GND			GND				GND			GND		Y2							
		89				-			GND				-			-		Y3							
		90				-			-				-			-		Y4							

See footnotes at end of device type 55.

Source: https://assist.dla.mil -- Downloaded: 202610-21T13:05Z
Check the source to verify that this is the current version before use.

TABLE III. Group A inspection for device type 55 - Continued.

Symbol	MIL-STD-883 method	Cases A,C,D, T,X, and Y	For terminal conditions and limits see 1/														Measured terminal	Test Limits						Unit
			1	2	3	4	5	6	7	8	9	10	11	12	13	14		Subgroup 1 T_C = 25°C		Subgroup 2 T_C = 125°C		Subgroup 3 T_C = -55°C		
		Test no.	Y1	Y1	A1	Y2	Y2	A2	V_{SS}	Y3	Y3	A3	Y4	Y4	A4	V_{DD}		Min	Max	Min	Max	Min	Max	
I_{OH1}		91	4.6 V		5 V			GND	GND			GND			GND	5 V	Y1	-1.4		-1.0		-1.75		nA
		92			GND	4.6 V		5 V	"			GND			"	"	Y2	"		"		"		"
		93			"			"	"	4.6 V		5 V			"	"	Y3	"		"		"		"
		94			"			"	"			GND	4.6 V		5 V	"	Y4	"		"		"		"
		95		4.6 V	"			"	"			"			GND	"	Y1	-0.6		-0.4		-0.75		"
		96			"		4.6 V	GND	"			"			"	"	Y2	"		"		"		"
		97			"			"	"		4.6 V	"			"	"	Y3	"		"		"		"
		98			"			"	"			"		4.6 V	"	"	Y4	"		"		"		"
I_{OH2}		99	13.5 V		15 V			"	"			"			"	15 V	Y1	-9.0		-6.0		-11.0		"
		100			GND	13.5 V		15 V	"			"			"	"	Y2	"		"		"		"
		101			"			GND	"	13.5 V		15 V			"	"	Y3	"		"		"		"
		102			"			"	"			GND	13.5 V		15 V	"	Y4	"		"		"		"
		103		13.5 V	"			"	"			"			GND	"	Y1	-4.0		-2.7		-4.8		"
		104			"		13.5 V	"	"			"			"	"	Y2	"		"		"		"
		105			"			"	"		13.5 V	"			"	"	Y3	"		"		"		"
		106			"			"	"			"		13.5 V	"	"	Y4	"		"		"		"
I_{IH1} 5/	3010	107			18 V			18 V	"			18 V			18 V	18 V	All inputs together		4					nA
I_{IH2}	"	108			18 V			GND	"			GND			GND	"	A1		1		45			"
		109			GND			18 V	"			GND			"	"	A2		"		"			"
		110			"			GND	"			18 V			"	"	A3		"		"			"
		111			"			"	"			GND			18 V	"	A4		"		"			"
I_{IL1} 5/	3009	112			"			"	"			GND			GND	"	All inputs together		-4					"
I_{IL2}	"	113			GND			18 V	"			18 V			18 V	"	A1		-1		-45			"
		114			18 V			GND	"			18 V			"	"	A2		"		"			"
		115			"			18 V	"			GND			"	"	A3		"		"			"
		116			"			18 V	"			18 V			GND	"	A4		"		"			"
																		Subgroup 4 T_C = 25°C						
																		Min	Max					
C_I	3012	117			A 6/			A 6/	GND							GND	A1		12					pF
	"	118							"							"	A2		"					"
	"	119							"			A 6/				"	A3		"					"
	"	120							"						A 6/	"	A4		"					"

See footnotes at end of device type 55.

https://assist.dla.mil -- Downloaded: 20260-21T13:05Z
Check the source to verify that this is the current version before use.

TABLE III. Group A inspection for device type 55 - Continued.

Symbol	MIL-STD-883 method	Cases A,C,D, T,X, and Y	For terminal conditions and limits see 1/														Measured terminal	Test limits						Unit
			1	2	3	4	5	6	7	8	9	10	11	12	13	14		Subgroup 9 T_C = 25°C		Subgroup 10 T_C = 125°C		Subgroup 11 T_C = -55°C		
		Test no.	Y1	$\overline{Y1}$	A1	Y2	$\overline{Y2}$	A2	V_{SS}	Y3	$\overline{Y3}$	A3	Y4	$\overline{Y4}$	A4	V_{DD}		Min	Max	Min	Max	Min	Max	
t_{PHL}	3003 Fig. 5	121	OUT		IN				GND							5.0 V	A1 to Y1	6	115	9	172	6	115	ns
		122				OUT		IN	"							"	A2 to Y2	"	"	"	"	"	"	
		123							"	OUT		IN				"	A3 to Y3	"	"	"	"	"	"	
		124							"				OUT		IN	"	A4 to Y4	"	"	"	"	"	"	
		125		OUT	IN				"							"	A1 to $\overline{Y1}$	"	"	"	"	"	"	
		126					OUT	IN	"							"	A2 to $\overline{Y2}$	"	"	"	"	"	"	
		127							"		OUT	IN				"	A3 to $\overline{Y3}$	"	"	"	"	"	"	
		128							"					OUT	IN	"	A4 to $\overline{Y4}$	"	"	"	"	"	"	
t_{PLH}		129	OUT		IN				"							"	A1 to Y1	"	125	"	188	"	125	"
		130				OUT		IN	"							"	A2 to Y2	"	"	"	"	"	"	
		131							"	OUT		IN				"	A3 to Y3	"	"	"	"	"	"	
		132							"				OUT		IN	"	A4 to Y4	"	"	"	"	"	"	
		133		OUT	IN				"							"	A1 to $\overline{Y1}$	"	110	"	165	"	110	
		134					OUT	IN	"							"	A2 to $\overline{Y2}$	"	"	"	"	"	"	
		135							"		OUT	IN				"	A3 to $\overline{Y3}$	"	"	"	"	"	"	
		136							"					OUT	IN	"	A4 to $\overline{Y4}$	"	"	"	"	"	"	
t_{THL}	3004 Fig. 5	137	OUT		IN				"							"	A1 to Y1	"	50	"	75	"	50	"
		138				OUT		IN	"							"	A2 to Y2	"	"	"	"	"	"	
		139							"	OUT		IN				"	A3 to Y3	"	"	"	"	"	"	
		140							"				OUT		IN	"	A4 to Y4	"	"	"	"	"	"	
		141		OUT	IN				"							"	A1 to $\overline{Y1}$	"	110	"	165	"	110	
		142					OUT	IN	"							"	A2 to $\overline{Y2}$	"	"	"	"	"	"	
		143							"		OUT	IN				"	A3 to $\overline{Y3}$	"	"	"	"	"	"	
		144							"					OUT	IN	"	A4 to $\overline{Y4}$	"	"	"	"	"	"	
t_{TLH}		145	OUT		IN				"							"	A1 to Y1	"	70	"	105	"	70	"
		146				OUT		IN	"							"	A2 to Y2	"	"	"	"	"	"	
		147							"	OUT		IN				"	A3 to Y3	"	"	"	"	"	"	
		148							"				OUT		IN	"	A4 to Y4	"	"	"	"	"	"	
		149		OUT	IN				"							"	A1 to $\overline{Y1}$	"	120	"	180	"	120	
		150					OUT	IN	"							"	A2 to $\overline{Y2}$	"	"	"	"	"	"	
		151							"		OUT	IN				"	A3 to $\overline{Y3}$	"	"	"	"	"	"	
		152							"					OUT	IN	"	A4 to $\overline{Y4}$	"	"	"	"	"	"	

1/ Input pins not designated may be tied to V_{CC} or GND or may be left open provided they do not influence the outcome of the measurement. Output pins not designated may be tied to the loads or may be left open provided they do not influence the outcome of the measurement.

2/ Terminal 16 is not connected for device types 53 and 54.

3/ Test parameter $V_{IC(pos)}$ does not apply to device types 53 and 54.

4/ When performing quiescent supply current measurements (I_{SS}), the meter shall be placed so that all currents flow through the meter.

5/ The device manufacturer may, at his option, measure I_{IL} and I_{IH} at 25°C for each individual input or measure all inputs together.

6/ (A) Capacitance bridge between measured terminal and V_{SS}; frequency = 1 MHz.

7/ Test limits t_{PHL}, t_{PLH}, t_{THL}, and t_{TLH} for device types 51/53 and 52/54 consists of two sets of values and are expressed XXX/XXXX in the limits columns. The digits preceding the slash apply to the first device in a set.

Source: https://assist.dla.mil -- Downloaded: 20260-21T13:05Z
Check the source to verify that this is the current version before use.