INCH-POUND

MIL-C-50446A(AR)
AMENDMENT 3
17 October 1996
SUPERSEDING
AMENDMENT 2
04 November 1993

MILITARY SPECIFICATION

CASE, CARTRIDGE, 40MM, M118
OR PARTS

This amendment forms a part of MIL-P-50446A(AR) dated 27 July 1981, and is approved for use by the US Army Armament, Research, Development and Engineering Center and is available for use by all the Department and Agencies of the Department of Defense.

PAGE 2

* 2.2 Add: "ASTM E 8-94 Tension Testing of Metallic Materials, Methods of"

PAGE 3

* 4.3.1 Under "Part description", "Drawings" and "Quantity" add the following in the applicable:

"Tensile Specimen 9202576 6"

PAGE 4

Table I, under cartridge case, add:

"Tensile properties 6 4.5.5"

PAGE 6

Delete "MIL-C-50466A(AR)" and substitute MIL-C-50446A(AR)"

PAGE 7

Delete "MIL-C-50466A(AR)" and substitute "MIL-C-50446A(AR)"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:25Z
Check the source to verify that this is the current version before use.

4.4.2.1, Major 116, Delete in its entirety and substitute:

"116.	Parallelism of open end to base	0.40%	3.2	Gage"

4.4.2.1, Major 123 under inspection method add: "See Note a"

Add: Under notes:

"Note a - Case must fall freely without any force into the applicable gage."

* 4.4.2.1 Add Major 126 as follows:

"126.	Tensile Properties	6	0 - 1	3.2	4.5.5"

PAGE 8

Delete "MIL-C-50466A(AR)" and substitute "MIL-C-50446A (AR)"

PAGE 10

4.5.3, Delete "This test shall be conducted for 68 hours. . ." and substitue "This test shall be conducted for 72 hours. . ."

* Add the following paragraph:

"4.5.5 Tensile properties of cartridge case. The shape of the specimen for determining tensile strength shall be as specified on equipment Dwg. 9202576. The specimen shall be taken from each heat treat batch prior to trimming and anodizing from a 3/4 inch wide hoop, 1/2 inch in from the mouth of the cartridge case. The hoop shall be split, unrolled and cut to the required shape. The test shall be conducted in accordance with ASTM E 8. Each specimen must exhibit a minimum tensile strength of 50,000 p.s.i. and a minimum yield strength of 45,000 p.s.i.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:25Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1310-0579)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:25Z
Check the source to verify that this is the current version before use.