
INCH-POUND

MIL-DTL-3933/28
22 December 2004

ATTENUATORS, FIXED, COAXIAL LINE (SMP CONNECTORS - SMP FULL DETENT MALE TO SMP FULL DETENT MALE), 0 dB, FREQUENCY RANGE: DC TO 18 GHZ

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-3933.



NOTES:
1. Dimensions are in inches.
2. Metric equivalents, in parentheses are given for general information only.
3. Unless otherwise specified:
   a. All dimensions are after plating.
   b. Break corners and edges .005 R maximum.
   c. Chamfer first and last threads.
   d. Surface roughness 63 ✓ .
   e. Remove all burrs.
   f. Diameters on common centers to be concentric within .005 T. I. R.
4. Tolerances: Decimals:± .030 (0.76 mm) for one decimal point, ± .015 (0.38 mm) for two decimal points and ± .005 (0.13 mm) for three decimal points.
5. SMP connector interfaces (both ends of attenuator) shall be in accordance with MIL-STD-348, Figure 326-2.

FIGURE 1. Dimensions and configurations for PIN M3933/28-1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:34Z
Check the source to verify that this is the current version before use.

ENGINEERING DATA:

Attenuators for use in general field equipment.

Materials:

Bodies and sleeves: Stainless steel in accordance with AMS-5640, UNS 530300, type I.

Contact: Beryllium copper in accordance with ASTM-B196/B196M, condition TD04, Alloy UNS-C17300.

Insulators: Teflon in accordance with ASTM-D1710.

Finishes:

Bodies and sleeves: Passivate in accordance with AMS-QQ-P-35C, type II.

Contact: Gold in accordance with ASTM-B488, type II, grade C, class I.27 over nickel plate in accordance with AMS-QQ-N-290, class I.

Operating frequency range: DC to 18 gigahertz (GHz).

Operating temperature range: -55°C to +100°C.

Maximum weight: 0.16 ounce.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Nominal impedance: 50 ohms.

Attenuation: 0 dB to 0.75 dB. Stability and sensitivity:

Maximum change in attenuation after:	**Attenuation change maximum (dB)**
Temperature change or thermal shock	0.5
Vibration or shock	0.5
Moisture resistance or salt spray	0.5
Peak power	0.5

Power: Maximum power output

AV (W) at 25°C (continuously) - 0.5 watt.

Peak (W) - 50 watt (Duty cycle 5 x 10^{-4} ; maximum pulse duration of 5 μsec).

Power sensitivity of attenuation, maximum: 0.005 dB/dB/Watt.
Temperature sensitivity of attenuation, maximum: 0.0006 dB/dB/°C.

VSWR:

DC to 4 GHz: 1.20:1 maximum.
4 to 12 GHz: 1.35:1 maximum.
12 to 18 GHz: 1.50:1 maximum.

Part or Identifying Number (PIN): M3933/28-01.

Connector repeatability, maximum variation in attenuation: 0.02 dB.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:34Z
Check the source to verify that this is the current version before use.

Referenced documents. In addition to MIL-DTL-3933, this document references the following:

AMS-5640
ASTM-B196/B196M
AMS-QQ-P-35
ASTM-D1710
AMS-QQ-N-290
MIL-STD-348
ASTM-B488

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5985-1321)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:34Z
Check the source to verify that this is the current version before use.