INCH-POUND

MIL-DTL-3933/32
w/AMENDMENT 1
12 April 2021
SUPERSEDING
MIL-DTL-3933/32
10 August 2010

DETAIL SPECIFICATION SHEET


ATTENUATORS, FIXED COAXIAL CONNECTOR SPACE LEVEL, NON SPACE LEVEL

TYPE 2.92 mm (SMK)

FREQUENCY RANGE: DC TO 42 GHz, CLASS III, LOW POWER

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-3933.



NOTES:
1. Dimension A, 1.50 ± 0.02 (38 ± 0.5).
2. Dimensions are in inches.
3. Metric equivalents are given in parentheses for general information only.

FIGURE 1. Dimensions and configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:34Z
Check the source to verify that this is the current version before use.

ENGINEERING DATA:

Operating frequency range: DC to 42 gigahertz (GHz) (see table I).

Test frequency range for SWR and attenuation measurements, measured or recorded, when using an Automatic Network Analyzer (ANA) or equivalent test equipment: 100 MHz (or lower) to 42 GHz.

Basic test frequency for sensitive measurements like temperature sensitivity, power sensitivity, and any other measurements where a 'delta' specification is imposed: 21 GHz.

Operating temperature range: -55 °C to +100 °C.

Weight: 0.30 ounces (8 g) maximum.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Nominal impedance: 50 ohms.

Attenuation: See table I. Stability and sensitivity:

Maximum attenuation change after:	Up to 10 dB, inclusive (dB)	Over 10 dB (dB/dB)
Temperature change/ thermal shock	0.05	0.005
Vibration or shock	0.1	0.01
Moisture resistance or salt spray	0.2	0.02
Peak power	0.05	0.005

Temperature sensitivity of attenuation, maximum: 0.0004 dB/dB/°C.

Power: See table I.

Power sensitivity for full input power, maximum: 0.004 dB/dB/Watt.

VSWR: See table I.

Part or Identifying Number (PIN): M3933/32- (and dash number from table I with three device level designators are space level (T), screened (S) and non-screened (N) options).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:34Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical characteristics.

Dash number		Attenuation (dB)			Maximum power Input		VSWR maximum 1/		Dimension A in inches (mm) ±0.02 (0.5)
		Nominal	Deviation						
			DC to 26.5 GHz	26.5 to 42 GH	AV (W) at 25°C 2/ (continuously)	Peak 3/ (kW)	DC to 26.5 GHz	26.5 to 42 GHz	
01	N S T	3	± 0.50	± 1.00	2	0.2	1.25:1	1.45:1	1.50 (38)
02	N S T	6	± 0.50	± 1.00	2	0.2	1.25:1	1.45:1	1.50 (38)
03	N S T	10	± 0.8	± 1.5	2	0.2	1.25:1	1.45:1	1.50 (38)
04	N S T	20	± 0.8	± 1.5	2	0.2	1.25:1	1.45:1	1.50 (38)
05	N S T	30	± 0.8	± 1.5	2	0.2	1.25:1	1.45:1	1.50 (38)

1/ VSWR value is for both ends.
2/ Power rating derated linearly to 0.2 watts at 100°C.
3/ Peak power : 200 watts at 5 x 10^{-4} duty cycle, 5 microseconds pulsewidth.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:34Z
Check the source to verify that this is the current version before use.

Referenced documents. This specification sheet only references MIL-DTL-3933.

Amendment notations. The margins of this specification sheet are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5985-2021-006)

Review activities:
Army - MI
Navy - AS, MC, SH

Civil agencies:
NASA - NA

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:34Z
Check the source to verify that this is the current version before use.