NOT MEASUREMENT SENSITIVE


MIL-D-3943/2D
24 June 1994
SUPERSEDING
MIL-D-3943/2C
7 August 1991


MILITARY SPECIFICATION SHEET

DECORATION, MEDAL OF HONOR, NAVY

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-D-3943.


OBVERSE


REVERSE

MATERIAL: Red Brass

FINISH: Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 4.

DIMENSIONS:
PENDANT:
HEIGHT (Overall): 2 inches (5.08 cm) (REF)
WIDTH (Overall): 2-1/16 inches (5.24 cm) (REF)
THICKNESS (At Thickest Point): 0.150 inch ± 0.010 inch (0.381 cm ± 0.025 cm)

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:39Z
Check the source to verify that this is the current version before use.

SUSPENSION (ANCHOR) BAR:
HEIGHT (Overall): 23/32 inch (1.83 cm) (REF)
WIDTH (Overall): 23/32 inch (1.83 cm) (REF)
THICKNESS (At Thickest Point): 0.115 inch ± 0.010 inch (0.292 cm ± 0.025 cm)

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Jump rings shall be fabricated from 0.040 inch ± 0.002 inch (0.101 cm ± 0.005 cm) nominal diameter wire with the same material and finish as the pendant. The rings shall be oval, 3/16 inch ± 1/64 inch (0.48 cm ± 0.04 cm) by 5/16 inch ± 1/64 inch (0.79 cm ± 0.04 cm) and shall be hard soldered closed with the ends in line.

3. Jump ring closure shall be located on the reverse side of the pendant.

4. Two holes, 0.065 inch ± 0.005 inch (0.165 cm ± 0.012 cm) in diameter, shall be drilled through the pendant. The holes shall be located 1/4 inch (0.64 cm) in from and 1/4 inch (0.64 cm) below the tip of the star points.

5. The neck ribbon, shield and attaching device shall be fabricated as shown on Figures 2 and 3 of the basic specification.

6. Decoration set shall consist of a neck ribbon with shield and pendant, regular size medal, a service ribbon and a rosette all packaged in a presentation case conforming to MIL-C-14633, Type I, Style 4 with a Type I, Class 1 or 1A pad.

7. The ribbon for the pendant drape and service ribbon shall conform to MIL-R-11589/83.

8. The rosette shall conform to MIL-R-14649/1.

9. The use of any type of plastic packaging material is prohibited.

Custodians:
Army - IH
Navy - NU

Review activities:
Navy - MC
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-0763)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:39Z
Check the source to verify that this is the current version before use.