NOT MEASUREMENT SENSITIVE

MIL-DTL-3943/3F
11 May 1999
SUPERSEDING
MIL-DTL-3943/3E
1 May 1997

DETAIL SPECIFICATION SHEET

DECORATION, MEDAL OF HONOR, AIR FORCE

Inactive for new design after 14 January 1999.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3943 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

OBVERSE




REVERSE

MATERIAL:

PENDANT, SUSPENSION BAR: Gilding Metal
CONNECTING BAR, HINGE, AND PIN: Bronze

FINISH:

PENDANT: Hard Enameled, Gold Plated, Rose Gold Plated, Relieved, Matte Finish.
SUSPENSION BAR, CONNECTING BAR, HINGE, AND PIN: Gold Plated, Rose Gold Plated, Relieved, Matte Finish.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:40Z
Check the source to verify that this is the current version before use.

DIMENSIONS:

PENDANT:
HEIGHT (overall): 2 inches (REF)
WIDTH (overall): 2-1/16 inches (REF)
THICKNESS (at thickest point): 0.170 inch ± 0.010 inch

SUSPENSION BAR:
HEIGHT (overall): 1-1/4 inches (REF)
WIDTH (overall): 1-1/8 inches (REF)
THICKNESS (at thickest point): 0.115 inch ± 0.010 inch

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Piercing shall be as indicated.

3. The enameled color shall be Transparent Green as indicated. The enamel color shall conform to TIOH Hard Enamel Color Chip Number 11.

4. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of the manufacturer. When epoxy resin is used in lieu of hard enamel, the material requirement shall be gilding metal or red brass.

5. The green enamel areas of the wreath shall be convex within the dikes.

6. The pendant shall be attached to the suspension device by means of a connecting bar and pinned hinge. The connecting bar shall be 0.055 inch ± 0.005 inch square and shall be soldered to the suspension bar so as to insure a distance 5/64 inch ± 1/64 inch between the tip of the lightning bolts and the edge of the star point.

7. The hinge shall be 1/8 inch by 1/8 inch deep by 3/16 inch and shall be soldered to the vertical center line of the pendant 3/32 inch + 1/32 inch - 0 below the lowest point of the "V".

8. The neck ribbon, shield, and attaching device shall be as shown on Figures 6 and 7.

9. Decoration set shall consist of a neck ribbon with shield and pendant, a service ribbon, and a rosette all packaged in a presentation case conforming to MIL-DTL-14633, Type I, Style 4 with a Type 1, Class 1 or 1A pad.

10. The ribbon for the neck ribbon, shield, and service ribbon shall conform to MIL-DTL-11589/83.

11. The rosette shall conform to MIL-DTL-14649/1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:40Z
Check the source to verify that this is the current version before use.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH
Air Force - 45

Preparing activity:
Army - IH

Review activities:
Air Force - 32, 82, 99
DLA - CT

(Project No. 8455-0978)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:40Z
Check the source to verify that this is the current version before use.