[NON-MEASUREMENT SENSITIVE]

A-A-2364A
January 6, 1992
superseding
A-A-2364
May 16, 1986

COMMERCIAL ITEM DESCRIPTION

TYPING, ELEMENT
(96 CHARACTERS)

The General Services Administration has authorized the use of this commercial item description.

This commercial item description covers typing elements (BALL) for use on IBM Selectric III and Electronic Models 50, 60, 65, 75, 85, 95 typewriter machines.

The elements shall have 96 characters and shall be of the following types:

Type I - 10 pitch
Type II - 12 pitch
Type III - Proportional spacing (IBM Models 50, 65, 85, 95)

I. Salient characteristics.

A. The typing element shall consist of appropriate materials and be of such design to fit and function on the machine for which it is designed and conform to the specification of this commercial item description.

B. Typing elements shall be of the dimensions established by the machine manufacturer for proper operations and the contractor shall certify that the typing elements are made to the original manufacturers specifications (OEM) unless specified otherwise (see notes in section VIII). The typing elements designed for proper operation with the machines specified (see notes - section VIII).

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited

FSC 7510

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:22Z
Check the source to verify that this is the current version before use.

C. When properly installed in accordance with the machine manufacturer's instructions the typing elements shall produce clear, clean, and legible typed letters during the typing operation.

D. The typing elements shall produce the proper marks and shall produce record copy impressions which are of uniform density, clean, legible and sharp.

E. Workmanship. The imaging stamp (letter) shall be free from pinholes, breaks, or blisters; free from ragged or nicked edges, foreign matter or other defects which may adversely affect performance or serviceability. Typing elements shall be free from defects which may affect performance or serviceability and which may present a hazard to the user.

II. Performance test. Select one sample and place in the machine designated for its use in the contract and operate the machine in the normal manner until one full page of typing is complete. During the course of the test operation, the typing element shall be observed to ensure that it is not binding or twisting so as to interfere with proper machine operation. Upon completion of the test, the printed matter shall be examined to ensure that the quality of print is uniformly dark and with no blank spots, light spots, or discontinuities. The typing element shall not be the cause of improperly aligned characters. Failure to comply with any of these requirements shall be cause for rejection.

As an alternative to the prescribed performance test, the contractor shall supply a certification from the equipment manufacturer that the element, identified by part number has been tested and will function properly on the equipment for which it was designed. Selected samples will then be tested on any compatible printer for the print quality defined above.

As an alternative to the above performance tests or certification, the manufacturer may certify that the typing element will function properly on the equipment for which it has been designed. Selected samples will be tested on any compatible printer for the print quality defined above.

III. Regulatory requirements. The offerer/contractor is encouraged to use recovered materials in accordance with Public Law 94-580, as amended, to the maximum extent practicable.

IV. Hazardous material requirements.

A. Toxicity. Use of any toxic substance must be in accordance with all applicable federal statutes. The use of any known carcinogens as ingredients is prohibited. The harmful substances shall be defined as the poison and injurious substances as designated in Fed Std. 313. The vendor shall

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:22Z
Check the source to verify that this is the current version before use.

prepare a certification that the inks conforms to the above requirements.

B. Material safety data sheets. Safety data shall be furnished in accordance with Fed. Std. 313. The pertinent government mailing addresses for submission of data are listed in appendix B of Fed. Std. 313.

C. Labeling. Containers shall be labeled to comply with the "Federal Hazardous Substances Act Regulations", 16 Code of Federal Regulations, Part 1500.

V. Quality assurance requirements.

A. Responsibility for inspection. Unless otherwise specified in the contract or purchase order (see VIII), the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

B. Lot definition. Each lot of typing elements shall be inspected for conformance to the requirements herein. Inspection shall be in accordance with MIL-STD-105 using the sampling plans specified below. The lot shall be expressed in typing elements manufactured from the same materials, at essentially the same time.

C. Examination of the end item for visual defects. The sample unit for this examination shall be one typing element. A random sample shall be taken from each lot in accordance with Inspection Level S-3. The AQL shall be 2.5 percent defective. Samples shall be examined for defects listed below. Any typing element containing one or more defects shall be rejected.

Examine	Defects
Typing element	Not compatible with machine specified
Material	Not as specified
Quality	Not as specified
Workmanship	See Workmanship paragraph

D. Examination of the end item for dimensional defects. The sample unit for this examination shall be one typing element. A random sample shall be taken from each lot in accordance with Inspection Level S-2. The AQL shall be 4.0 percent defective. Samples shall be examined for defects listed below. Any typing element containing one or more defects shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:22Z
Check the source to verify that this is the current version before use.

The examination for the characteristics listed in the following table will be based on the specifications/requirements obtained from the OEM for the specific typing elements being examined.

Examine	Defects
OEM specifications	Not as specified

E. Sampling of end items for performance tests. The sample unit shall be one typing element. The sample from each lot in accordance with Inspection Level S-1. The AQL shall be 2.5 percent defective.

1. Performance Testing. The typing element will be performance tested in accordance with paragraph II for each lot delivered. If the reject number is reached for the sample size, the lot will be rejected.

F. Packaging, Packing, and Marking. Inspection Level S-2 with an AQL of 4.0 percent defective. The sample unit shall be one fully prepared shipping container inspected for conformance with the requirements of section VI.

VI. Preparation for delivery.

A. Packaging, and packing. Packaging, and packing shall be as indicated below, unless specified otherwise in the contract or purchase order (see VIII). The normal commercial number of unit packages shall be packed in a close-fitting fiberboard box used commercially for this item and provide product protection against loss and damage during multiple shipments, handling, and storage.. The complete pack shall be in compliance with the Uniform Freight Classification and the National Motor Freight Classification. The weight of the shipping container shall not exceed 65 pounds.

B. Marking. Marking shall be as indicated below, unless specified otherwise in the contract or purchase order (see VIII).

1. For Shipment To Civil agencies. In addition to any special marking required by the contract or order, interior packages and exterior shipping containers shall be marked in accordance with Fed. Std. No. 123. Bar code marking is required, unless specified otherwise (See VIII).

2. For Shipment To Military activities. In addition to any special marking required by the contract or order, interior packages and exterior shipping containers shall be marked in accordance with MIL-STD-129. Bar code marking is required, unless specified otherwise (See VIII).

3. Additional marking. The unit and shipping containers shall include any precautionary marking required by the National

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:22Z
Check the source to verify that this is the current version before use.

Motor Freight Classification Item 222, Uniform Freight Classification Rule 41, and Department of Transportation regulations.

VII. Applicable documents.

The following documents, of the issues in effect on the date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

A. Public Law and Code of Federal Regulations:

Public Law 94-580 - Use of Recovered Materials

16 CFR Part 1500 - Federal Hazardous Substances Labeling Act.

Code of Federal Regulations and Federal Acquisition Regulations are for sale by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

B. National Motor Freight Traffic Association, Inc. Agent:

National Motor Freight Classification - Item 222

Application for copies shall be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W. Washington, D.C., 20036.

C. Uniform Classification Committee Agent:

Uniform Freight Classification - Rule 41

Application for copies shall be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, Illinois 60606.

D. Federal Standards, Specifications, and Commercial Item Descriptions:

FED-STD-123 Marking for Domestic Shipment (Civil Agencies)

FED-STD-313 Material Safety Data, Transportation Data and Disposal Data for Hazardous Materials Furnished to Government Activities.

Federal standards and specifications are available from GSA Business Service Centers and Specification and Consumer Information Distribution Section, Building 197, Washington Navy Yard, Washington DC 20407.

Single copies of this specification and other specifications required by activities outside the Federal Government for

Source: https://assist.dla.mil - Downloaded: 2026-10-26T08:22Z
Check the source to verify that this is the current version before use.

bidding purposes are available without charge from Business Service Centers at the General Services Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles, and Auburn, Washington.

E. Military Standards:

MIL-STD-105 Sampling Procedures and Tables for Inspection by Attributes.

MIL-STD-129 Marking for Shipment and Storage.

Military Standards are available from the Standardization Documents Order Dept. Bldg. 4D 700 Robbins Avenue, Philadelphia, PA 19111-5094.

VIII. Notes.

A. Ordering information. Purchasers shall select the required options permitted herein, and include the following information in procurement documents:

(1) Title, number, and date of this commercial item description.
(2) Purchaser shall specify the typing element specifications (OEM) and the machine on which the typing elements are intended to be used.
(3) Purchasers shall specify arrangement for inspection and inspection facilities, if other than specified (See section VI)
(4) Purchasers shall specify packaging, packing, and any special marking for shipment, if other than required (See section VI).
(5) Identification marking, if other than required.
(6) If bar code marking is not required.
(7) Material safety data sheets required, in addition to those required by Fed-Std-313.
(8) Purchasers shall specify palletization , if required.
(9) Purchasers shall specify any additional tests or test typing pattern (automated test pattern), if required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:22Z
Check the source to verify that this is the current version before use.

B. Item Identifiers/Reference Part Number System (For classification use, only):

AA2364 A (Describes a Typing Element, Type I, in accordance with CID A-A-2364A.)

------ Types: A. Type I
B. Type II
C. Type III

MILITARY INTERESTS:

NONE: DOD has determined that no military activity has an official interest in this commercial item description.

Preparing Activity:
GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:22Z
Check the source to verify that this is the current version before use.