INCH-POUND

A-A-52053
October 5, 1989

COMMERCIAL ITEM DESCRIPTION

SAWS, BAND, MEAT CUTTING

The General Services Administration has authorized the use of this commercial item description in preference to MIL-S-40601.

1. CLASSIFICATION

1.1 Classification. This commercial item description covers two sizes of electric band saws as follows (see 5.2):

Size 1 - Minimum cutting clearance of 14-1/2 inches high by 12-1/2 inches wide
Size 2 - Minimum cutting clearance of 17-1/2 inches high by 15 inches wide

2. SALIENT CHARACTERISTICS

2.1 Design and construction. The band saw shall be a floor model with means provided for leveling. The maximum basic dimensions of the band saw are 75 inches high by 40 inches wide by 50 inches long. Minimum cutting clearance for size 1 is 14-1/2 inches high by 12-1/2 inches wide. Minimum cutting clearance for size 2 is 17-1/2 inches high by 15 inches wide. All large surfaces (other than blade and pusher block) coming in contact with meat shall be fabricated from 300 series stainless steel, including cabinet, stationary and meat carrying tables. The movable table is to be a minimum 14 gage stainless steel, not less than 15-1/2 inches by 18-1/2 inches for size 1 and 15-1/2 inches by 22-1/2 inches for size 2, which shall slide on ball bearing rollers and allow a minimum 20 inch stroke. The staionary table is to be a minimum 16 gage stainless steel with a minimum top surface area of 575 square inches for size 1 and 680 square inches for size 2. Tables shall be readily removable or designed for cleaning without disassembly (including area under the table) and be easily cleanable. The meat saw shall have a gauge face plate of stainless steel providing positive regulation for cut thicknesses of at least two inches. An end cut pusher plate is required with each machine and shall be protected from contacting the blade during use.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any other data which may improve this document should be sent by letter to: Commander, U.S. Army Natick Research, Development, and Engineering Center, ATTN: STRNC-ES, Natick, MA 01760-5014.

AMSC N/A FSC 7320

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.

All moving parts shall be completely guarded for operator safety, except that portion of the band saw blade used for cutting. A removable scrap tray for catching residue shall be furnished with the machine. Scrap tray shall be readily cleanable. All bearings will be lubricated to capacity with the manufacturer's recommended lubricant. Parts requiring daily cleaning will be detachable without the use of tools. Finish for components not available in stainless steel or aluminum, e.g., painted surfaces shall not peel; be blistered, chipped or scratched; or have area of no flim or finish, runs, sags, wrinkles, or foreign matter imbedded in the finish. Each machine will be able to sustain washing by a complete hose down with water or by subjection to high pressure cleaning without corrosion.

2.1.1 Blade. The saw blade shall be made of hardened high carbon steel 5/8 inch wide, between .020 and .025 inch thick, have a maximum of five teeth per inch and skip-tooth type. An adjustable blade guard is required for operator safety. The design will incorporate provisions to insure the blade runs true and possesses blade cleaning capability. Twenty-five blades shall be furnished with the machine, along with a parts catalog. Upper and lower pulleys shall be mounted in a manner to permit quick removal for easy cleaning. Each machine shall be equipped with an easily accessible, quick-acting, manually operated blade tensioning device which will incorporate a visible means of indicating correct tension to permit accurate adjustment. Blade speed for both the size 1 and size 2 band saws shall be minimum 3500 feet per minute.

2.1.2 Electrical requirements. Unless otherwise specified, the band saw shall be electrically operated on a 208 volt, 3 phase, 60 Hertz alternating current system. It shall be powered by a high speed, heavy duty bearing water tight motor conforming to NEMA standard MG-1. The size 1 band saw motor shall be no less than 2 horsepower, and the size 2 motor no less than 3 horsepower. Switches and wiring shall be mounted in a separate ventilated drip-proof compartment, guarded from contacting all meat scraps. A magnetic thermal overload switch with manual reset is required. Motor switch controls are to be situated convenient to the operator.

2.2 Codes and standards. The meat cutting band saw shall comply with Underwriter's Laboratories (UL) Standard No. 763 and National Sanitation Foundation (NSF) Standard No. 8.

2.3 Data name plate (Government unique requirement (see 5.4)). The saw shall be furnished with a data name plate in accordance with the applicable requirements of MIL-STD-130 except the requirements for: (a) Methods of applying; (b) Identification tags; (c) Information not required and (d) Optional marking information shall not apply. The data plate shall be made of minimum 20 gauge corrosion-resisting metal and attached to the saw by rivets, screws, or welding in such a manner as to meet the applicable National Sanitation Foundation sanitary requirements for this equipment. The plate shall contain the following information which shall be stamped, engraved or applied by photosensitive means:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.

National Stock Number
Procurement Contract Number
Specification Data
Manufacturer's Name, Address and Telephone Number
Supplier's Name, Address and Telephone Number (List only if different from Manufacturer)
Manufacturer's Model Number
Government Approved Manual Number (when specified, see 5.2)

Each plate shall be placed so that it is readily visible to the operator during normal operating use and so as to adversely affect the life and utility of the saw.

3. QUALITY ASSURANCE

3.1 Certification. The contractor shall certify, and maintain substantiating evidence, that the product offered meets the salient characteristics and requirements of this Commericial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

4. PACKAGING

4.1 Packaging and packing. Packaging and packing shall be commercial or export as specified (see 5.2).

4.2 Commercial packaging and packing. Each saw shall be cleaned, preserved, packaged, packed and unitized in accordance with ASTM D 3951.

4.3 Export packaging and packing.

4.3.1 Export packaging. Each saw shall be cleaned, preserved and cushioned to protect against corrosion, deterioration and physical damage during shipping and storage. Exposed uncoated ferrous surfaces shall be coated with a preservative and covered or wrapped with greaseproof barrier material. Openings and electrical components shall be sealed with tape. The following caution tag shall be attached to the saw:

CAUTION: Remove protective tape from the exterior of the motor before operation of saw.

Detached components shall be packaged in a fiberboard box conforming to PPP-B-636, type CF or SF, class domestic, style optional.

4.3.2 Export packing. Each saw and its components package shall be packed in a crate conforming to type I, class 1 or 2, style A of MIL-C-104. Contents shall be anchored and each crate shall be closed and strapped in accordance with MIL-C-104.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.

4.4 Marking (commercial and export). Marking of unit pack, shipping container and unit load shall be in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

5. NOTES

5.1 Intended use. The saws covered by this commerical item description are intended for cutting fresh or frozen meats into desired portions. The size 1 machine is intended to cut pork and the size 2 is intended to cut beef in meat markets.

5.2 Ordering data. Acquisition documents must specify the following:

a. Title, number, and date of this document.
b. Size of saw required (see 1.1).
c. Government approved manual number to be included on the data name plate when manuals are purchased under the contract (see 2.3).
d. Type of packaging and packing required (see 4.1).

5.3 Sources of documents.

5.3.1 Sources of nongovernment association documents.

ASTM D 3951 - Standard Practice for Commerical Packaging, is available from:

The American Society for Testing and Materials (ASTM)
1916 Race Street
Philadelphia, PA 19103-1187

UL Standard No. 763 - Motor Operated Commercial Food Preparing Machines, is available from:

Underwriters Laboratories, Inc. (UL)
333 Pfingsten Road
Northbrook, IL 60062

NSF Standard No. 8 - Commericial Powered Food Preparation Equipment, is available from:

National Sanitation Foundation (NSF)
3475 Plymouth Road
PO Box 1468
Ann Arbor, MI 48106

NEMA Standard MG-1 - Motors and Generators, is available from:

National Electrical Manufacturers Association (NEMA)
2101 L Street NW
Washington, DC 20037

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.

5.3.2 Source of governmental documents. Copies of Military and Federal documents are available from:

Naval Publications and Forms Center
ATTN: NPODS
5801 Tabor Avenue
Philadelphia, PA 19120-5099

5.4 Government unique requirements. Whenever "(Government unique requirements)" is included in the title of a paragraph under "salient characteristics" it is meant that the requirement is something that is not normally offered to the commercial marketplace by the manufacturer.

MILITARY INTERESTS:

Custodians:

Army - GL
Air Force - 99

Review activities:

Army - MD, TS
Air Force - 84
DLA - GS

User activity:

Navy - MC

CIVIL AGENCY COORDINATING ACTIVITY:

GSA-FSS

PREPARING ACTIVITY:

Army - GL

(Project 7320-0850)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.