INCH-POUND

A-A-52101
March 29, 1991

COMMERCIAL ITEM DESCRIPTION

TAGS, BLANK, CABLE IDENTIFICATION

(CABLE MARKERS MX-892 ( )/G, MX-893 ( )/G, MX-894 ( )/G, and MX-895 ( )/G)

The General Services Administration has authorized the use of this commercial item description in preferance to military specification MIL-T-12755.

1. CLASSIFICATION

1.1 Classification. This commercial item description covers one type of plastic tag in the following colors (see 5.2):

(a) Red
(b) Yellow
(c) Green
(d) White

2. SALIENT CHARACTERISTICS

2.1 Description. The plastic sheet used for the tags shall be a rigid poly (vinyl chloride) or a poly (vinyl chloride-vinyl acetate) with a brass black chemical finished grommet. The tags shall have a steel wire with a standard galvanized finish.

2.2 Base material. The plastic sheeting shall be resistant to chemicals, transparency, moisture and oxidation, and to changes in: color, dimensions and mechanical strength. The plastic sheeting shall conform to composition A, type II, grade GU; or composition B, type I, class 1 of L-P-535. For composition B, type I, class 1, the thermal stability and volume resistivity requirements shall not apply.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: Commander, U.S. Army Natick Research, Development, and Engineering Center, ATTN: STRNC-UXT, Natick, MA 01760-5017.

AMSC N/A FSC 9905

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:06Z
Check the source to verify that this is the current version before use.

2.3 Appearance (color). The colors of the plastic sheeting for the identification tags shall approximate the following Munsell colors:

Cable Marker Indentification	Munsell Notation
MX-892 ( )/G-Red	5R 4/12 or brighter
MX-893 ( )/G-Yellow	5Y 8/12 or brighter
MX-894 ( )/G-Green	5G 5/8 or brighter
MX-895 ( )/G-White	9.0 (neutral) or brighter

2.4 Finish and color uniformity. The identification tags shall have a matte finish on both sides and shall be clean and uniform in color.

2.5 Pencil marking. A mark, made with a 2H grade lead pencil using a pressure of ordinary writing, shall be legible when viewed with the naked eye at a distance of 18 inches.

2.6 Heat stability of color and dimensional stability. The identification tags shall have a heat stability of color and shall show no more than a slight change in color. The tags shall also have dimensional stability showing not more than a 5 percent dimensional change. Testing shall be as follows:

Two tags, pre-measured to the nearest 1/16 inch in length and width and 0.0015 inch in thickness, prior to heating, shall be subjected to a temperature of 212°F ± 2°F for 5 minutes in a circulating air oven. Once cooled, examine the tags for color change and dimensional change. The failure of any test shall be cause for the rejection of the lot.

2.7 Cold bend. The tags shall not show breaks or cracks to cold bend when tested as follows:

The identification tag, together with a 1/4 inch diameter mandrel, shall be stored in a cold chamber at a temperature of -40°F ± -2°F for 24 hours. While at -40°F, the tag shall be bent across its lesser axis one half turn around the mandrel at a rate of 5 seconds per half turn. Examine for breaks and cracks. The failure of this test shall be cause for rejection of the lot.

2.8 Grommet. The grommet used for the identification tags shall conform to type I, brass, with a black chemical finish of MIL-G-16491. The size shall be 00 of MS-20230.

2.9 Wire. The identification tag wire shall be 12 inches ± 1/16 inch in length, No. 23 steel wire gage, 0.0258 inch nominal diameter with a standard galvanized finish, and shall meet the requirements of the American Iron and Steel Institution (AISI) Steel Products Manual, for Wire and Rods, Carbon Steel.

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:06Z
Check the source to verify that this is the current version before use.

2.10 Design and construction. The identification tags shall be 3-1/4 inches ± 1/16 inch long, 1-5/8 inches ± 1/16 inch wide, and 0.015 inch ± 0.0015 inch thick. The grommet shall be centered 7/16 inch from the top edge of the tag and midway between the two outer edges at the top of the tag. The wire shall be passed through the grommet and bent 180° back to the other half, twisting the wire one full turn close to the marker leaving two free ends. Each end shall be approximately 12 inches in length. Any dimension not within the specified tolerance shall be cause for rejection of the lot.

3. QUALITY ASSURANCE

3.1 Certification. The contractor shall certify, and maintain substantiating evidence, that the product offered meets the salient characteristics and requirements of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

3.2 Metric product. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within specified tolerances using conversion tables contained in the latest revision of FED-STD-376, and all other requirements of this Commercial Item Description are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable. The contracting officer has the option of accepting or rejecting the product.

3.3 Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

4. PACKAGING

4.1 Packaging. Fifty tags of one color shall be bundled. Twenty bundles (1000 tags) shall be packaged in a fiberboard or paperboard box.

4.2 Packing. Eight boxes (8000 tags), packaged as specified above, shall be packed in a close fitting, style RSC corrugated fiberboard shipping container conforming to type CF (variety SW) or SF, class domestic, grade 275 of PPP-P-636. Each shipping container shall be closed in accordance with the appendix of PPP-P-636.

Source: https://assist.dla.mil -- Downloaded: 202640-26T09:06Z
Check the source to verify that this is the currentversion before use.

4.3 Palletization. When specified (see 5.2), shipping containers shall be palletized in accordance with load type Ia of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means C and D, or film bonding means F or G. Pallet pattern shall be in accordance with the appendix of MIL-STD-147.

4.4 Marking. Marking of unit packs, shipping containers and palletized unit loads shall be in accordance with MIL-STD-129, or ASTM D 3951, as applicable.

5. NOTES

5.1 Intended use. The identification tags are intended for tactical use for line identification on field wires and cables.

5.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number and date of this document.
b. Color required (see 1.1).
c. When palletization is required (see 4.3).

5.3 Sources of documents.

5.3.1 Sources of government documents. Copies of Military and Federal documents are available from:

Standardization Documents Order Desk
Building 4D
700 Robbins Avenue
Philadelphia, PA 19111-5094

5.3.2 Sources of nongovernment association documents.

ASTM D 3951 - Packaging, Commercial, is available from:

The American Society for Testing and Materials (ASTM)
1916 Race Street
Philadelphia, PA 19103-1187

Steel Products Manual, Wire and Rods, Carbon Steel, is available from:

The American Iron and Steel Institute (AISI)
1133 15th Street, N.W.
Washington, DC 20005

Munsell Book of Colors is available from:

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:06Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Custodians

Army - GL
Navy - YD
Air Force - 99

Review activities

Army - MD, CR
Navy - SA
Air Force - 84

User activity

Navy - MC

CIVIL AGENCY COORDINATING ACTIVITY:

GSA-FSS

PREPARING ACTIVITY:

Army - GL

Project 9905-0302

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:06Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:06Z
Check the source to verify that this is the current version before use.