INCH-POUND

A-A-52122D
15 May 2018
SUPERSEDING
A-A-52122C
17 December 2012

COMMERCIAL ITEM DESCRIPTION

KIT, WATER PURIFICATION, EMERGENCY

The General Services Administration has authorized the use of this commercial item description for all federal agencies.

1. SCOPE. This commercial item description (CID) covers one type of emergency water purification kit recommended for use in situations where municipal treated water is not provided or where the available water is suspected of being polluted.

2. SALIENT CHARACTERISTICS

2.1 Components. The water purification kit shall consist of the following components:

2.1.1 Sachet, chlorine, flocculating. The sachet shall conform to the requirements of A-A-52119, "Sachet, Chlorine, Flocculating, Emergency Water Purification".

2.1.2 Filter pouch. The filter pouch shall be fabricated from either bleached, 100 percent cotton or 65 percent polyester/35 percent cotton cloth conforming to the requirements specified in table I (yarn size 15/1 in warp and 7/1 in filling has been found to provide satisfactory material). The finished dimensions of the filter shall be 6 inches deep by 2-1/2 inches wide at the top opening. The filter shall be formed from a double layer of the cloth with a side and bottom seam. The bottom of the filter shall be semicircular. All raw edges shall be overedge stitched. The top opening edge of the filter shall be folded down and stitched.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data that may improve this document should be sent to: STDZNMGT@dla.mil or Defense Logistics Agency - Aviation, ATTN: DLA Aviation-VEB, 8000 Jefferson Davis Highway, Richmond, VA 23297-5616. Since contact information can change, you may want to verify the currency of this address information using the ASSIST database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:06Z
Check the source to verify that this is the current version before use.

TABLE I. Physical requirements

Characteristic	Test method	Test results
Weave	Visual	Oxford[6]
Air Permeability Per single layer (ft^3/min./ft^2)	ASTM D737[1]	56-80
Weight (bleached), oz/sq yd	ASTM D3776/D3776M[2]	5.2 (min.)
Yarns/inch Warp Filling	ASTM D3775[3]	81 (min.) 27 (min.)
Tearing strength, (lb) Warp Filling	ASTM D1424[4]	11 (min.) 8 (min.)
Breaking strength, (lb) Warp Filling	ASTM D5034[5]	136 (min.) 92 (min.)

[1]ASTM D737, "Standard Test Method for Air Permeability of Textile Fabrics".
[2]ASTM D3776/D3776M, "Standard Test Method for Mass Per Unit Area (Weight) of Fabric".
[3]ASTM D3775, "Standard Test Method for End (Warp) and Pick (Filling) Count of Woven Fabrics".
[4]ASTM D1424, "Standard Test Method for Tearing Strength of Fabrics by Falling-Pendulum (Elmendorf-Type) Apparatus".
[5]ASTM D5034, "Standard Test Method for Breaking Strength and Elongation of Textile Fabrics (Grab Test)".
[6]Oxford defined as a plain weave with two (2) warp ends weaving as one (1)

2.1.3 Water treatment bag. The water treatment bag shall be constructed of 4 mil (0.004 inches) polyethylene material in compliance with 21 CFR 177 and 178 for food contact. The measurements of the treatment bag shall be 11-3/4 inches in length and 7-1/2 inches in width. All side seams shall be heat sealed with 1/8 inch seam width. The bag shall include tapes over wires to protect the bag against piercing and two center tabs to aid in opening and closing.

2.1.4 Emergency water purification procedure label. The procedure label shall conform to figure 1 and shall be embossed (printed) on the outside of the water treatment bag.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:06Z
Check the source to verify that this is the current version before use.




FIGURE 1. Procedure label.

3. REGULATORY REQUIREMENTS

3.1 Recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:06Z
Check the source to verify that this is the current version before use.

4. PRODUCT CONFORMANCE PROVISIONS

4.1 Product conformance. The products provided shall meet the salient characteristics of this CID, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial marketplace. The government reserves the right to require proof of such conformance.

4.2 Market acceptability. The product offered must have been previously sold either to the government or on the commercial market.

4.3 Metric product. Products manufactured using metric units will be considered on an equal basis with those manufactured using inch-pound units, provided that the product measurements fall within specified tolerances using conversion tables contained in the latest revision of FED-STD-376, "Preferred Metric Units for General Use by the Federal Government", and that all other requirements of this CID are met.

5. PACKAGING

5.1 Preservation, packing, and marking. Unless otherwise specified (see 5.2, 5.3, 5.4, and 5.5), preservation, packing, and marking shall be as specified in the acquisition order (see 6.2(b)).

5.2 Filter pouch. Each filter pouch shall be heat-sealed in a snug-fitting polyethylene bag. The polyethylene film shall be 0.001 (minimum) inch thick.

5.3 Complete kit. Each complete kit consisting of one water treatment bag, 30 sachets contained in one intermediate package as described in A-A-52119, and three filter pouches (unit packed as specified in 5.2) shall be compactly arranged in a clear polyethylene film bag. The polyethylene film shall be 3 mil (0.003 inches) thick and the bag shall be closed by heat sealing. Avoid trapping excess air in the bag during the sealing operation. The date of manufacturing shall be printed on this bag to allow for the expiration date to be determined and managed.

5.4 Intermediate packaging. Fifty kits, unit packed as specified in 5.3, shall be packed in an intermediate fiberboard box conforming to the style of a regular slotted box (RSC) of ASTM D1974/D1974M, "Standard Practice for Methods of Closing, Sealing, and Reinforcing Fiberboard Boxes". The kits shall be arranged on edge in two layers with 25 kits per layer. The layers shall be separated by a full length and width fiberboard pad. Approximate inside dimensions of the intermediate box shall be 21-7/8 inches in length, 7-3/8 inches in width, and 6-5/8 inches in depth. Each intermediate box shall be securely closed.

5.5 Packing. One hundred kits (two intermediate boxes) shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC of ASTM D1974/D1974M. Each shipping container shall be closed and waterproofed in accordance with ASTM D1974/D1974M. Approximate inside dimensions of the shipping container shall be 22-1/4 inches in length, 15-7/8 inches in width, and 7-3/8 inches in depth. Each shipping container shall be closed and waterproofed in accordance with ASTM D1974/D1974M.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:06Z
Check the source to verify that this is the current version before use.

5.6 Storage. Kits containing the chlorine flocculating sachets shall not be stored in excessive heat, in direct sunlight, nor above 77 ºF (25 ºC).

6. NOTES

6.1 Sources of documents.

6.1.1 FAR. The FAR may be obtained from https://www.acquisition.gov

6.1.2 CFR. The CFR may be obtained from https://www.ecfr.gov/

6.1.3 Federal specifications and standards. Copies of federal specifications and standards may be obtained from http://quicksearch.dla.mil.

6.1.4 ASTM standards. Copies of ASTM standards may be obtained from https://www.astm.org/.

6.2 Ordering data. The acquisition order should specify the following:

a. CID document number and revision.
b. Packaging requirements (see 5.1).

6.3 Subject term (key word) listing.

disinfectant
filter
treatment

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:06Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Custodians:
Army – GL
Navy – MC
Air Force – 68
DLA – GS

Review Activities:
Army - EA, MD
Air Force - 50

CIVIL AGENCY
COORDINATING ACTIVITY:

GSA – FAS

Preparing Activity:
DLA – GS3

(Project 6850-2018-005)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:06Z
Check the source to verify that this is the current version before use.