INCH-POUND

A-A-52135
December 8, 1993

COMMERCIAL ITEM DESCRIPTION

KETTLES, STEAM JACKETED; TWIN; 5-GALLON; TILTING,

CABINET MOUNTED; NATURAL GAS HEATED

The General Services Administration has authorized the use of this Commercial Item Description in preference to MIL-K-43943.

1. ABSTRACT

1.1 Abstract. This commercial item description covers natural gas heated, cabinet mounted, tilting, 5-gallon twin steam-jacketed kettles.

2. SALIENT CHARACTERISTICS

2.1 Design and construction. The tilting kettle assembly shall consist of two 5 +1; -0 gallons capacity, 300 series stainless steel, steam jacketed tilting kettles with trunnion(s) mounted on an enclosed cabinet base. The completely assembled unit shall be provided with all piping, valves, drains, gauges, etc., for connection to gas, electric, and water supplies. Kettles shall operate at a range of 150°F to not less than 240°F by means of steam generated in a gas heated boiler housed in the cabinet base.

2.1.1 Tilting kettles. Tilting kettles shall be thermostatically operated at a pressure not to exceed 15 pounds per square inch gauge (psig) and shall be provided with a steam jacket with a 30 psi to 50 psi steam rating. The kettles shall have tilt handles, a hot/cold serving spout faucet, a removable cover with handle or knob, a pouring lip, and a means for complete drainage. Each kettle shall be equipped with a safety valve and a control valve to control the steam supply from the generator to the kettle.

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any data which may improve this document should be sent to: Commander, U.S. Army Natick Research, Development, and Engineering Center, ATTN: SATNC-WEE, Natick, MA 01760-5018.

AMSC N/A FSC 7310

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-26T09:07Z
Check the source to verify that this is the current version before use.

2.1.2 Cabinet base. The totally enclosed cabinet base shall be provided with four 6 inch adjustable legs, front opening doors, a sink with drain and drip tray, and a back-splash.

2.1.3 Steam generator. The 200,000 BTU (minimum) gas operated steam generator shall be located in the cabinet base and shall be designed for operation at a pressure not to exceed 15 psig. The generator shall be provided with the necessary piping and valves for connection to the kettles. The generator shall also be provided with drains and a low water safety cutoff. All controls shall operate on a 120 V, 60 Hz single-phase system. The generator shall operate on natural gas and shall be equipped with a pressure regulator. Burners shall be equipped with an automatic ignition system and a 100% automatic shut-off device.

2.1.4 Standard compliance. The tilting kettle assembly shall comply with the applicable requirements of UL Standard No. 197, ANSI Z83.15, ASME Sections IV and VIII; and NSF International Standard No. 4.

2.2 Users instructions ("Government unique" requirement). Operating instructions shall be on an aluminum, brass, or stainless steel plate permanently affixed to the item. Marking shall be stamped, embossed, engraved or applied by photosensitive means. The plate shall contain the information listed below. The words "STEAM-JACKETED KETTLE" shall be not less than 3/16 inch high and the words "USER'S INSTRUCTIONS" shall be not less than 1/8 inch high. All other characters shall be not less than 3/32 inch high. The plate shall be mounted on the inner door of the cabinet.

STEAM-JACKETED KETTLE

USER'S INSTRUCTIONS

1. Caution: Steam supply shall not exceed 15 psig.
2. Do not tamper with or obstruct safety valve.
3. Do not clean with abrasives.
4. Wash and sanitize kettle before and after each use with hot soapy water and rinse thoroughly with clean hot water. Sanitize all food contact surfaces either by rinsing, spraying, or swabbing the kettle with a solution of 100 parts per million (ppm) available chlorine or 25 ppm available iodine.
5. Do not turn steam on unless water or food is in the kettle.
6. Do not put water in hot dry kettle.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:07Z
Check the source to verify that this is the current version before use.

7. When heating a cold kettle, turn the steam on gradually, thus allowing the kettle to become warm before full pressure is applied. After kettle becomes warm, and before applying full pressure, open the safety valve momentarily to release any air trapped within the jacket.

2.3 Data nameplate ("Government unique" requirement). The kettles shall be furnished with a data nameplate in accordance with the applicable requirements of MIL-STD-130 except the requirements for: (a) Methods of applying, (b) Identification tags, (c) Information not required, and (d) Optional marking information shall not apply. The data nameplate shall be made of minimum 20 gauge corrosion-resisting metal and attached to the kettle by rivets, screws, or welding in such a manner as to meet the applicable NSF International sanitary requirements for this equipment. The plate shall contain the following information which shall be stamped, engraved, or applied by photosensitive means:

Contract Number
National Stock Number
Procurement Instrument Identification Number
CID Based Part Identification Number (PIN)
Manufacturer's Name, Address, and Telephone Number
Supplier's Name, Address, and Telephone Number (List Only if Different from Manufacturer)
Manufacturer's Model and Serial Number
Government Approved Manual Number (see 5.2)

Each plate shall be placed so that it is readily visible to the operator during normal operating use and so as to not adversely affect the life and utility of the kettle.

2.4 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within the tolerances specified using conversion tables contained in the latest revision of Federal Standard No. 376, and all other requirements of this commercial item description are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable. The contracting officer has the option of accepting or rejecting the product.

2.5 Regulatory requirements. In accordance with section 23.403 of the Federal Acquisition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:07Z
Check the source to verify that this is the current version before use.

adversely affecting performance requirements or exposing suppliers' employees to undue hazards from the recovered materials. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products are allowed under this commercial item description unless otherwise specified.

2.6 Workmanship. The finished kettles shall be complete, clean, and free of fabrication marks, scratches, dents, sharp edges, sharp corners, burrs, slivers, or visible evidence of rust. Rivets, when used, shall be tight and the rivet heads and peened ends shall be round and concentric and in full contact with the joined metal surfaces. There shall be no empty rivet holes. Welds shall be clean, continuous, sound, and free of flux, pits, buildups, undercuts, and shall be ground so as to blend with the adjacent surfaces. Spot welds shall be free from pits, burn throughs, and flashes.

3. QUALITY ASSURANCE

3.1 Contractor certification. The contractor shall certify that the product offered meets the salient characteristics and requirements of this commercial item description and except for those Government unique requirements specified, conforms to the producer's own drawings, specifications, standards, and quality assurance practices, and is the same product offered for sale in the commercial marketplace or that had successfully been delivered to the Government on a previous contract or purchase order. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

3.2 Compliance. Prior to approval of the first shipment, the contractor shall submit satisfactory evidence to the contracting officer or his authorized representative that the tilting kettle conforms to the applicable requirements of UL Standard No. 197, ANSI Z83.15, ASME Sections IV and VIII, and NSF International Standard No. 4.

3.2.1 Underwriters Laboratories, Inc. (UL). Acceptable evidence of meeting the requirements of UL Standard No. 197 shall be the UL listing mark, or a certified test report from a recognized independent laboratory acceptable to the Government indicating compliance with the applicable requirements of UL Standard No. 197.

3.2.2 American National Standards Institute (ANSI). Acceptable evidence of meeting the applicable requirements of ANSI Z83.15 shall be a photostatic copy of the American Gas Association (AGA) Appliance Certificate; a listing of the tilting kettle, regular and quick disconnect devices and connections in the AGA Directory of Certified Appliances and Accessories.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:07Z
Check the source to verify that this is the current version before use.

3.2.3 American Society of Mechanical Engineers (ASME). Acceptable evidence of meeting the requirements of ASME Boiler and Pressure Vessel Code Sections IV and VIII shall be the ASME mark, or a certified test report from a recognized indented laboratory acceptable to the Government indicating compliance with the applicable requirements of sections IV and VIII.

3.2.4 NSF International. Acceptable evidence of meeting the requirements of NSF International Standard No. 4 shall be a listing in the current edition of the NSF International "Listing of Food Service Equipment" and display of the NSF International mark on the finished product, or a certified test report from a recognized independent laboratory acceptable to the Government indicating compliance with the applicable NSF International requirement(s).

4. PACKAGING

4.1 Packaging and packing. Packaging and packing shall be commercial or export, as specified (see 5.2).

4.2 Commercial.

4.2.1 Commercial packaging. Each steam kettle shall be cleaned, preserved, packaged, and packaged in accordance with ASTM D 3951.

4.2.2 Commercial packing. The steam kettle shall be packed in accordance with ASTM D 3951.

4.3 Export packaging and packing.

4.3.1 Export packaging. Each kettle shall be cleaned, preserved, and cushioned to afford protection against corrosion, deterioration, and physical damage during shipping and storage.

4.3.2 Export packing. Each kettle shall be packed in a snug-fitting, wood-cleated plywood box conforming to domestic type, style A or B, type 3 load of PPP-B-601. The contents of the box shall be cushioned, blocked, and braced to prevent movement and damage during transit and provide a minimum space of 1 inch between the legs of the kettle assembly and the inside surface of the bottom of the box.

4.4 Marking (commercial and export). Marking of shipping containers shall be in accordance with MIL-STD-129.

5. NOTES

5.1 Intended use. The kettles covered by this commercial item description are intended for use in permanent kitchens and galleys.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:07Z
Check the source to verify that this is the current version before use.

5.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this commercial item description.
b. Government approved manual number to be included on data nameplate (see 2.3).
c. Selection of applicable packaging and packing required (see 4.1).

5.3 Sources for documents.

5.3.1 Sources for non-Government association documents.

ANZI Z83.15 - Gas Food Service Equipment Kettles, Steam, Generators

ANSI documents are available from:

American National Standards Institute (ANSI)
11 West 42nd Street
New York, NY 10036

ASME documents are available from:

American Society of Mechanical Engineers (ASME)
Managing Director of Codes and Standards
345 East 47th Street
New York, NY 10017

ASTM D 3951 - Standard Practice for Commercial Packaging

ASTM documents are available from:

American Society for Testing and Materials (ASTM)
1916 Race Street
Philadelphia, PA 19103-1187

NSF International Standard No. 4 - Commercial Cooking, Rethermalization and Powered Hot Food Holding and Transport Equipment

NSF International documents are available from:

NSF International
3475 Plymouth Road
P.O. Box 130140
Ann Arbor, MI 48113-0140

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:07Z
Check the source to verify that this is the current version before use.

UL 197 - Commercial Electric Cooking Appliances

UL standards are available from:

Underwriters Laboratories, Inc. (UL)
333 Pfingsten Road
Northbrook, IL 60062

5.3.2 Source for Government documents. Copies of military and federal documents are available from:

Standardization Documents Order Desk
Building 4D
700 Robbins Avenue
Philadelphia, PA 19111-5094

5.4 "Government unique" requirements. Whenever a "Government unique" requirement is included in the title of a paragraph under "Salient Characteristics", it is meant that the requirement is something that is not normally offered to the commercial marketplace by the manufacturer.

MILITARY INTERESTS:

Custodians

Army - GL
Navy - SA
Air Force - 99

Review Activities

Army - MD, QM
Navy - CG
Air Force - 50, 84
DLA - GS

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

Army - GL

Project 7310-0827

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:07Z
Check the source to verify that this is the current version before use.