INCH-POUND

A-A-52136A
June 15, 1995
SUPERSEDING
A-A-52136
December 8, 1993

COMMERCIAL ITEM DESCRIPTION

KETTLES, STEAM JACKETED (STAINLESS STEEL, STEAM HEATED)

The General Services Administration has authorized the use of this Commercial Item Description in preference to RR-K-195 for all federal agencies.

1. SCOPE

1.1 Scope. This commercial item description covers stainless steel, steam-jacketed, steam heated kettles for use in permanent kitchens and galleys.

2. CLASSIFICATION

2.1 Classification. The steam jacketed kettles shall be of the following types, styles, capacities, and classes, as specified (see 7.1):

Type I - Deep, 2/3 jacketed

Style A - Leg mounted, stationary
Capacities - 10, 20, 30, 40, 60, 80, and 100 gallons

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: Commander, U.S. Army Natick Research, Development and Engineering Center, ATTN: SSCNC-WEF, Natick, MA 01760-5018 by using the Standardization Documents Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 7310

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-26T09:07Z
Check the source to verify that this is the current version before use.

Style B - Wall mounted, stationary
Capacities - 10, 20, 30, 40, 60, 80, and 100 gallons
Style C - Pedestal mounted, stationary
Capacities - 10, 20, 30, 40, 60, 80, and 100 gallons
Style D - Pedestal mounted, tilting
Capacities - 10, 20, 30, 40, 60, and 80 gallons
Style E - Table mounted, tilting
Capacities - 2-1/2, 5, and two-5 gallon, 7-1/2, and 10 gallons
Style F - Wall mounted, tilting
Capacities - 10, 20, 30, 40, 60, and 80 gallons
Style G - Leg mounted, tilting
Capacities - 10, 20, 30, 40, 60, 80, and 100 gallons

Type II - Shallow, fully jacketed

Style A - Leg mounted, stationary
Capacities - 20, 25, 40, 60, and 80 gallons
Style B - Pedestal mounted, stationary
Capacities - 20, 25, 40, 60, and 80 gallons
Style C - Wall mounted, tilting
Capacities - 20, 25, 40, and 60 gallons
Style D - Wall mounted, stationary
Capacities - 20, 25, 40, and 60 gallons

Class 1 - Insulated (not applicable to type I, style E)
Class 2 - Noninsulated

2.2 CID based part identification number (PIN). A document based PIN to identify types, styles, capacities, and classes is included in section 7. This identification numbering procedure is for Government purposes and does not constitute a requirement for the contractor.

3. SALIENT CHARACTERISTICS

3.1 Design and construction. The kettles, including the outer casings, shall be fabricated from 300 series stainless steel. The inner body shall be fabricated of a single piece of 18.8 type 304 or 316 stainless steel, as specified (see 7.1). The interior and exterior of the kettle shall have a number 4 sanitary finish as referenced in ASTM A 240. Unless otherwise specified, the kettles shall be constructed in accordance with the appropriate ASME codes and shall be operated dependably by direct steam at pressures ranging from 5 to 25 pounds per square inch (psi) (see 7.1). The completely assembled units shall be provided with all piping, inlet and outlet valves, controls, and gauges for connection to steam supplies. The size of the steam inlet pipe shall be as specified (see 7.1). Globe and check valves shall be appropriate for working pressures up to 125 pounds per square

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:07Z
Check the source to verify that this is the current version before use.

inch gauge (psig). The kettles shall be provided with a draw-off located at the bottom of the kettle body to allow for complete drainage. Class A kettles shall be fabricated with insulation contained between the kettle body and the outer casing. The kettles shall be provided with safety valves designed for the maximum operating pressures. The kettles shall be equipped with one piece covers with handles. Table mounted kettles shall be provided with a stainless steel basket. Unless otherwise specified, a swing spout water supply connection with faucet shall be provided (see 7.1). When specified, an electric or mechanical water metering device shall be furnished (see 7.1). Unless otherwise specified, a graduated stainless steel measuring stick shall be furnished with all kettles, except for the type I, style E kettle (see 7.1).

3.1.1 Tilting kettles. When specified, tilting kettles shall be equipped with a cover with handle and shall be of the lift-off type (see 7.1). When specified, actuators and counter-balancing springs shall be provided (see 7.1). Steam inlets and outlets shall be through trunnions. An insulated handle shall be mounted on the side of the kettle for tilting purposes.

3.1.2 Non-tilting kettles. Non-tilting kettles shall be equipped with covers and handles. A tangent draw-off assembly equipped with an outlet strainer, a strainer hook, and draw-off valve shall be provided and located at the lowest point inside the kettle body.

3.1.3 Kettle mountings.

3.1.3.1 Leg mounted. Leg mounted kettles shall be constructed with stainless steel tubular legs and stainless steel adjustable floor flanges. Legs shall be either continuously welded to the kettle or threaded into sockets located on the outside kettle bottom as specified (see 7.1). When specified legs shall be braced (see 7.1).

3.1.3.2 Wall mounted. Wall mounted kettles shall be furnished with a wall-bracket or an in-wall carrier support. Wall brackets and in-wall carrier supports shall be capable of supporting the weight of the kettle plus its contents. Bracket frames shall have provisions for securing valves, fittings, piping, and openings for controls. Frames shall have at least three bolt holes.

3.1.3.3 Pedestal mounted. Pedestals shall be of the manufacturer's standard design and shall be provided with a base with a minimum of four equally spaced bolt holes. Pedestals for tilting tables shall be provided with trunnions for tilting. Tilting shall be controlled by a hand wheel or crank.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:07Z
Check the source to verify that this is the current version before use.

3.1.3.4 Table mounted (tilting). Table mounted tilting kettles shall be provided with two vertical supports and trunnions which will allow the kettle to be tilted 90° from the normal position. A handle shall be attached to the kettle body.

3.2 Kettle options. Optional equipment such as:

- Steam trap assembly
- Steam pressure reducing valve
- 1-1/2 inch, 2 inch, or 3 inch drawoffs
- Cooking basket systems
- Cooking basket inserts
- Water fillers
- 1/8 inch perforated or solid disc strainers
- Kettle brush kits

can be ordered as specified in 7.1.

3.3 Standard compliance. The kettles shall comply with the applicable requirements of ASME Sections IV and VIII, ASTM A 240, and NSF International Standard No. 4, as appropriate.

3.4 Users instruction plate. Each kettle shall have a metal user's instruction plate which shall be permanently attached to the kettle in such a manner as to meet the applicable NSF International sanitary requirements for this equipment. The plate shall be mounted so as to be visible to the operator. The plate shall contain the following information:

STEAM-JACKETED KETTLE

USERS' INSTRUCTIONS

1. Do not turn on steam unless water or food is in kettle.
2. Do not tamper with or obstruct safety valve.
3. Wash and sanitize kettle before and after each use. Wash with hot soapy water. Sanitize all food contact surfaces either by rinsing, spraying, or swabbing the kettle with a solution of 100 parts per million (ppm) available chlorine or 25 ppm available iodine. Rinse thoroughly without allowing water to enter into the control housing. Dry thoroughly inside and outside.
4. Leave cover open when not in use.
5. Do not put water in hot dry kettle.
6. When heating a cold kettle, allow the kettle to become warm before full pressure is applied. After kettle becomes warm, and before applying full pressure, open the safety valve momentarily to release any air trapped within the jacket.

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:07Z
Check the source to verify that this is the current version before use.

7. Clean strainer, draw-off valve, and draw-off tube thoroughly after each use in accordance with the manufacturer's recommendations.

3.5 Data nameplate. The kettles shall be furnished with a corrosion-resistant metal nameplate attached to the kettle in such a manner as to meet the applicable NSF International sanitary requirements for this equipment. The nameplate shall contain the following information:

Manufacturer's Name and Address
Model Number
Serial Number
Steam Pressure (Working/Maximum)

Each data nameplate shall be placed so that it is readily visible to the operator during normal operating use, and so as to not adversely affect the life and utility of the kettle.

3.6 Workmanship. The finished kettles shall be complete, clean, and free of fabrication marks, scratches, dents, sharp edges, sharp corners, burrs, slivers, or visible evidence of rust. Rivets, when used, shall be tight and the rivet heads and peened ends shall be round and concentric and in full contact with the joined metal surfaces. There shall be no empty rivet holes. Welds shall be clean, continuous, sound, and free of flux, pits, buildups, undercuts, and shall be ground so as to blend with the adjacent surfaces. Spot welds shall be free from pits, burn throughs, and flashes.

4. REGULATORY REQUIREMENTS

4.1 Contractor recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

5. QUALITY ASSURANCE PROVISIONS

5.1 Contractor certification. The contractor shall certify, and maintain substantiating evidence, that the product offered meets the salient characteristics and requirements of this Commercial Item Description, conforms to the producer's own drawings, specifications, standards and quality assurance practices; and is the same product that has been sold in the commercial marketplace for over one year, or is the same product that has successfully been delivered to the Government on a previous contract or purchase order. The Government reserves the right to require

Source: https://assist.dla.mil -- Downloaded: 202640-26T09:07Z
Check the source to verify that this is the current version before use.

proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

5.2 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within the tolerances specified using conversion tables contained in the latest revision of ASTM E 380, and all other requirements of this Commercial Item Description are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable. The contracting officer has the option of accepting or rejecting the product.

5.3 Compliance. Prior to approval of the first shipment, the contractor shall submit satisfactory evidence to the contracting officer or his authorized representative that the kettles conform to the applicable requirements of ASME Sections IV and VIII, ASTM A 240, and NSF International Standard No. 4.

5.3.1 American Society of Mechanical Engineers (ASME). Acceptable evidence of meeting the applicable requirements of ASME Boiler and Pressure Vessel Code Sections IV and VII shall be the ASME mark.

5.3.2 NSF International. Acceptable evidence of meeting the requirements of NSF International Standard No. 4 shall be a listing in the current edition of the NSF International "Listing of Food Service Equipment" and display of the NSF International mark on the finished product, or a certified test report from a recognized independent laboratory acceptable to the medical authority of the Government indicating the item complies with the applicable NSF International requirement(s). Acceptability of the medical authority of the Government will be obtained prior to the award of any contract or procurement document.

6. PACKAGING

6.1 Packaging, packing, and marking. Packaging, packing, and marking shall be in accordance with the requirements of ASTM D 3951, unless otherwise specified in the contract or purchase order (see 7.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:07Z
Check the source to verify that this is the current version before use.

7. NOTES

7.1 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this commercial item description.
b. Type, style, capacity in gallons, and class required, designated by PIN (see 2.1, 2.2, and 7.3).
c. Type of stainless steel required for inner body (see 3.1).
d. Steam pressure requirements if other than 5 to 25 psi (see 3.1).
e. Steam inlet pipe size required (see 3.1)
f. Type of water supply connection required, if other than the swing spout type normally provided (see 3.1).
g. Whether an electrical or mechanical water metering device is required (see 3.1).
h. When no measuring stick is required (see 3.1).
i. Whether a lift-off type cover with handle is required (see 3.1.1).
j. Whether actuators and counter-balancing springs are required (see 3.1.1).
k. How legs shall be attached to the kettle (see 3.1.3.1).
l. Whether legs are required to be braced (see 3.1.3.1).
m. Optional equipment required (see 3.2).
n. Packaging requirements (see 6.1).

7.2 Sources for documents.

7.2.1 Sources for non-Government association documents.

ASME documents are available from:

American Society of Mechanical Engineers
United Engineering Center
345 East 47th Street
New York, NY 10017

ASTM documents

A 240 - Heat-Resisting Chromium and Chromium-Nickel Stainless Steel Plate, Sheet, and Strip for Pressure Vessels
D 3951 - Standard Practices for Commercial Packaging
E380 - Use of the International System of Units (SI) (The Modernized Metric System)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:07Z
Check the source to verify that this is the current version before use.

These documents are available from:

American Society for Testing and Materials (ASTM)
1916 Race Street
Philadelphia, PA 19103-1187

NSF International Standard No. 4 - Commercial Cooking, Rethermalization and Powdered Hot Food Holding and Transport Equipment

NSF International documents are available from:

NSF International
3475 Plymouth Road
Ann Arbor, MI 48105

7.3 Part identification number (PIN). The PINs to be used for items required by this CID are created as follows:

AA 52136-1-A-010-1 (Example of a PIN: AA52136-1A0101)

- Class: 1 - Insulated; 2 - Noninsulated
- Capacity in gallons
- Style
- Type: 1 -Type I - Deep, 2/3 jacketed; 2 -Type II - Shallow, fully jacketed
- CID number
- Designates a Commercial Item Description

MILITARY INTERESTS:

Custodians

Army - GL
Navy - SA
Air Force - 99

Review Activities

Army - MD, QM
Navy - CG, MC
Air Force - 35, 84
DLA - GS

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

Army - GL

Project 7310-0861

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:07Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	A-A-52136A	950615

3. DOCUMENT TITLE

Kettles, Steam Jacketed (Stainless Steel, Steam Heated)

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial	(2) AUTOVON /DSN
U.S. Army Natick RD&E Center	(508) 651-5175	256-5175
c. ADDRESS (Include Zip Code) Commander, U.S. Army Natick RD&E Center ATTN: SSCNC-WEF Natick, MA 01760-5018	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil/wwa/ 2640-26T09:07Z
Check the source to verify that this is the current version before use.