MILITARY SPECIFICATION

DIAPER, INFANT'S, COTTON, BIRDSEYE

This limited coordination military specification has been prepared by the Defense Personnel Support Center based upon currently available technical information but it has not been approved for promulgation as a coordinated revision of MIL-D-36180(DM) It is subject to modification However, pending its promulgation as a coordinated military specification, it may be used in procurement.

1 SCOPE

1.1 Scope This specification covers the requirements for one type and size of a birdseye, cotton, infant's diaper

2 APPLICABLE DOCUMENTS

2 1 Issues of documents The following documents of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein

SPECIFICATIONS

FEDERAL

V-T-276	- Thread, Cotton
CCC-C-425	- Cloth, Birdseye and Gauze Cotton.
PPP-B-636	- Boxes, Shipping, Fiberboard.

MILITARY

MIL-T-43548	- Thread, Polyester, Cotton-covered
MIL-T-43624	- Thread, Polyester, Spun

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to Defense Personnel Support Center, Directorate of Medical Materiel, DPSC-ATT, 2800 South 20th Street, Philadelphia, PA 19101, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter

FSC 6532

Source: https://assist.dla.mil -- Downloaded: 202640-21T08:10Z
Check the source to verify that this is the current version before use.

STANDARDS

FEDERAL

FED-STD-751 - Stitches, Seams and Stitching

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage

(Copies of specifications, standards, and drawings, required by the contractor in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3 REQUIREMENTS

3.1 Materials and components. The materials and components shall conform to the applicable specifications and standards as listed or required herein.

3.1.1 Cloth. The diapers shall be fabricated from the birdseye cloth conforming to CCC-C-425, type I, class 1, except that optical brighteners and tinting compounds shall not be used.

3.1.2 Thread. The hemming or overedge stitching shall be performed with either the cotton, cotton covered polyester or polyester sewing thread conforming to 3.1.2.1, 3.1.2.2 or 3.1.2.3. The color of the sewing thread shall be white.

3.1.2.1 Cotton. The cotton sewing thread shall conform to V-T-276, type 1A2, ticket number 50, 3 ply needle and bobbin threads.

3.1.2.2 Cotton covered polyester. The cotton covered polyester sewing thread shall conform to MIL-T-43548, ticket number 70 and ticket number 50, 2 ply. The number 50 thread shall be used for the needle and bobbin thread. The number 70 thread shall be used for the looper thread.

3.1.2.3 Polyester. The spun polyester sewing thread shall conform to MIL-T-43624, class 1 or 2, ticket number 70, 2 or 3 ply for the looper thread or ticket number 40, 3 ply for the needle and bobbin thread, and ticket number 50, 3 ply for the needle and bobbin thread.

3.2 Design. The diaper shall be fabricated from the cloth, with selvaged sides and hemmed or overedge stitched ends.

3.3 Construction. The diaper shall be fabricated from a single piece of cloth. Each end of the diaper shall be hemmed with stitching type EFb-1 and stitch type 301, containing 8 to 12 stitches per inch, located 1/16 to 1/8 inch from the turned edge. The width of the hem shall be 1/4 ± 1/8 inch. As an alternate, instead of hemming, each end may be overedge stitched with stitch type 503, 8 to 12 stitches per inch

Source: https://assist.dla.mil -- Downloaded: 2026-01-21T08:10Z
Check the source to verify that this is the current version before use.

The bight of the overedge stitching shall be 3/16 minimum from the edge of the cloth. All the stitch and stitching types shall conform to FED-STD-751. The hems on the diaper shall not be twisted, puckered or pleated and no part of the diaper shall be caught in an unrelated operation The hem shall not contain any runoff or open seam. All thread ends shall be trimmed to a maximum length of 1/4 inch.

3 3 1 Sewing Each row of stitching shall be straight and parallel to the seam edge. The straightness of the stitching, in any row, shall be maintained within a tolerance of plus or minus 1/32 inch The same tolerance for spacing and parallelism shall be applicable for the double row of stitches The ends of the stitch type 301 stitching that are not caught in other seams or stitching shall be backstitched, by overlapping on themselves, a minimum of one inch Each thread break, skip, and runoff shall be overstitched not less than one inch Skipped stitches or thread breaks on stitch type 503 stitching may be repaired using stitch type 301 The thread tension shall be maintained so that there shall not be any loose or tight stitching and the lock shall be embedded in the materials sewn together.

3 4 Dimensions The assembled diaper shall be 27 ± 1/2 inches wide and 27 ± 1/2 inches long

3 5 Workmanship The diaper shall not contain any spot, stain, hole, abraded area, tear, cut, mend, patch, scorch, needle chew or any other defect which detracts from the appearance or impairs its serviceability The diapers shall conform to the quality and grade of product established by this specification The occurence of defects shall not exceed the acceptance criteria established herein. Material shall be free from missing, broken or coarse yarn, thin place, misweave, woven in waste, loose yarn or snagged thread

4 QUALITY ASSURANCE PROVISIONS

4 1 Responsibility for inspection Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements

4 1 1 Records Records of examinations and tests performed by or for the contractor shall be maintained by the contractor and made available to the Government, upon the Government's request, at any time, or from time to time, during the performance of the contract and for a period of three years after delivery of the supplies to which such records relate

4 1 2 Inspection Inspection, as used in this specification, is defined as both examination (such as visual and auditory investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties) of the item

Source: https://assist.dla.mil -- Downloaded: 20260-21T08:10Z
Check the source to verify that this is the current version before use.

4 1.3 Certificates of quality. Certificates of quality, supplied by the manufacturer of the materials may be furnished in lieu of actual performance of such testing by the contractor, provided lot identity has been maintained and can be demonstrated to the Government The certificate shall include the name of the contractor, the contract number, the name of the manufacturer or supplier, the NSN, the Item Identification, the name of the component/material, the lot number, the lot size, the sample size, the date of testing, the test method, individual test results, and the specification requirements

4.2 Sampling

4 2 1 For examination. Sampling for examination shall be conducted in accordance with MIL-STD-105, and table I The unit of product for sampling purposes shall be one diaper.

TABLE I Sampling for examination

	Inspection level	AQL (percent per hundred units)
For visual examination		
Major defects	II	2 5
Minor defects	II	10 0
For dimensional examination	S-1	2.5

4 3 Examination The diapers shall be examined to determine compliance with all requirements contained in this specification

4 3 1 Classificatior of defects Examination shall be conducted in accordance with the classification of defects listed in table II Examination shall not be restricted to the classified possible defects listed below

TABLE II Classification of defects

DEFECT	MAJOR	MINOR
GENERAL		
a Any hole, scissors or knife cut, tear, mend, burn, or weakening defect such as smash, multiple float, loose slub, needle chew, or abraded area	X	
b Any portion of the diaper stiffened by any process of manufacture	X	
c Any missing, broken or coarse yarn, thin place, misweave, woven in waste, loose yarn or snagged thread	X	

Source: https://assist.dla.mil -- Downloaded: 202610-21T08:10Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of defects. - Continued

DEFECT	MAJOR	MINOR
d Color of any component not as specified	X	
CLEANNESS		
a Any end not trimmed to a maximum length of 1/4 inch or any thread scrap not removed		X
b Any unsightly slub, spot, or stain	X	
COMPONENTS AND ASSEMBLY		
a Any component not as specified or any defect of component or defect of assembly, not herein classified	1/	
b Any component or required operation omitted, or any operation improperly performed, not herein classified	1/	
SEAMS AND STITCHING		
a Accuracy of seaming		
1 Any part twisted, puckered, or pleated, any part of the diaper caught in an unrelated operation or stitching		X
2 Ends of stitching		
(a) Any not securely backstitched	X	
(b) Any secure but backstitched for a distance less than one inch or the backstitching is not overlapped on itself		X
3 Thread breaks		
(a) Any not securely overstitched	X	
(b) Any secure but overstitched for a distance of less than one inch		X
b Gage of stitching 2/		
1 Any stitching irregular, uneven or not gaged as specified		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:10Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of defects - Continued

DEFECT	MAJOR	MINOR
c Open seams 3/		
1 Any more than 1/8 inch but not more than 1/4 inch		X
2 Any more than 1/4 inch	X	
d Raw edges 4/		
1 Any more than 1/4 inch but not more than 1/2 inch		X
2 Any more than 1/2 inch	X	
e Stitching and stitch type		
1 Not specified stitching or stitch type	1/	
f Stitch tension		
1 Any loose stitching 5/	1/	
2 Any tight stitching, resulting in breakage of the stitches, when normal pull is applied 6/	X	
g Stitches per inch 7/		
1 Stitches more or less than specified		
a One or 2		X
b More than 2	X	
DIMENSIONS		
a Width or length of the diaper less than 26 1/2 inches or greater than 27 1/2 inches	X	
b Width of any hem less than 1/8 inch or more than 3/8 inch, when applicable		X
c Any hem varying in uniformity of width by more than 1/8 inch, when applicable		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:10Z
Check the source to verify that this is the current version before use.

1/ The defect shall be classified and scored as a major defect when it seriously affects the serviceability or appearance; otherwise, it shall be classified and scored as a minor defect

2/ The gage of stitching defect shall be scored only when the condition exists for more than 2 inches on any row of stitching.

3/ A seam shall be classified and scored as open when one or more stitches joining a seam are broken or when two or more continuous skipped stitches or runoffs occur. On double stitched seams, a seam shall be classified and scored as open when either one or both sides of the seam contain any of the aforementioned for a single stitched seam

4/ Any edge that should be turned and is not but is securely caught in the stitching shall be classified and scored as a raw edge. Any raw edge that is not securely caught in the stitching shall be classified and scored as an open seam

5/ A seam shall be classified and scored as loose when the top and bobbin threads are on the same surface

6/ Puckering is evidence of tight tension or gathering of the material When puckering is evident and is not caused by the gathering of the material, the stitching shall be inspected for tight tension and breaking of stitches by exerting normal pull in the lengthwise direction of the stitching by pulling the material taut to straighten out the seam Puckering due to the gathering of the material shall be classified and scored as an accuracy of seaming defect.

7/ The stitches per inch defect shall be scored only when the condition exists for more than 3 inches on any row of stitching

4.3.2 Dimensional examination The diaper shall be examined for defects in dimensions Any dimension not within the tolerances specified herein shall be classified as a defect

4.4 Tests Tests shall be conducted to determine compliance with specification requirements

4.5 Packaging inspection The inspection of the unit package, packing and marking of for shipment and storage shall be in accordance with the quality assurance provisions of the applicable container specification and the marking requirements of MIL-STD-129

5 PACKAGING

5.1 Packaging Packaging shall be level A or C, as specified (see 6.2)

5.1.1 Unit of issue One package containing six hundred diapers, as specified, constitutes one unit of issue

Source: https://assist.dla.mil -- Downloaded: 2026-04-21T08:10Z
Check the source to verify that this is the current version before use.

5 1.2 Level A

5 1.2.1 Unit packaging Each diaper shall be clean, dry and neatly folded in accordance with the contractor's commercial practice Six hundred clean, dry and neatly folded diapers shall be packaged in a box conforming to PPP-B-636, class domestic. The box shall have contents completely covered on the top and bottom with kraft paper. Closure shall be as specified in the appendix of the box specification As an alternate, three hundred clean, dry and neatly folded diapers shall be packaged in a corrugated fiberboard box having a minimum bursting strength of 200 pounds The box shall have the contents completely covered on the top and bottom with kraft paper Closure of the box shall be secured with tape or by other suitable means Two boxes, each containing three hundred diapers, shall be further packaged in a snug fitting box conforming to PPP-B-636, class domestic Closure shall be as specified in the appendix of the box specification

5 1 3 Level C Six hundred clean, dry and neatly folded diapers shall be packaged in a manner that will afford adequate protection against physical damage during shipment from the supply source to the first receiving activity

5 2 Packing Packing shall be level A, B or C, as specified (see 6.2)

5 2 1 Level A Diapers packaged as specified in 5 1 2 1 shall require no further packing with the exception that shipping containers shall conform to PPP-B-636, class weather-resistant In addition, water-proofing and strapping as specified in the box specification shall be required

5 2 2 Level B Diapers packaged as specified in 5 1 2 1 shall require no further packing

5 2 3 Level C The six hundred packaged diapers shall be packed in shipping containers in a manner that will afford adequate protection against damage during direct shipment from the supply source to the first receiving activity These packs shall conform to the carrier's rules and regulations

5 3 Marking

5 3 1 Interior packages Interior packages shall be marked to identify contents and quantity contained

5 3 2 Unit package Since the unit package is also the shipping container, the shipping container markings as specified in 5 3 3 shall be show on the unit package

5 3 3 Shipping containers Shipping containers shall be marked as specified in MIL-STD-129 The level of protection shall be shown as "A" in lieu of A/A, or "B" in lieu of A/B, or "C" in lieu of C/C

Source: https://assist.dla.mil -- Downloaded: 202640-21T08:10Z
Check the source to verify that this is the current version before use.

6. NOTES

6 1 Intended use The birdseye, cotton, infant's diapers are intended for use by infants in Military hospitals

6 2 Ordering data Procurement documents shall specify the following

a Title, number, and date of this specification.
b Selection of applicable levels of packaging and packing (see 5 1 and 5 2)

6 3 This specification covers the following item appearing in the Federal Supply Catalog

National Stock Number	Item Identification
6532-01-048-0847	DIAPER, INFANT'S, COTTON, BIRDSEYE, 600s

Preparing activity
DLA - DM

Project No 6532-1124

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:10Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS This form is provided to solicit beneficial comments which may improve this document and enhance its use DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government Fold on lines on reverse side, staple in corner and send to preparing activity Attach any pertinent data which may be of use in improving this document If there are additional papers attach to form and place both in an envelope addressed to preparing activity A response will be provided to the submitter when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed

NOTE This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-D-0036180A(DLA-DM) DIAPER, INFANT'S, COTTON, BIRDSEYE

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1 ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID RESTRICTIVE LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW

A GIVE PARAGRAPH NUMBER AND WORDING

B RECOMMENDED WORDING CHANGE

C REASON FOR RECOMMENDED CHANGE(S

2 REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO

DATE

DD FORM 1426 1 OCT 76

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED

Source: https://assist.dla.mil -- Downloaded: 202610-21T08:10Z
Check the source to verify that this is the current version before use.

FOLD

DEFENSE PERSONNEL SUPPORT CENTER
2800 SOUTH 20TH STREET
PHILADELPHIA, PA 19101

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

POSTAGE AND FEES PAID



DEFENSE PERSONNEL SUPPORT CENTER
DIRECTORATE OF MEDICAL MATERIEL, CODE ATT
2800 SOUTH 20TH STREET
PHILADELPHIA, PA 19101

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-21T08:10Z
Check the source to verify that this is the current version before use.