MIL-B-50957(MU)
AMENDMENT 2
31 May 1973
SUPERSEDING
AMENDMENT 1
13 October 1972

MILITARY SPECIFICATION

BATTERY, THERMAL: M9

This amendment forms a part of Military Specification MIL-B-50957(MU) dated 27 September 1971.

Page 4, paragraph 3.10: Delete and substitute:

"3.10 Thermal battery operational tests.- During these tests, and unless otherwise specified, a constant load of 13 ± 0.7 ohm shall be applied across the battery output terminals. The total resistance of the leads connecting the battery output terminals to the load resistor shall be 0.30 ohm ± 5 per cent (a suitable resistance may be placed in series with either battery terminal and the load to obtain this value). Battery voltage shall be measured across the 13 ohm load resistor using the method specified in 4.4.7."

Page 6, paragraph 3.12, line 2: Delete "-65° ± 5°F." and substitute "-33° ± 3°F."

Page 7 paragraph 3.15, line 5: Delete "SMUPA-NR2" and substitute "SMUPA-QA-T-M".

Page 14, paragraph 4.4.9, line 3 and line 11: Delete "-65°F." and substitute "-33°F."

Page 16, paragraph 6.1.2, line 3: Delete "or this specification".

Page 16, paragraph 6.4, last line: Delete "SMUPA-NR4" and substitute "SMUPA-QA-N-I".

Custodian:
Army-MU
Preparing Activity:
Army-MU
Project No.: 6135-A133

FSC 6135

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:45Z
Check the source to verify that this is the current version before use.